20005058 -3
IPOS copy!

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A61F 13/15 | A1

(11) International Publication Number: WO 99/45875

(43) International Publication Date: 16 September 1999 (16.09.99)

(21) International Application Number: PCT/US98/05040

(22) International Filing Date: 13 March 1998 (13.03.98)

(71) Applicant *(for all designated States except US)*: THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: EHRNSPERGER, Bruno, Johannes [DE/DE]; Westerbachstrasse 89, D–65936 Frankfurt (DE). DESAI, Fred [US/US]; 6383 Jamesfield Court, Fairfield, OH 45014 (US). SCHMIDT, Mattias [DE/DE]; Altkoenigweg 3, D–65510 Idstein (DE).

(74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.

(54) Title: ABSORBENT ARTICLES WITH IMPROVED DISTRIBUTION PROPERTIES UNDER SUB–SATURATION

(57) Abstract

The present invention is an absorbent article, containing at least one fluid storage member and at least one fluid distribution member. The fluid distribution member has an improved fluid handling property especially under sub–saturation conditions. Such members exhibit at 50 % of their saturation capacity an increased permeability of at least about 14 % of the one at saturation. The fluid storage member has a higher Capillary Sorption Absorbency Height than the fluid distribution member.

