

Description

The present invention relates generally to cellular mobile telephone systems, and more specifically to a channel selection technique for selecting a control channel during call setup periods.

According to the EIA or TACS cellular mobile telephone system, idle mobile stations are normally tuned to an assigned standby channel to receive identifiers of call setup channels specified by the standby channel. When originating or receiving a call, the mobile station detects the signal levels of the specified call setup channels and selects one having the highest signal level and transmits a call-request signal or returns an answer signal over the selected channel.

Recent demands for mobile telephone systems have given rise to the establishment of similar mobile telephone systems by different common carriers, using the frequency reuse scheme. However, in some fringe areas, an undesirable situation can occur in which a certain frequency band is shared between adjacent cells served by different common carriers. Mobile station is constantly receiving call setup channel identifiers specified by the strongest standby channel of the own system. If the up-direction call setup channel that is paired with the strongest down-direction call setup channel is shared with the subscribers of a different common carrier in an adjacent cell, the signal levels of the different common carrier may, in some cases, be stronger than those of the own signal. If a call is attempted under such circumstances, it is likely that the mobile station will seize a call setup channel of the different common carrier.

In the specification of a patent application having an international publication number WO88/08238, which was published on October 20 1988, in the name of Motorola, Inc., there was proposed a method of registration for radio telephones located in one or more radio telephone systems in which as mobiles moved about the networked coverage area, intrasystem handoffs were provided between cells of the same cellular system, and intersystem handoffs were provided between border cells of adjacent cellular systems.

The specification of United States patent number 4,750,198, which was published on June 7 1988, disclosed a proposal for a cellular radio-telephone system with a mechanism for dividing a plurality of channels into two diverse sets based on a division of the control channels which were used to transmit control information. A first group of subscriber sets scanned one number of control channels and a second group of subscriber sets scanned a second number of control channels.

A feature of an arrangement to be described is that it reduces the likelihood of a mobile station selecting undesired control channels.

A particular arrangement to be described disclo-

ses a method for selecting channels of a mobile station for a cellular mobile telephone system serving a plurality of cells. Each of the cells is assigned a unique standby, or paging channel, and the mobile station is assigned a plurality of standby channels and a system identifier. During idle states, the assigned standby channels are constantly scanned by mobile station and one of the scanned standby channels having a highest signal level is selected. If there is a match between the system identifier of the selected standby channel and that of the mobile station, the mobile station is ready to originate or receive a call. If there is no originating or incoming call, the channel number of a call setup channel specified by the standby channel is stored into a successive location of a memory. If there is an originating or incoming call, the channel numbers stored in the memory are scanned, and one of the scanned call setup channels is selected for returning an answer signal or a call request signal.

The following description and drawings disclose, by means of examples, the invention which is characterised in the appended claims, whose terms determine the extent of the protection conferred hereby.

In the drawings:-

Fig. 1 is a block diagram of a block diagram of a cellular mobile unit according to the present invention;

Fig. 2 is a flowchart describing the instructions performed by the controller of Fig. 1 according to an embodiment of this invention;

Fig. 3 is a flowchart illustrating a modified embodiment of Fig. 2; and

Figs. 4A and 4B are flowcharts describing the controller instructions according to a further modification of this invention.

DETAILED DESCRIPTION

Referring now to Fig. 1, there is shown a mobile telephone station embodying the present invention for a cellular mobile telephone system covering a plurality of service zones, or cells each being assigned a unique standby control channel. The standby channel is a down-direction (from the base station to mobile stations) channel and contains information specifying a number of two-way call setup channels. These control channels occupy a band of frequencies adjacent to a band of speech channels within the allocated frequency spectrum. The mobile station is assigned a plurality of different standby channels.

RF signal from a cell site is received by an antenna 1 and passed through a duplexer 2 to a mixer 3 where it is converted to a first intermediate frequency with a local carrier generated by a frequency synthesizer 4. After passing through an amplifier 5, the mixer 3 output is converted to a second intermediate frequency by a mixer 6 using a local carrier from an os-

cillator 7. The output of mixer 6 is passed through an amplifier 8 and applied to a discriminator 9 in which the original digital signal is recovered. A decoder 10 is coupled to discriminator 9 to supply decoded signals to a channel controller 11.

On the other hand, coded transmit signal is supplied from an encoder 12 to a mixer 13 in which it is converted to radio frequency with a local carrier supplied from a frequency synthesizer 14 for transmission to a cell site. Frequency synthesizers 4 and 14 are controlled by channel controller 11. A memory 15 is connected to controller 15 to store channel selection data in a manner as will be described below.

Channel controller 11 is programmed to perform instructions described in Figs. 2, 3, 4A and 4B. In Fig. 2, the program execution starts with an initialization step 21 in which a variable K is reset to zero. Exit then is to second initialization step 22 in which flags F_R and F_O are reset to zero. Exit then is to operations step 23 which directs the scanning of standby channels assigned to the mobile station by sweeping the frequency of the local carrier of receive frequency synthesizer 4. The signal level of each scanned channel is detected and recorded. Control exits to step 24 to select one of the scanned standby channels having the highest signal level. Exit then is to decision step 25 which checks to see if there is a match between the system identifier of the selected standby channel and that of the mobile station. If the answer is negative, control returns to step 22, and if it is affirmative, exit is to decision step 26 to check to see if a ringing signal is received. If the answer is negative, control moves to decision step 27 to check to see if there is an off-hook condition. If there is none, control proceeds to decision step 28 to determine if there is a match between the call-setup channel number of the selected standby channel and a most recently stored channel number in memory 15. If a match is detected, control returns to step 25 to repeat the process. If a mismatch is detected, control advances to operations step 29 to store the channel number of a call setup channel specified by the selected standby channel into a location K of memory 15. Variable K is incremented by 1 (step 30) and checked against a maximum value representing the capacity of memory 15 (step 31). If the answer is negative, control returns to step 25, and if affirmative, it returns to step 21 to reset the variable K to zero again. As control loops through steps 22 to 31 while driving the vehicle, the channel numbers of call setup channels specified by multiple standby channels will be stored in several locations of memory 15.

If a call is received from the base station, the answer in step 26 becomes affirmative and flag F_R is set equal to 1 (step 32) or a call is originated from the mobile station, the answer in step 27 becomes affirmative and flag F_O is set equal to 1 (step 33). Control exits to operations step 34 to scan all channel numbers stored in memory 15 by sweeping the frequency of

the synthesizer 4 to tune the mobile receiver successively to the call setup channels having their channel numbers stored in the memory. The signal levels of these call setup channels are detected and recorded. Exit then is to step 35 to select one of the call setup channels having the highest signal level.

Exit then is to step 36 to check to see which of flag F_R or F_O is set equal to 1. If $F_R = 1$, step 37 is executed by returning an answer signal over the selected call setup channel to establish a ringing connection, and if $F_O = 1$, step 38 is executed by sending a call request signal over the selected call setup channel to establish a dialing connection.

A modified embodiment of this invention is shown in Fig. 3 which differs from the Fig. 2 embodiment in that operations steps 34 and 35 of Fig. 2 are replaced with operations step 40. Following the execution of step 32 or 33, control exits to step 40 to select the call setup channel whose channel number is most recently stored into memory location K. Frequency synthesizers 4 and 14 are controlled so that the mobile station is tuned to the selected call setup channel.

Figs. 4A and 4B are flowcharts of a further modification of the present invention. In Fig. 4A, following the negative decision of step 31, control goes to operations step 41 (Fig. 4B) to transfer all channel numbers stored in memory locations K to memory locations L. Step 42 is followed by decision step 42 which checks to see if the contents of memory locations L are sufficient to make a statistical analysis. If the answer is affirmative, exit is to operations step 43 in which the channel numbers stored in locations L are sorted according to different channels. Exit then is to operations step 44 in which the same channel numbers are counted. Control moves to step 45 to detect a maximum count value and store the channel number of the maximum count into a memory location M (step 46).

In Fig. 4A, operations steps 34 and 35 of Fig. 2 are replaced with step 47 in which the call setup channel of the identifier stored in memory location M is selected, and the frequency synthesizers 4 and 14 are controlled to tune the mobile station to the selected call setup channel.

The foregoing description shows only preferred embodiments of the present invention. Various modifications are apparent to those skilled in the art without departing from the scope of the present invention which is only limited by the appended claims. For example, if memory 15 is implemented with a first-in-first-out (FIFO), steps 21, 30 and 31 could be dispensed with. Furthermore, two-way channels could also be used for standby channels as well as for call-setup channels.



Claims

1. A method for selecting channels for a mobile station located in a cellular mobile communication system serving a plurality of cells, each of the cells being assigned a unique standby channel, and the mobile station being assigned a plurality of standby channels and a system identifier identifying the system, the method including the steps of:-
 - a) scanning the standby channels to detect their signal levels and selecting a scanned channel of the highest signal level,
 - b) comparing a system identifier contained in the selected channel and the system identifier of the mobile station to identify the selected channel as belonging to the system if there is a match therebetween,
 - c) storing a channel number specified by the identified channel into a memory, and
 - d) establishing a call setup channel in accordance with the stored channel number when a call is originated or received.
2. A method as claimed in claim 1, further including the steps of:-
 - A) repeating the steps (a) to (c); and
 - B) selecting one of the stored channel numbers from the memory when the call is originated or received, in which the step (d) includes establishing the call setup channel in accordance with the selected channel number.
3. A method as claimed in claim 2, wherein the step (c) further includes storing the signal level of the identified standby channel in the memory and the step (B) includes selecting the highest of the stored signal levels and selecting the stored channel number corresponding to the selected highest of the stored signal levels.
4. A method as claimed in claim 2, wherein the selected channel is the most recently stored channel number.
5. A method as claimed in claim 2, wherein the selected channel is the most frequently stored channel number.
6. A mobile station for a cellular communication system serving a plurality of cells, each of the cells being assigned a unique standby channel, and the mobile station being assigned a plurality of standby channels and a system identifier identifying the system, the mobile station including a memory (15), a tunable radio-frequency transceiver (2, 3, 4, 13, 14), and a channel controller (11) coupled to the transceiver (2, 3, 4, 13, 14) for causing the transceiver to tune to a standby channel of the highest of the signal levels of the standby channels, for comparing a system identifier contained in the selected channel and the system identifier of the mobile station to identify the selected channel as belonging to the system if there is a match therebetween, for storing a channel number specified by the identified channel into the memory (15) and for causing the transceiver (2, 3, 4, 13, 14) to establish a call setup channel in accordance with the stored channel number when a call is originated or received.
7. A mobile station as claimed in claim 6, wherein the channel controller (14) includes means for successively storing a channel number in the memory (15) by repeatedly causing the transceiver to a standby channel of the highest of the signal levels of the standby channels, for comparing a system identifier contained in the repeatedly selected channel and the system identifier of the mobile station to identify the repeatedly selected channel as belonging to the system if there is a match therebetween, for storing a channel number specified by the repeatedly identified channel into the memory (15), for selecting one of the stored channel numbers when the call is originated or received, and for causing the transceiver (2, 3, 4, 13, 14) to establish the call setup channel in accordance with the selected channel number.
8. A mobile station as claimed in claim 7, wherein the channel controller (14) further includes means for storing the highest signal levels of the repeatedly identified channels into the memory (15) and for selecting the highest of the stored signal levels and selecting one of the stored channel numbers corresponding to the selected highest of the stored signal levels.
9. A mobile station as claimed in claim 7, wherein the selected channel is the most recently stored channel number.
10. A mobile station as claimed in claim 7, wherein the selected channel is the most frequently stored channel number.

Patentansprüche

1. Verfahren zum Auswählen von Kanälen für eine Mobilstation, die in einem zellularen Mobil-Kommunikationssystem angeordnet ist, das mehrere Zellen bedient, wobei jeder Zelle ein eindeutiger Reservekanal zugeordnet ist, und der Mobilstation mehrere Reservekanäle und ein das System



identifizierender Systemidentifikator zugeordnet sind, wobei das Verfahren die Schritte umfaßt:

- a) Durchscannen der Reservekanäle, um deren Signalpegel zu detektieren und um einen gescannten Kanal mit dem höchsten Signalpegel auszuwählen, 5
 - b) Vergleichen eines in dem ausgewählten Kanal enthaltenen Systemidentifikators und des Systemidentifikators der Mobilstation, um den ausgewählten Kanal als systemzugehörigen zu identifizieren, wenn dazwischen eine Übereinstimmung vorliegt, 10
 - c) Einspeichern einer durch den identifizierten Kanal spezifizierten Kanalnummer in einen Speicher, und 15
 - d) Einrichten eines Rufaufbaukanals in Übereinstimmung mit der gespeicherten Kanalnummer, wenn ein Ruf erzeugt oder empfangen wird. 20
2. Verfahren nach Anspruch 1, welches ferner die Schritte umfaßt:
- A) Wiederholen der Schritte (a) bis (c); und 25
 - B) Auswählen einer der gespeicherten Kanalnummern aus dem Speicher, wenn der Ruf erzeugt oder empfangen wird, in welchem der Schritt (d) das Einrichten des Rufaufbaukanals in Übereinstimmung mit der ausgewählten Kanalnummer umfaßt. 30
3. Verfahren nach Anspruch 2, wobei der Schritt (c) ferner das Speichern des Signalpegels des identifizierten Reservekanals in dem Speicher umfaßt und der Schritt (B) das Auswählen des höchsten der gespeicherten Signalpegel und das Auswählen der gespeicherten Kanalnummer umfaßt, die dem ausgewählten höchsten von den gespeicherten Signalpegeln entspricht. 35
4. Verfahren nach Anspruch 2, wobei der ausgewählte Kanal die zuletzt gespeicherte Kanalnummer ist. 40
5. Verfahren nach Anspruch 2, wobei der ausgewählte Kanal die am häufigsten gespeicherte Kanalnummer ist. 45
6. Mobilstation für einem zellulares Mobil-Kommunikationssystem, das mehrere Zellen bedient, wobei jeder Zelle ein eindeutiger Reservekanal zugeordnet ist, und der Mobilstation mehrere Reservekanäle und ein das System identifizierender Systemidentifikator zugeordnet sind, die Mobilstation einen Speicher (15), einen abstimmbaren Funkfrequenz-Sender/Empfänger (2, 3, 4, 13, 14) und eine mit dem Sender/Empfänger (2, 3, 4, 13, 14) verbundene Kanalsteuerung (11) umfaßt, um den Sender/Empfänger zu veranlassen, 50

sich auf einen Reservekanal mit dem höchsten Signalpegel von den Reservekanälen abzustimmen, um einem in dem ausgewählten Kanal enthaltenen Systemidentifikator und den Systemidentifikator der Mobilstation zu vergleichen, um den ausgewählten Kanal als systemzugehörigen zu identifizieren, wenn dazwischen eine Übereinstimmung vorliegt, um eine von dem identifizierten Kanal spezifizierte Kanalnummer in den Speicher (15) einzuspeichern und um den Sender/Empfänger (2, 3, 4, 13, 14) zum Einrichten eines Rufaufbaukanals in Übereinstimmung mit der gespeicherten Kanalnummer zu veranlassen, wenn ein Ruf erzeugt oder empfangen wird.

7. Mobilstation nach Anspruch 6, wobei die Kanalsteuerung (14) eine Einrichtung zum sukzessiven Speichern einer Kanalnummer in dem Speicher (15) aufweist, indem der Sender/Empfänger wiederholt veranlaßt wird, auf einen Reservekanal mit dem höchsten Signalpegel von den Reservekanälen abzustimmen, um einen in dem wiederholt ausgewählten Kanal enthaltenen Systemidentifikator und den Systemidentifikator der Mobilstation zu vergleichen, um den wiederholt ausgewählten Kanal als systemzugehörigen zu identifizieren, wenn dazwischen eine Übereinstimmung vorliegt, um eine von dem wiederholt identifizierten Kanal spezifizierte Kanalnummer in den Speicher (15) einzuspeichern und um eine der gespeicherten Kanalnummern auszuwählen, wenn der Ruf erzeugt oder empfangen wird, und um den Sender/Empfänger (2, 3, 4, 13, 14) zum Einrichten des Rufaufbaukanals in Übereinstimmung mit der ausgewählten Kanalnummer zu veranlassen. 55
8. Mobilstation nach Anspruch 7, wobei die Kanalsteuerung (14) ferner eine Einrichtung zum Einspeichern der höchsten Signalpegel der wiederholt identifizierten Kanäle in den Speicher (15) und zum Auswählen des höchsten der gespeicherten Signalpegel und zum Auswählen einer der gespeicherten Kanalnummern, die dem höchsten der gespeicherten Signalpegel entspricht, umfaßt.
9. Mobilstation nach Anspruch 7, wobei der ausgewählte Kanal die zuletzt gespeicherte Kanalnummer ist.
10. Mobilstation nach Anspruch 7, wobei der ausgewählte Kanal die am häufigsten gespeicherte Kanalnummer ist.



Revendications

1. Procédé pour sélectionner des canaux pour une station mobile placée dans un système de communication mobile cellulaire servant une multitude de cellules, chacune des cellules étant affectée à un canal de veille particulier et la station mobile étant affectée à une multitude de canaux de veille et un identificateur de système identifiant le système, le procédé comprenant les étapes consistant à :
 - a) scruter les canaux de veille afin de détecter leurs niveaux de signal et sélectionner un canal scruté du niveau de signal le plus élevé,
 - b) comparer un identificateur de système contenu dans ledit canal sélectionné et l'identificateur de système de la station mobile afin d'identifier le canal sélectionné comme appartenant au système s'il existe une correspondance entre ceux-ci,
 - c) mémoriser un numéro de canal spécifié par le canal identifié dans une mémoire, et
 - d) établir un canal d'établissement d'appel en conformité avec le numéro de canal mémorisé lorsqu'un appel est émis ou reçu.
2. Procédé selon la revendication 1, comportant de plus les étapes consistant à :
 - A) répéter les étapes (a) à (c) ; et
 - B) sélectionner un des numéros de canal mémorisé dans la mémoire lorsque l'appel est émis ou reçu, laquelle étape (d) comporte d'établir le canal d'établissement d'appel en conformité avec le numéro de canal sélectionné.
3. Procédé selon la revendication 2, dans lequel l'étape (c) comporte de plus la mémorisation du niveau de signal du canal de veille identifié dans la mémoire et l'étape (b) comporte la sélection du niveau de signal mémorisé le plus élevé parmi les niveaux de signal mémorisé et de sélectionner le numéro de canal mémorisé correspondant au niveau le plus élevé sélectionné parmi les niveaux de signal mémorisé.
4. Procédé selon la revendication 2, dans lequel le canal sélectionné est le numéro de canal mémorisé le plus récemment.
5. Procédé selon la revendication 2, dans lequel le canal sélectionné est le numéro de canal mémorisé le plus fréquemment.
6. Station mobile pour un système de communication cellulaire servant une multitude de cellules, chacune des cellules étant affectée à un canal de veille particulier et la station mobile étant affectée avec une multitude de canaux de veille et un identificateur de système identifiant le système, la station mobile comportant une mémoire (15), un émetteur/récepteur radio-fréquence accordable (2, 3, 4, 13, 14) et un contrôleur de canaux (11) couplé à l'émetteur/récepteur (2, 3, 4, 13, 14) pour amener l'émetteur/récepteur à s'accorder sur un canal de veille du niveau le plus élevé parmi les niveaux de signal des canaux de veille, pour comparer un identificateur du système contenu dans le canal sélectionné et l'identificateur de système de la station mobile afin d'identifier le canal sélectionné comme appartenant au système s'il existe une correspondance entre ceux-ci, pour mémoriser un numéro de canal spécifié par le canal identifié dans la mémoire (15) et pour amener l'émetteur/récepteur (2, 3, 4, 13, 14) à établir un canal d'établissement d'appel en conformité avec le numéro de canal mémorisé lorsqu'un appel est émis ou reçu.
7. Station mobile selon la revendication 6, dans lequel le contrôleur de canal (14) comporte un moyen pour mémoriser successivement un numéro de canal dans la mémoire (15) en amenant de manière répétée l'émetteur/récepteur sur le canal de veille du niveau le plus élevé parmi les niveaux de signal parmi les canaux de veille, pour comparer un identificateur de système contenu dans le canal sélectionné de manière répétée et l'identificateur de système de la station mobile à identifier le canal sélectionné de manière répétée comme appartenant au système s'il existe une correspondance entre ceux-ci, pour mémoriser un numéro de canal spécifié par le canal identifié de manière répétée dans la mémoire (15), pour sélectionner un des numéros de canal mémorisé lorsque l'appel est émis ou reçu et pour amener l'émetteur/récepteur (2, 3, 4, 13, 14) à établir le canal d'établissement d'appel en conformité avec le numéro de canal sélectionné.
8. Station mobile selon la revendication 7, dans lequel le contrôleur de canal (14) comporte de plus un moyen pour mémoriser les niveaux de signal les plus élevés parmi les canaux identifiés de manière répétée dans la mémoire (15) et pour sélectionner le niveau de signal mémorisé le plus élevé parmi les niveaux de signal mémorisé et sélectionner un des numéros de canal mémorisé correspondant au niveau le plus élevé sélectionné des niveaux de signal mémorisé.
9. Station mobile selon la revendication 7, dans lequel le canal sélectionné est le numéro de canal mémorisé le plus récemment.
10. Station mobile selon la revendication 7, dans le-



quel le canal sélectionné est le numéro de canal
mémoire le plus fréquemment.

5

10

15

20

25

30

35

40

45

50

55

7