

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau9905014-8
(POS')

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: G01N 27/60	A1	(11) International Publication Number: WO 98/48267 (43) International Publication Date: 29 October 1998 (29.10.98)
(21) International Application Number: PCT/US98/07489 (22) International Filing Date: 15 April 1998 (15.04.98) (30) Priority Data: 08/840,069 24 April 1997 (24.04.97) US (71)(72) Applicant and Inventor: AFILANI, Thomas [US/US]; R.D. 5, Box 171, Jersey Shore, PA 17740 (US). (74) Agent: KAGEN, Alan, M.; Nixon & Vanderhye P.C., 8th floor, 1100 North Glebe Road, Arlington, VA 22201-4714 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: SELECTIVE POLARIZATION MATCHING FILTER FOR TRIGGERING AND MAXIMIZING RAPID DIELECTROKINESIS RESPONSE (57) Abstract A composition of matter utilizes an exact dielectric replicate matching reference material to make a detection device component that triggers and maximizes a dielectrokinesis (phoresis) phenoma (force, torque, energy replenishment), which can be used to detect the presence of specific entities of a predetermined type that contain as a major component the matching dielectric material. Different designs and materials of construction for the detection device component enable the detection of a variety of specific entities including human beings, animals, plastics, metals, water, etc. Detectors using the component can detect the present of a specific entity irrespective of the presence or absence of any type of intervening, visual obstructing material structures or barriers, lighting conditions, weather conditions or electromagnetic interference (EMI).		