

Description

BACKGROUND OF THE INVENTION

The present invention relates to a mount for mounting a cradle of a telephone such as a vehicle telephone.

A prior art mount of the kind described includes a mounting member for mounting a telephone cradle, a fixing member for fixing the mounting member to the body of a vehicle, and a pin for interconnecting bearing sections which are rigidly provided on the mounting and fixing members. Such a configuration allows a telephone to be mounted in a desired angular position. However, since this prior art mount cannot be opened and closed except for one direction, end portions of the mounting member become uncovered depending upon the relative angular position of the mounting member and the cradle, e.g., when the mounting member and the cradle are oriented to cross each other. Such is not only dangerous but also undesirable from the viewpoint of space-saving and design of a vehicle compartment.

To prevent the end portions of the mounting member from being exposed, each of the mounting and fixing members may be provided with a bearing section at each of its four corners such that the mount is selectively openable in two perpendicular directions as needed. However, a drawback with this implementation is that those bearing portions which are not used interface with the opening and closing movements, limiting the opening and closing angle available.

SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide a telephone cradle mount which allows desired direction and angle of opening and closing movements to be set up with ease.

It is another object of the present invention to provide a telephone cradle mount which prevents its end portions from becoming uncovered even when a telephone is mounted crosswise.

It is another object of the present invention to provide a telephone cradle mount which is openable over a sufficient angle.

It is another object of the present invention to provide a telephone cradle mount which prevents the mounting angle of a telephone from being easily changed by shocks and impacts.

It is another object of the present invention to provide a telephone cradle mount which is suitable for mass production.

In an embodiment to be described, there is provided a telephone cradle mount comprising a mounting member for mounting a telephone cradle

and a fixing member, each of the mounting and fixing members comprises a generally rectangular mounting plate section, a first and a second stationary bearing sections each provided on and perpendicularly to the mounting plate section and extending along, respectively, one of first opposite sides of the mounting plate section and one of second opposite sides which are perpendicular to the first opposite sides, the first and second stationary bearing sections being provided with a first and a second opening, respectively, and a rotatable bearing section having a third opening and rotatable such that the third opening selectively becomes aligned with the first and second openings.

In another embodiment to be described, there is provided a telephone cradle mount comprising a generally rectangular first member for mounting the cradle, and a second member provided with a same shape as the first member for mounting the mount to a predetermined body, each of the first and second members comprises a first stationary bearing section provided on and perpendicularly to one of opposite sides and provided with a first opening at one end of the first stationary bearing section, a second stationary bearing section provided on and perpendicularly to one of opposite sides which are perpendicular to the opposite sides and provided with a second opening at one end of the second stationary bearing section, and a rotatable bearing section provided at and perpendicularly to a corner where the sides which individually plate section those sides where the first and second stationary bearing sections are provided join each other, the rotatable bearing section being provided with a third opening through a perpendicular portion thereof, the rotatable bearing portion being rotatable such that the perpendicular portion becomes parallel to the first or second stationary bearing sections, the mount further comprising male screws for selectively interconnecting the rotatable bearing sections and the first or second stationary bearing sections which are engaged with each other when the rotatable bearing portions of the first and second flat members are oriented in a same direction as each other with the first and second flat members facing each other.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the present invention will become more apparent from the following detailed description taken with the accompanying drawings in which:

Figs. 1 and 2 are, respectively, a perspective view and an exploded perspective view of a telephone cradle mount embodying the present invention and which is configured to be openable

ble in a lengthwise direction;

Figs. 3 and 4 are views similar to Figs. 1 and 2, respectively, showing the mount of the present invention which is configured to be openable in a direction perpendicular to the opening direction as shown in Fig. 1;

Figs. 5A to 5F are views of a mounting member or a fixing member of the mount held in the condition of Fig. 1 and seen in six different directions;

Figs. 6A to 6E are views of the mounting member or the fixing member of the mount held in the condition of Fig. 3 and seen in five different directions;

Figs. 7A to 7D are views of the mount in which the mounting member and fixing member are put together with their rotatable bearing sections positioned as shown in Fig. 5, as seen in four different directions;

Figs. 8A to 8D are views of the mount in which the mounting member and fixing member are put together with the rotatable bearing sections positioned as shown in Fig. 6, as viewed in four different directions;

Figs. 9A and 9B are views of a stationary bearing section as seen in two different directions; and

Figs. 10A to 10C are views of the rotary bearing section as seen in three different directions.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figs. 1 and 2, a telephone cradle mount embodying the present invention and which is so configured as to be openable in a lengthwise direction is shown. Also shown in Fig. 1 are a telephone handset 10 and a cradle 31.

The mount includes a mounting plate section 11 for mounting the cradle 31, stationary bearing sections 12, 13, 17 and 18, rotatable bearing sections 15 and 19, a fixing plate section 16, a mounting member 20, a fixing member 21, and two male screws 22 (only one is shown).

The rotatable bearing section 15 is connected to the mounting member 20 in such a manner as to be rotatable by 90 degrees relative to the mounting member 20. In this particular embodiment, the rotatable bearing section 15 is oriented such that the general plane of its bent and raised upright portion extends in the same direction as that of the stationary bearing section 18. Likewise, the rotatable bearing section 19 is connected to the fixing member 21 to be rotatable by 90 degrees and includes a bent and raised upright portion whose general plane extends in the same direction as that of the stationary bearing section 13. The rotatable bearing section 15 and the stationary bearing section 18

are connected by the male screw 22. Likewise, the rotatable bearing section 19 and the stationary bearing section 13 are connected together by a male screw, not shown.

After the mounting member 20 has been positioned at any desired angle within the range of 0 to 90 degrees relative to the fixing member 21, the two male screws 22 are fastened to fix the members 20 and 21 at the desired angle. As will be described in detail later, the rotatable bearing sections 15 and 19 and the stationary bearing sections 18 and 13 are shaped to mesh with each other. This prevents the angular position of the member 20 relative to the member 21 from being easily changed after the male screws 22 have been fastened.

The cradle 31 is mounted on the mounting plate section 11 of the mount 20 as indicated by an arrow. On the other hand, the fixing plate section 16 of the mount 21 is fixed to the body of a vehicle.

Referring to Figs. 3 and 4, the mount in accordance with the present invention is shown in another specific position in which it is openable in a direction perpendicular to the opening direction as shown in Figs. 1 and 2. Specifically, the mounting member 20 and the fixing member 21 are put together after rotating the mounting member 20 by 180 degrees relative to the fixing member 21 and rotating the rotatable bearing sections 15 and 19 by 90 degrees, respectively. In this configuration, the mounting member 20 can be opened and closed perpendicularly to the mounting member 20 of Fig. 1.

In any of the configurations shown in Figs. 1 to 4, those of the stationary bearing portions 12, 17, 13 and 18 which are not used are located on the opposite side to the side where the male screws 22 are positioned. This, coupled with the fact that those bearing sections not used do not abut against each other when the mounting member 20 and fixing member 21 are closed, prevents them from interfering with the opening and closing movements of the member 20. It is to be noted that the mounting member 20 and fixing member 21 are provided with exactly the same shape.

The structure of the mounting member 20 and fixing member 21 will be described in more detail with reference to Figs. 5 to 9.

Figs. 5A to 5F shows the mounting member 20 or the fixing member 21 of Fig. 1 as viewed in six different directions. Specifically, Figs. 5A, 5B, 5C, 5D, 5E and 5F are a plan view, a back view, a side elevation as seen from the left, a side elevation as seen from the right, a rear end view, and a front end view, respectively.

As shown and previously stated, the mounting member 20 (or fixing member 21) includes the

mounting plate section 11 (or fixing plate section 16) which is provided with a plurality of openings 40. These openings 40 are used to fix its associated member to the cradle or to the vehicle body. The stationary bearing sections 13 (or 18) and 12 (or 17) respectively extend from one of opposite longer sides and one of opposite shorter sides of the mounting plate section 11 (or fixing plate section 16) along and perpendicularly to the latter. The rotatable bearing section 15 (or 19) is positioned in the vicinity of that corner of the plate section 11 (or 16) where the other sides which lack the stationary bearing sections 13 and 12 (or 18 and 17) join each other. The rotatable bearing section 15 (or 19) is rotatable 90 degrees about a pin 42 as indicated by an arrow in Fig. 5A and, in the configuration shown in Figs. 1 and 2, positioned such that the general plane of its upright portion extends parallel to that of the stationary bearing section 13 (or 18). A stop 43 is provided for positively positioning the plane of the upright portion of the rotatable bearing section 15 (or 19) parallel to that of the stationary bearing section 13 (or 18). Each of the rotatable bearing section 15 (or 19) and the stationary bearing section 13 (or 18) is provided with an opening 44 in which the male screw 22 (Fig. 2 or 4) for openably connecting the members 20 and 21 may be inserted.

Figs. 6A to 6E shows the mounting member 20 (or fixing member 21) of Fig. 3 as viewed in five different directions. Specifically, Figs. 6A, 6B, 6C, 6D and 6E are, respectively, a plan view, a side elevation as seen from the left, a side elevation as seen from the right, a rear end view, and a front end view. The back view is omitted since it is the same as that of Fig. 5. As shown, the rotatable bearing section 15 (or 19) is rotated 90 degrees from the position of Fig. 5 such that the plane of the upright portion thereof extends parallel to that of the stationary bearing section 12 (or 17). In this configuration, the mounting member 20 is openable in the manner shown in Fig. 3.

Referring to Figs. 7A to 7D, there is shown the mount in which the mounting member 20 and the fixing member 21 are assembled with the rotatable bearing sections 15 and 19 conditioned as shown in Fig. 5. Specifically, Figs. 7A, 7B, 7C and 7D show the mount in a plan view, a side elevation as seen from the left, a rear end view, and a front end view, respectively. The mounting member 20 and the fixing member 21 are angularly movable toward and away from each other about the male screws 22 and over a range of 0 to 90 degrees, as indicated by an arrow in Fig. 7B. The male screws 22 may be secured to fix the members 20 and 21 at a desired angular position. When the angular distance between the members 20 and 21 is zero, the stationary bearing sections 12 and 17 which are

not used do not interfere with the opening and closing movements because they are located at the opposite side to the male screws 22 and, as shown in Fig. 7D, configured not to abut against each other.

Fig. 8A to 8D shows the mount in which the mounting member 20 and the fixing member 21 are assembled with the rotatable bearing sections 15 and 19 held in the condition of Fig. 6. Specifically, Figs. 8A, 8B, 8C and 8D are, respectively, a plan view, a side elevation as seen from the left, a side elevation as seen from the right, and a front end view. In Fig. 8, as in Fig. 7, the mounting member 20 and the fixing member 21 are angularly movable toward and away from each other about the male screws 22 and over a range of 0 to 90 degrees, as indicated by an arrow in Fig. 8D. The members 20 and 21 are fixed in a desired angular position by fastening the male screws 22. The stationary bearing sections 13 and 18 which are not used are located at the opposite side to the male screws 22 and, as shown in Fig. 8B, aligned with each other. Again, this prevents those bearing sections 13 and 18 from interfering with the opening and closing movements of the members 20 and 21.

A reference will be made to Figs. 9A to 9B and 10A to 10C for describing the stationary and rotatable bearing sections in further detail. Specifically, Figs. 9A and 9B are, respectively, an enlarged front view and an enlarged side elevation of the stationary bearing section, as indicated by X in Fig. 5D. It is to be noted that the portion X of Fig. 5D is common to all the stationary bearing sections 12, 13, 17 and 18. Figs. 10A, 10B and 10C are, respectively, a plan view, a front end view, and a side elevation as seen from the left, each showing the rotatable bearing section 15 or 19 in an enlarged scale.

In Figs. 9 and 10, the stationary bearing sections 12, 13, 17 or 18 includes an undulated portion 51 while the rotatable bearing section 15 or 19 includes an undulated portion 54. The undulated portions 51 and 54 are meshed with each other to set up a desired angle between the mounting plate 20 and the fixing plate 21. The undulated portions 51 and 54 are firmly fixed in place by the male screw 22 through the opening 44. Such prevents the mounting angle of the telephone 10 from being easily changed by shocks and impacts. Further, an opening 52 is provided so that a fixing pin 42, Fig. 5, may be passed therethrough. The extreme end 53 of the rotatable bearing section 15 or 19 is so shaped as to be engageable with the stop 43.

As described above, in accordance with the present invention, the direction and angle of opening and closing movements of a mount for a telephone cradle are readily changeable by simply rotating rotatable bearing sections, which are pro-



vided one on each of a mounting and a fixing member, and changing the positions of male screws. Since stationary bearing sections which are not used do not interfere with the opening and closing movements of the mount, a sufficiently opening and closing angle is guaranteed. Hence, a telephone can be manipulated with unprecedented efficiency. Further, even if the telephone is mounted crosswise, the end portions of the mount do not show themselves and, therefore, promote space-saving and pleasant design.

In addition, the mounting member and the fixing member share exactly the same configuration allowing the mount to be produced on a quantity basis and, therefore, at low cost.

Claims

1. A mount for a telephone cradle, including a mounting member (20) for mounting the telephone cradle and a fixing member (21) characterised in that the mounting member (20) and the fixing member (21) each include a plate section (11) (16), in that there are provided first (12,17) and second (13,18) stationary bearing sections on and extending along one side of and perpendicular to each respective plate section (11)(16), the first (12,17) and second (13,18) stationary bearing sections being respectively on sides which are perpendicular to one another and being provided with a respective first and a second opening (44), and in that there are further provided on each of the plate sections (11)(16) a respective rotatable bearing section (15)(19), each rotatable bearing section (15,19) having a third opening (44) and being rotatable such that the third openings (44) may be aligned with the first and second openings (44).
2. A mount as claimed in claim 1, characterised in that each of the first (12,17) and second (13,18) stationary bearing sections is provided with a first undulated portion (51) around the first or second opening (44) associated with the stationary bearing section, the rotatable bearing section (15,19) being provided with a second undulated portion (54) around the third opening and corresponding to the first undulated portions (51).
3. A mount as claimed in claim 2, characterised in that each rotatable bearing section (15,19) has a projecting extreme end (53).
4. A mount as claimed in claim 1, characterised in that the plate section (16) of the fixing member (21) is provided with openings (40) for

fixing the plate section (16) of said fixing member (21) to a predetermined body.

5. A mount as claimed in claim 4, characterised in that the predetermined body is a vehicle body.
6. A mount as claimed in claim 3, characterised in that the plate section (11) of the mounting member (20) has a stop (43) for stopping the rotation of said rotatable bearing section, the stop (43) corresponding to the projecting extreme end (53).

15 Revendications

1. Monture pour support de téléphone, comprenant un élément de montage (20) pour le montage du support du téléphone et un élément de fixation (21), caractérisée en ce que l'élément de montage (20) et l'élément de fixation (21) comprennent chacun une section de plaque (11) (16), en ce qu'on a prévu des première (12, 17) et seconde (13, 18) sections d'appui fixes sur chaque section respective de plaque (11) (16), s'étendant le long d'un côté de chaque section et perpendiculairement à chaque section, les première (12, 17) et seconde (13, 18) sections d'appui fixes étant respectivement sur des côtés qui sont perpendiculaires l'un à l'autre et munies de première et seconde ouvertures respectives (44), et en ce qu'on prévoit en outre sur chacune des sections de plaque (11) (16) une section respective d'appui rotative (15) (19), chaque section d'appui rotative (15, 19) ayant une troisième ouverture (44) et pouvant tourner de façon que les troisièmes ouvertures (44) puissent être en alignement avec les première et seconde ouvertures (44).
2. Monture selon la revendication 1, caractérisée en ce que chacune des première (12, 17) et seconde (13, 18) sections d'appui fixes comporte une première partie ondulée (51) autour de la première ou de la seconde ouverture (44) associée à la section d'appui fixe, la section d'appui rotative (15, 19) comportant une seconde partie ondulée (54) autour de la troisième ouverture et correspondant à la première partie ondulée (51).
3. Monture selon la revendication 2, caractérisée en ce que chaque section d'appui rotative (15, 19) a une extrémité en saillie (53).
4. Monture selon la revendication 1, caractérisée en ce que la section de plaque (16) de l'élément de fixation (21) comporte des ouvertures



(40) pour la fixation de la section de plaque (16) dudit élément de fixation (21) à un corps prédéterminé.

5. Monture selon la revendication 4, caractérisée en ce que le corps prédéterminé est la caisse d'un véhicule.
6. Monture selon la revendication 3, caractérisée en ce que la section de plaque (11) de l'élément de montage (20) comporte une butée (43) pour arrêter la rotation de ladite section d'appui rotative, la butée (43) correspondant à l'extrémité en saillie (53).

Patentansprüche

1. Halterung für ein Telefon-Traggestell mit einem Halteelement (20) zum Anordnen des Telefon-Traggestells und einem Befestigungselement (21), **dadurch gekennzeichnet**, daß das Halteelement (20) und das Befestigungselement (21) je einen Plattenabschnitt (11)(16) aufweisen, daß erste (12,17) und zweite (13,18) feste Lagerabschnitte vorgesehen sind, die an jedem zugehörigen Plattenabschnitt (11, 16) entlang einer Seite und senkrecht dazu angeordnet sind, wobei die ersten (12,17) und zweiten (13,18) festen Lagerabschnitte jeweils auf Seiten angeordnet sind, die senkrecht zueinander sind und jeweils eine erste und zweite Öffnung (44) aufweisen, und daß ferner auf jedem Plattenabschnitt (11)(16) ein zugehöriger schwenkbarer Lagerabschnitt (15)(19) vorgesehen ist, wobei jeder schwenkbare Lagerabschnitt (15,19) eine dritte Öffnung (44) aufweist und derart schwenkbar ist, daß die dritten Öffnungen (44) mit der ersten und zweiten Öffnung (44) ausgerichtet werden können.
2. Halterung nach Anspruch 1, **dadurch gekennzeichnet**, daß jeder der ersten (12,17) und zweiten (13,18) festen Lagerabschnitte einen ersten welligen Abschnitt (51) um die erste oder zweite Öffnung (44) aufweist, die dem festen Lagerabschnitt zugehörig ist, wobei der schwenkbare Lagerabschnitt (15, 19) einen zweiten welligen Abschnitt (54) um die dritte Öffnung aufweist, der mit den ersten welligen Abschnitten (51) zusammenwirkt.
3. Halterung nach Anspruch 2, **dadurch gekennzeichnet**, daß jeder schwenkbare Lagerabschnitt (15, 19) ein vorstehendes äußeres Ende (53) aufweist.
4. Halterung nach Anspruch 1, **dadurch gekennzeichnet**, daß der Plattenabschnitt (16) des

Befestigungselements (21) Öffnungen (40) zum Fixieren des Plattenabschnitts (16) des Befestigungselements (21) an einem bestimmten Körper aufweist.

5. Halterung nach Anspruch 4, **dadurch gekennzeichnet**, daß der bestimmte Körper ein Fahrzeugkörper ist.
6. Halterung nach Anspruch 3, **dadurch gekennzeichnet**, daß der Plattenabschnitt (11) des Halteelements (20) einen Anschlag (43) zum Begrenzen des Schwenkens des schwenkbaren Lagerabschnitts aufweist, wobei der Anschlag (43) mit dem vorstehenden äußeren Ende (53) zusammenwirkt.