

WHAT IS CLAIMED IS:

1. A vehicle comprising:
 - a vehicle main body having a passenger compartment and a rear compartment located more rearward than the passenger compartment;
 - a rear hatch provided on the vehicle main body and configured to open and close the rear compartment;
 - a cooling box disposed in the rear compartment;
 - a first communication device configured to communicate with an external server;
 - a second communication device having a communication distance shorter than that of the first communication device;
 - a locking device configured to lock the rear hatch; and
 - a processor,the processor being configured to receive information about an opening signal from the server through the first communication device, and to open the rear hatch when the processor receives the opening signal through the second communication device.
2. The vehicle according to claim 1, wherein
 - the cooling box is disposed closer to the rear hatch than the passenger compartment.
3. The vehicle according to claim 1, further comprising
 - a front-row seat and a rear-row seat disposed more rearward than the front-row seat, wherein
 - the front-row seat and the rear-row seat are disposed in the passenger compartment,
 - the passenger compartment and the rear compartment are separated by

the rear-row seat, and

by deforming at least a part of the rear-row seat, an object contained in the cooling box can be taken out from the passenger compartment.

4. The vehicle according to any one of claims 1 to 3, further comprising:
a first side surface and a second side surface arranged in a width direction;
a first rear wheel disposed more rearward than a center in a front-back direction of the vehicle main body and on the first side surface side; and
a second rear wheel disposed more rearward than the center and on the second side surface side, wherein
the cooling box is disposed between the first rear wheel and the second rear wheel.

5. The vehicle according to any one of claims 1 to 4, wherein
the cooling box is disposed at a center in a width direction of the vehicle main body.

6. The vehicle according to any one of claims 1 to 5, wherein
the cooling box is provided so as to be movable in a front-back direction of the vehicle main body within the rear compartment.