

【DESCRIPTION】**【Disclosure Title】****CLOTHING-MANUFACTURING 3D PRINTER****【Technical Field】**

5 **【1】** The disclosure relates to a clothing-manufacturing 3D printer, and more particularly to a clothing-manufacturing 3D printer of which a needle unit for clothing manufacturing is moved forward and backward by a simple structure.

【Background Art】

10 **【2】** In general, a flat-knitting machine or the like knitting machine is employed to manufacture clothing. The flat-knitting machine knits cloth with a programmed pattern while a carriage feeds a plurality of needles arranged in a needle unit with threads by reciprocating left and right above the needle unit. A principle of actuating a conventional flat-knitting machine is as follows. The needle of the needle unit is formed with a protrusion, and the carriage is formed with a track
15 corresponding to the butt on the rear thereof, so that the protrusion can move along the track while the carriage reciprocates. With this structure, the needles move forward or backward as a whole, thereby performing knitting. Such general things about the flat-knitting machine have been disclosed in Korean Patent Application No. 10-2020-0007693, etc.

20 **【3】** However, a conventional knitting machine has had a problem that the carriage needs to reciprocate between both ends of the arranged needle unit.

25 **【4】** Further, a forward and backward moving distance of the needle unit is varied depending on the track formed in the carriage, and therefore there has been a problem of difficulty in freely adjusting the forward and backward moving distance of the needle unit.

【Disclosure】

【Technical Problem】

[5] An aspect of the disclosure is to solve such conventional problems, and provide a clothing-manufacturing 3D printer with a new actuating system.

5 **[6]** Another aspect of the disclosure is to provide a clothing-manufacturing 3D printer in which forward and backward movement of a needle unit is freely adjustable.

【Technical Solution】

[7] According to an embodiment of the disclosure, there is provided a 3D printer for clothing, comprising: a needle unit comprising a needle hook formed in an end
10 portion and a protrusion formed in a middle region; a connector comprising a screw thread formed to mesh with the protrusion of the needle unit; and an actuator configured to actuate the connector to rotate, wherein the needle unit meshing with the screw thread is moved forward or backward as the connector is rotated by the actuator.

15 **[8]** Here, the connector is movable closer to or far away from the needle unit in a direction intersecting with a lengthwise direction of the needle unit, thereby selectively transmitting or releasing an actuation force.

[9] The needle units are provided in plural, the connector are provided in plural, the connectors are fewer than the needle units, and the connector selectively
20 meshes with the but of the needle unit while moving in parallel with a direction where the plurality of needle units are arranged.

[10] The actuator is rotatable forward and backward to generate a forward and backward actuation force for the needle unit, and the actuator further comprises an encoder to adjust the number of rotations of the connector.

25 **【Advantageous Effects】**

[11] According to the disclosure, there is provided a clothing-manufacturing 3D printer with a new actuating system.

[12] Further, there is provided a clothing-manufacturing 3D printer in which forward and backward movement of a needle unit is freely adjustable.

5 **【Description of Drawings】**

[13] FIG. 1 is a perspective view illustrating a main configuration of a clothing-manufacturing 3D printer according to a first embodiment of the disclosure,

[14] FIG. 2 is a perspective view illustrating an actuation mechanism of the clothing-manufacturing 3D printer according to the first embodiment of the disclosure,

10 **[15]** FIG. 3 illustrates a principle of actuating a needle unit in the clothing-manufacturing 3D printer according to the first embodiment of the disclosure,

[16] FIG. 4 is a perspective view showing a needle unit, a connector and an actuator of the clothing-manufacturing 3D printer according to the first embodiment of the disclosure,

15 **[17]** FIG. 5 is a perspective view showing a supporting plate of the clothing-manufacturing 3D printer according to the first embodiment of the disclosure,

[18] FIG. 6 illustrates actuation of a solenoid valve of the clothing-manufacturing 3D printer according to the first embodiment of the disclosure,

[19] FIG. 7 is a perspective view illustrating an actuation mechanism of a clothing-manufacturing 3D printer according to a second embodiment of the disclosure, and

20 **[20]** FIG. 8 illustrates actuation of the clothing-manufacturing 3D printer according to the second embodiment of the disclosure.

【Mode for Carrying out Disclosure】

[21] Below, a clothing-manufacturing 3D printer according to a first embodiment of
25 the disclosure will be described in detail with reference to the accompanying

drawings.

[22] FIG. 1 is a perspective view illustrating a main configuration of a clothing-manufacturing 3D printer according to a first embodiment of the disclosure, and FIG. 2 is a perspective view illustrating an actuation mechanism of a needle unit and a connector. As shown therein, the clothing-manufacturing 3D printer according to the disclosure includes a needle unit 10, a connector 20, an actuator 30, a supporting plate 40 and a solenoid valve 50.

[23] The needle unit 10 includes a main body 11 formed long in a lengthwise direction, a needle hook 12 formed at one end of the main body 11 and hooking a thread, a protrusion 13 formed in a certain region of the main body 11. The needle hook 12 has a structure by which a thread positioned in front thereof is hooked as the needle unit 10 is moved forward, and the hooked thread is pulled backward as the needle unit 10 is moved backward. The protrusion 13 protrudes outward from the certain region of the main body 11 and meshes with the connector 20. The protrusion 13 in the drawings is formed by bending the main body 11 twice, but the protrusion may have any structure without being bent twice as long as it protrudes from the main body 11.

[24] The connector 20 transmits a rotational force generated by the actuator 30 to the needle unit 10 so that the needle unit 10 can move forward and backward, and has a body formed with a screw thread 21 with which the protrusion 13 of the needle unit 10 meshes. A width of a groove of the screw thread 21 may be the same as or a little wider than the width of the protrusion 13 of the needle unit 10, so that the protrusion 13 of the needle unit 10 can be inserted in the groove. Therefore, as shown in FIG. 3, when the connector 20 rotates, the protrusion 13 of the needle unit 10 inserted in the groove of the screw thread 21 moves forward or backward along

the screw thread 21 while interlocking with the rotation of the connector 20. The forward or backward moving distance of the needle unit 10 is varied depending on the number of rotations of the connector 20.

[25] The actuator 30 is embodied by a motor 51 that can rotate the connector 20.

5 In this embodiment, the motor is described by way of example. However, any actuator may be used as long as it can rotate the connector 20. Further, the actuator 30 may include an encoder 32 to sense the number of rotations of the connector 20 and control the forward and backward moving distance of the needle unit 10.

10 **[26]** The connectors 20 may be provided fewer than the needle units 10, and be selectively in contact with the needle units 10 while the connector 20 moves left and right on the plurality of needle units 10 arranged side by side in a row, thereby transmitting an actuation force to the needle unit 10.

[27] FIG. 4 is a perspective view showing a needle unit, a connector and an
15 actuator of the clothing-manufacturing 3D printer according to the first embodiment of the disclosure, and FIG. 5 is a perspective view showing a supporting plate of the clothing-manufacturing 3D printer according to the first embodiment of the disclosure. As shown therein, the supporting plate 40 is provided to support the connector 20 and the actuator 30. The supporting plate 40 includes a first plate 41 and a second
20 plate 42, and the first plate 41 is mounted to a rail 43 and movable in left and right directions intersecting with a lengthwise direction of the needle unit 10. The second plate 42 is mounted to the first plate 21 and movable up and down, and provided as many as the number of connectors 20 and the number of actuators 30 to support the connector 20 and the actuator 30.

25 **[28]** FIG. 6 illustrates actuation of a solenoid valve of the clothing-manufacturing

3D printer according to the first embodiment of the disclosure. As shown therein, the solenoid valves 50 are respectively connected to the second plates 42, so that the second plates 42 can move up and down. Therefore, the solenoid valve 50 actuates the second plate 42 to independently move up and down, so that the connector 20 and the needle unit 10 can mesh with or be released from each other for linking or unlinking.

[29] From now on, the actuation of the clothing-manufacturing 3D printer according to the first embodiment will be described.

[30] First, the supporting plate 40 supporting the connector 20 and the actuator 30 is moved left and right along a rail 43, and placed at a position corresponding to the needle unit 10 to be actuated. Then, the solenoid valve 50 actuates the second plate 42 of the supporting plate 40 to move upward. As the second plate 42 moves upward, the connector 20 supported on the second plate 42 also moves upward, and therefore the protrusion 13 of the needle unit 10 is inserted in the groove of the screw thread 21 of the connector 20.

[31] Next, the actuator 30 actuates the connector 20 to rotate, and the rotation of the connector 20 causes the protrusion 13 meshing with the screw thread 21 to moves forward, thereby moving the needle unit 10 forward. At this time, the number of rotations of the connector 20 is sensed by the encoder 32, and the forward moving distance of the needle unit 10 is adjusted based on the number of rotations of the connector 20.

[32] When the needle unit 10 moves forward up to a given position, the thread is hooked to the needle hook 12 of the needle unit 10. Then the actuator 30 is reversely rotated to move the needle unit 10 backward, and therefore the thread hooked to the needle hook 12 is also moved backward. With such an actuation

mechanism, the needle unit 10 moves forward and backward to perform knitting, and the supporting plate 40 reciprocates to manufacture clothing having a desired size or a desired shape.

[33] Below, a clothing-manufacturing 3D printer according to a second embodiment of the disclosure will be described. In the following description, descriptions about elements like those of the first embodiment will be omitted. FIG. 7 is a perspective view illustrating an actuation mechanism of a clothing-manufacturing 3D printer according to a second embodiment of the disclosure, and FIG. 8 illustrates actuation of the clothing-manufacturing 3D printer according to the second embodiment of the disclosure. As shown therein, in the clothing-manufacturing 3D printer according to the second embodiment of the disclosure, the screw thread 21 formed in the connector 20 is provided as a self-reversing screw. The self-reversing screw refers to a screw of which screw threads are not formed only in one direction but formed to intersect so that an object moving along the screw can move in a reverse direction to a previous moving direction when the object reaches a certain position.

[34] When the thread is hooked to the needle hook 12 of the needle unit 10 as the needle unit 10 moves forward up to the given position, the protrusion of the needle unit 10 is placed at a position where direction switching of the self-reversing screw is possible, and the needle unit 10 is moved backward even though the actuator 30 rotates in the same direction. At this time, the thread hooked to the needle hook 12 is also moved backward. With such an actuation mechanism, the needle unit 10 moves forward and backward to perform knitting, and the supporting plate 40 reciprocates to manufacture clothing having a desired size or a desired shape.

[35] The scope of the disclosure is not limited to the foregoing embodiments, but

may be embodied in various forms within the scope of the appended claims. The scope of the claims appended in the disclosure falls within various scopes in which any changes can be made by a person having ordinary knowledge in the art to which the disclosure pertains, without departing from the gist of the disclosure defined in the claims.

【Industrial Applicability】

[36] There is provided a 3D printer for clothing, which includes a needle unit formed with a needle hook in an end portion and a protrusion in a middle region, a connector formed with a screw thread to mesh with the protrusion of the needle unit, and an actuator actuating the connector to rotate, wherein the needle unit meshing with the screw thread is moved forward or backward as the connector is rotated by the actuator.

【CLAIMS】**【Claim 1】**

A knitting machine for clothing, comprising:

a needle unit comprising a needle hook formed in an end portion and a protrusion formed in a middle region;

a connector comprising a screw thread formed to mesh with the protrusion of the needle unit; and

an actuator configured to actuate the connector to rotate,

wherein the needle unit meshing with the screw thread is moved forward or backward as the connector is rotated by the actuator.

【Claim 2】

The knitting machine for clothing according to claim 1, wherein the connector is movable closer to or far away from the needle unit in a direction intersecting with a lengthwise direction of the needle unit.

【Claim 3】

The knitting machine for clothing according to claim 1 or 2, wherein the needle units are provided in plural and arranged side by side.

【Claim 4】

The knitting machine for clothing according to claim 3, wherein the connectors are provided in plural and arranged side by side.

【Claim 5】

The knitting machine for clothing according to claim 4, wherein the connectors

are fewer than the needle units, and the connector selectively meshes with the protrusion of the needle unit while moving in parallel with an direction where the plurality of needle units are arranged.

【Claim 6】

The knitting machine for clothing according to claim 1, wherein the actuator is rotatable forward and backward.

【Claim 7】

The knitting machine for clothing according to claim 1, wherein the actuator further comprises an encoder.

【Claim 8】

The knitting machine for clothing according to claim 2, wherein the connector is moved by a solenoid valve.

【Claim 9】

The knitting machine for clothing according to claim 8, wherein the connectors and the solenoid valves are provided in plural, and the solenoid valves individually move the connectors.

【Claim 10】

The knitting machine for clothing according to claim 1, wherein the screw thread of the connector is provided as a self-reversing screw.