CLAIMS:

1. A method of recycling tires comprising the steps of:

- placing tires and/or pieces of tires within a casing or mold;
- applying binders to the tires and/or pieces of tires so that the tires are bound together wherein the binders are an adhesive or adhesives in combination with metal pins, screws, nails, nuts and bolts, wire and steel and/or nylon bands;
- applying a reinforcing means through the tires and/or pieces of tires;
- melting and pouring an encapsulating means over the top of the tires, binders and the reinforcing means to encapsulate them inside the casing or mold and the encapsulating means and wherein the encapsulating means is plastic and wherein the encapsulating means is heated to a temperature which is sufficiently high enough to soften and melt the encapsulating means such that it becomes moldable so that it is spread to cover and encapsulate the tires, binders and the reinforcing means; and
- causing or allowing the encapsulating means to set such that a recycled product is formed.

2. A method according to claim 1, wherein waste materials are placed within the casing or mold before an adhesive is added and when the adhesive is applied it binds the tires and waste materials together.

3. A method according to claim 2, wherein the waste material comprises:

- plastic;
- electronic components and circuit boards;
- batteries;
- pieces of metal and machine components;
- glass and light bulbs;
- asbestos, fibrous cement and/or concrete; and/or
- fabrics.

4. A method according to claim 1, 2 or 3, wherein the tires or pieces of tires are arranged in a generally concentric arrangement.

5. A method according to any one of the preceding claims, wherein the reinforcing means is metal rods, metal pins and/or metal wire.

6. A method according to any one of the preceding claims, wherein the reinforcing means are in addition to going through the tires arranged in a grid like a pattern and are configured such that they are placed on top of or surround the tires and/or pieces of tires.

7. A method according to any one of the preceding claims, wherein the casing:

- has a base and four side walls connected to the base;
- has a leach proof lining;
- is leach proof;
- blocks or resists UV; and/or
- is fire resistant.

8. A recycled product created according to the method of any one of the preceding claims.

9. A building component having:

- a casing;
- tires and/or pieces of tires housed within the casing wherein the tires are bound together by binders wherein the binders are an adhesive or adhesives in combination with metal pins, screws, nails, nuts and bolts, wire and steel and/or nylon bands;
- a reinforcing means which has been forced through the tires; and
- an encapsulating means which encapsulates the tires and/or pieces of tires and the binders and the reinforcing means within the casing and wherein the encapsulating means is plastic and had been heated to a temperature which was sufficiently high enough to soften and melt the encapsulating means such that it was moldable and spread to cover and encapsulate the tires, binders and the reinforcing means.

10. A building component according to claim 9, wherein the component also has waste materials housed within the casing which are bound together and bound to the tires and/or pieces of tires.

11. A building component according to claim 10, wherein the waste material comprises:

- plastic;
- electronic components and circuit boards;
- batteries;
- pieces of metal and machine components;
- glass and light bulbs;

- asbestos, fibrous cement and/or concrete; and/or
- fabrics.

12. A building component according to any one of claims 9, 10, or 11, wherein the tires or pieces of tires are arranged in a generally concentric arrangement.

13. A building component according to any one of claims 9-12, wherein the reinforcing means are metal pins and/or metal rods.

14. A building component according to any one of claims 9-13, wherein the reinforcing means in addition to being forced through the tires are arranged in a grid like pattern and are configured such that they are on top of or surround the tires and/or pieces of tires.

15. A building component according to any one of claims 9-14, wherein the casing:

- comprises a base and four side walls connected to the base;
- has a leach proof lining;
- is leach proof;
- blocks or resists UV; and/or
- is fire resistant.