

PRODUCT DISPENSING SYSTEM

Field

[0001] The present invention relates to a product
5 dispensing system, and more particularly, to a product
dispensing system that is applied to a vending machine
vending product such as canned beverage or beverage in a
plastic bottle and that appropriately discharges product
stored in a product storage passage.

10 Background

[0002] In the related art, in a vending machine vending
product such as canned beverage or beverage in a plastic
bottle, a product storage rack is disposed in a product
storage in a main cabinet which is a main body of the
15 vending machine. The product storage rack includes a
product storage passage that extends in a vertical
direction and a product discharging device that is disposed
in a lower part of the product storage passage.

[0003] The product discharging device includes a lower
20 pedal and an upper pedal. The lower pedal and the upper
pedal are linked to an AC solenoid as an actuator via a
link and move forward to and backward from a product
storage passage by supplying power to the AC solenoid.

[0004] In the product discharging device, in a standby
25 state, the upper pedal moves backward from the product
storage passage and the lower pedal moves forward to the
product storage passage. Accordingly, the lower pedal
comes in contact with a lowest product stored in the
product storage passage to regulate downward movement of
30 product stored in the product storage passage.

[0005] In the product discharging device in a lower part
of the product storage passage storing the corresponding
product, when a product discharge command is issued, the

upper pedal moves forward to the product storage passage via the link by supplying power to the AC solenoid, and comes in contact with a second lowest product to regulate downward movement of the product and the products stored above the product. By supplying power to the AC solenoid, the lower pedal moves backward from the product storage passage, only the lowest product is discharged downward, and the lower pedal moves forward to the product storage passage by a biasing force of a spring when the lowest product gets out of the lower pedal. Thereafter, when the supply of power to the AC solenoid is stopped and the AC solenoid is in a non-powered state, the backward movement of the lower pedal having moved forward to the product storage passage is regulated and the upper pedal moves backward from the product storage passage, whereby the product discharging device is returned to the standby state.

[0006] In the product storage rack, two product storage passages are generally adjacent to each other in the front-rear direction and thus the product discharging devices respectively applied to the product storage passages are coupled to each other back to back and are disposed in the product storage passages. In the product discharging devices, the AC solenoid as a drive source is required for each of the coupled product discharging devices.

[0007] Accordingly, a product dispensing system has been proposed in which product discharging devices from which an AC solenoid has been removed are disposed back to back, a drive source and a cam member are disposed therebetween, and the product discharging devices are driven by driving of the drive source and rotation of the cam member so as to achieve a decrease in manufacturing cost by reducing the number of drive sources (for example, see Patent Literature 1).

Citation List

Patent Literature

[0008] Patent Literature 1: JP 2749917 B2

Summary

5 Technical Problem

[0009] In the product dispensing system proposed in Patent Literature 1, since the product discharging devices from which an AC solenoid has been removed are disposed back to back and the drive source and the cam member are
10 disposed therebetween, it is possible to decrease the number of drive sources in comparison with the number of product discharging devices, but it is difficult to separate two product discharging devices which are elements coupled back to back from each other to use only anyone.
15 That is, the product dispensing system proposed in Patent Literature 1 can be applied to a product storage rack including an even number of product storage passages adjacent in the front-rear direction but cannot be used as individual product discharging devices for a product
20 storage rack including an odd number of product storage passages. In the product dispensing system, in general, two types of product discharging devices having different widths are prepared to correspond to types of the product storage rack, that is, product having a relatively small
25 maximum width and product having a relatively large maximum width, and the product discharging device having a width corresponding to the maximum width of the product stored in the product storage rack is mounted in the product storage rack.

30 [0010] The present invention is made in consideration of the above-mentioned circumstances and an object thereof is to provide a product dispensing system that can achieve a decrease in manufacturing cost and flexibly work depending

on the number of product storage passages adjacent in the front-rear direction.

Solution to Problem

[0011] To achieve the above-described object, a product
5 dispensing system according to the present invention
includes: one product discharging device that is applied to
one product storage passage storing an input product in a
vertical direction, regulates downward movement of the
product stored in the one product storage passage in a
10 standby state, and discharges a lowest product stored in
the one product storage passage downward in an activated
state; and the other product discharging device that is
applied to the other product storage passage being adjacent
to the one product storage passage and storing an input
15 product in the vertical direction thereof, regulates
downward movement of the product stored in the other
product storage passage in a standby state, and discharges
a lowest product stored in the other product storage
passage downward in an activated state, the one product
20 discharging device and the other product discharging device
being coupled to each other back to back, wherein the one
product discharging device includes a drive source for the
one product discharging device and the other product
discharging device, a driving force applying unit
25 configured to alternatively select the one product
discharging device and the other product discharging device
in accordance with a discharge command and to apply a
driving force from the drive source to the selected product
discharging device when the discharge command is issued,
30 and a control unit configured to perform sold-out
processing of considering that only the product discharging
device is out of order and determining that the products of
the product storage passage of the product discharging

device is sold out when the product discharging device which is alternatively selected and supplied with a driving force by the driving force applying unit is not activated within a predetermined time.

5 [0012] Moreover, in the above-described product dispensing system according to the present invention, the control unit performs a retry process of performing the operation of causing the driving force applying unit to select the product discharging device and to apply the
10 driving force to the selected product discharging device again when the product discharging device which is alternatively selected and supplied with a driving force by the driving force applying unit is not activated within the predetermined time.

15 [0013] Moreover, in the above-described product dispensing system according to the present invention, the control unit causes the product discharging device to return to a predetermined standby position and performs the retry process when the product discharging device which is
20 alternatively selected and supplied with a driving force by the driving force applying unit is not activated within the predetermined time.

[0014] Moreover, in the above-described product dispensing system according to the present invention, the
25 driving force applying unit includes: an output gear that is disposed to be rotatable positively and reversely about its own axis, rotates positively when the discharge command is issued to the one product discharging device, and rotates reversely when the discharge command is issued to
30 the other product discharging device; and a link lever that is disposed to be rotatable about its own axis in correspondence with the product discharging devices, sets the corresponding product discharging device to the standby

state in a normal state, and drives the corresponding product discharging device when the link lever is supplied with the driving force to rotate by rotation of the output gear.

5 [0015] Moreover, in the above-described product dispensing system according to the present invention, the drive source is common to the one product discharging device and the other product discharging device.

[0016] Moreover, in the above-described product
10 dispensing system according to the present invention, the drive source is a DC motor.

Advantageous Effects of Invention

[0017] According to the present invention, since one product discharging device includes the drive source for
15 the one product discharging device and the other product discharging device and the driving force applying unit that alternatively selects the one product discharging device and the other product discharging device in accordance with the discharge command and applies the driving force from
20 the drive source to the selected product discharging device when the discharge command is issued, it is possible to decrease the number of drive sources in comparison with the number of product discharging devices and thus to decrease the manufacturing cost. Since one product discharging
25 device includes the drive source and the driving force applying unit, it is also possible to use only the one product discharging device. That is, the present invention can be applied to a product storage device in which an odd number of product storage passages are arranged in the
30 front-rear direction as well as a product storage device in which an even number of product storage passages are arranged in the front-rear direction. Accordingly, it is possible to achieve a decrease in manufacturing cost and

flexibly work depending on the number of product storage passages adjacent in the front-rear direction.

Brief Description of Drawings

[0018] FIG. 1 is a cross-sectional side view
5 illustrating an internal structure of a vending machine to which a product dispensing system according to an embodiment of the present invention is applied when viewed from the right side.

FIG. 2 is a side view illustrating the product
10 dispensing system illustrated in FIG. 1 when viewed from the right side.

FIG. 3 is a perspective view illustrating the product dispensing system illustrated in FIG. 1 when viewed from the front-right side.

15 FIG. 4 is a perspective view illustrating the product dispensing system illustrated in FIG. 1 when viewed from the rear-right side.

FIG. 5 is a perspective view illustrating a first product discharging device illustrated in FIGS. 2 to 4 when
20 viewed from the rear-right side.

FIG. 6 is a diagram schematically illustrating a principal part of the first product discharging device illustrated in FIGS. 2 to 5 when viewed from the right side.

FIG. 7 is a diagram schematically illustrating a
25 principal part of the first product discharging device illustrated in FIGS. 2 to 5 when viewed from the right side.

FIG. 8 is a diagram schematically illustrating a principal part of the first product discharging device illustrated in FIGS. 2 to 5 when viewed from the right side.

30 FIG. 9 is a perspective view illustrating a base of the first product discharging device illustrated in FIGS. 2 to 5.

FIG. 10 is a perspective view illustrating a bearing

portion and a harness guide attached to the base illustrated in FIG. 9.

FIG. 11 is a perspective view illustrating a first sold-out link and a second sold-out link.

5 FIG. 12 is a side view illustrating a principal part of the product dispensing system illustrated in FIGS. 2 to 4.

FIG. 13 is a side view illustrating a relationship of the first sold-out link and a first sold-out detection
10 switch when a lower pedal is changed to a product-present standby posture.

FIG. 14 is a perspective view of a rotation stopper constituting the first product discharging device illustrated in FIGS. 2 to 5.

15 FIG. 15 is a perspective view illustrating a relationship of the first sold-out link and the first sold-out detection switch when the lower pedal moves backward.

FIG. 16 is an exploded perspective view illustrating principal parts of a drive unit in the first product
20 discharging device when viewed from the front-right side.

FIG. 17 is an exploded perspective view illustrating principal parts of the drive unit in the first product discharging device when viewed from the rear-left side.

FIG. 18 is a perspective view illustrating a second
25 product discharging device illustrated in FIGS. 2 to 4 when viewed from the front-right side.

FIG. 19 is a diagram schematically illustrating a principal part of the second product discharging device illustrated in FIGS. 2 to 4 and FIG. 18 when viewed from
30 the right side.

FIG. 20 is a perspective view illustrating a base of the second product discharging device illustrated in FIG. 18.

FIG. 21 is a perspective view illustrating a bearing portion and a guide attached to the base illustrated in FIG. 20.

FIG. 22 is a block diagram illustrating a
5 characteristic control system of the product dispensing system.

FIG. 23 is a perspective view illustrating the first product discharging device when viewed from the rear-right side.

10 FIG. 24 is a flowchart illustrating process details of a dispensing control process which is performed by a dispensing control unit.

FIG. 25 is a perspective view illustrating the first product discharging device when viewed from the rear-right
15 side.

FIG. 26 is a diagram illustrating operations of the principal parts of the drive unit when viewed from the front side.

FIG. 27 is a diagram illustrating the operations of
20 the principal parts of the drive unit when viewed from the rear-front side.

FIG. 28 is a flowchart illustrating process details of a retry process (1) in the dispensing control process illustrated in FIG. 24.

25 FIG. 29 is a flowchart illustrating process details of a retry process (2) in the dispensing control process illustrated in FIG. 24.

FIG. 30 is an exploded perspective view illustrating a modified example of the drive unit.

30 FIG. 31 is a perspective view illustrating a modified example of the product dispensing system.

Description of Embodiments

[0019] Hereinafter, a product dispensing system

according to an exemplary embodiment of the present invention will be described in detail with reference to the accompanying drawings.

[0020] FIG. 1 is a cross-sectional side view illustrating an internal structure of a vending machine to which a product dispensing system according to an embodiment of the present invention is applied when viewed from the right side. The vending machine exemplified herein vends product in a cooled or heated state and includes a main cabinet 1, an outer door 2, and an inner door 3.

[0021] The main cabinet 1 has a rectangular parallelepiped shape of which a front surface is opened by appropriately combining plural steel sheets and includes a product storage 4 having a heat-insulating structure therein. The outer door 2 serves to cover the front opening of the main cabinet 1 and is disposed at one edge portion of the main cabinet 1 so as to be opened and closed. The front surface of the outer door 2 is provided with elements required for vending product such as a display window, a product selection button, a bill input port, a coin input port, a return lever, a built-in display, a coin return port, and a product output port 2a. The inner door 3 is a heat-insulating door which is divided into upper and lower parts to cover the front opening of the product storage 4, an upper heat-insulating door 3a is disposed at a position inside the outer door 2 at one edge portion of the outer door 2 so as to be opened and closed, and a lower heat-insulating door 3b is disposed at one edge portion of the main cabinet 1 so as to be opened and closed. A product discharge port 3c for discharging a product to the outside of the product storage 4 is disposed in a lower part of the lower heat-insulating door 3b of the inner door

3.

[0022] In the vending machine, a product chute 5 is disposed in the product storage 4, a temperature control unit 6 is disposed in an area below the product chute 5
5 (hereinafter, also referred to as a "heat exchange area"), and a product storage rack 10 is disposed in an area above the product chute 5 (hereinafter, also referred to as a "product storage area").

[0023] The product chute 5 is a plate-like member that
10 guides a product discharged from the product storage rack 10 to the product discharge port 3c of the inner door 3 and is disposed to be gradually inclined downward toward the front side. Although not clearly illustrated in the drawing, plural vent holes (not illustrated) causing the
15 heat exchange area and the product storage area to communicate with each other are formed in the product chute 5.

[0024] The temperature control unit 6 serves to maintain the internal atmosphere of the product storage 4 in a
20 desired temperature state and includes an evaporator 6a, an electric heater 6b, and a blower fan 6c of a refrigeration cycle. In the temperature control unit 6, for example, when the blower fan 6c is driven in a state in which the refrigeration cycle operates, air cooled in the evaporator
25 6a is supplied upward through the vent holes of the product chute 5 and thus the product storage area can be maintained in a low-temperature state. On the other hand, when the blower fan 6c is driven in a state in which power is supplied to the electric heater 6b, air heated by the
30 electric heater 6b is supplied upward through the vent holes of the product chute 5 and thus the product storage area can be maintained in a high-temperature state. Although not clearly illustrated in the drawing, a

compressor, a condenser, and an expansion valve of the refrigeration cycle are all disposed in a machine room 7 outside the product storage 4.

[0025] The product storage racks 10 are arranged in
5 three lines in the front-rear direction, includes plural
(two in the illustrated example) product storage passages
13 which are disposed in a meandering shape in the vertical
direction by disposing passage elements 12 between a pair
of base side plates 11, and stores plural products with a
10 sideways posture in the vertical direction in the product
storage passages 13. More specifically, the passage
elements 12 are appropriately disposed on the front side
and the rear side of the product storage passages 13 so as
to face each other and are fixed to the base side plate 11.
15 Accordingly, in each product storage rack 10, two product
storage passages 13 are disposed to be adjacent to each
other in the front-rear direction. In the following
description, the front product storage passage 13 in one
product storage rack 10 is also referred to as a first
20 product storage passage 13a and the rear product storage
passage 13 is also referred to as a second product storage
passage 13b.

[0026] The passage elements 12 are provided with
flappers which are not clearly illustrated in the drawing.
25 The flappers are swingably disposed in the passage elements
12 so as to move forward to and backward from the product
storage passage 13. The flappers are biased by coil
springs (not illustrated) and moves forward to the product
storage passages 13 in a normal state. The flapper moves
30 backward along the meandering product storage passage 13
against a bias force of the coil spring to correct the
posture of a product by coming in contact with the product
passing through the product storage passage 13.

[0027] In the product storage rack 10, a top tray 14 is disposed in the top of the product storage passage 13 and a product dispensing system 20 is disposed in the bottom of the product storage passage 13.

5 [0028] The top tray 14 is formed by bending a plate-like metal sheet, and the top tray is disposed between the base side plates 11 so as to be gradually inclined downward from the front side to the rear side. The top surface of the top tray 14 constitutes a product guide passage 15 that
10 guides a product input through an input port to the product storage passage 13.

[0029] FIGS. 2 to 4 illustrate a product dispensing system 20 illustrated in FIG. 1, where FIG. 2 is a side view when viewed from the right side, FIG. 3 is a
15 perspective view when viewed from the front-right side, and FIG. 4 is a perspective view when viewed from the rear-right side.

[0030] As illustrated in FIGS. 2 to 4, the product dispensing system 20 includes one product discharging
20 device (hereinafter, also referred to as a first product discharging device) 20a and the other product discharging device (hereinafter, also referred to as a second product discharging device) 20b, where the first product discharging device 20a and the second product discharging
25 device 20b are coupled to each other back to back. FIGS. 2 to 4 illustrate a state in which the first product discharging device 20a and the second product discharging device 20b constituting the product dispensing system 20 store no product.

30 [0031] FIG. 5 is a perspective view illustrating the first product discharging device 20a illustrated in FIGS. 2 to 4 when viewed from the rear-right side. In the following description, the configuration of the first

product discharging device 20a will be first described and then the second product discharging device 20b will be described.

[0032] FIGS. 6 to 8 are diagrams schematically illustrating principal parts of the first product discharging device 20a illustrated in FIGS. 2 to 5 when viewed from the right side. In the following description, the configuration of the first product discharging device 20a will be described appropriately with reference to FIGS. 6 to 8.

[0033] The first product discharging device 20a is applied to the first product storage passage 13a and is disposed in the bottom of the first product storage passage 13a. The first product discharging device 20a serves to store products in the first product storage passage 13a in a standby state and to discharge a product to the product chute 5 in an activated state by controlling behavior of product between an opposite passage width defining plate 16 and the first product discharging device, and includes a base 21.

[0034] As illustrated in FIG. 9, the base 21 is formed by performing a cutting process and a bending process on a steel sheet and is disposed to cause its own surface to face the passage width defining plate 16. A side wall 21a of the base 21 is formed by bending both sides and a first insertion hole 22 and a second insertion hole 23 are formed in an intermediate portion thereof. The circumferential edges of the first insertion hole 22 and the second insertion hole 23 are bent similarly to the side wall 21a to form a flange.

[0035] The first insertion hole 22 and the second insertion hole 23 are arranged in the right-left direction and have the same size in the vertical direction. Among

the first insertion hole 22 and the second insertion hole 23, the first insertion hole 22 is located on the left side of the second insertion hole 23, and the width in the right-left direction of the first insertion hole 22 is larger than the width in the right-left direction of the second insertion hole 23. The first insertion hole 22 and the second insertion hole 23 are through-openings (concave portions for enabling a lower pedal 28 and an upper pedal 29 to be described later to move backward into the base 21) having a substantially rectangular shape as a whole, the top end of the first insertion hole 22 protrudes to the left side, and the top end of the second insertion hole 23 protrudes to the right side. A first left bearing piece 22a is disposed at the left edge portion of the first insertion hole 22, a first right bearing piece 22b is disposed at the right edge portion of the first insertion hole 22, a second left bearing piece 23a is disposed at the left edge portion of the second insertion hole 23, and a second right bearing piece 23b is disposed at the right edge portion of the second insertion hole 23. The first left bearing piece 22a and the second right bearing piece 23b correspond to the flange formed at the circumferential edges of the first insertion hole 22 and the second insertion hole 23. The first right bearing piece 22b and the second left bearing piece 23a are formed integrally with the base 21 in a place in which a bearing portion 24 to be described later is fitted and supported and are formed in shaft insertion flanges forming both U-shaped leg portions in a bearing support portion formed in a U-shaped cross-section (discontinuous). The bearing support portion has a function of maintaining the strength of the base 21 even when a large through-opening including the first insertion hole 22 and the second insertion hole 23 which

form a substantially rectangular shape as a whole is formed in the base 21.

[0036] As illustrated in FIG. 10, a bearing portion 24 and a harness guide 25 are attached to the base 21 having
5 the above-mentioned configuration. The bearing portion 24 is formed of a resin material or the like and is interposed between the first right bearing piece 22b and the second left bearing piece 23a.

[0037] The harness guide 25 is formed of a resin
10 material or the like similarly to the bearing portion 24 and is disposed along the right side wall 21a of the base 21 so as to be adjacent to the second right bearing piece 23b. The harness guide 25 serves to guide a harness of electronic components mounted on the first product
15 discharging device 20a. The harness guide 25 serves as a guide member when the first product discharging device 20a and the second product discharging device 20b are coupled to each other back to back.

[0038] The harness guide 25 is provided with a first
20 sold-out detection switch 26 and a second sold-out detection switch 27.

[0039] The first sold-out detection switch 26 is arranged in the front-rear direction along with the second sold-out detection switch 27, and is located in front of
25 the second sold-out detection switch 27. The first sold-out detection switch 26 is a so-called push type switch and includes a contactor 26a that is biased to rise upright by a spring not illustrated. The first sold-out detection switch 26 is switched to an OFF state to output an OFF
30 signal to a dispensing control unit 110 to be described later when the contactor 26a is not pressed, and is switched to an ON state to output an ON signal to the dispensing control unit 110 when the contactor 26a is

pressed and displaced against the biasing force of the spring.

[0040] In this embodiment, the first sold-out detection switch 26 is switched to the OFF state when the contactor 26a is not pressed and is switched to the ON state when the contactor 26a is pressed and displaced, but in the present invention, the first sold-out detection switch 26 may be switched to the ON state when the contactor 26a is not pressed and may be switched to the OFF state when the contactor 26a is pressed and displaced.

[0041] The second sold-out detection switch 27 is located on the rear side of the first sold-out detection switch 26. The second sold-out detection switch 27 is a so-called push type switch and includes a contactor 27a that is biased to rise upright by a spring not illustrated. The second sold-out detection switch 27 is switched to an OFF state to output an OFF signal to the dispensing control unit 110 to be described later when the contactor 27a is not pressed, and is switched to an ON state to output an ON signal to the dispensing control unit 110 when the contactor 27a is pressed and displaced against the biasing force of the spring.

[0042] In this embodiment, the second sold-out detection switch 27 is switched to the OFF state when the contactor 27a is not pressed and is switched to the ON state when the contactor 27a is pressed and displaced, but in the present invention, the second sold-out detection switch 27 may be switched to the ON state when the contactor 27a is not pressed and may be switched to the OFF state when the contactor 27a is pressed and displaced.

[0043] The base 21 is provided with a first swing support shaft 28a and a second swing support shaft 29a. The first swing support shaft 28a is an axial member

disposed to penetrate through-holes 22a1, 22b1, 23a1, 23b1, and 24a formed in a first left bearing piece 22a, a first right bearing piece 22b, a second left bearing piece 23a, a second right bearing piece 23b, and the bearing portion 24 so as to extend substantially in the horizontal direction, and supports the lower pedal 28 in the middle way.

[0044] A first sold-out link 30 is disposed at the right end of the first swing support shaft 28a. As illustrated in FIG. 11, the first sold-out link 30 includes a first sold-out base portion 31, a first sold-out contact portion 32, and a first sold-out pressing portion 33. The first sold-out base portion 31 has a substantially disk-like shape and a penetration hole 31a penetrated by the right end of the first swing support shaft 28a is formed. The first sold-out contact portion 32 extends to the left side from the rear part of the first sold-out base portion 31. The first sold-out pressing portion 33 is formed to protrude to the right side from the bottom of the first sold-out base portion 31. The penetration hole 31a formed in the first sold-out base portion 31 is formed to be larger than the first swing support shaft 28a and is configured such that the first sold-out link 30 can freely move relative to the first swing support shaft 28a.

[0045] The second swing support shaft 29a is an axial member disposed to penetrate the through-holes 22a2, 22b2, 23a2, 23b2, and 24b formed in the first left bearing piece 22a, the first right bearing piece 22b, the second left bearing piece 23a, the second right bearing piece 23b, and the bearing portion 24 so as to extend substantially in the horizontal direction in an area above the first swing support shaft 28a, and supports the upper pedal 29 in the middle way.

[0046] The lower pedal 28 is a plate-like member and is

disposed to be swingable about the central axis of the first swing support shaft 28a by inserting the first swing support shaft 28a into the base end thereof.

[0047] The tip portion of the lower pedal 28 extends in
5 an outer radial direction of the first swing support shaft 28a, and can move forward to and backward from the first product storage passage 13a via the first insertion hole 22 and the second insertion hole 23 when the lower pedal swings about the central axis of the first swing support
10 shaft 28a. That is, the lower pedal 28 is swingably disposed to move forward to and backward from the first product storage passage 13a.

[0048] A lower pedal spring 28b is interposed between the lower pedal 28 and the base 21. The lower pedal spring
15 28b normally biases the lower pedal 28 in the forward moving direction to the first product storage passage 13a. More specifically, the lower pedal spring 28b causes the lower pedal 28 to take a standby posture (hereinafter, also referred to as a product-absent standby posture) such that
20 the tip portion of the lower pedal 28 is located higher than the first swing support shaft 28a as illustrated in FIG. 6. When product is placed on the top surface of the lower pedal 28, the lower pedal spring 28b causes the lower pedal 28 to take a standby posture (hereinafter, also
25 referred to as a product-present standby posture) such that the tip portion of the lower pedal 28 is located at the same height level as the first swing support shaft 28a as illustrated in FIG. 7.

[0049] Accordingly, in the product-absent standby
30 posture, the tip portion of the lower pedal 28 is located higher than in the product-present standby posture.

[0050] When the lower pedal 28 takes the product-absent standby posture, the base end of the lower pedal 28 comes

in contact with the first sold-out contact portion 32 of the first sold-out link 30 as illustrated in FIG. 12, thus the first sold-out link 30 rotates about the first swing support shaft 28a, and thus the first sold-out pressing portion 33 presses the contactor 26a of the first sold-out detection switch 26. Accordingly, in the first sold-out detection switch 26, the contactor 26a is pressed and displaced forward against the biasing force of the spring and is switched to the ON state, and thus an ON signal is output to the dispensing control unit 110.

[0051] On the other hand, when the lower pedal 28 takes the product-present standby posture, the base end of the lower pedal 28 is separated from the first sold-out contact portion 32 of the first sold-out link 30 as illustrated in FIG. 13 and thus the first sold-out link 30 is switched to a free state. Accordingly, in the first sold-out detection switch 26, the contactor 26a is biased by the spring to rise upright and is switched to the OFF state, and thus an OFF signal is output to the dispensing control unit 110. That is, the first sold-out link 30 switched to the free state rotates about the first swing support shaft 28a by pressing the first sold-out pressing portion 33 against the contactor 26a.

[0052] The lower pedal 28 includes a plate-like pedal body 281 and a pair of guide portions 282. The pair of guide portions 282 is disposed on the rear side of the pedal body 281. Each guide portion 282 is a plate-like member extending in the vertical direction and both guide portions are formed to face each other. A guide groove 283 is formed on the facing surfaces of the guide portions 282.

[0053] The guide groove 283 includes a fitting portion 283a which is located at the lowest position in a state in which the lower pedal 28 is disposed at a forward-moved

position at which the lower pedal most moves forward to the first product storage passage 13a (the state illustrated in FIG. 6) and into which a pedal operating shaft 361 of a rotation stopper 36 to be described later is fitted, a
5 contact portion 283d which is located at the highest position in a state in which the lower pedal 28 is disposed at a backward-moved position at which the lower pedal most moves backward from the first product storage passage 13a (the state illustrated in FIG. 8) and with which the pedal
10 operating shaft 361 of the rotation stopper 36 comes in contact, and a first guide portion 283b and a second guide portion 283c which are continuously connected to the fitting portion 283a and the contact portion 283d.

[0054] The first guide portion 283b is formed in the
15 guide portion 282 to be inclined obliquely upward from the fitting portion 283a so as to get away from the base 21, be inclined obliquely upward so as to get close to the base 21, and then reach the contact portion 283d in a state in which the lower pedal 28 is located at the position (forward-
20 moved position) at which the lower pedal most moves forward to the first product storage passage 13a.

[0055] The second guide portion 283c is formed in the guide portion 282 to be inclined obliquely downward from the contact portion 283d so as to get away from the base 21
25 and then reach the fitting portion 283a in a state in which the lower pedal 28 is located at the position (forward-moved position) at which the lower pedal most moves forward to the first product storage passage 13a.

[0056] The length in the outer radial direction of the
30 lower pedal 28 from the first swing support shaft 28a is set to a length with which a gap smaller than the maximum width of a product having a small maximum width can be secured between the passage width defining plate 16 and the

lower pedal when the lower pedal is located at the position (forward-moved position) at which the lower pedal most moves forward to the first product storage passage 13a.

[0057] The upper pedal 29 is a plate-like member and is
5 disposed in the base 21 so as to be swingable about the central axis of the second swing support shaft 29a by inserting the second swing support shaft 29a into the base end thereof.

[0058] The tip portion of the upper pedal 29 extends in
10 an outer radial direction of the second swing support shaft 29a, and can move forward to and backward from the first product storage passage 13a via the first insertion hole 22 and the second insertion hole 23 when the upper pedal swings about the central axis of the second swing support
15 shaft 29a. That is, the upper pedal 29 is swingably disposed to move forward to and backward from the first product storage passage 13a.

[0059] An upper pedal spring (not illustrated) is
interposed between the upper pedal 29 and the base 21. The
20 upper pedal spring normally biases the upper pedal 29 in the backward moving direction to the first product storage passage 13a.

[0060] The upper pedal 29 is provided with a pressing
inclined surface 291, a concave portion 292, a stopper
25 contact portion 293, and a protrusion 294. The pressing inclined surface 291 is disposed in the tip portion of the upper pedal 29 and is a curved inclined surface which is formed to be gradually lowered toward the first product storage passage 13a when the upper pedal 29 moves backward
30 from the first product storage passage 13a. The concave portion 292 is disposed on the rear side of the upper pedal 29 and is a set of concave places extending substantially in the horizontal direction and being formed to be opened

to both side surfaces of the upper pedal 29. The stopper contact portion 293 is a portion with which a stopper pin 34a to be described later comes in contact and is disposed to be inclined to the upper side of the concave portion 292 on the rear surface of the upper pedal 29.

[0061] The protrusion 294 is disposed at the base end of the upper pedal 29 so as to protrude toward the first product storage passage 13a.

[0062] The upper pedal 29 is biased to move backward from the first product storage passage 13a by a biasing force of the upper pedal spring, but the initial position thereof is set in a state in which the upper pedal moves backward from the first product storage passage 13a by bringing the stopper pin 34a into contact with the concave portion 292.

[0063] The upper pedal 29 is inclined to the front side with respect to the vertical plane passing through the second swing support shaft 29a in a state (the state illustrated in FIG. 8) in which the upper pedal is located at the position (forward-moved position) at which the upper pedal most moves forward to the first product storage passage 13a. The length in the outer radial direction of the upper pedal 29 from the second swing support shaft 29a is set to a length with which a gap smaller than the maximum width of a product having a small maximum width can be secured between the passage width defining plate 16 and the upper pedal in the state in which the upper pedal is inclined to the front side.

[0064] In the base 21, the stopper pin 34a, a pedal stopper pin 34b, and a stopper shaft 34c are disposed between the bearing portion 24 and the second right bearing piece 23b.

[0065] The stopper pin 34a is an axial member which is

disposed substantially in the horizontal direction between the bearing portion 24 and the second right bearing piece 23b, where one end thereof is inserted into a stopper pin insertion hole 23b3 of the second right bearing piece 23b and the other end thereof is inserted into a stopper pin insertion hole 24c1 of the bearing portion 24 exposed from the second left bearing piece 23a. The stopper pin 34a is coupled to a pedal link 35 and is movable in the vertical direction in the stopper pin insertion holes 23b3 and 24c1 with the movement in the vertical direction of the pedal link 35. The stopper pin 34a comes in contact with the concave portion 292 of the upper pedal 29 located at the initial position.

[0066] The pedal stopper pin 34b is an axial member which is disposed substantially in the horizontal direction between the bearing portion 24 and the second right bearing piece 23b, where one end thereof is inserted into a pedal stopper pin support groove 24c2 of the bearing portion 24 (which is a long groove extending in the vertical direction similarly to the stopper pin insertion hole 24c1, which is closed by a groove bottom which is a drawn portion denoted by a reference sign 24c1, and which is not illustrated in FIG. 6) and the other end thereof is inserted into a pedal stopper pin support groove 23b4 of the second right bearing piece 23b. The second right bearing piece 23b is provided with an insertion groove 23a4 so as to expose a pedal stopper pin insertion hole 24c2. The pedal stopper pin 34b is coupled to the pedal link 35 and is movable in the vertical direction in the pedal stopper pin support grooves 23b4 and 24c2 with the movement in the vertical direction of the pedal link 35. The circumferential surface of the pedal stopper pin 34b slides in the pedal stopper pin support grooves 23b4 and 24c2 when the pedal link 35 moves

in the vertical direction.

[0067] The stopper shaft 34c is an axial member which is disposed substantially in the horizontal direction between the bearing portion 24 and the second right bearing piece 5 23b, where one end thereof is inserted into a stopper shaft insertion hole 24c3 of the bearing portion 24 and the other end thereof is inserted into a through-hole 23b5 of the second right bearing piece 23b. The insertion hole of the stopper shaft 34c is formed in the second right bearing 10 piece 23b. The stopper shaft 34c supports the rotation stopper 36 in the middle way thereof.

[0068] The rotation stopper 36 is disposed between the bearing portion 24 and the second right bearing piece 23b so as to insert the stopper shaft 34c into the insertion 15 hole of the base end thereof and to be swingable about the central axis of the stopper shaft 34c.

[0069] The tip portion of the rotation stopper 36 extends in the outer radial direction of the stopper shaft 34c and is movable forward to and backward from the first 20 product storage passage 13a via the second insertion hole 23 when the rotation stopper swings about the central axis of the stopper shaft 34c.

[0070] The rotation stopper 36 includes a pedal operating shaft 361 so as to insert the pedal operating 25 shaft 361 into a through-hole 36a of the tip portion thereof. The pedal operating shaft 361 is an axial member which is disposed substantially in the horizontal direction and both ends thereof are fitted into the guide grooves 283 of the lower pedal 28.

30 [0071] A pedal operating spring (not illustrated) is interposed between the rotation stopper 36 and the base 21. The pedal operating spring normally biases the rotation stopper 36 in the forward moving direction to the first

product storage passage 13a.

[0072] The rotation stopper 36 is biased in the forward moving direction to the first product storage passage 13a by the pedal operating spring, movement in the backward moving direction thereof is regulated by moving the pedal stopper pin 34b into a recessed portion 36b of the rotation stopper 36 to come in contact with the pedal stopper pin 34b, and the initial position thereof in the state in which the rotation stopper moves forward to the first product storage passage 13a is set. Since the lower pedal 28 is biased by the lower pedal spring 28b, the initial position of the rotation stopper 36 is set to a position at which both ends of the pedal operating shaft 361 are located in the fitting portion 283a of the guide grooves 283 and the lower pedal 28 moves forward to the first product storage passage 13a.

[0073] As illustrated in FIG. 14, the rotation stopper 36 is provided with a panel-like blindfold portion 36c extending upward on the rear side thereof, that is, on the rear side of the recessed portion 36b. The blindfold portion 36c covers a part of the pedal stopper pin 34b opposite to the first product storage passage 13a. More specifically, the blindfold portion 36c covers the part, which is opposite to the first product storage passage 13a, of the pedal stopper pin 34b moving in the vertical direction.

[0074] The pedal link 35 is a long plate-like member extending in the vertical direction and an upper portion thereof is bent to the front side and then extends upward. The upper portion of the pedal link 35 is provided with a contact piece 351 extending backward and then extending obliquely upward and a locking portion 352 locking a link spring 35a. The link spring 35a is interposed between the

pedal link 35 and the base 21 and normally biases the pedal link 35 downward.

[0075] In a state in which the pedal link 35 is biased by the link spring 35a and is located on the lower side, the stopper pin 34a is disposed at the bottom ends of the stopper pin insertion holes 23b3 and 24c1 and the pedal stopper pin 34b is disposed at the bottom ends of the stopper pin support grooves 23b4 and 24c2. In this state, the concave portion 292 of the upper pedal 29 disposed at the backward-moved position comes in contact with the stopper pin 34a. The rotation stopper 36 disposed at the forward-moved position comes in contact with the pedal stopper pin 34b to regulate the backward movement of the rotation stopper 36. The pedal operating shaft 361 of the rotation stopper 36 disposed at the forward-moved position is fitted into the fitting portion 283a of the lower pedal 28 to regulate the backward movement of the lower pedal 28 disposed at the forward-moved position.

[0076] On the other hand, in the state in which the pedal link 35 is located on the upper side against the biasing force of the link spring 35a, as illustrated in FIG. 8, the stopper pin 34a is disposed at the top ends of the stopper pin insertion holes 23b3 and 24c1 and the pedal stopper pin 34b is disposed at the top ends of the stopper pin support grooves 23b4 and 24c2. In this state, the stopper contact portion 293 of the upper pedal 29 comes in contact with the stopper pin 34a to regulate the backward movement of the upper pedal 29, and the upper pedal 29 moves forward against the biasing force of the upper pedal spring and is disposed at the forward-moved position.

[0077] On the other hand, since the regulation of the backward movement due to the pedal stopper pin 34b is released, the regulation of the backward movement of the

rotation stopper 36 with respect to the stopper shaft 34c is released. Here, the weight of a product coming in contact with the lower pedal 28 maintained at the forward-moved position by the rotation stopper 36 is applied to the rotation stopper 36, and the rotation stopper 36 starts its backward movement with releasing the regulation of the backward movement of the rotation stopper 36. When the backward movement of the rotation stopper 36 is started, the pedal operating shaft 361 departs from the fitting portion 283a of the lower pedal 28. Accordingly, the lower pedal 28 is allowed to move backward about the first swing support shaft 28a and moves backward against the elastic biasing force of the lower pedal spring 28b by the weight of the product (see FIG. 8).

[0078] When the lower pedal 28 moves backward in this way, as illustrated in FIG. 15, the base end of the lower pedal 28 is separated from the first sold-out contact portion 32 of the first sold-out link 30 and thus the first sold-out link 30 is switched to the free state. Accordingly, in the first sold-out detection switch 26, the contactor 26a is biased by the spring to rise upright and thus to maintain the OFF state. That is, when the lower pedal 28 moves backward, similarly to the product-present standby posture, the first sold-out link 30 does not press the contactor 26a of the first sold-out detection switch 26.

[0079] The first product discharging device 20a having the above-mentioned configuration includes a drive unit 40 in addition to the above-mentioned configuration.

[0080] FIGS. 16 and 17 illustrate principal parts of the drive unit 40 in the first product discharging device 20a, where FIG. 16 is an exploded perspective view thereof when viewed from the front-right side and FIG. 17 is an exploded perspective view thereof when viewed from the rear-left

side.

[0081] The drive unit 40 is disposed in an upper center area of the rear side of the base 21. The drive unit 40 includes a unit base 41 which is attached to the rear
5 surface of the base 21.

[0082] The unit base 41 is formed of, for example, a resin material and is formed in a box shape of which the rear surface is opened. In the unit base 41, the opening of the rear surface is closed by attaching a unit cover 42
10 formed of a resin thereto, thereby forming a storage space between the unit base and the unit cover 42. A motor 43, a gear member 44, a carrier switch 45, and a link lever 46 are stored in the storage space formed by the unit base 41 and the unit cover 42.

[0083] The motor 43 serves as a drive source and is a DC motor that can rotate positively and reversely and that is driven in accordance with a command issued from the dispensing control unit 110 to be described later. The motor 43 is disposed in a state in which the motor is held
20 by a motor holding portion 41a of the unit base 41.

[0084] The gear member 44 includes a worm gear 441, an intermediate gear 442, and an output gear 443. The worm gear 441 includes a worm 441a and a worm wheel 441b.

[0085] The worm 441a has a cylindrical shape and is
25 attached to an output shaft 43a of the motor 43. The worm wheel 441b includes a first worm wheel 441b1 having a disk shape and a second worm wheel 441b2 having a disk shape.

[0086] In the first worm wheel 441b1, an axial portion protruding rearward is formed at the center thereof and a gear portion including plural teeth is formed on the
30 circumferential surface thereof.

[0087] The second worm wheel 441b2 is located on the front side of the first worm wheel 441b1 and is formed such

that an axial portion of which the central axis matches the central axis of the axial portion of the first worm wheel 441b1 protrudes to the front side. A gear portion including plural teeth is also formed on the

5 circumferential surface of the second worm wheel 441b2.

[0088] The worm wheel 441b is disposed to be rotatable about the central axis of the axial portion by inserting the axial portion into concave portions 41b and 42b of the unit base 41 and the unit cover 42 in a state in which the
10 gear portion of the first worm wheel 441b1 engages with the worm 441a.

[0089] The intermediate gear 442 includes a disk-like first intermediate gear 442a and a disk-like second intermediate gear 442b. In the first intermediate gear
15 442a, an axial portion protruding to the rear side is formed at the center thereof and a gear portion including plural teeth is formed on the circumferential surface thereof.

[0090] The second intermediate gear 442b is located on
20 the rear side of the first intermediate gear 442a and is disposed such that an axial portion of which the central axis matches the central axis of the axial portion of the first intermediate gear 442a protrudes to the front side. A gear portion including plural teeth is also formed on the
25 circumferential surface of the second intermediate gear 442b.

[0091] The intermediate gear 442 is disposed to be rotatable about the central axis of the axial portion by inserting the axial portion into concave portions 41c and
30 42c of the unit base 41 and the unit cover 42 in a state in which the gear portion of the first intermediate gear 442a engages with the gear portion of the second worm wheel 441b2.

[0092] The output gear 443 has a disk shape having a diameter larger than that of the worm wheel 441b or the intermediate gear 442. A gear portion including plural teeth is also formed on the circumferential surface of the output gear 443. An axial portion protruding in the front-rear direction is formed at the center of the output gear 443. A cam portion 443a is formed on the front surface of the output gear 443 and a pressing piece 443b is formed on the rear surface thereof.

[0093] The cam portion 443a has an arc shape and is formed to protrude to the front side. The cam portion 443a is formed such that the length of the arc shape thereof is set to a size sufficient for holding a state in which the pedal link 35 has moved upward.

[0094] The pressing piece 443b has a substantially V shape and is formed to protrude to the rear side on the rear surface opposite to the cam portion 443a.

[0095] The output gear 443 is disposed to be rotatable about the central axis of the axial portion by inserting the axial portion into concave portions 41d and 42d of the unit base 41 and the unit cover 42 in a state in which the gear portion engages with the gear portion of the second intermediate gear 442b.

[0096] The carrier switch 45 is a so-called push switch and includes a contactor 45a. The carrier switch 45 is disposed in the unit base 41 in a state in which the carrier switch is held slightly above the area in which the output gear 443 is disposed. The carrier switch 45 is switched to an ON state to supply details thereof as an ON signal to the dispensing control unit 110 when the contactor 45a is pressed, and is switched to an OFF state to supply details thereof as an OFF signal to the dispensing control unit 110 when the contactor 45a is not

pressed.

[0097] The link lever 46 includes a first link lever 461 and a second link lever 462. The first link lever 461 is formed of, for example, a resin material and a through-hole 5 461a1 is formed at a base end 461a thereof. The first link lever 461 has a hook shape in which a tip portion 461b extends obliquely downward to the right side from the base end 461a and is then curved obliquely upward to the right side. The base end 461a of the first link lever 461 is 10 provided with a locking portion 461c. The locking portion 461c is a plate-like elastic member which extends downward from the left end of the base end 461a and which is elastically deformable.

[0098] The first link lever 461 is disposed to be 15 rotatable about the central axis of a first link shaft 42e on the front side of the output gear 443 by inserting the first link shaft 42e disposed in the unit cover 42 into the through-hole 461a1 of the base end 461a. In this case, the first link lever 461 penetrates a right opening (not 20 illustrated) formed by the unit base 41 and the unit cover 42 and the tip portion 461b is located outside the unit base 41 and the unit cover 42. The posture in the normal state of the first link lever 461 is determined by bringing the locking portion 461c into contact with a left edge 25 portion 471 of the right opening.

[0099] The second link lever 462 is formed of, for example, a resin material and a through-hole 462a1 is formed at a base end 462a thereof. The second link lever 462 has a hook shape in which a tip portion 462b extends 30 obliquely downward to the left side from the base end 462a and is then curved obliquely upward to the left side. The tip portion 462b of the second link lever 462 has a width in the front-rear direction larger than that of the tip

portion 461b of the first link lever 461. The base end 462a of the second link lever 462 is provided with a locking portion 462c. The locking portion 462c is a plate-like elastic member which extends downward from the right end of the base end 462a and which is elastically deformable.

[0100] The second link lever 462 is disposed to be rotatable about the central axis of a second link shaft 42f on the front side of the output gear 443 by inserting the second link shaft 42f disposed in the unit cover 42 into the through-hole 462a1 of the base end 462a. In this case, the second link lever 462 penetrates a left opening (not illustrated) formed by the unit base 41 and the unit cover 42 and the tip portion 462b is located outside the unit base 41 and the unit cover 42. The posture in the normal state of the second link lever 462 is determined by bringing the locking portion 462c into contact with a right edge portion 472 of the left opening.

[0101] FIG. 18 is a perspective view illustrating the second product discharging device 20b illustrated in FIGS. 2 to 4 when viewed from the front-right side. FIG. 19 is a diagram schematically illustrating principal parts of the second product discharging device 20b illustrated in FIGS. 2 to 4 and FIG. 18 when viewed from the right side. The most elements of the second product discharging device 20b are common to the elements of the first product discharging device 20a and are different from the elements of the first product discharging device 20a, in that the front-rear direction is different and thus the right-left direction is reversed. Accordingly, in describing the second product discharging device 20b, the elements will be appropriately skipped, and the elements of the second product discharging device 20b common to the elements of the first product

discharging device 20a will be referenced by adding "'" to the reference signs in the first product discharging device 20a and will be described in brief.

[0102] The second product discharging device 20b is
5 applied to the second product storage passage 13b and is disposed in the bottom of the second product storage passage 13b. The second product discharging device 20b serves to store products in the second product storage passage 13b in a standby state and to discharge a product
10 to the product chute 5 in an activated state by controlling behavior of product between an opposite passage width defining plate 17 and the second product discharging device, and includes a base 21'.

[0103] As illustrated in FIG. 20, the base 21' is formed
15 by performing a cutting process and a bending process on a steel sheet and is disposed to cause its own surface to face the passage width defining plate 17. A side wall 21a' of the base 21' is formed by bending both sides and a first insertion hole 22' and a second insertion hole 23' are
20 formed in an intermediate portion thereof. The circumferential edges of the first insertion hole 22' and the second insertion hole 23' are bent similarly to the side wall 21a' to form a flange.

[0104] The first insertion hole 22' and the second
25 insertion hole 23' are arranged in the right-left direction and have the same size in the vertical direction. Among the first insertion hole 22' and the second insertion hole 23', the first insertion hole 22' is located on the right side of the second insertion hole 23', and the width in the
30 right-left direction of the first insertion hole 22' is larger than the width in the right-left direction of the second insertion hole 23'. The first insertion hole 22' and the second insertion hole 23' are through-openings

(concave portions for enabling a lower pedal 28' and an upper pedal 29' to be described later to move backward into the base 21') having a substantially rectangular shape as a whole, the top end of the first insertion hole 22'

5 protrudes to the right side, and the top end of the second insertion hole 23' protrudes to the left side. A first right bearing piece 22a' is disposed at the right edge portion of the first insertion hole 22', a first left bearing piece 22b' is disposed at the left edge portion of
10 the first insertion hole 22', a second right bearing piece 23a' is disposed at the right edge portion of the second insertion hole 23', and a second left bearing piece 23b' is disposed at the left edge portion of the second insertion hole 23'. The first left bearing piece 22b' and the second
15 right bearing piece 23a' correspond to the flange formed at the circumferential edges of the first insertion hole 22' and the second insertion hole 23'. The first left bearing piece 22b' and the second right bearing piece 23a' are formed integrally with the base 21' in a place in which a
20 bearing portion 24' to be described later is fitted and supported and are formed in shaft insertion flanges forming both U-shaped leg portions in a bearing support portion formed in a U-shaped cross-section (discontinuous). The bearing support portion has a function of maintaining the
25 strength of the base 21' even when a large through-opening including the first insertion hole 22' and the second insertion hole 23' which form a substantially rectangular shape as a whole is formed in the base 21'.

[0105] As illustrated in FIG. 21, the bearing portion
30 24' and a guide 48 are attached to the base 21' having the above-mentioned configuration. The bearing portion 24' is formed of a resin material or the like and is interposed between the first left bearing piece 22b' and the second

right bearing piece 23a'. The guide 48 is formed of a resin material or the like similarly to the bearing portion 24' and is disposed in the base 21' so as to be adjacent to the second left bearing piece 23b'.

5 [0106] The base 21' is provided with a first swing support shaft 28a' and a second swing support shaft 29a'. The first swing support shaft 28a' is an axial member disposed to penetrate through-holes 22a1', 22b1', 23a1', 23b1', and 24a' formed in the first right bearing piece 10 22a', the first left bearing piece 22b', the second right bearing piece 23a', the second left bearing piece 23b', and the bearing portion 24' so as to extend substantially in the horizontal direction, and supports the lower pedal 28' in the middle way.

15 [0107] A second sold-out link 50 is disposed at the right end of the first swing support shaft 28a'. As illustrated in FIG. 11, the second sold-out link 50 includes a second sold-out base portion 51, a second sold-out contact portion 52, and a second sold-out pressing 20 portion 53. The second sold-out base portion 51 is formed, for example, by connecting the bottom ends of two disc-shaped portions 511 and 512 having a C shape to a connecting portion 513, and penetration holes 511a and 512a penetrated by the right end of the first swing support 25 shaft 28a' are formed in the disc-shaped portions 511 and 512, respectively. The second sold-out contact portion 52 extends to the left side from the front part of the disc-shaped portion 512 of the left side of the second sold-out base portion 51. The second sold-out contact portion 52 is 30 disposed on the left side of the first sold-out contact portion 32 constituting the first sold-out link 30 so as not to interfere with each other. The second sold-out pressing portion 53 is formed to protrude to the right side

from the lower part of the right disc-shaped portion 511 of the second sold-out base portion 51. The penetration holes 511a and 512a formed in the second sold-out base portion 51 is formed to be larger than the first swing support shaft 28a' and is configured such that the second sold-out link 50 can freely move relative to the first swing support shaft 28a'.

[0108] The second swing support shaft 29a' is an axial member disposed to penetrate the through-holes 22a2', 22b2', 23a2', 23b2', and 24b' formed in the first right bearing piece 22a', the first left bearing piece 22b', the second right bearing piece 23a', the second left bearing piece 23b', and the bearing portion 24' so as to extend substantially in the horizontal direction in an area above the first swing support shaft 28a', and supports the upper pedal 29' in the middle way.

[0109] The lower pedal 28' is a plate-like member and is disposed to be swingable about the central axis of the first swing support shaft 28a' by inserting the first swing support shaft 28a' into the base end thereof.

[0110] The tip portion of the lower pedal 28' extends in an outer radial direction of the first swing support shaft 28a', and can move forward to and backward from the second product storage passage 13b via the first insertion hole 22' and the second insertion hole 23' when the lower pedal swings about the central axis of the first swing support shaft 28a'. That is, the lower pedal 28' is swingably disposed to move forward to and backward from the second product storage passage 13b.

[0111] A lower pedal spring 28b' is interposed between the lower pedal 28 and the base 21'. The lower pedal spring 28b' normally biases the lower pedal 28' in the forward moving direction to the second product storage

passage 13b. More specifically, the lower pedal spring 28b' causes the lower pedal 28' to take a standby posture (hereinafter, also referred to as a product-absent standby posture) such that the tip portion of the lower pedal 28' is located higher than the first swing support shaft 28a' as illustrated in FIG. 19. When product is placed on the top surface of the lower pedal 28', the lower pedal spring 28b' causes the lower pedal 28' to take a standby posture (hereinafter, also referred to as a product-present standby posture) such that the tip portion of the lower pedal 28' is located at the same height level as the first swing support shaft 28a'.

[0112] Accordingly, in the product-absent standby posture, the tip portion of the lower pedal 28' is located higher than that of the product-present standby posture.

[0113] When the lower pedal 28' takes the product-absent standby posture, the base end of the lower pedal 28' comes in contact with the second sold-out contact portion 52 of the second sold-out link 50 as illustrated in FIG. 12, thus the second sold-out link 50 rotates about the first swing support shaft 28a', and thus the second sold-out pressing portion 53 presses the contactor 27a of the second sold-out detection switch 27. Accordingly, in the second sold-out detection switch 27, the contactor 27a is pressed and displaced backward against the biasing force of the spring and is switched to the ON state, and thus an ON signal is output to the dispensing control unit 110.

[0114] On the other hand, when the lower pedal 28' takes the product-present standby posture, the base end of the lower pedal 28' is separated from the second sold-out contact portion 52 of the second sold-out link 50 and thus the second sold-out link 50 is switched to a free state. Accordingly, in the second sold-out detection switch 27,

the contactor 27a is biased by the spring to rise upright and is switched to the OFF state, and thus an OFF signal is output to the dispensing control unit 110. That is, the second sold-out link 50 switched to the free state rotates
5 about the first swing support shaft 28a' by pressing the second sold-out pressing portion 53 against the contactor 27a.

[0115] The lower pedal 28' includes a plate-like pedal body 281' and a pair of guide portions 282'. The pair of
10 guide portions 282' is disposed on the rear side of the pedal body 281'. Each guide portion 282' is a plate-like member extending in the vertical direction and both are formed to face each other. A guide groove (not illustrated) is formed on the facing surfaces of the guide
15 portions 282'.

[0116] The guide groove includes a fitting portion which is located at the lowest position in a state in which the lower pedal 28' is disposed at a forward-moved position at which the lower pedal most moves forward to the second
20 product storage passage 13b and into which a pedal operating shaft (not illustrated) of a rotation stopper 36' to be described later is fitted, a contact portion which is located at the highest position in a state in which the lower pedal 28' is disposed at a backward-moved position at
25 which the lower pedal most moves backward from the second product storage passage 13b and with which the pedal operating shaft 361' of the rotation stopper 36' comes in contact, and a first guide portion and a second guide portion which are continuously connected to the fitting
30 portion and the contact portion.

[0117] The first guide portion is formed in the guide portion 282' to be inclined obliquely upward from the fitting portion so as to get away from the base 21', be

inclined obliquely upward so as to get close to the base 21', and then reach the contact portion in a state in which the lower pedal 28' is located at the position (forward-moved position) at which the lower pedal most moves forward to the second product storage passage 13b.

[0118] The second guide portion is formed in the guide portion 282' to be inclined obliquely downward from the contact portion so as to get away from the base 21' and then reach the fitting portion in a state in which the lower pedal 28' is located at the position (forward-moved position) at which the lower pedal most moves forward to the second product storage passage 13b.

[0119] The length in the outer radial direction of the lower pedal 28' from the first swing support shaft 28a' is set to a length with which a gap smaller than the maximum width of a product having a small maximum width can be secured between the passage width defining plate 17 and the lower pedal when the lower pedal is located at the position (forward-moved position) at which the lower pedal most moves forward to the second product storage passage 13b.

[0120] The upper pedal 29' is a plate-like member and is disposed in the base 21' so as to be swingable about the central axis of the second swing support shaft 29a' by inserting the second swing support shaft 29a' into the base end thereof.

[0121] The tip portion of the upper pedal 29' extends in an outer radial direction of the second swing support shaft 29a', and can move forward to and backward from the second product storage passage 13b via the first insertion hole 22' and the second insertion hole 23' when the upper pedal swings about the central axis of the second swing support shaft 29a'. That is, the upper pedal 29' is swingably disposed to move forward to and backward from the second

product storage passage 13b.

[0122] An upper pedal spring (not illustrated) is interposed between the upper pedal 29' and the base 21'. The upper pedal spring normally biases the upper pedal 29' in the backward moving direction to the second product storage passage 13b.

[0123] The upper pedal 29' is provided with a pressing inclined surface 291', a concave portion 292', a stopper contact portion 293', and a protrusion 294'. The pressing inclined surface 291' is disposed in the tip portion of the upper pedal 29' and is a curved inclined surface which is formed to be gradually lowered toward the second product storage passage 13b when the upper pedal 29' moves backward from the second product storage passage 13b. The concave portion 292' is disposed on the rear side of the upper pedal 29' and is a set of concave places extending substantially in the horizontal direction and being formed to be opened to both side surfaces of the upper pedal 29'. The stopper contact portion 293' is a portion with which a stopper pin to be described later comes in contact and is disposed to be inclined to the upper side of the concave portion 292' on the rear surface of the upper pedal 29'.

[0124] The protrusion 294' is disposed at the base end of the upper pedal 29' so as to protrude toward the second product storage passage 13b.

[0125] The upper pedal 29' is biased to move backward from the second product storage passage 13b by a biasing force of the upper pedal spring, but the initial position thereof is set in a state in which the upper pedal moves backward from the second product storage passage 13b by bringing the stopper pin into contact with the concave portion 292'.

[0126] The upper pedal 29' is inclined to the front side

with respect to the vertical plane passing through the second swing support shaft 29a' in a state in which the upper pedal is located at the position (forward-moved position) at which the upper pedal most moves forward to the second product storage passage 13b. The length in the outer radial direction of the upper pedal 29' from the second swing support shaft 29a' is set to a length with which a gap smaller than the maximum width of a product having a small maximum width can be secured between the passage width defining plate 17 and the upper pedal in the state in which the upper pedal is inclined to the front side.

[0127] In the base 21', the stopper pin (not illustrated), the pedal stopper pin 34b', and the stopper shaft 34c' are disposed between the bearing portion 24' and the second left bearing piece 23b'.

[0128] The stopper pin is an axial member which is disposed substantially in the horizontal direction between the bearing portion 24' and the second left bearing piece 23b'. The stopper pin is coupled to the pedal link 35' and is movable in the vertical direction with the movement in the vertical direction of the pedal link 35'. The stopper pin comes in contact with the concave portion 292' of the upper pedal 29' located at the initial position.

[0129] The pedal stopper pin 34b' is an axial member which is disposed substantially in the horizontal direction between the bearing portion 24' and the second left bearing piece 23b'. The pedal stopper pin 34b' is coupled to the pedal link 35' and is movable in the vertical direction with the movement in the vertical direction of the pedal link 35'.

[0130] The stopper shaft 34c' is an axial member which is disposed substantially in the horizontal direction

between the bearing portion 24' and the second left bearing piece 23b' and supports the rotation stopper 36' in the middle thereof.

[0131] The rotation stopper 36' is disposed between the
5 bearing portion 24' and the second left bearing piece 23b' so as to insert the stopper shaft 34c' into the insertion hole of the base end thereof and to be swingable about the central axis of the stopper shaft 34c'.

[0132] The tip portion of the rotation stopper 36'
10 extends in the outer radial direction of the stopper shaft 34c' and is movable forward to and backward from the second product storage passage 13b via the second insertion hole 23' when the rotation stopper swings about the central axis of the stopper shaft 34c'.

[0133] The rotation stopper 36' includes a pedal
15 operating shaft 361' so as to insert the pedal operating shaft 361' (see FIG. 4) into the through-hole (not illustrated) of the tip portion thereof. The pedal operating shaft 361' is an axial member which is disposed
20 substantially in the horizontal direction and both ends thereof are fitted into the guide grooves of the lower pedal 28'.

[0134] A pedal operating spring (not illustrated) is
interposed between the rotation stopper 36' and the base
25 21'. The pedal operating spring normally biases the rotation stopper 36' in the forward moving direction to the second product storage passage 13b.

[0135] The rotation stopper 36' is biased in the forward
moving direction to the second product storage passage 13b
30 by the pedal operating spring, movement in the backward moving direction thereof is regulated by moving the pedal stopper pin 34b' into a recessed portion 36b' of the rotation stopper 36' to come in contact with the pedal

stopper pin 34b', and the initial position thereof in the state in which the rotation stopper moves forward to the second product storage passage 13b is set. Since the lower pedal 28' is biased by the lower pedal spring 28b', the
5 initial position of the rotation stopper 36' is set to a position at which both ends of the pedal operating shaft 361' are located in the fitting portion of the guide grooves and the lower pedal 28' moves forward to the second product storage passage 13b.

10 [0136] The rotation stopper 36' is provided with a panel-like blindfold portion 36c' extending upward on the rear side thereof, that is, on the rear side of the recessed portion 36b'. The blindfold portion 36c' covers a part of the pedal stopper pin 34b' opposite to the second
15 product storage passage 13b. More specifically, the blindfold portion 36c' covers the part, which is opposite to the second product storage passage 13b, of the pedal stopper pin 34b' moving in the vertical direction.

[0137] The pedal link 35' is a long plate-like member
20 extending in the vertical direction and an upper portion thereof is bent to the rear side and then extends upward. The upper portion of the pedal link 35' is provided with a contact piece 351' extending forward and then extending obliquely upward and a locking portion 352' locking a link
25 spring 35a'. The link spring 35a' is interposed between the pedal link 35' and the base 21' and normally biases the pedal link 35' downward.

[0138] In a state in which the pedal link 35' is biased by the link spring 35a' and is located on the lower side,
30 the concave portion 292' of the upper pedal 29' disposed at the backward-moved position comes in contact with the stopper pin. The rotation stopper 36' disposed at the forward-moved position comes in contact with the pedal

stopper pin 34b' to regulate the backward movement of the rotation stopper 36'. The pedal operating shaft 361' of the rotation stopper 36' disposed at the forward-moved position is fitted into the fitting portion of the lower pedal 28' to regulate the backward movement of the lower pedal 28' disposed at the forward-moved position.

[0139] On the other hand, in the state in which the pedal link 35' is located on the upper side against the biasing force of the link spring 35a', the stopper contact portion 293' of the upper pedal 29' comes in contact with the stopper pin to regulate the backward movement of the upper pedal 29', and the upper pedal 29' moves forward against the biasing force of the upper pedal spring and is disposed at the forward-moved position.

[0140] On the other hand, since the regulation of the backward movement due to the pedal stopper pin 34b' is released, the regulation of the backward movement of the rotation stopper 36' with respect to the stopper shaft 34c' is released. Here, the weight of a product coming in contact with the lower pedal 28' maintained at the forward-moved position by the rotation stopper 36' is applied to the rotation stopper 36', and the rotation stopper 36' starts its backward movement with releasing the regulation of the backward movement of the rotation stopper 36'. When the backward movement of the rotation stopper 36' is started, the pedal operating shaft 361' departs from the fitting portion 283a of the lower pedal 28'. Accordingly, the lower pedal 28' is allowed to move backward about the first swing support shaft 28a' and moves backward against the elastic biasing force of the lower pedal spring 28b' by the weight of the product.

[0141] When the lower pedal 28' moves backward in this way, the base end of the lower pedal 28' is separated from

the second sold-out contact portion 52 of the second sold-out link 50 and thus the second sold-out link 50 is switched to the free state. Accordingly, in the second sold-out detection switch 27, the contactor 27a is biased by the spring to rise upright and thus to maintain the OFF state. That is, when the lower pedal 28' moves backward, similarly to the product-present standby posture, the second sold-out link 50 does not press the contactor 27a of the second sold-out detection switch 27.

10 [0142] The product dispensing system 20 is constituted by coupling the first product discharging device 20a and the second product discharging device 20b having the above-mentioned configurations to each other back to back using the harness guide 25 as a guide member. In this case, the tip of the first link lever 461 constituting the drive unit 40 is located in an area below the contact piece 351 of the pedal link 35, and the tip of the second link lever 462 is located in an area below the contact piece 351' of the pedal link 35'.

20 [0143] FIG. 22 is a block diagram illustrating a characteristic control system of the product dispensing system 20. As illustrated in FIG. 22, the product dispensing system 20 includes a dispensing control unit 110. The dispensing control unit 110 comprehensively controls the operations of the product dispensing system 20 on the basis of programs or data stored in a memory 111, and can communicate with a vending machine controller 100 that comprehensively controls the vending operation of the vending machine.

30 [0144] The product dispensing system 20 having the above-mentioned configuration operates as follows in the standby state.

[0145] In the drive unit 40 of the first product

discharging device 20a, the cam portion 443a and the pressing piece 443b of the output gear 443 are located at the highest position and the pressing piece 443b presses the contactor 45a of the carrier switch 45. In this case, 5 the carrier switch 45 is in the ON state. In this standby state, the tip portion 461b of the first link lever 461 constituting the drive unit 40 is located at a position separated downward from the contact piece 351 of the pedal link 35 and the tip portion 462b of the second link lever 10 462 is located at a position separated downward from the contact piece 351' of the pedal link 35'.

[0146] Accordingly, in the first product discharging device 20a, as illustrated in FIG. 5 or 23, the pedal link 35 is disposed on the lower side. When a product is placed 15 on the top surface of the lower pedal 28 due to the productss input to the first product storage passage 13a, the lower pedal 28 takes the product-present standby posture and the upper pedal 29 takes the posture in which the upper pedal moves backward from the first product 20 storage passage 13a. In this way, since the lower pedal 28 takes the product-present standby posture, the first sold-out detection switch 26 takes the posture in which the contactor 26a rises upright and is in the OFF state.

[0147] In the second product discharging device 20b, the 25 pedal link 35' is disposed on the lower side, the lower pedal 28' takes the product-present standby posture, and the upper pedal 29' takes the posture in which the upper pedal moves backward from the second product storage passage 13b. In this way, since the lower pedal 28' takes 30 the product-present standby posture, the second sold-out detection switch 27 takes the posture in which the contactor 27a rises upright and is in the OFF state.

[0148] FIG. 24 is a flowchart illustrating processing

details of a dispensing control process which is performed by the dispensing control unit 110. The operation of the product dispensing system 20 will be described below while describing the dispensing control process. In the

5 following description, the product stored in the first product storage passage 13a is also referred to as "first product", and the product stored in the second product storage passage 13b is also referred to as "second product".

[0149] In the dispensing control process, when a command
10 to discharge the first product is issued from the vending machine controller 100 (YES in step S101), the dispensing control unit 110 drives the motor 43 positively (step S102).

[0150] When the motor 43 is driven positively, the output gear 443 to which the driving force of the motor 43
15 is transmitted via the worm gear 441 and the intermediate gear 442 rotates clockwise in a front view.

[0151] When the output gear 443 rotates clockwise in a front view, the pressing piece 443b of the output gear 443 departs from the contactor 45a of the carrier switch 45.
20 Accordingly, the contactor 45a of the carrier switch 45 is opened from the pressed state and is switched to the OFF state.

[0152] When the cam portion 443a comes in contact with the base end 461a of the first link lever 461 from the
25 upper side with the rotation of the output gear 443, the first link lever 461 rotates counterclockwise in the front view. When the first link lever 461 rotates counterclockwise, the tip portion 461b moves upward. When the tip portion 461b moves upward in this way, as
30 illustrated in FIGS. 25 to 27, the tip portion comes in contact with the contact piece 351 of the pedal link 35, the pedal link 35 can move upward by a predetermined distance against the biasing force of the link spring 35a,

and the pedal link 35 can be held in the state in which the pedal link moves upward by the predetermined distance while the cam portion 443a comes in sliding contact with the base end 461a.

5 [0153] In this case, when the first link lever 461 comes in sliding contact with the cam portion 443a, the first link lever is adjusted such that the plane (A) including the portion coming in sliding contact with the cam portion 443a is substantially perpendicular to the plane (B) including its central axis (the central axis of the first link shaft 42e) and a stop axis of the output gear 443.

[0154] With the upward movement of the pedal link 35, the stopper pin 34a moves upward from the bottom ends of the stopper pin insertion holes 23b3 and 24c1 and the pedal stopper pin 34b moves upward from the bottom ends of the pedal stopper pin support grooves 23b4 and 24c2.

[0155] At this time, since the stopper pin 34a moves upward while coming in contact with the edge wall of the concave portion 292 of the upper pedal 29, the upper pedal 29 moves forward from the initial position against the biasing force of the upper pedal spring. The forward movement of the upper pedal 29 is performed along with the upward movement of the stopper pin 34a. At the time at which the stopper pin 34a reaches the top ends of the stopper pin insertion holes 23b3 and 24c1, the stopper pin comes in contact with the stopper contact portion 293 to regulate the backward movement of the upper pedal 29.

[0156] The upper pedal 29 moving forward comes in contact with a second lowest piece of first product (hereinafter, also referred to as a next product) to regulate downward movement of the next product.

[0157] On the other hand, since the weight of the product coming in contact with the lower pedal 28

maintained at the forward-moved position is applied to the rotation stopper 36, the rotation stopper 36 starts its backward movement by releasing the regulation of the backward movement due to the upward movement of the pedal stopper pin 34b.

[0158] When the rotation stopper 36 starts the backward movement in this way, the pedal operating shaft 361 departs from the fitting portion 283a and the lower pedal 28 starts its backward movement against the biasing force of the lower pedal spring 28b with the weight of the product. The pedal operating shaft 361 of the rotation stopper 36 departing from the fitting portion 283a moves to a position at which the first guide portion 283b and the second guide portion 283c intersect each other along the first guide portion 283b.

[0159] Thereafter, the lower pedal 28 moves backward with the weight of the lowest product, the downward movement of the lowest product is allowed, and the lowest product is discharged downward (see FIG. 8). The discharged product is guided to the product discharge port 3c via the product chute 5 and can be taken out via the product output port 2a.

[0160] When the lowest product passes through the lower pedal 28, the lower pedal 28 moves to the forward-moved position with the elastic biasing force of the lower pedal spring 28b and the rotation stopper 36 also moves to the forward-moved position with the elastic biasing force of the pedal operation spring. When the lower pedal 28 and the rotation stopper 36 move to the forward-moved position, the pedal operating shaft 361 held at the position at which the first guide portion 283b and the second guide portion 283c intersect each other moves to the fitting portion 283a along the second guide portion 283c, and the lower pedal 28

and the rotation stopper 36 are returned to the forward-moved position.

[0161] In the meantime, the pedal link 35 moves upward, the stopper pin 34a is located at the top ends of the
5 stopper pin insertion holes 23b3 and 24c1, and the pedal stopper pin 34b is located at the top ends of the pedal stopper pin support grooves 23b4 and 24c2.

[0162] Thereafter, when the contact of the cam portion 443a with the base end 462a is released with the rotation
10 of the output gear 443, the pedal link 35 is biased to move downward by the link spring 35a.

[0163] With the downward movement of the pedal link 35, the stopper pin 34a moves downward from the top ends of the stopper pin insertion holes 23b3 and 24c1 and the pedal
15 stopper pin 34b moves downward from the top ends of the pedal stopper pin support grooves 23b4 and 24c2.

[0164] When the pedal stopper pin 34b moves downward to the bottom ends of the pedal stopper pin support grooves 23b4 and 24c2, the pedal stopper pin 34b comes in contact
20 with the recessed portion 36b on the rear side of the rotation stopper 36 returned to the forward-moved position. Accordingly, the movement in the backward moving direction is regulated and the lower pedal 28 is returned to the product-absent standby posture in which the lower pedal
25 moves forward to the first product storage passage 13a by the biasing force of the lower pedal spring 28b.

[0165] On the other hand, the upper pedal 29 is biased by the upper pedal spring and moves backward with the downward movement of the stopper pin 34a. Accordingly, the
30 downward movement of the next product is allowed, then the next product comes in contact with the forward-moved lower pedal 28 to regulate the downward movement thereof, and the lower pedal 28 transitions to the product-present standby

posture and is returned to the standby state.

[0166] In the drive unit 40, the cam portion 443a comes in contact with the base end 462a of the second link lever 462 with the clockwise rotation of the output gear 443 in a front view. In this case, since the locking portion 462c comes in contact with the right edge portion 472 of the left opening, the rotation of the second link lever 462 about the central axis is regulated. Accordingly, the locking portion 462c is elastically deformed to bring the base end 462a close to the locking portion 462c, thereby not interfering with the movement of the cam portion 443a due to the rotation of the output gear 443.

[0167] Thereafter, when the cam portion 443a is returned to the position of the standby state with the rotation of the output gear 443, the pressing piece 443b presses the contactor 45a of the carrier switch 45 to switch the carrier switch 45 to the ON state. Immediately after the pressing piece 443b presses the contactor 45a of the carrier switch 45, the cam portion 443a departs from the base end 462a of the second link lever 462 and the second link lever 462 is returned to the original state by the locking portion 462c.

[0168] In the above-mentioned positive driving of the motor 43 in step S102, the dispensing control unit 110 monitors whether the carrier switch 45 is switched to the ON state within a predetermined time (steps S103 and S104). That is, it is monitored whether the output gear 443 rotates by one turn within a predetermined time.

[0169] When it is determined that the carrier switch 45 is switched to the ON state within the predetermined time (YES in step S103 and NO in step S104), the dispensing control unit 110 stops the positive driving of the motor 43 (step S105), returns the control flow, and ends the process.

As a result, it is possible to reliably discharge the first product for which a discharge command is issued as described above.

[0170] When the carrier switch 45 is not switched to the ON state within the predetermined time, that is, when the ON signal is not output from the carrier switch 45 within the predetermined time (NO in step S103 and YES in step S104), the dispensing control unit 110 performs a retry process (1) (step S200).

10 [0171] FIG. 28 is a flowchart illustrating processing details of the retry process (1) in the dispensing control process illustrated in FIG. 24.

[0172] In the retry process (1), the dispensing control unit 110 drives the motor 43 reversely and monitors whether the carrier switch 45 is switched to the ON state within a predetermined time (steps S201, S202, and S203). When the motor 43 is driven reversely, the output gear 443 to which the driving force of the motor 43 is transmitted via the worm gear 441 and the intermediate gear 442 rotates counterclockwise in a front view. When the motor 43 is driven reversely, at least the cam portion 443a of the output gear 443 does not come in contact with the base end 462a of the second link lever 462, that is, the cam portion 443a does not pass through the base end 462a. Accordingly, even when the motor 43 is driven reversely, the second link lever 462 is not adversely affected (the second product is not discharged from the second product discharging device 20b).

[0173] When it is determined that the carrier switch 45 is switched to the ON state within the predetermined time (YES in step S202 and NO in step S203), the dispensing control unit 110 stops the reverse driving of the motor 43 (step S204) and drives the motor 43 positively again (step

S205). Then, it is monitored whether the carrier switch 45 is switched to the ON state within the predetermined time (steps S206 and S207).

[0174] Thereafter, when the carrier switch 45 is
5 switched to the ON state within the predetermined time (YES
in step S206 and NO in step S207), that is, when the output
gear 443 rotates by one turn clockwise in a front view
within the predetermined time, it is considered that the
first product is discharged as described above, the driving
10 of the motor 43 is stopped, it is determined that the retry
is successful (steps S208 and S209), the control flow is
returned, and the retry process (1) is ended.

[0175] On the other hand, the carrier switch 45 is not
switched to the ON state within the predetermined time (NO
15 in step S206 and YES in step S207), the dispensing control
unit 110 considers that a problem occurs, determines that
the retry fails (step S210), returns the control flow, and
ends the retry process (1). When it is determined in step
S201 that the carrier switch 45 is not switched to the ON
20 state within the predetermined time (NO in step S202 and
YES in step S203), the dispensing control unit 110
determines that the retry fails (step S210), returns the
control flow, and ends the retry process (1).

[0176] When the retry succeeds (YES in step S106), the
25 dispensing control unit 110 having performed the retry
process (1) holds the standby state (step S107), then
returns the control flow, and ends the dispensing control
process. As a result, by issuing a new command to dispense
the first product, dispensing of the first product is
30 enabled.

[0177] On the other hand, when the retry fails (NO in
step S106), the dispensing control unit considers and
determines that the first product in the first product

storage passage 13a is sold out (step S108), then returns the control flow, and ends the process. Accordingly, it is determined that the first product is sold out, and thus a sold-out lamp or the like can be lighted to stop vending of the first product.

[0178] On the other hand, when a command to discharge the second product is issued from the vending machine controller 100 (NO in step S101 and YES in step S109), the dispensing control unit 110 drives the motor 43 reversely (step S110).

[0179] When the motor 43 is driven reversely in this way, the output gear 443 to which the driving force of the motor 43 is transmitted via the worm gear 441 and the intermediate gear 442 rotates counterclockwise in a front view.

[0180] When the output gear 443 rotates counterclockwise in a front view, the pressing piece 443b of the output gear 443 departs from the contactor 45a of the carrier switch 45. Accordingly, the contactor 45a of the carrier switch 45 is opened from the pressed state and is switched to the OFF state.

[0181] When the cam portion 443a comes in contact with the base end 462a of the second link lever 462 from the upper side with the rotation of the output gear 443, the second link lever 462 rotates clockwise in the front view. When the second link lever 462 rotates clockwise, the tip portion 462b moves upward. When the tip portion 462b moves upward in this way, the tip portion comes in contact with the contact piece 351' of the pedal link 35', the pedal link 35' can move upward by a predetermined distance against the biasing force of the link spring 35a', and the pedal link 35' can be held in the state in which the pedal link moves upward by the predetermined distance while the

cam portion 443a comes in sliding contact with the base end 462a.

[0182] In this case, when the second link lever 462 comes in sliding contact with the cam portion 443a, not
5 clearly illustrated in the drawing, the second link lever is adjusted such that the plane including the portion coming in sliding contact with the cam portion 443a is substantially perpendicular to the plane including its central axis (the central axis of the second link shaft
10 42f) and the stop axis of the output gear 443.

[0183] With the upward movement of the pedal link 35', the stopper pin moves upward and the pedal stopper pin 34b' also moves upward.

[0184] At this time, since the stopper pin moves upward
15 while coming in contact with the edge wall of the concave portion 292' of the upper pedal 29', the upper pedal 29' moves forward from the initial position against the biasing force of the upper pedal spring. The forward movement of the upper pedal 29' is performed along with the upward
20 movement of the stopper pin. At the time at which the stopper pin reaches the top end of the stopper pin insertion hole, the stopper pin comes in contact with the stopper contact portion 293' to regulate the backward movement of the upper pedal 29'.

25 [0185] The upper pedal 29' moving forward comes in contact with a second lowest piece of second product (hereinafter, also referred to as a next product) to regulate downward movement of the next product.

[0186] On the other hand, since the weight of the
30 product coming in contact with the lower pedal 28' maintained at the forward-moved position is applied to the rotation stopper 36', the rotation stopper 36' starts its backward movement by releasing the regulation of the

backward movement due to the upward movement of the pedal stopper pin 34b'.

[0187] When the rotation stopper 36' starts the backward movement in this way, the pedal operating shaft 361'

5 departs from the fitting portion and the lower pedal 28' starts its backward movement against the biasing force of the lower pedal spring 28b' with the weight of the product. The pedal operating shaft 361' of the rotation stopper 36' departing from the fitting portion moves to a position at
10 which the first guide portion and the second guide portion intersect each other along the first guide portion.

[0188] Thereafter, the lower pedal 28' moves backward with the weight of the lowest product, the downward movement of the lowest product is allowed, and the lowest
15 product is discharged downward. The discharged product is guided to the product discharge port 3c via the product chute 5 and can be taken out via the product output port 2a.

[0189] When the lowest product passes through the lower pedal 28', the lower pedal 28' moves to the forward-moved
20 position with the elastic biasing force of the lower pedal spring 28b' and the rotation stopper 36' also moves to the forward-moved position with the elastic biasing force of the pedal operation spring. When the lower pedal 28' and the rotation stopper 36' move to the forward-moved position,
25 the pedal operating shaft 361' held at the position at which the first guide portion and the second guide portion intersect each other moves to the fitting portion along the second guide portion, and the lower pedal 28' and the rotation stopper 36' are returned to the forward-moved
30 position.

[0190] Thereafter, when the contact of the cam portion 443a with the base end 462a is released with the rotation of the output gear 443, the pedal link 35' is biased to

move downward by the link spring 35a'.

[0191] With the downward movement of the pedal link 35', the stopper pin moves downward and the pedal stopper pin 34b' also moves downward.

5 [0192] When the pedal stopper pin 34b' moves to the bottom end of the pedal stopper pin support groove, the pedal stopper pin 34b' comes in contact with the recessed portion 36b' on the rear side of the rotation stopper 36' returned to the forward-moved position. Accordingly, the
10 movement in the backward moving direction is regulated and the lower pedal 28' is returned to the product-absent standby posture in which the lower pedal moves forward to the second product storage passage 13b by the biasing force of the lower pedal spring 28b'.

15 [0193] On the other hand, the upper pedal 29' is biased by the upper pedal spring and moves backward with the downward movement of the stopper pin. Accordingly, the downward movement of the next product is allowed, then the next product comes in contact with the forward-moved lower
20 pedal 28' to regulate the downward movement thereof, and the lower pedal 28' transitions to the product-present standby posture and is returned to the standby state.

[0194] In the drive unit 40, the cam portion 443a comes in contact with the base end 461a of the first link lever
25 461 with the counterclockwise rotation of the output gear 443 in a front view. In this case, since the locking portion 461c comes in contact with the left edge portion 471 of the right opening, the rotation of the first link lever 461 about the central axis is regulated. Accordingly,
30 the locking portion 461c is elastically deformed to bring the base end 461a close to the locking portion 461c, thereby not interfering with the movement of the cam portion 443a due to the rotation of the output gear 443.

[0195] Then, when the cam portion 443a is returned to the position of the standby state with the rotation of the output gear 443, the pressing piece 443b presses the contactor 45a of the carrier switch 45 to switch the carrier switch 45 to the ON state.

[0196] In the above-mentioned reverse driving of the motor 43 in step S110, the dispensing control unit 110 monitors whether the carrier switch 45 is switched to the ON state within a predetermined time (steps S111 and S112). That is, it is monitored whether the output gear 443 rotates by one turn within a predetermined time.

[0197] When it is determined that the carrier switch 45 is switched to the ON state within the predetermined time (YES in step S111 and NO in step S112), the dispensing control unit 110 stops the reverse driving of the motor 43 (step S113), returns the control flow, and ends the process. As a result, it is possible to reliably discharge the second product for which a discharge command is issued as described above.

[0198] When the carrier switch 45 is not switched to the ON state within the predetermined time, that is, when the ON signal is not output from the carrier switch 45 within the predetermined time (NO in step S111 and YES in step S112), the dispensing control unit 110 performs a retry process (2) (step S300).

[0199] FIG. 29 is a flowchart illustrating processing details of the retry process (2) in the dispensing control process illustrated in FIG. 24.

[0200] In the retry process (2), the dispensing control unit 110 drives the motor 43 positively and monitors whether the carrier switch 45 is switched to the ON state within a predetermined time (steps S301, S302, and S303). When the motor 43 is driven positively, the output gear 443

to which the driving force of the motor 43 is transmitted via the worm gear 441 and the intermediate gear 442 rotates clockwise in a front view.

[0201] When it is determined that the carrier switch 45
5 is switched to the ON state within the predetermined time (YES in step S302 and NO in step S303), the dispensing control unit 110 stops the positive driving of the motor 43 (step S304) and drives the motor 43 reversely again (step S305). Then, it is monitored whether the carrier switch 45
10 is switched to the ON state within the predetermined time (steps S306 and S307).

[0202] Thereafter, when the carrier switch 45 is switched to the ON state within the predetermined time (YES in step S306 and NO in step S307), that is, when the output
15 gear 443 rotates by one turn counterclockwise in a front view within the predetermined time, it is considered that the second product is discharged as described above, the driving of the motor 43 is stopped, it is determined that the retry is successful (steps S308 and S309), the control
20 flow is returned, and the retry process (2) is ended.

[0203] On the other hand, the carrier switch 45 is not switched to the ON state within the predetermined time (NO in step S306 and YES in step S307), the dispensing control unit 110 considers that a problem occurs, determines that
25 the retry fails (step S310), returns the control flow, and ends the retry process (2). When it is determined in step S301 that the carrier switch 45 is not switched to the ON state within the predetermined time (NO in step S302 and YES in step S303), the dispensing control unit 110
30 determines that the retry fails (step S310), returns the control flow, and ends the retry process (2).

[0204] When the retry succeeds (YES in step S114), the dispensing control unit 110 having performed the retry

process (2) holds the standby state (step S115), then returns the control flow, and ends the dispensing control process. As a result, by issuing a new command to dispense the second product, dispensing of the second product is enabled.

[0205] On the other hand, when the retry fails (NO in step S114), the dispensing control unit considers and determines that the second product in the second product storage passage 13b is sold out (step S116), then returns the control flow, and ends the process. Accordingly, it is determined that the second product is sold out, and thus a sold-out lamp or the like can be lighted to stop vending of the second product.

[0206] For example, when the product in the first product storage passage 13a is sold out, the lower pedal 28 of the first product discharging device 20a is biased by the lower pedal spring 28b and is switched to the product-absent standby posture. In this case, as illustrated in FIG. 12, the base end of the lower pedal 28 comes in contact with the first sold-out contact portion 32 of the first sold-out link 30 and thus the first sold-out link 30 rotates about the first swing support shaft 28a to cause the first sold-out pressing portion 33 to press the contactor 26a of the first sold-out detection switch 26. Accordingly, in the first sold-out detection switch 26, the contactor 26a is pressed and displaced forward against the biasing force of the spring into the ON state, and outputs the ON signal to the dispensing control unit 110. Accordingly, the dispensing control unit 110 can consider that the first product is sold out and thus can light a sold-out lamp or the like.

[0207] For example, when the product in the second product storage passage 13b is sold out, the base end of

the lower pedal 28' comes in contact with the second sold-out contact portion 52 of the second sold-out link 50 and thus the second sold-out link 50 rotates about the first swing support shaft 28a' to cause the second sold-out pressing portion 53 to press the contactor 27a of the second sold-out detection switch 27. Accordingly, in the second sold-out detection switch 27, the contactor 27a is pressed and displaced backward against the biasing force of the spring into the ON state, and outputs the ON signal to the dispensing control unit 110. Accordingly, the dispensing control unit 110 can consider that the second product is sold out and thus can light a sold-out lamp or the like.

[0208] The dispensing control unit 110 may be configured to determine that the product is sold out when the ON signal of the first sold-out detection switch 26 or the second sold-out detection switch 27 is maintained for a predetermined time or more. Accordingly, it is possible to prevent an erroneous operation when the lower pedal 28 (28') is returned to the product-absent standby posture every vending or an erroneous operation due to chattering which occurs by bound or the like when the lower pedal 28 is returned.

[0209] The product discharging device and the product dispensing system 20 which have been described above exhibit the following operational advantages.

[0210] In the first product discharging device 20a, the first sold-out detection switch 26 switches its state to detect presence or absence of the first product in the first product storage passage 13a when the lower pedal 28 transitions to the product-absent standby posture and the product-present standby posture, and the second sold-out detection switch 27 switches its state to detect presence

or absence of the second product in the second product storage passage 13b when the lower pedal 28' transitions to the product-absent standby posture and the product-present standby posture. Accordingly, it is possible to

5 satisfactorily recognize that no product is present in the product storage passages 13 and to match the number of sales opportunities of product with the number of products in the product storage passages 13. Accordingly, according to the first product discharging device 20a, it is possible
10 to increase the number of product sales opportunities.

[0211] In the first product discharging device 20a and the second product discharging device 20b, since the rotation stoppers 36 and 36' include the blindfold portions 36c and 36c' covering the sides of the pedal stopper pins
15 34b and 34b' opposite to the product storage passages 13, a blindfold plate as in the related art is not necessary and it is possible to retain the antitheft capability while decreasing the number of components. As a result, according to the first product discharging device 20a and
20 the second product discharging device 20b, it is possible to achieve a decrease in manufacturing cost and to improve the antitheft capability.

[0212] In the first product discharging device 20a, the output gear 443 constituting the drive unit 40 is linked to
25 the motor 43 via the worm gear 441 and rotates by the driving force of the motor 43 transmitted via the worm gear 441. The first link lever 461 and the second link lever 462 constituting the drive unit 40 causes the upper pedals 29 and 29' to move forward to the product storage passage
30 13 and to come in contact with the second lowest product and causes the lower pedals 28 and 28' to move backward from the product storage passage 13 to discharge the lowest product downward by staying in the upward-rotated state and

maintaining the pedal links 35 and 35' in the upward-moved state when the link levers come in sliding contact with the cam portion 443a disposed in the output gear 443, and causes the upper pedals 29 and 29' to move backward from the product storage passage 13 and causes the lower pedals 28 and 28' to move forward to the product storage passage 13 to regulate downward movement of the products by allowing the pedal links 35 and 35' to move downward when the sliding contact with the cam portion 443a is released.

10 In the first product discharging device 20a, the worm gear 441 is interposed between the output gear 443 and the motor 43 even when the supply of power is intercepted due to power outage or the like during driving of the motor 43, and thus the output gear 443 does not rotate reversely but

15 can maintain its state even when the motor 43 is stopped, whereby the pedal links 35 and 35' can be maintained in the upward-moved state. Accordingly, since the upper pedals 29 and 29' can be maintained in the forward-moved state, the phenomenon in the related art using the AC solenoid in

20 which the AC solenoid is switched to a non-powered state and the pedal link moves downward due to interception of the supply of power due to power outage or the like does not occur. As a result, according to the first product discharging device 20a, it is possible to prevent plural

25 products from being discharged when supply of power is intercepted due to power outage or the like at the time of discharging of a product. The first link lever 461 and the second link lever 462 are configured to be substantially perpendicular to the surface (A) including a part coming in

30 sliding contact with the cam portion 443a and the plane (B) including the own axes and the axis of the output gear 443 when the link levers come in sliding contact with the cam portion 443a. Accordingly, the output gear 443 can

reliably hold the pedal links 35 and 35' in the upward-moved state without receiving a load in the rotating direction.

[0213] According to the above-mentioned product dispensing system 20, since the first product discharging device 20a includes the motor 43 serving as a drive source for the first product discharging device 20a and the second product discharging device 20b and the drive unit 40 that alternatively selects the first product discharging device 20a and the second product discharging device 20b in accordance with a discharge command and applies the driving force from the motor 43 to the selected discharging device when the discharge command is issued, it is possible to decrease the number of drive sources in comparison with the number of discharge mechanisms and to decrease the manufacturing cost. Since the first product discharging device 20a includes the drive unit 40 including the motor 43, it is also possible to use only the first product discharging device 20a. That is, the present invention can be applied to a product storage rack 10 in which an odd number of product storage passages 13 are arranged in the front-rear direction as well as the product storage rack 10 in which an even number of product storage passages 13 are arranged in the front-rear direction. Accordingly, it is possible to achieve a decrease in manufacturing cost and to flexibly work depending on the number of product storage passages 13 adjacent in the front-rear direction.

[0214] According to the product dispensing system 20, since the motor 43 as a drive source is a DC motor, the motor is not easily affected by a local voltage or a frequency fluctuation and can be disposed at various locations.

[0215] According to the product dispensing system 20,

since the first product discharging device 20a is provided with the first sold-out detection switch 26 and the second sold-out detection switch 27, it may be possible to use only the first product discharging device 20a. Accordingly, it is possible to flexibly work depending on the number of product storage passages 13 adjacent in the front-rear direction. In addition, since electrical components are disposed in only the first product discharging device 20a, harnesses can be integrated in the first product discharging device 20a.

[0216] According to the product dispensing system 20, since the postures of the first link lever 461 and the second link lever 462 in the normal state are determined by bringing the elastically deformable locking portions 461c and 462c formed therein into contact with predetermined parts (471 and 472), it is possible to easily attach the unit cover 42 to the unit base 41.

[0217] According to the product dispensing system 20, when the product discharging device 20a or 20b which is alternatively selected and is supplied with the driving force by the drive unit 40 is not driven within a predetermined time, the dispensing control unit 110 considers that only the product discharging device 20a or 20b is out of order and performs sold-out processing of determining that the product in the product storage passage 13 of the product discharging device 20a or 20b is sold out. Accordingly, even when any one of the first product discharging device 20a and the second product discharging device 20b is subjected to vending stop by the sold-out processing, the other can continue to discharge the product and it is thus possible to perform a moderate operation corresponding to each product storage passage 13.

[0218] According to the product dispensing system 20,

since the first sold-out detection switch 26 and the second sold-out detection switch 27 are disposed in the harness guide 25, it is possible to protect the harness and the sold-out detection switches 26 and 27 well when the first product discharging device 20a and the second product discharging device 20b are attached and detached.

[0219] While the exemplary embodiment of the present invention has been described above, the present invention is not limited to the exemplary embodiment and can be modified in various forms.

[0220] In the above-mentioned embodiment, the postures of the first link lever 461 and the second link lever 462 in the normal state are determined by bringing the elastically deformable locking portions 462c formed therein into contact with a predetermined part, but in the present invention, a spring 61 biasing the link lever 46' clockwise in a front view and a spring 62 biasing the link lever 46' counterclockwise in a front view may be interposed therebetween as illustrated in FIG. 30, whereby the springs 61 and 62 serve as torsion springs to determine the posture of the link lever 46' in the normal state by the biasing forces thereof.

[0221] In the above-mentioned embodiment, the first sold-out link 30 and the second sold-out link 50 are disposed in the first swing support shafts 28a and 28a' of the lower pedal 28 and 28' and the first sold-out detection switch 26 and the second sold-out detection switch 27 are switched to the ON state by switching the lower pedals 28 and 28' to the product-absent standby posture, but in the present invention, a lever member 71 that is swingable to move forward to and backward from the product storage passage 13 may be disposed in an area above the lower pedals 28 and 28' as illustrated in FIG. 31. Similarly to

the lower pedals 28 and 28', the lever member 71 is biased to move forward to the product storage passage 13 by a lever spring not illustrated, and is changed to a posture in which the tip thereof extends upward to be separated
5 from the top surfaces of the lower pedals 28 and 28' when no product is placed on the top surface, and a part of the lever member 71 presses a contactor 72 of a sold-out detection switch 27 not illustrated to turn on the sold-out detection switch 27. On the other hand, when the top
10 surface is pressed by product input to the product storage passage 13, the lever member 71 is changed to a posture in which the tip thereof comes in contact with the top surfaces of the lower pedals 28 and 28', the part pressing the contactor 72 of the sold-out detection switch is
15 separated from the contactor 72 to turn off the sold-out detection switch 27. According to this configuration, it is possible to satisfactorily recognize that no product is present in the product storage passage 13 and to match the number of sales opportunities of product with the number of
20 products in the product storage passages 13. As a result, it is possible to increase the number of product sales opportunities.

[0222] In the above-mentioned embodiment, the antitheft capability is retained by providing the rotation stoppers
25 36 and '36' with the blindfold portions 36c and 36c', but in the present invention, the antitheft capability may be retained by providing an antitheft link mechanism that regulates upward movement of the pedal link in the normal state and departs from the area above the pedal link to
30 allow movement of the pedal link when the pedal link is made to move upward by the driving of the drive unit.

[0223] In the above-mentioned embodiment, the first product discharging device 20a corresponds to the first

product storage passage 13a and the second product
 discharging device 20b corresponds to the second product
 storage passage 13b, but the present invention is not
 limited to this configuration. One product discharging
 5 device may correspond to the other product storage passage
 and the other product discharging device may correspond to
 one product storage passage.

Reference Signs List

	[0224]	1	MAIN CABINET
10		4	PRODUCT STORAGE
		10	PRODUCT STORAGE RACK
		13	PRODUCT STORAGE PASSAGE
		20	PRODUCT DISPENSING SYSTEM
		20a	FIRST PRODUCT DISCHARGING DEVICE
15		20b	SECOND PRODUCT DISCHARGING DEVICE
		25	HARNESS GUIDE
		26	FIRST SOLD-OUT DETECTION SWITCH
		27	SECOND SOLD-OUT DETECTION SWITCH
		28	LOWER PEDAL
20		29	UPPER PEDAL
		35	PEDAL LINK
		40	DRIVE UNIT
		41	UNIT BASE
		42	UNIT COVER
25		43	MOTOR
		44	GEAR MEMBER
		45	CARRIER SWITCH
		46	LINK LEVER
		110	DISPENSING CONTROL UNIT
30			

CLAIMS

1. A product dispensing system comprising:

one product discharging device that is applied to one product storage passage storing an input product in a vertical direction, regulates downward movement of the product stored in the one product storage passage in a standby state, and discharges a lowest product stored in the one product storage passage downward in an activated state; and

the other product discharging device that is applied to the other product storage passage being adjacent to the one product storage passage and storing an input product in the vertical direction thereof, regulates downward movement of the product stored in the other product storage passage in a standby state, and discharges a lowest product stored in the other product storage passage downward in an activated state,

the one product discharging device and the other product discharging device being coupled to each other back to back,

wherein the one product discharging device includes a drive source for the one product discharging device and the other product discharging device,

a driving force applying unit configured to alternatively select the one product discharging device and the other product discharging device in accordance with a discharge command and to apply a driving force from the drive source to the selected product discharging device when the discharge command is issued, and

a control unit configured to perform sold-out processing of considering that only the product discharging device is out of order and determining that the products of the product storage passage of the product discharging

device is sold out when the product discharging device which is alternatively selected and supplied with a driving force by the driving force applying unit is not activated within a predetermined time.

5

2. The product dispensing system according to claim 1, wherein the control unit performs a retry process of performing the operation of causing the driving force applying unit to select the product discharging device and to apply the driving force to the selected product discharging device again when the product discharging device which is alternatively selected and supplied with a driving force by the driving force applying unit is not activated within the predetermined time.

15

3. The product dispensing system according to claim 2, wherein the control unit causes the product discharging device to return to a predetermined standby position and performs the retry process when the product discharging device which is alternatively selected and supplied with a driving force by the driving force applying unit is not activated within the predetermined time.

4. The product dispensing system according to claim 1, wherein the driving force applying unit includes:

an output gear that is disposed to be rotatable positively and reversely about its own axis, rotates positively when the discharge command is issued to the one product discharging device, and rotates reversely when the discharge command is issued to the other product discharging device; and

a link lever that is disposed to be rotatable about its own axis in correspondence with the product discharging

devices, sets the corresponding product discharging device to the standby state in a normal state, and drives the corresponding product discharging device when the link lever is supplied with the driving force to rotate by
5 rotation of the output gear.

5. The product dispensing system according to claim 1, wherein the drive source is common to the one product discharging device and the other product discharging device.
10

6. The product dispensing system according to claim 1, wherein the drive source is a DC motor.