



(51) International Patent Classification:
C10M 145/16 (2006.01)

(21) International Application Number:
PCT/US2013/026009

(22) International Filing Date:
14 February 2013 (14.02.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/599,992 17 February 2012 (17.02.2012) US

(71) Applicant: THE LUBRIZOL CORPORATION
[US/US]; 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US).

(72) Inventors: BAKER, Mark R.; 2300 James Savage Road, Midland, Michigan 48642 (US). BAUM, Marina; 9911 Brecksville Road, Cleveland, Ohio 44141-3247 (US). HICKMAN, Lynsey; P.O. Box 88, The Knowle, Belper Derby DE56 1QN (GB). VISGER, Daniel C.; 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US). BARTON, William R.S.; P.O. Box 88, The Knowle, Belper Derby DE56 1QN (GB).

(74) Agents: TYRPAK, Michele M. et al.; The Lubrizol Corporation, 29400 Lakeland Blvd., Mail Drop 022B, Wickliffe, Ohio 44092-2298 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: LUBRICATING COMPOSITION INCLUDING ESTERIFIED COPOLYMER AND LOW DISPERSANT LEVELS SUITABLE FOR DRIVELINE APPLICATIONS

(57) Abstract: A lubricating composition, method of making, and method of use are disclosed. The lubricant includes an esterified copolymer including a backbone that includes units derived from a vinyl aliphatic monomer and units derived from a carboxylic acid monomer, the carboxylic acid monomer comprising an α,β -ethylenically unsaturated dicarboxylic acid or derivative thereof. The lubricating composition also includes an oil of lubricating viscosity. The lubricating composition includes no more than 2.5 wt. % of dispersant for dispersing oxidation products, other than the esterified copolymer.

