

{Description}

{Title of Invention}

DISPOSABLE WEARING ARTICLE

{Technical Field}

5 {0001}

The present invention relates to disposable wearing articles and more particularly to disposable wearing articles such as disposable diapers, disposable toilet-training pants, disposable incontinent pants, disposable sanitary pants and the like, each provided in a crotch region thereof with leg elastic elements secured thereto in a curved state.

{Background}

{0002}

Conventionally, wearing articles including elasticized lateral portions adapted to be put in close contact with the wearer's thighs are known. For example, JP 2000-254176 A (PTL 1) discloses a disposable wearing article including a pair of elasticized lateral portions on both sides of a liquid-absorbent structure each provided with a plurality of strand- or string-like leg elastic elements.

{Citation List}

{Patent Literature}

{0003}

{PTL 1} JP 2000-254176 A

{Summary}

{Technical Problem}

{0004}

5 In wearing articles such as disposable diapers, it is generally required for a crotch region to have, in its middle and in the vicinity thereof, a fit better than that in the other regions in order to prevent body waste from sideways leaking out of the article. In the wearing article according to the invention disclosed in PTL 1, each of elasticized lateral
10 portions is provided in its entire area in a transverse direction with leg elastic elements extending in a longitudinal direction in parallel one to another at regular intervals. With such an arrangement, it is impossible to make a tensile stress
15 in the middle of the crotch region outstanding. While the tensile stress generated by the leg elastic elements may be locally enhanced by adjusting the total number or the total tensile stress of the leg elastic elements, when such measure is adopted that the elasticized lateral portions as a whole
20 should excessively tighten the wearer's legs and create a feeling of discomfort against the wearer. Furthermore, to increase the number of the elastic elements locally, an additional step for this purpose will be required.

{0005}

An object of the present invention is to provide a disposable wearing article improved so that the tensile stress in the middle of the crotch region as well as in the vicinity thereof can be set to be higher than in the other regions without adjusting the number and thickness of the leg elastic elements and a relatively large body waist retaining space can be formed to protect the wearer's skin from being soiled with body waste.

{Solution to Problem}

10 {0006}

According to the present invention, there is provided a disposable wearing article having a longitudinal direction and a transverse direction orthogonal to the longitudinal direction, including a side facing the wearer's skin and a side facing away from the wearer's skin, a front waist region, a rear waist region and a crotch region extending between the front and rear waist regions.

{0007}

The improvement according to the present invention is characterized in that the article further includes front and rear elastic waist panels defining the front and rear waist regions, a crotch member located in the crotch region and a part of the front and rear waist regions and having a front end and

a rear end bonded to the front waist panel and the rear waist panel, respectively, and a liquid-absorbent structure bonded to the crotch region on the side facing the wearer's skin, the crotch region has elasticized lateral portions formed by
5 folding lateral portions of the crotch member and adapted to be spaced upward from the liquid-absorbent structure, each of the elasticized lateral portions is provided with strand- or string-like leg elastic elements extending from the crotch region to the front and rear waist regions, the leg elastic
10 elements comprise first leg elastic elements extending rectilinearly in the longitudinal direction immediately inboard of the respective elasticized lateral portions and second leg elastic elements extending in the longitudinal direction outboard of the first leg elastic elements as viewed
15 in the transverse direction, each of the second leg elastic elements comprises rectilinear segments disposed in the front and rear ends of the crotch member and extending in the front and rear waist regions and a concavely curved segment located
20 in the crotch region, and elasticized regions defined by the first leg elastic elements have tensile stress higher than that of elasticized regions defined by the second leg elastic elements.

{0008}

The present invention additionally includes embodiments as follows:

(1) A dimension by which each pair of the adjacent second leg elastic elements is spaced from each other in the transverse direction is gradually reduced as the second elastic elements get closer to the middle zone of the crotch region.

(2) The concavely curved segment of the second leg elastic elements has a tensile stress higher than that of the rectilinear segments of the second leg elastic elements.

(3) The front and rear ends of the crotch member are bonded to the outer surfaces of the front and rear elastic waist panels, respectively.

(4) The front adhesive region substantially overlaps an inner end of the front waist panel and has a substantially trapezoidal shape contoured by an inner end extending in the transverse direction between the inner side edges of the respective elasticized lateral portions, an outer end substantially overlapping the front end of the crotch member and extending in the transverse direction, and both side edges obliquely extending from the outer end toward the inner end between the inner and outer ends, and the rear adhesive region has a substantially rectangular shape which is transversally long and

includes an inner end extending in the transverse direction and substantially overlapping an inner end of the rear waist panel and an outer end extending in the transverse direction and substantially overlapping an rear end of the crotch member.

5 {Advantageous Effects of Invention}

{0009}

According to the present invention, the crotch region is provided along side edges thereof with a plurality of leg elastic elements contractibly attached thereto under tension so as to extend in the longitudinal direction. Of the elastic elements defining the leg elastic elements, the elastic elements lying on the outside as viewed in the transverse direction have concavely curved segments in the longitudinally middle zone of the crotch region and in the vicinity thereof.

10

15 With this unique arrangement, the tensile stress of the regions defined by these concavely curved segments may be set to be higher than in the other regions without varying the kind, the number and the thickness of the elastic elements.

{Brief Description of Drawings}

20 {0010}

{Fig. 1} Fig. 1 is a perspective view showing a disposable diaper as one example of disposable wearing articles according to a first embodiment of the present invention.

{Fig. 2} Fig. 2 is a partially cutaway plan view showing the diaper as has been developed and flattened in the front-back direction after the front and rear waist regions have been peeled off at seams as viewed from the inner surface of the
5 diaper.

{Fig. 3} Fig. 3(a) is a sectional view taken along the line III-III in Fig. 2 and Fig. 3(b) is a sectional view similar to Fig. 3(a) but illustrating the diaper put on the wearer's body.

{Fig. 4} Fig. 4 is a sectional view taken along the line IV-IV
10 in Fig. 2.

{Fig. 5} Fig. 5 is a plan view of a crotch member.

{Fig. 6} Fig. 6 is a perspective view illustrating a part of the diaper manufacturing apparatus used to make the crotch member.

15 {Fig. 7} Fig. 7 is a plan view similar to Fig. 5, showing the second embodiment of the present invention.

{Description of Embodiments}

{0011}

<First Embodiment>

20 Fig. 1 is a perspective view showing a disposable diaper 10 as one example of the disposable wearing articles according to a first embodiment of the present invention, Fig. 2 is a partially cutaway plan view showing the diaper 10 as has been

developed and flattened in the front-back direction after front and rear waist regions have been peeled off from each other at seams 18 as viewed from the inner surface of the diaper 10, Fig. 3(a) is a sectional view taken along the line III-III in Fig. 2 and Fig. 3(b) is a sectional view similar to Fig. 3(a) but illustrating the diaper 10 put on the wearer's body, Fig. 4 is a sectional view taken along the line IV-IV in Fig. 2 and Fig. 5 is a plan view of a crotch member 12. In Fig. 5, a liquid-absorbent structure 40 is not illustrated for convenience of illustration.

{0012}

Referring to Figs. 1 and 2, the disposable diaper 10 has a longitudinal direction Y and a transverse direction X orthogonal to the longitudinal direction Y, an imaginary center line P-P bisecting a dimension of the diaper 10 in the transverse direction X, including a side facing the wearer's skin and a side facing away from the diaper wearer's skin, an annular elasticized waist panel 11 and a crotch member 12 attached to the side of the annular waist panel 11 to define a front waist region 13, a rear waist region 14 and a crotch region 15 extending in the longitudinal direction Y between the front and rear waist regions 13, 14. The diaper 10 is formed symmetrically about the imaginary center line P-P. The elastic waist panel 11 includes

a front waist panel 16 defining the front waist region 13 and
a rear waist panel 17 defining the rear waist region 14.

{0013}

The front waist panel 16 has a horizontally long
5 substantially rectangular shape contoured by an inner end 16a
intersecting with the crotch member 12 and extending in the
transverse direction X, an outer end 16b opposed to and spaced
from the inner end 16a and extending in the transverse direction
X and both side edges 16c, 16d extending in the longitudinal
10 direction Y between the inner and outer ends 16a, 16b.

{0014}

The rear waist panel 17 is substantially the same as the
front waist panel 16 in size as well as in shape and its
horizontally long substantially rectangular shape is contoured
15 by an inner end 17a intersecting with the crotch member 12 and
extending in the transverse direction X, an outer end 17b
opposed to and spaced from the inner end 17a and extending in
the transverse direction X and both side edges 17c, 17d
extending in the longitudinal direction Y between the inner and
20 outer ends 17a, 17b.

{0015}

Both side edges 16c, 16d of the front waist panel 16 and
both side edges 17c, 17d of the rear waist panel 17 are put flat

and joined together at seams 18 arranged intermittently in the longitudinal direction Y to define a waist-opening 20 and a pair of leg-openings 21 (See Fig. 1). The seams 18 may be formed by joining means of well known art, for example, various kinds of heat-sealing techniques such as heat-embossing treatments or ultrasonic sealing treatments.

{0016}

The front waist panel 16 includes a first topsheet 23 lying on the side facing the wearer's skin and a first backsheet 24 lying on the side facing away from the wearer's skin, each being formed of breathable and hydrophobic nonwoven fabrics or liquid-impervious but moisture-pervious plastic sheets or laminated sheets thereof wherein these two sheets are bonded to each other by the intermediary of hot melt adhesives (not shown) applied to at least one of these sheets 23, 24. Between the first topsheet 23 and the first backsheet 24, a plurality of strand- or string-like front waist elastic elements 25 extending in the transverse direction X are contractibly attached under tension in the transverse direction X with hot melt adhesives (not shown) so that the front waist panel 16 may be elasticized at least in the transverse direction X. It is also possible to bond the first topsheet 23 and the first backsheet 24 to each other only by the intermediary of hot melt

adhesives with which the respective elastic elements constituting the front waist elastic elements 25 are coated.

{0017}

The rear waist panel 17 includes a second topsheet 26 lying
5 on the side facing the wearer's skin and a second backsheet 27
lying on the side facing away from the wearer's skin, each being
formed of breathable and hydrophobic nonwoven fabrics or
liquid-impervious but moisture-pervious plastic sheets or
laminated sheets thereof wherein these two sheets are bonded
10 to each other by the intermediary of hot melt adhesives (not
shown) applied to at least one of these sheets 26, 27. Between
the second topsheet 26 and the second backsheet 27, a plurality
of strand- or string-like rear waist elastic elements 28
extending in the transverse direction X are contractibly
15 attached under tension in the transverse direction X with hot
melt adhesives (not shown) so that the rear waist panel 17 may
be elasticized at least in the transverse direction X. It is
also possible to bond the second topsheet 26 and the second
backsheet 27 only by the intermediary of hot melt adhesive with
20 which the respective elastic elements constituting the rear
waist elastic elements 28 are coated.

{0018}

The crotch member 12 is contoured by a front end 31

extending in the transverse direction X in the front waist region 13, a rear end 32 opposed to and spaced from the front end 31 in the longitudinal direction and extending in the transverse direction X in the rear waist region 14 and both side edges 33, 34 spaced from and opposed to each other in the transverse direction X and extending in the longitudinal direction Y. In the diaper 10 having been developed and flattened, the crotch member 12 is substantially formed of a vertically long rectangle (See Fig. 2).

10 {0019}

The crotch member 12 has a front end 35 attached to the outer surface of the front waist panel 16, a rear end 36 attached to the outer surface of the rear waist panel 17, an intermediate zone 37 extending in the longitudinal direction Y between the front and rear ends 35, 36, a crotch topsheet 38 formed of a plastic film, a crotch backsheet 39 formed of a breathable and hydrophobic nonwoven fabric and a liquid-absorbent structure 40 attached to the side of the crotch topsheet 38 facing the wearer's skin. The crotch topsheet 38 and the crotch backsheet 39 are bonded to each other with hot melt adhesives (not shown) applied to at least one of these two sheets 38, 39. Both lateral portions of these two sheets 38, 39 bonded to each other are folded inward to define a pair of elasticized lateral portions

41 extending in the longitudinal direction Y on the inner surface of the liquid-absorbent structure 40. The liquid-absorbent structure 40 at least includes a semi-rigid absorbent core formed from a mixture of super-absorbent polymer particles and fluff pulp fibers having stiffness higher than the other sheets and wrapped with a liquid-pervious sheet.

{0020}

The respective elasticized lateral portions 41 have inner side edges 42 defined by the respective side edges of the crotch top- and backsheets 38, 39 bonded together, front and rear ends 44, 45 and outer side edges 43 defined by fold lines (corresponding to the both side edges 33, 34 of the crotch member 12) along which the elasticized lateral portions 41 are folded inward in the course of making the diaper 10. At the front and rear ends 44, 45 of the respective elasticized lateral portions 41, front and rear ends of the crotch topsheet 38 defining the respective elasticized lateral portions 41 and front and rear ends of the crotch backsheet 39 are sealed together with adhesive regions 48, 49 extending in the transverse direction X, respectively. In consequence, body waste flowing and permeating into the respective elasticized lateral portions 41 through the front and rear ends 44, 45 should not leak out of the diaper 10. Though not illustrated, the front and rear ends

44, 45 of the elasticized lateral portions 41 are secured to the crotch topsheet 38 defining the front and rear ends 31, 32 of the crotch member 12 by various types of bonding means such as adhesives. With the front and rear ends 44, 45 of the elasticized lateral portions 41 secured to the front and rear ends 31, 32 of the crotch member 12 in this manner, body waste excreted onto the liquid-absorbent structure 40 should not leak out of the diaper 10 through a gap which would otherwise be left between the front and rear ends 44, 45 of the elasticized lateral portions 41 and the front and rear ends 31, 32 of the crotch member 12. The adhesive regions 48, 49 may be formed by various types of the same adhesives as or different from the hot melt adhesives applied to the entire inner surfaces of the crotch top- and backsheets 38, 39, or the other means such as heat sealing treatments, and ultrasonic sealing treatments or combinations thereof.

{0021}

Referring to Figs. 2 through 5, the elasticized lateral portions 41 are respectively provided with a plurality of strand- or string-like first leg elastic elements 50 and a plurality of strand- or string-like second leg elastic elements 51 and thereby the elasticized lateral portions 41 are elasticized at least in the longitudinal direction Y. The first

and second leg elastic elements 50, 51 are sandwiched between the two sheets 38, 39 and secured thereto under tension in the longitudinal direction Y with hot melt adhesives (not shown). Specifically, in the disposable diaper for adult, front and rear ends 50a, 51a, 50b, 51b of the first and second leg elastic elements 50, 51 are located at a distance of about 15 to about 100mm from the front and rear ends 44, 45 of the elasticized lateral portions 41. While the first and second leg elastic elements 50, 51 are provided in the form of strand- or string-like elastic elements according to the present embodiment, sheet-like elastic elements may be used so long as the desired effect of the present invention can be obtained.

{0022}

The first and second leg elastic elements 50, 51 have the front and rear ends 50a, 51a, 50b, 51b are retracted inward from the front and rear ends 44, 45 by so-called cut-back and, for the purpose of uplift prevention, preferably these front and rear ends 50a, 51a, 50b, 501b are locally coated with larger amount of adhesives than the amount of adhesives applied to the other regions. More specifically, the basis mass of adhesives to fix the first and second leg elastic elements 50, 50 as whole between the crotch top- and backsheets 38, 39 is preferably in a range of 0.5 to 10.0g/m² while the basis mass of adhesives

to sandwich the front and rear ends 50a, 51a, 50b, 51b between the two sheets 38, 39 is preferably in a range of 3 to 80g/m².

{0023}

As illustrated in Fig. 3(a) and Fig. 4, crotch top- and
5 backsheets 38, 39 having respective inner ends integrally sealed together. Specifically, these sheets 38, 39 are integrate with hot melt adhesives applied thereto in a planar or fibrous pattern to assure sealed condition within the respective elasticized lateral portions 41 and thereby to
10 prevent the first leg elastic elements 50 from falling off through the inner side edges 42 of the respective first leg elastic elements 50.

{0024}

Referring to Fig. 3(b), an apparent dimension of each of
15 the elasticized lateral portions 41 in the transverse direction X is defined by the dimension between the inner side edge 42 and the outer side edge 43 as long as the elasticized lateral 41 is kept in an inwardly folded state. However, under the effect of the first and second leg elastic elements 50, 50 secured to
20 the respective elasticized lateral portions 41, these elasticized lateral portions 41 raise themselves toward the wearer's body and the crotch region 15 is sterically deformed. In consequence, the elasticized lateral portions are spaced

upward from the liquid-absorbent structure 40 and come in contact with the wearer's inguinal regions. With the diaper 10 put on the wearer's body, the crotch member 12 has a shape like a bag suspended from the elasticized waist panel 11 (See Fig. 1). When body waste is excreted onto the liquid-absorbent structure 40 in such a state of the diaper 10 put on the wearer's body, the liquid-absorbent structure 40 is spaced downward from the wearer's buttocks under its own weight and thereby a body waste retention space for temporary retention of body waste is formed between the wearer's body and the liquid-absorbent structure 40.

{0025}

The first leg elastic elements 50 include three (3) elastic elements rectilinearly extending along the inner side edge 42 of the elasticized lateral 41 in the longitudinal direction Y. The second leg elastic elements 51 include a plurality of elastic elements each including concavely curved segment 53 in the middle zone of the crotch region 12 and rectilinear segments 54, 55 being contiguous to the concavely curved segment 53 and extending in the vicinity of the front and rear ends 35, 36 of the crotch member 12.

{0026}

More specifically, a width dimension L_1 of each of the

elasticized lateral portions 41 in the transverse direction X is preferably in a range of 30 to 120mm, more preferably, in a range of 60 to 100mm and a dimension by which the first and second leg elastic elements 50, 50 are spaced from each other in the transverse direction X is in a range of 3 to 20mm. A dimension L_2 by which the outermost point 53a of the concavely curved segment 53 is spaced from the outer side edge 43 of the elasticized lateral 41 is in a range of about 20 to about 50mm. In this way, the first and second leg elastic elements 50, 50 get closer to each other in the middle zone of the crotch region 15 and the elastic elements are locally gathered to enhance a tensile stress. Consequently, it is possible to put these zones in close contact with the wearer's skin and thereby to prevent body waste from sideways leaking in an effective manner. In addition, the tensile stress can be locally enhanced without adjusting the tensile stress of the elastic elements themselves and/or partially increasing the number of the elastic elements. This leads to reduction of cost and simplification of a manufacturing process. In the vicinity of the ends of the respective elasticized lateral portions 41, the first leg elastic elements 50 are spaced from the second leg elastic elements 51 by a given distance so that these ends may come in planar contact with the wearer's skin and thereby prevent body

waste from leaking out in the vicinity of these ends.

{0027}

Referring to Fig. 3(b), the respective elasticized lateral portions 41 have the required width dimension L_1 in the transverse direction X and the concavely curved segments of the second leg elastic elements 51 are spaced from the side edges of the liquid-absorbent structure 40 by the required dimension in the middle zone of the crotch region 15 and in the vicinity thereof. With the diaper 10 of this arrangement put on the wearer's body, the regions provided with the first and second leg elastic elements 50, 51 are held in contact with the wearer's inguinal regions and the regions defined between the respective outer side edges 53a of the second leg elastic elements 51 and the associated side edges of the liquid-absorbent structure 40, inclusive of the regions each having the width dimension L_2 trail down. Compared to the case in which the second leg elastic elements 51 rectilinearly extend in the longitudinal direction Y and/or the elasticized lateral portions 41 have an insufficient height dimension, the present embodiment makes it possible to form a relatively large space for retention of body waste and thereby to protect the wearer's skin from being soiled with body waste. If the height dimension of the elasticized lateral portions 41 is 30mm or less, it is impossible to form

the body waste retention space of the desired volume and there is possibility that the wearer's skin might be soiled with body waste. If the height dimension of the elasticized lateral portions 41 exceeds 120mm, the volume of the body waste retention space will become too large to follow movement of the wearer's body and the inner side edges 42 of the respective elasticized lateral portions 41 will get close to or overlap with each other. As a result, the opening defined between the inner side edges 42 will become narrower and, in some cases, there is a possibility that body waste could not properly excreted onto the liquid-absorbent structure 40.

{0028}

The length dimension L_2 as has been described above is preferably set in a range of 0.20 to 0.95 times and more preferably set in a range of 0.30 to 0.85 times of the width dimension L_1 . If the length dimension L_2 is less than 0.20 times of the width dimension L_1 , the dimension by which the first leg elastic elements 50 are spaced from the concavely curved segments 53 of the second leg elastic elements 51 will be unacceptably widened and the elastic elements may not be locally gathered. In consequence, the desired tensile stress may not be created and eventually the effect of the present invention may not be obtained. If the length dimension L_2 exceeds 0.95

times of the width dimension L_1 , the concavely curved segments 53 of the second leg elastic elements 51 may intersect with the first leg elastic elements 50 depending on various factors such as the number and the location of the first leg elastic elements 50 and an excessively high tensile stress may be generated, with apprehensive result such that the wearer should experience uncomfortable feeling and pressure marks left on the his or her skin. It should be noted here that, while the elasticized lateral portions 41 of the crotch region 15 are provided with the first and second leg elastic elements 50, 51 according to the present embodiment, these leg elastic elements 50, 51 may be arranged not on the elasticized lateral portions 41 but directly on the side edges of the crotch region 15 so long as the same effect as that of the present invention can be obtained.

15 {0029}

The tensile stress in the elasticized regions defined by the first leg elastic elements 50 is preferably higher than that in the elasticized regions defined by the second leg elastic elements 51. Specifically, at the time point of 80% stretch, the tensile stress in the elasticized regions defined by the first leg elastic elements 50 is about 1.05N/10mm and the tensile stress in the elasticized regions defined by the second leg elastic elements 51 is about 0.49N/10mm according to the

present embodiment. By setting the tensile stress in the regions closest to the wearer's inguinal regions, i.e., in the elasticized regions defined by the first leg elastic elements 50 to be higher than the tensile stress in the elasticized regions in the vicinity of the inner side edges 41 of the elasticized lateral portions 41, possibly occurring sideways leakage of body waste can be further effectively prevented. In addition, the dimension by which the inner side edges of the respective elasticized lateral portions 41 are spaced from each other can be sufficiently assured and these elasticized lateral portions 41 can raise themselves sufficiently. In this way, the volume of the body waste retention space formed above the crotch member 12 can be further enlarged. It should be appreciated here that the respective tensile stress of the first and second leg elastic elements 50, 51 may be selectively set by varying various factors such as the number and the stretch ratio of the elastic elements.

{0030}

The tensile stress in the regions elasticized by the first and second leg elastic elements 50, 51 is measured by the method as described below.

{0031}

The diaper 10 is developed to put the first and second

leg elements 50, 51 in a stretched state. A portion of the elasticized lateral 41 including the first leg elastic elements 50 is cut off as a test piece 1 and a portion of the elasticized lateral 41 including the rectilinear segment 54, 55 of the second leg elastic elements 51 is cut off as a test piece 2. Each of the first and second test pieces is a strip having a dimension (including the inner- and outermost elastic elements) of about 10mm in the transverse direction X of the diaper 10 and a dimension of about 160mm (including the length of 30mm overlapped by the chucks of the tester) in the longitudinal direction Y of the diaper 10. The method is based on measurement of region width (a dimension in the longitudinal direction Y of the diaper 10) of the respective test pieces. Each of the test piece 1 and the test piece 2 is secured in a contracted state between chucks (the initial chuck distance is set to a range of 20 to 30mm and appropriately adjusted if desired) of the Tensile Tester (manufactured by Shimadzu Corporation in Japan). From the initial state, the test piece is stretched at a tension rate of 100mm/min in the direction corresponding to the longitudinal direction Y of the diaper 10 and a load (mN) is measured at the moment the test piece has been stretched to 80% of the maximally stretched length (80% of the maximally stretched length of the test piece 1 or 2 corresponding to the

maximum displacement in the longitudinal direction Y of the diaper 10). Tensile stress is calculated from a calculating formula of measured value (mN) / region width (mm).

{0032}

5 Referring again to Figs. 2 - 4, the crotch member 12 is attached to the respective outer surfaces of the front and rear waist panels 16, 17 in a front adhesive region 61 and a rear adhesive region 62 defined by hot melt adhesives applied to the surface of the front end 35 and the rear end 36 of the crotch
10 member 12 facing the wearer's skin, respectively. The front adhesive region 61 substantially overlaps the inner end 16a of the front waist panel 16 and has a substantially trapezoidal shape contoured by an inner end 61a extending in the transverse direction X between the inner side edges 42 of the respective
15 elasticized lateral portions 41 of the crotch member 12, an outer end 61b substantially overlapping the front end 31 of the crotch member 12 and extending in the transverse direction X and both side edges 61c extending between the inner and outer ends 61a, 61b obliquely with respect to the center line P-P so
20 that each of these side edges 61c extends outward as viewed in the transverse direction X as it extends outward as viewed in the longitudinal direction Y. The rear adhesive region 62 has a substantially rectangular shape which is horizontally long

and includes an inner end 62a substantially overlapping the inner end 17a of the rear waist panel 17 and extending in the transverse direction X and an outer end 62b substantially overlapping the rear end 32 of the crotch member 12 and extending
5 in the transverse direction X. In the front and rear adhesive regions 61, 62, sub-regions 63 (corresponding to shaded portions in Fig. 2) in which the inner surface of the liquid-absorbent structure 40 is bonded to the respective outer surfaces of the front and rear waist panels 16, 17 may be left
10 not coated with adhesive. In this case, void spaces are defined between the liquid-absorbent structure 40 and the front and rear waist panels 16, 17 so that these void spaces may function as pockets adapted to absorb and to retain body waste.

{0033}

15 By attaching the front and rear ends 35, 36 to the respective outer surfaces of the front and rear waist panels 16, 17, the volume of the body waste retention space can further enlarged. It should be appreciated that one of the front end 35 and the rear end 36 may be attached to the outer surface of
20 the associated one of the waist panels 16, 17 so long as the volume of the body waste retention space can be effectively enlarged. When the rear end 36 is attached to the outer surface of the rear waist panel 17, the body waste retention space can

be shaped in accordance with the shape of the wearer's buttocks and thereby feeling to wear the diaper 10 can be improved.

{0034}

Fig. 6 is a perspective diagram illustrating a part of
5 an apparatus for making the diaper 10, more particularly,
illustrating a step of making the crotch member 12. In Fig. 6,
the machine direction in which first and second webs 138, 139
are fed is designated by MD and the direction intersecting with
this is designated by CD.

10 {0035}

Referring to Fig. 6, first web 138 as stock materials for
the crotch topsheet 38 is stretched by a tension roll (not shown)
extending in the cross direction CD and then guided by a guide
roll 140 to a press step 143 including a pair of press rolls
15 141, 142. Second web 139 as stock materials for the crotch
backsheet 39 is stretched by a tension roll (not shown)
extending in the cross direction CD and then fed to an adhesive
coating step 144. In the adhesive coating step 144, the entire
inner surface 139a of the second web 139 is coated with hot melt
20 adhesives to bond the first and second webs 138, 139 to each
other and simultaneously to sandwich a pair of first continuous
elastic members 150 as stock material for the first leg elastic
elements 50 and a pair of second continuous elastic members 151

as stock material for the second leg elastic elements 51 between the two webs 138, 139 and to secure them therebetween. After having been coated with hot melt adhesive, the second web 139 is guided to a press step 143.

5 {0036}

In the press step 143, the first continuous elastic members 150 are arranged to be rectilinear in the machine direction MD while the second continuous elastic members 151 are oscillated at high velocity by oscillating arms 146 in the cross direction CD so as to draw undulation repeated in the cross direction CD. The first and second continuous elastic members 150, 151 are pressed together with the first web 138 and the second web 139 to form composite web 160. Lateral portions of composite web 160 extending in the machine direction MD and opposed to each other in the cross direction CD are folded inward to form the elasticized lateral portions 41.

{0037}

In the composite web 160 formed in this manner, concavely curved segments of the second continuous elastic members 151 (corresponding to the concavely curved segments 53 in the second leg elastic elements 51) are pulled in the cross direction CD with a force stronger than a force exerted on the rectilinear segments 162 extending in front of and behind (corresponding

to the rectilinear segments 54, 55 of the first leg elastic elements 51) and thereby generate a tensile stress higher than that generated in the rectilinear segments 162. As a result, in the rectilinear segments 162, the second continuous elastic members 151 are slightly stretched or not stretched at all in the cross direction CD. Consequentially, in the respective elasticized lateral portions 41, the concavely curved segments 53 of the second leg elastic elements 51 come in close contact with the wearer's inguinal regions and contribute to improvement in fit and, at the same time, allow the body waste retention space having a large volume to be formed. Relatively low tensile stress generated in the rectilinear segments 54, 55 serves to prevent the workability from lowering due to interference between the tensile stress when the front and rear ends 35, 36 of the crotch member 12 are attached to the elasticized waist panel 11. It is also possible to set the tensile stress of the concavely curved segments 161 to be lower than that of the rectilinear segments 162 by, for example, regulating the oscillation amplitude of the oscillating arms 146.

{0038}

<Second Embodiment>

Fig. 7 is a plan view of the crotch member 12 similar to

Fig. 5, illustrating a second embodiment of the present invention. For convenience of illustration, like Fig. 5, the liquid-absorbent structure 40 is indicated by imaginary lines and basic features of the diaper 10 are similar to those in the first embodiment. Only dissimilarities from the first embodiment will be described below.

{0039}

Referring to Fig. 7, a dimension by which each pair of the adjacent second leg elastic elements 51 is spaced from each other in the transverse direction X is gradually reduced as these elastic elements 51 get closer to the middle zone of the crotch region 15. In other words, these adjacent elastic elements get closest to each other in the concavely curved segments 53 thereof. According to the present embodiment, the tensile stress of the elasticized lateral 41 can be set to become higher as they get closer to the middle zone of the crotch region 15 and thereby the middle zone of the crotch region 15 can be put in close contact with the wearer's skin.

{0040}

As stock materials for the component members such as the elasticized waist panel 11 and the crotch member 12, various kinds of material widely used in the field of the disposable wearing article may be selectively used. While so-called

pants-type diaper 10 including the elasticized waist panel 11 and the crotch member 12 separately prepared has been described as the typical example of the disposable wearing article according to the present invention, the present invention may
 5 be implemented in the form of the diaper including a substantially hourglass-shaped pair of sheets and an absorbent core sandwiched between these two sheets or in the form of so-called open-type diaper.

{0041}

- 10 10 disposable wearing article (disposable diaper)
- 11 elasticized waist panel
- 12 crotch member
- 13 front waist region
- 14 rear waist region
- 15 15 crotch region
- 35 front end
- 36 rear end
- 40 liquid-absorbent structure
- 41 elasticized lateral portion
- 20 50 first leg elastic element
- 51 second leg elastic elements
- 53 concavely curved segment
- 54, 55 rectilinear segment

X transverse direction

Y longitudinal direction

5

10

15

20

{Claims}

[Claim 1]

A disposable wearing article having a longitudinal direction and a transverse direction orthogonal to the longitudinal direction, comprising a side facing the wearer's skin and a side facing away from the wearer's skin, a front waist region, a rear waist region and a crotch region extending between the front and rear waist regions, wherein:

the article further includes

front and rear elastic waist panels defining the front and rear waist regions, respectively,

a crotch member located in the crotch region and a part of the front and rear waist regions and having a front end and a rear end bonded to the front waist panel and the rear waist panel, respectively, and

a liquid-absorbent structure disposed in the crotch region on the side facing the wearer's skin,

the crotch region has elasticized lateral portions formed by folding lateral portions of the crotch member and adapted to be spaced upward from the liquid-absorbent structure,

each of the elasticized lateral portions is provided with strand- or string-like leg elastic elements extending from the crotch region to the front and rear waist regions,

the leg elastic elements comprise first leg elastic elements extending rectilinearly in the longitudinal direction immediately inboard of the respective elasticized lateral portions and second leg elastic elements extending in the longitudinal direction and outboard of the first leg elastic elements as viewed in the transverse direction,

each of the second leg elastic elements comprises rectilinear segments located in the front and rear ends of the crotch member and extending in the front and rear waist regions and a concavely curved segment located in the crotch region, and

elasticized regions defined by the first leg elastic elements have tensile stress higher than that of elasticized regions defined by the second leg elastic elements.

[Claim 2]

The wearing article defined by Claim 1, wherein a dimension by which each pair of the adjacent second leg elastic elements is spaced from each other in the transverse direction is gradually reduced as the second elastic elements get closer to a middle zone of the crotch region.

[Claim 3]

The wearing article defined by Claim 1 or 2, wherein the concavely curved segment of the second leg elastic elements has a tensile stress higher than that of the rectilinear segments
5 of the second leg elastic elements.

[Claim 4]

The wearing article defined by any one of Claims 1 through 3, wherein the front and rear ends of the crotch member are bonded
10 to outer surfaces of the front and rear elastic waist panels, respectively.

[Claim 5]

The wearing article defined by Claim 4, wherein
15 the front adhesive region substantially overlaps an inner end of the front waist panel and has a substantially trapezoidal shape contoured by an inner end extending in the transverse direction between the inner side edges of the respective elasticized lateral portions, an outer end substantially
20 overlapping the front end of the crotch member and extending in the transverse direction, and both side edges obliquely extending from the outer end toward the inner end between the inner and outer ends, and

the rear adhesive region has a substantially rectangular shape which is transversally long and includes an inner end extending in the transverse direction and substantially overlapping an inner end of the rear waist panel and an outer
5 end extending in the transverse direction and substantially overlapping an rear end of the crotch member.