



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06K 9/20, H04N 1/00, G06T 5/50		A1	(11) International Publication Number: WO 99/57678
			(43) International Publication Date: 11 November 1999 (11.11.99)
(21) International Application Number: PCT/SE99/00716 (22) International Filing Date: 30 April 1999 (30.04.99) (30) Priority Data: 9801531-6 30 April 1998 (30.04.98) SE 60/091,324 30 June 1998 (30.06.98) US (71) Applicant (for all designated States except US): C TECHNOLOGIES AB [SE/SE]; Forskningsbyn Ideon, S-223 70 Lund (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): FÄHRÆUS, Christer [SE/SE]; Sölvegatan 3, S-223 62 Lund (SE). (74) Agent: AWAPATENT AB; P.O. Box 5117, S-200 17 Malmö (SE).		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. In English translation (filed in Swedish).	
(54) Title: DEVICE FOR RECORDING INFORMATION IN DIFFERENT MODES			
(57) Abstract A device for recording information by means of imaging with the aid of a light-sensitive sensor with a two-dimensional sensor surface is described. The device is adjustable between a first mode and a second mode. In the first mode, the imaging is effected by means of a plurality of images with partially overlapping contents. Each of the images depicts a small area on an information carrier and the images are put together into a composite image. In the second mode, the imaging is effected by means of at least one image of a larger area of the information carrier. The device has means for indicating the size of the imaging area.			