

CLAIMS

What is claimed is:

1. A mobile secure network system comprising:

5 a computing apparatus configured to extend a remote home network to a current location of the network device so that one or more endpoint devices at the current location of the network device can join the remote home network;

 a housing supporting the computing apparatus and including a door to access the computing apparatus, the housing being constructed and arranged for mobile transport and
10 including a back-up power supply supported thereon;

 an access control mechanism to secure the enclosure including a credential reader communicably connected to the door and a locking device to secure the door in a locked position, the locking device movable between a locked and unlocked position to allow
access to the computing apparatus;

15 a security control module communicably connected to the access control mechanism and constructed and arranged to deny access to the enclosure upon occurrence of one or more predefined occurrences; and

 wherein upon access to the housing being denied by the security control module a shutdown protocol is initiated to secure the computing apparatus.

20

2. The system of claim 1, wherein the predefined occurrences are selected from the group including unverified users attempting to gain access to the computing apparatus through the

access control module, failure to synchronize a local cache with a remote cache on the parent network, a physical breach of the housing, and power loss.

3. The system of claim 1, further comprising a local cache supported by the housing, the
5 local cache including a listing of users who are authorized to access the computing apparatus.
4. The system of claim 3, wherein the local cache further includes a log of users who have accessed the credential reader.
- 10 5. The system of claim 3, wherein to verify the users' credentials data representing the user is compared to the local cache of authorized users and, upon finding a match the door is unlocked.
- 15 6. The system of claim 5, wherein the shutdown protocol is initiated upon a predetermined number of tries by a user who is not verified upon comparison to the local cache of authorized users.
7. The system of claim 1, wherein the security control module further comprises a local
20 cache configured to cache data remotely that has not yet been synced with the remote home

network, and the security module is configured to synchronize the data on the local cache with the remote home network.

8. The system of claim 7, wherein upon a reduction in bandwidth the security control
5 module prioritizes the order in which data on the local cache is synchronized with the home network, with high priority activities being synchronized first and lower priority activities being synchronized afterwards with any remaining bandwidth.

9. The system of claim 8 wherein synchronizing a log of users who have accessed the
10 credential reader with the home network and authorizing users who are attempting to access the computing apparatus are high priority activity and synchronizing other cached data from the local cache to the home network are lower priority activities.

10. The system of claim 7, wherein the access control mechanism is configured to deny
15 access to the enclosure if the security module fails to synchronize the local cache with the remote home network.

11. The system of claim 1, further comprising a kill switch to disable access to the housing by deactivating the credential reader upon initiation of the shutdown protocol.

12. The system of claim 1, further comprising a kill switch activated to clear the local cache and disable access to the remote home network upon a signal received due to a forced breach of the mobile secure network device from a fail secure device.

5 13. The system of claim 12, wherein the fail secure device is selected from the group comprising a glass shatter sensor, a lock sensor, and a power sensor.

14. The system of claim 1, further comprising a global positioning system supported by the housing wherein location of the secure network device can be tracked remotely.

10

15. A mobile secure network device comprising:

a computing apparatus configured to extend a remote home network to a current location of the network device so that one or more endpoint devices at the current location of the network device can join the remote home network;

15 a local cache of data stored by the computing apparatus;

a housing supporting the computing apparatus and including a door to access the computing apparatus, the housing being constructed and arranged for mobile transport and including a back-up power supply supported thereon;

20 an access control mechanism to secure the enclosure including a locking device to secure the door in a locked position, the locking device movable between a locked and unlocked position to allow access to the computing apparatus;

a security control module communicatively connected to the access control mechanism and constructed and arranged to deny access to the enclosure upon occurrence of one or more predefined occurrences; and

wherein upon access to the housing being denied by the security control module a shutdown protocol is initiated to physically secure the housing and secure the data contained on the local cache.

16. The device of claim 15, wherein to secure the data on the local cache the data is deleted from the local cache and access to the remote home network is disabled.

10

17. The device of claim 16, wherein prior to deleting the data from the local cache it is transferred to the home network.

18. The device of claim 15, wherein the predefined occurrences are selected from the group including unverified users attempting to gain access to the computing apparatus through the access control module, failure to synchronize a local cache with a remote cache on the home network, a physical breach of the housing, and power loss.

19. The device of claim 18, wherein the shutdown protocol is initiated upon a predetermined number of tries by a user who is not verified upon comparison to the local cache including a listing of authorized users.

5 20. The device of claim 15, further comprising a kill switch to disable access to the housing by deactivating a credential reader communicatively connected to the locking device upon initiation of the shutdown protocol.

21. The device of claim 15, further comprising a fail secure device that when activated
10 provides a signal to the security control module to delete the local cache and disable access to the remote home network.

22. The device of claim 21, wherein the fail secure device is selected from the group comprising a glass shatter sensor, a lock sensor, and a power sensor.