

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F16L	A2	(11) International Publication Number: WO 00/61976 (43) International Publication Date: 19 October 2000 (19.10.00)
(21) International Application Number: PCT/US00/09716 (22) International Filing Date: 11 April 2000 (11.04.00) (30) Priority Data: 60/129,259 14 April 1999 (14.04.99) US (71)(72) Applicant and Inventor: RODRIGUEZ, Alan, F. [US/US]; 3722 Tarrytown Place, Carrollton, TX 75007 (US). (74) Agent: CHAUZA, Roger, N.; Howison, Chauza, Handley & Arnott, L.L.P., P.O. Box 741715, Dallas, TX 75374-1715 (US).		(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: POST-TENSION ANCHOR SEAL CAP**(57) Abstract**

A seal cap (10) for use in sealing an end (20) of a tendon (14) anchored to an anchor plate (12). The seal cap (10) includes a receptacle (32) for holding therein a sealing agent (37). The seal cap (10) further includes a push nut (34) that grips to the tendon end (20) when forced thereon. A foam washer (35) is held in the front part of the seal cap (10). When the seal cap (10) is forced, such as by hammering, on the end (20) of the tendon (14), the sealant is displaced onto the tendon (14), and the foam washer (35) is squeezed against the anchor plate (12). A high quality moisture seal is formed.

