

**METHOD FOR AUTOMATICALLY INSERTING ITEMS INTO ENVELOPES,
PARTICULARLY DOCUMENTS, AND DEVICE IMPLEMENTING THE
METHOD**

5 **Technical Domain**

 The present invention concerns a method for automatically inserting small objects into envelopes, particularly documents or objects to be transmitted in envelopes using a mailing service, by utilizing a device that comprises a storage means and a means for successively feeding individual envelopes, a means for moving the documents or objects
10 to be transmitted toward said individual envelopes comprising a folded closing flap, and a means for introducing one of said documents or one of said objects into one of said envelopes.

 It also concerns the device implementing this method.

Prior Art

15 Devices of this type for inserting letters, publicity material, or the like into envelopes for large scale distribution are already known in the art. These devices are generally complicated in design and comprise a large number of moving mechanical parts to guide and feed the envelopes on the one hand and the documents on the other hand toward the zone where the two delivery components meet, called the packaging zone.
20 Since the paths taken by the envelopes and by the documents are separate, whereas the packaging area is a common one, in currently used devices the envelopes are usually first moved along a trajectory in the direction opposite to that of the documents and then along a trajectory identical to that of the documents after the documents have been introduced inside the envelopes. This reversal of direction generally requires the use of a switching
25 mechanism to separate the arrival and departure paths of the envelopes.

Such a design is complicated and it operates slowly, considerably reducing the speed of the packaging operation. In practice, with this system each cycle must be completely finished before the next cycle can start up, that is, one envelope must be filled with the documents intended for it and evacuated from the packaging zone before the
5 next envelope can be delivered to this same zone to receive its documents. The resulting reduced speed, in addition to the complicated equipment design, makes the equipment difficult to maintain and subject to frequent breakdowns.

U.S. Patent No. 2, 643,119A describes a packaging device comprising several units with a storage unit for obliquely arranged envelopes which are removed one at a
10 time using a rotary drum. An air blower is located behind the zone where the envelopes stop in order to open them and allow them to receive the letters or documents to be placed inside. However, this device has several drawbacks. The envelopes are removed while they are closed and through gravitational force pass in groups from a first platform to a second platform where they are taken up by the drum. There is a considerable risk
15 that several envelopes will be selected simultaneously, causing a jam. Furthermore, the envelopes, which are transferred while closed, are not opened by the blower until the moment they arrive at the stop. This sequence reduces speed and creates a high risk that the envelopes will fail to open.

The objective of U.S. Patent No. 3,423,900 A is to achieve a machine that can
20 insert into an envelope several documents, cards, or letters that are separately stored. The envelopes are transported by a rotary drum equipped with a mechanical gripping means and which comprises grooves for the envelope flaps. The documents and the envelopes are driven towards a zone for filling the envelopes with said documents. This machine is

completely mechanical and all the operations of the maintenance or gripping fingers are controlled by cams. This procedure, however, does not allow work to progress at a very high speed.

U.S. Patent 4,649,691 A concerns an automatic envelope filling machine in which
5 the envelopes are removed mechanically using claws attached to a rotary drum. The envelope is opened by blowers that raise the flap when it arrives in the position for receiving documents. It does not provide any mechanical control to guaranty that the envelope is correctly opened.

U.S. Patent No. 3,962,848A describes a device wherein envelopes stacked in a
10 column are removed using friction from a rotary drum, opened by a blower, and transported on a conveyor. This system is based only on friction and cannot work reliably at high speed.

The automatic envelope filling machine which is the subject of U.S. Patent No. 3,381,447 A comprises a first drum for removing an item from stored instruction inserts
15 or the like, and a second drum for removing envelopes. The instruction inserts are fed towards a wheel with radial cavities through which the envelopes have been introduced previously, said cavities comprising opening means. Such a device is relatively slow because the envelopes and the documents introduced inside them must be inserted into and then withdrawn from the cavities in the rotating wheel, which cannot be done
20 continuously and thus requires time to stop the wheel.

Explanation of the Invention

The objective of the present invention is to eliminate the disadvantages of these known devices by providing a simple, effective device that is easy to maintain and is capable of automatically filling envelopes at a very high speed.

5 This goal is achieved by the method defined in the preamble and characterized in that the envelopes are stored in such a way that the flap of each individual envelope is located on the bottom of the envelope and towards the front in the direction of removal, in that said flap is unfolded downward in the direction in which the envelope opens, in that said envelope flap is moved into contact with the control drum, in that each envelope
10 is displaced individually and successively by pulling its flap placed against the exterior surface of said control drum towards the zone for introducing the documents or objects, in that the envelope is then opened and said document or said object is then introduced inside said previously opened envelope.

Advantageously, said envelope flap is unfolded by at least one stream of air and
15 flattened against the surface of the positioning drum by means of radial suction produced inside said drum.

Preferably, the envelopes are detached from the positioning drum using at least one scraper that is tangential relative to the drum surface.

It is possible to open each envelope using opening guides, and said envelope can
20 also be compressed laterally.

The device for implementing this method of automatically inserting small objects into envelopes, particularly documents or objects to be sent by a mailing service, is characterized in that said means for feeding the individual envelopes consists of a control

drum design to displace the envelopes individually and successively from said storage means towards the zone for introduction of one of the documents or one of the objects into one of said individual envelopes, and in that the means for introducing one of these documents or one of these objects into one of said envelopes comprises a means for
5 unfolding the flap of the individual envelope and opening this envelope.

According to a preferred embodiment, said control drum comprises at least one peripheral zone that is perforated with openings and said openings are connected to a suction device in an intermediate zone between said storage means and the zone for introducing one of said documents into one of said individual envelopes.

10 According to an advantageous embodiment, said openings are connected to a pressurized air generating device in said zone for introducing one of said documents into one of said individual envelopes.

Said control drum preferably comprises on at least a portion of its periphery a covering with a high coefficient of friction.

15 According to one advantageous embodiment, the peripheral covering on said control drum extends over an angular section comprising from 25% to 75% of the periphery.

According to a particular embodiment, said peripheral coating on said control drum comprises several parallel bands extending over an angular section comprising
20 from 25% to 75% of the periphery.

The said means for opening said individual envelopes preferably comprises at least one rotary cam designed to engage beneath the flap of each individual envelope in order to unfold it.

In order for one envelope to be taken up during each cycle that corresponds to one rotation by the control drum, said rotary cam is driven synchronously with said drum.

According to a particularly advantageous design, said rotary cam is equipped with at least one organ that generates at least one stream of air to assist in unfolding the flap of
5 each individual envelope in order to open it.

Said rotary cam is preferably equipped with at least one projection to initiate the unfolding of the flap of the individual envelope.

Preferably, the control drum and the rotary cam have the same diameter and are driven synchronously at the same speed and, on one portion of their circular trajectory,
10 said rotary cam contacts the peripheral surface of said control drum to drive one envelope from said storage means towards the introduction zone.

To detach the envelopes from the control drum, the device advantageously comprises at least one scraper which detaches said individual envelope from said control drum in said introduction zone.

15 Advantageously, the device comprises several scrapers parallel to each other, said scrapers being located between the parallel bands of the covering on said control drum.

To facilitate opening the envelope, the device may comprise lateral deflectors for pushing together the lateral edges of the individual envelopes to assist in opening them.

According to a first embodiment, said lateral deflectors comprise guide rollers.

20 According to a second embodiment, said lateral deflectors comprises guide sections.

According to a particular embodiment, said control drum comprises at least two cylindrical sections that are separated by at least one unattached ring.

Summary Description of the Drawings.

The present invention and its features will be better understood from the description of its preferred embodiments, furnished by way of non-limiting examples, with reference to the attached drawings, wherein:

- 5 • Figure 1A is a partial perspective representing the principal elements constituting a first embodiment of the device according to the invention;
- Figure 1B is an elevation of the device of Figure 1A shown in a particular phase of operation;
- Figure 1C is an elevation of the device of Figure 1A shown in another particular
10 phase of operation;
- Figures 1D, 1E and 1F are enlarged partial views of certain portions of the device of Figure 1A in particular positions corresponding to operational phases of the device;
- Figure 1G is a detailed view showing one element of the device of Figure 1A;
- 15 • Figure 1H shows one portion of the device of Figure 1A during operation;
- Figure 1I is a plane view from the top of the device of Figure 1A;
- Figure 1J is a perspective view from below showing the device of Figure 1A during operation;
- Figure 2A is a partial perspective showing the principal elements constituting a
20 second embodiment of the device according to the invention; and

- Figures 2B, 2C and 2D are enlarged partial views of certain portions of the device of Figure 2A in particular positions corresponding to operational phases of the device.

How to Achieve the Invention

5 With reference to Figures 1A through 1J, device 10 consists principally of a frame 11, shown schematically by a lateral support element, but which may comprise as shown in Figure 1I two lateral support elements that are parallel and essentially identical, to which a storage bin 12 for envelopes or packets is attached, said bin constituting said storage and delivery means, a control drum 13, and at least one rotary cam 14. Storage
10 bin 12 may contain a stack of superimposed envelopes 15 arranged so they may be removed one at a time from the base of the bin. The storage bin is open at the base, allowing rotary cam 14 to access envelope 15 located at the lower part of the stack. Each envelope is arranged so its closing flap is folded down against the envelope surface.

 Cylindrical control drum 13 is attached to a rotary shaft 16 supported by frame
15 11. It made be made of metal or synthetic material, for example, a carbon fiber based-material or the like. It comprises an exterior covering 17 consisting of a material with a high coefficient of friction, such as, for example, foam rubber or the like. This exterior covering 17 preferably extends along only one portion of the drum periphery, for example, along an angular section ranging from 25% to 75% and preferably of the order
20 of 50%. Said covering advantageously takes the form of several parallel bands 18 which may be three in number, separated by annular spaces 19. Drum 13 is perforated and in the area with the covering, it comprises a plurality of openings 20 penetrating exterior covering 17. These openings communicate with the hollow interior of control drum 13

and because of this they are connected through a turning connection to a suction device (not shown) when said control drum is in an intermediate zone between said storage means and the zone for introduction of one of said documents into one of said individual envelopes 15.

5 When said control drum 13 is located in the zone for introduction of one of said documents into one of said individual envelopes, said openings 20 are connected through a turning connection to a pressurized air delivery device which detaches the envelope from the control drum.

 Rotary cams 14, which number three in the embodiment shown, are attached to a
10 shaft 21 supported by said frame 11 and are driven in synchronous rotation with said control drum 13.

 The mechanism which drives and connects the two shafts 16 and 21 is shown schematically by a circle A. Said rotary cams 14 comprise a projection 22 which initiates the unfolding of the flap of each individual envelope during each operational cycle by the
15 device. This projection 22 is equipped with at least one nozzle 23 producing a stream of air 24 (see Figure 1D) designed to contribute to the unfolding of each individual envelope flap in order to open the envelope. This nozzle 23 is supplied with compressed air through a turning connection (not shown) attached to shaft 21.

 Device 10 further comprises at least one scraper 25 designed to detach said
20 individual envelope from said control drum 13 in the introduction zone. In the exemplary embodiment described, it comprises two parallel scrapers 25 attached to an axle 26 supported by frame 11. These scrapers consist of a thin plate slightly curved at its free end that contacts the peripheral surface of control drum 13.

In the example shown, control drum 13 comprises, on one portion of annular spaces 19, bearing supports 27 or roller supports 28 that rotate freely, which are level with the peripheral drum surface and over which scrapers 25 can slide without engaging. The function of these unattached bearings or rollers 28 is to facilitate detachment of the individual envelopes from the drum in the zone for introduction of documents or objects into the envelopes.

Parallel bands 18 of exterior coating 17 on control drum 13 form an extra layer and define two hollow annular spaces 19. The unattached ends of the plates constituting scrapers 25 contact the peripheral drum surface in the two hollow annular spaces 19. The number of these hollow annular spaces depends upon the number of parallel bands 18 of exterior covering. This number is not critical and there should be a minimum of two.

In the zone for introduction of one of said documents into one of said individual envelopes 15, the device is equipped with two opening guides 29 each comprising two branches 29a and 29b, converging at one extremity to define a projection for opening the envelopes. Documents 30 to be introduced in the individual envelopes are delivered in known manner along rails or some type of support and guide surface 31, for example, a conveyor belt, and are driven by cogs 32 integral with this endless conveyor belt. The filled envelopes are then taken up by a recovery cam 33 rotating on shaft 34, which rotates synchronously with control drum 13. The synchronous driving of shaft 16 for drum 13 and shaft 34 for recovery cam 33 is shown schematically by circle 35.

As shown more particularly by figure 11, device 10 is further equipped with two lateral deflectors 36 which push the lateral edges of the envelopes together to help open

them. These deflectors consist of guide profiles, but they may also be equipped with rollers to reduce the friction of contact with the envelope.

During one operating cycle said device operates according to the principle of the invention wherein the envelopes are stored in such a way that the flap of each individual envelope is on the bottom of the envelope and towards the front in the direction of
5 removal, said flap is unfolded downwards in the direction in which the envelope opens, said envelope flap is moved into contact with the surface of the control drum, the envelopes are individually and successively displaced by pulling the flaps placed against the exterior surface of the control drum towards the zone for introduction of one of said
10 documents or said envelopes, the envelopes are then opened and said documents or said objects are introduced inside said previously opened envelopes.

Consequently, to effect this series of operations, the elements comprising device
10 operate as follows:

- Rotary cams 14 turn counterclockwise so that projections 22 move closer to the
15 flap of the lower envelope in stack of envelopes 15
- Nozzles 23 begin to act and emit a stream of air 24 (see Figure 1D) that initiates unfolding of the envelope flap
- Projection 22 on rotary cam 14 comes into contact with the flap and completes the unfolding
- The unfolded flap comes into contact with control drum 13 in the zone which has
20 exterior covering 17

- Suction passing through holes 20 of the drum then flattens the unfolded flap against control drum 13 and the entire envelope is then sandwiched between said drum and rotary cams 14
- The envelope arrives at the document introduction zone and lateral deflectors 36 press in opposing directions against the lateral envelope edges to initiate opening
- Scrapers 25 detach the flap and then the entire envelope from control drum 13. The scrapers are assisted in this function by compressed air blown through openings 20 formed in the peripheral wall of the drum and exterior covering 17.
- The envelope is speared by opening guides 29 which complete the envelope opening by engaging their two branches 29a and 29b in the envelope opening and positioning it at the stop so it will be ready to receive documents 30.
- Said documents 30 arrive and engage with the open envelope
- The envelope is then driven by cogs 32 of conveyor belt 31 which has fed the documents
- The envelope containing documents 30 is evacuated through the action of uptake cam 33 which contacts unattached bearings or rollers 28 on control drum 13. Said bearings or rollers 28 rotate freely so as not to impede the envelope evacuation process activated by uptake cam 33.

During these later phases when the envelope is detached from control drum 13, the first phases of the next cycle may be already underway, allowing work to take place in condensed time and reducing the effective duration of a cycle, thereby increasing the speed of the device.

In the example shown in Figures 2A through 2D all the components of device 50 are identical to those of device 10 described above, except control drum 53 differs in design and function from control drum 13.

With reference to the drawings, said device 50 principally comprises a frame 51
5 shown schematically by a lateral support element to which there are attached a bin 52 for storing envelopes or packets, said bin constituting said storage and conveyance means, a control drum 53 and at least one rotary cam 54. Storage bin 52 may contain for example a stack of superimposed envelopes 55 arranged so they may be removed one by one from the base of the bin. The base of the storage bin is open, allowing rotary cam 54 to access
10 envelope 55 located at the lower portion of the stack. Each envelope is positioned so that its closing flap is folded against the body of the envelope.

Cylindrical control drum 53 is attached to a rotary shaft 56 supported by frame 51. Like drum 13, it has an exterior covering 57 consisting of a material with a high coefficient of friction which preferably extends along a portion of its periphery.

15 Said coating 57 advantageously takes the form of several parallel bands 58, which may be three in number, separated by annular spaces. The drum is perforated and in the covered zone it comprises a plurality of openings 60 penetrating said exterior covering. These openings communicate with the hollow interior of control drum 53 and for this reason they are connected by a turning connection to a suction device (not shown) when
20 said control drum is in an intermediate zone between said storage means 52 and the zone for introducing documents into one of said individual envelopes.

Rotary cams 54, which are three in number in the embodiment shown, are attached to a shaft 61 supported by said frame 51 and driven to rotate synchronously with

said control drum 53. Said rotary cams 54 comprise a projection 62 to initiate the unfolding of each individual envelope during each cycle of operation by the device. Said projection 62 is equipped with at least one nozzle 63 producing a stream of air 64 (see Figure 2D) which assists in unfolding the flap of each individual envelope in order to
5 open the envelope.

Device 50 further comprises at least one scraper 65 for detaching said individual envelope from said control drum 53 in the introduction zone.

In the zone for introduction of one of said documents into one of said individual envelopes, the device is equipped with two opening guides 69 each comprising two
10 branches 69a and 69b that reconnect at one of their extremities to define an envelope opening projection. The documents to be introduced into the individual envelopes are moved in known manner along rails or any sort of support and guide surface 71, for example a conveyor belt, and are driven by cogs 72 integral with said endless conveyor belt. The filled envelopes are then taken by an uptake cam 73 rotating on shaft 74 which
15 rotates synchronously with control drum 53.

As Figures 2B and 2C show more specifically, control drum 53 is composed of cylindrical segments 80, which may be three in number, each with a covering 57 along a portion of its periphery and which are separated by unattached rings 81 which are formed in the example shown of a ball bearing with a cage 82 composed of an interior ring 83
20 and an exterior ring 84 enclosing bearings 85. In this way cylindrical segments 80 and unattached rings 81 can turn independently. The envelopes are in contact with covering 57 along a portion of their trajectory and then, having received the documents, they are in

contact with unattached rings 81, or more specifically, they are sandwiched between these rings and uptake cams 73.

5

10

CLAIMS

1. A method for automatically inserting small items into envelopes, particularly documents or objects to be transmitted in envelopes using a mailing service by means of a device comprising a means for storage and for successively feeding
5 individual envelopes, a means for moving the documents or objects to be transmitted toward said individual envelopes comprising a folded closing flap, and a means for introducing one of these documents or one of these objects into one of said envelopes, said method being characterized in that the envelopes are stored in such a way that the flap of each individual envelope is located on the
10 bottom of the envelope and towards the front in the direction of removal, and in that said flap is unfolded downwards in the direction of envelope opening, in that said envelope flap is moved into contact with the surface of a control drum, and in that each envelope is individually and successively displaced by pulling its flap placed against the exterior surface of said control drum towards a zone for
15 introduction of one of said documents or one of said objects, in that the envelope is then opened, and in that said document or said object is introduced into said previously opened envelope.
2. A method according to claim 1 characterized in that said envelope flap is unfolded by generating at least one stream of air.
- 20 3. A method according to claim 1 characterized in that said envelope flap is placed against the surface of the control drum by radial suction produced inside said drum.

4. A method according to claim 1 characterized in that the envelopes are detached from the control drum by means of at least one scraper that is tangential in relation to the surface of said drum.
5. A method according to claim 1 characterized in that each envelope is opened by means of opening guides.
6. A method according to claim 5 characterized in that said enveloped is compressed laterally.
7. A device (10, 50) for implementing the method of automatically inserting small items into envelopes, particularly documents or objects to be transmitted by a mailing service, according to claim 1, said device comprising a storage means (12, 52) and a means for successively feeding individual envelopes (15), a means for feeding the documents or objects to be transmitted toward said individual envelopes which comprise a folded closing flap, and a means for introducing one of these documents or one of these objects inside one of said envelopes, characterized in that said means of feeding the individual envelopes comprises a control drum (13, 53) which displaces the envelopes (15) individually and successively from said storage means (12, 52) towards a zone for introducing one of said documents or one of said objects into one of said individual envelopes, and in that said means for introducing one of said documents or one of said objects into one of said envelopes comprises a means (14, 22, 23; 54, 52, 63) for unfolding the flap of said individual envelope and opening said envelope.

8. A device according to claim 7 characterized in that said control drum (13, 53) comprises at least one peripheral zone (17, 57) perforated with openings (20, 60) and in that said openings are connected to a suction device in an intermediate zone between said storage means and the zone for introduction of one of said documents into one of said individual envelopes.
9. A device according to claim 8 characterized in that said openings (20, 60) are connected to a pressurized air generating device in said zone for introduction of one of said documents into one of said individual envelopes.
10. A device according to claim 7 characterized in that said control drum (13, 53) comprises on at least a portion of its periphery a covering (17, 57) with a high coefficient of friction.
11. A device according to claim 10 characterized in that said peripheral covering (17, 57) on said control drum (13, 53) extends over an angular section comprising between 25% and 75% of the periphery.
12. A device according to claim 10 characterized in that said peripheral covering (17, 57) on said control drum comprises several parallel bands (18, 58) extending over an angular section comprising at least between 25% to 75% of the periphery.
13. A device according to claim 7 characterized in that said means for opening said individual envelopes comprises at least one rotary cam (14, 54) which engages below the flap of each individual envelope in order to unfold it.
14. A device according to claim 13 characterized in that said rotary cam (14, 54) is driven synchronously with said control drum.

15. A device according to claim 13 characterized in that said rotary cam (14, 54) is provided with at least one organ (23, 63) generating at least one stream of air (24, 64) to assist with unfolding the flap of each individual envelope in order to open it.
- 5 16. A device according to claim 13 characterized in that said rotary cam (14, 54) is provided with at least one projection (22, 62) for initiating the unfolding of the flap of each individual envelope.
17. A device according to claims 7 and 13 characterized in that the control drum (13, 53) and the rotary cam (14, 54) are the same diameter and are driven
- 10 synchronously at the same speed and in that along one portion of their circular trajectory, said rotary cam (14, 54) is in contact with the peripheral surface of said control drum (23, 53) to drive one envelope from said storage means (12, 52) towards said introduction zone.
18. A device according to claim 7 characterized in that it comprises at least one
- 15 scraper (25, 65) for detaching said individual envelope from said control drum (13, 53) in said introduction zone.
19. A device according to claims 7 and 12 characterized in that it comprises several scrapers (25, 65) arranged in parallel, said scrapers being located between the parallel bands (18, 58) of said peripheral covering (17, 67) on said control drum.
- 20 20. A device according to claim 7 characterized in that it comprises lateral deflectors (36) to push together the lateral edges of said individual envelopes and assist in opening them.