

Description

The invention relates generally to the field of photography and particularly to a film cassette containing roll film.

In conventional 35mm film manufacturers' cassettes, such as manufactured by Eastman Kodak Co. and Fuji Photo Film Co., Ltd., the filmstrip is wound on a flanged spool which is rotatably supported within a cylindrical shell. A leading end section of the filmstrip approximately 60 millimeter (2 1/3 inches) long, commonly referred to as a "film leader", protrudes from a light-trapped slit or mouth of the cassette shell. One end of the spool has a short axial extension which projects from the shell, enabling the spool to be turned by hand. If the spool is initially rotated in an unwinding direction, the film roll inside the shell will tend to expand radially since the inner end of the filmstrip is attached to the spool, and the fogged leader section protruding from the slit will remain stationary. The film roll can expand radially until a non-slipping relation is established between its outermost convolution and the inner curved wall of the shell. Once this non-slipping relation exists, there is a binding effect between the film roll and the shell which prevents further rotation of the spool in the unwinding direction. Thus, rotation of the spool in the unwinding direction cannot serve to advance the filmstrip out of the shell, and it is necessary in the typical 35mm camera to engage the protruding leader section to draw the filmstrip out of the shell.

A 35mm film cassette has been proposed which, unlike conventional film cassettes, includes a film leader that does not extend outside the cassette shell. The leader, instead, is located entirely within the cassette shell. Specifically, in U.S. Pat. No. 4,423,943, granted January 3, 1984, there is disclosed a film cassette wherein the outermost convolution of the film roll wound on the film spool is radially constrained by respective circumferential lips of two axially spaced flanges of the spool to prevent the outermost convolution from contracting an inner wall of the cassette shell. The trailing end of the filmstrip is secured to the film spool, and the leading end of the filmstrip is reduced in width to allow it to protrude from between the circumferential lips and rest against the shell wall. During initial unwinding rotation of the film spool, the leading end of the filmstrip is advanced to and through a film passageway opening in order to exit the cassette shell. The opening has a width which is slightly less than the width of the filmstrip, thus resulting in the filmstrip being transversely bowed as it is uncoiled from the film spool, and thereby facilitating movement of the film edges under the circumferential lips of the respective flanges. However, transverse bowing of the filmstrip to move its

edges under the circumferential lips results in increased friction between the filmstrip and the cassette structure which will impede advance of the filmstrip from the cassette shell and may damage the filmstrip.

In the film cassette disclosed in U.S. Pat. No. 4,423,943, the pair of coaxial flanges associated with the film spool include respective disks overlying opposite sides, i.e. ends, of the film roll wound on the spool, and they include respective annular lips which circumferentially extend from the disks at a 90° angle to radially confine the outermost convolution of the film roll. If the annular lips extend from the disks at an angle greater than 90°, the clock-springing force of the film roll against such a sloped lip, especially in the vicinity of a disk, will create an axial force that can urge the disk firmly against an inside face of the cassette shell. Resultant contact between the inside face and the disk will cause unwanted friction.

The invention advantageously solves the problem described above by providing an essentially radial contact between the annular lips of the respective flanges and the clock-springing film roll in the film cassette, thereby eliminating the possibility of the film roll generating axial forces against the flanges.

According to the invention, there is provided a film cassette comprising (a) a cassette shell in which a spool is arranged to rotate, (b) a convoluted film roll wound on the spool, and (c) a pair of flanges rotatable with the spool and having respective disks which overlie opposite sides of the film roll and respective annular lips which circumferentially extend from the disks to radially confine an outermost convolution of the film roll to prevent the outermost convolution from contacting an interior wall of the cassette shell, and characterized in that:

each of said lips including an annular constraining section positioned at a preferred distance from one of the disks and at a predetermined radial distance from the spool to enable a lip to contact the outermost convolution of the film roll at a limited area remote from a disk, to radially confine the outermost convolution, and including an annular section extending from the disk to the constraining section and positioned at a predetermined radial distance from the spool, greater than the first-mentioned radial distance, to enable the lip to avoid contacting the outermost convolution substantially between the disk and the constraining section.

This arrangement provides an essentially radial contact between each of the lips and the outermost convolution, thereby preventing any clock-springing of the film roll from generating an axial force against the flanges of the spool.

FIG. 1 is an exploded perspective view of an improved film cassette according to a preferred embodiment of the invention;

FIG. 2 is an elevation view in cross-section of the improved film cassette;

FIG. 3 is an end view in cross-section of the improved film cassette; and

FIG. 4 is an elevation view in cross-section of one of a pair of flanges associated with a spool in the improved film cassette.

The invention is disclosed as being embodied preferably in a 35mm film cassette. Because the features of this type of film cassette are generally well known, the description which follows is directed in particular to elements forming part of or cooperating directly with the disclosed embodiment. It is to be understood, however, that other elements not specifically shown or described may take various forms known to persons of ordinary skill in the art.

Referring now to the drawings, FIGS. 1-3 depict an improved 35mm film cassette 1 comprising a light-tight cassette shell 3 and a film spool 5 which is rotatably about an axis X within the cassette shell. The cassette shell 3 consists of two shell halves 7 and 9 which are mated along respective grooved and stepped edge portions 11 and 13. The mated halves 7 and 9 define upper and lower aligned openings 15 and 17 for relatively longer and shorter opposite end extensions 19 and 21 of a spool core or hub 23. Also, they define a light-trapped film passage slit or mouth 25. The light-trapping means for preventing ambient light from entering the film passage slit 25, although not shown, may be a known velvet or plush material which lines the interior of the slit.

The spool core 23 as shown in FIGS. 1-3 includes relatively longer and shorter coaxial holes 27 and 29 opening at the respectively longer and shorter opposite end extensions 19 and 21 of the spool core. A pair of spaced keying ribs 31 and 33 integrally formed with the spool core 23 are located within the longer coaxial hole 27, and a single keying rib 35 similarly formed with the spool core is located within the shorter coaxial hole 29. The several keying ribs 31, 33, and 35 according to custom may be engaged to rotate the film spool in an unwinding direction indicated by the arrow U in FIG. 1, or to rotate the spool in a winding direction opposite to the unwinding direction.

A roll 37 of convoluted 35mm film having a uniform width is wound about the spool core 23. As indicated in FIG. 3, the film roll 37 has an inner or trailing end 39 attached to the spool core 23 by a suitable piece of adhesive tape 41 and a film leader 43. The film leader 43 has a leading or forward end 45 and comprises 2-3 convolutions of the film roll 37. One of these leader convolutions is

the outermost convolution 47 and another of them is the next inward succeeding convolution 49.

A pair of identical flanges 51 and 53 are coaxially spaced along the spool core 23 as shown in FIGS. 1 and 2. The two flanges 51 and 53 comprise respective integral disks 55 and 57 and respective integral annular lips or skirts 59 and 61 which circumferentially extend from the disks. The two disks 55 and 57 cover opposite sides, i.e. ends, 63 and 65 of the film roll 37 and they have respective central holes 67 and 69 through which the spool core 23 longitudinally extends to permit rotation of the spool core relative to the flanges 51 and 53. Each of the lips 59 and 61 as depicted in FIG. 4 includes the following:

- (1) an annular constraining section 71 positioned relatively remote from one of the disks 55 and 57 at a predetermined radial distance R_1 from the spool core 23 to enable each of the lips 59 and 61 to contract the outermost convolution 47 of the film roll 37, to radially confine the outermost convolution and thereby prevent the film roll from radially expanding or clock-springing against an inner wall 73 of the cassette shell 3;
- (2) an annular relief section 75 extending from one of the disks 55 and 57 to the annular constraining section 71 of one of the lips 59 and 61 and positioned in a predetermined radial distance R_2 from the spool core 23, greater than the radial distance R_1 ; to enable each of the lips to avoid contacting the outermost convolution 47 substantially between one of the disks and the annular constraining section; and
- (3) an annular free end section 77 inclined radially outwardly from the annular constraining section 71 of one of the lips 59 and 61 and away from the outermost convolution 47.

The annular relief section 75 of each of the lips 59 and 61 is inclined radially inwardly from one of the disks 55 and 57 toward the outermost convolution 47 to form an acute relief angle A_1 with the outer most convolution. See FIG. 4. The relief angle A_1 may be $11^\circ 45'$, for example. The annular constraining section 71 of each of the lips 59 and 61 is curved radially inwardly with respect to the film roll 37 to enable both of the lips to contact the outermost convolution 47 in a substantially tangential manner (in the vertical sense in FIG. 4) and thereby limit the area of contact between the lips and the outermost convolution. The annular free end section 77 of each of the lips 59 and 61 is tilted slightly upwardly as shown in FIG. 4 to form an acute relief angle A_2 . The relief angle A_2 may be 10° , for example. Thus, as shown in FIG. 2 the lips 59 and 61 are either shaped in the form of a "Z" or an "S".

A pair of rigid identical spreader surfaces 79 and 81 are fixed to the cassette half 9 at separate locations inwardly of the film passage slit 25 as shown in FIG. 2. The respective spreader surfaces 79 and 81 deflect opposite limited portions 59' and 61' of the annular lips 59 and 61 axially away from each other to an axial dimension slightly exceeding the film width. See FIG. 2. In essence, the deflected portions 59' and 61' of the annular lips 59 and 61 are axially spaced sufficiently to prevent those portions of the lips from radially confining corresponding portions of the outermost convolution 47 of the film roll 37. As indicated in FIG. 2, the remaining portions of the two lips 59 and 61 are maintained in place by inner semi-circular flat surfaces 83 and 85 of the cassette shell 3. The flat surfaces 83 and 85 abut the respective disks 55 and 56, except in the vicinity of the spreader surfaces 79 and 81. Thus, the remaining portions of the two lips 59 and 61 continue to radially confine the outermost convolution 47.

As shown in FIG. 2, the annular free end section 77 of each of the annular lips 59 and 61, at the deflected portions 59' and 61' of the two lips, bears against the respective spreader surfaces 79 and 81. Since the annular free end section 77 of each of the lips has a gentle curve to it as best seen in FIG. 4, very little wear occurs between the free end section and either of the spreader surfaces 79 and 81. The relief angle A_2 of the annular free end section 77 of each of the lips is useful during assembly of the film cassette 1, to position either of the spreader surfaces 79 and 81 relative to an annular free end section.

When the spool core 23 is initially rotated in the unwinding direction U, the two flanges 51 and 53 may remain substantially stationary and the film roll 37, since its inner end 39 is attached to the spool core, tends to expand radially or clock-spring to ensure a non-slipping relation between the outermost convolution 47 of the film roll and the annular lips 59 and 61 of the flanges. Then, rotation of the spool core 23 in the same direction will similarly rotate the two flanges 51 and 53. As a result, the two spreader surfaces 79 and 81 will deflect successive portions 59' and 61' of the annular lips 59 and 61 axially away from each other as the respective portions are rotated past the spreader surfaces. The deflected portions 59' and 61' of the two lips 59 and 61 are returned to their original non-flexed condition by the semi-circular flat surfaces 83 and 85 of the cassette shell 3. As can be appreciated from FIG. 3, the leading end 45 of the film roll 37 will be freed from the radial confinement of the two lips 59 and 61 in the vicinity of the two spreader surfaces 79 and 81, and it will be advanced against a pair of rigid identical stripper-guide surfaces 87 and 89 integ-

rally formed with the respective spreader surfaces. The two stripper-guide surfaces 87 and 89 operate to direct the leading end 45 into the film passage slit 25, thereby allowing succeeding portions of the outermost convolution 47 to be freed from corresponding portions of the two lips 59 and 61 as those portions of the lips are deflected by the two spreader surfaces 79 and 81. Consequently, continued rotation of the spool core 23 will thrust the film leader 43 from the inside to the outside of the cassette shell 3.

According to the invention, the annular constraining section 71 of each of the annular lips 59 and 61 provides an essentially radial contact between the two lips and the clock-springing film roll 37. This prevents any clock-springing of the film roll from generating an axial force against either of the flanges 51 and 53 which would severely increase the friction between the respective disks 55 and 57 and the semi-circular flat surfaces 83 and 85 of the cassette shell 3.

The invention has been described with reference to a preferred embodiment. However, it will be appreciated that variations and modifications can be effected within the ordinary skill in the art without departing from the scope of the invention. For example, the leading end 45 of the film roll 37 could initially be located within the film passage slit 25 rather than be radially confined by the annular lips 59 and 61 of the two flanges 51 and 53 as shown in FIG. 1. Also, the leading end 45 could be tapered to allow it to freely protrude from between the annular lips 59 and 61.

According to another example, the annular lips 59 and 61 need not be "Z"-shaped or "S"-shaped as shown in FIGS. 2 and 4. Instead, they may have a somewhat different shape. All that is necessary is that the annular lips provide essentially radial contact between themselves and the film roll, without allowing the clock-springing force of the film roll to generate an axial force against either of the flanges 51 and 53.

Claims

1. A film cassette (1) comprising a cassette shell (3) in which a spool (5) is arranged to rotate, a convoluted film roll (37) wound on said spool, and a pair of flanges (51 & 53) rotatable with said spool and having respective disks (55 & 57) overlying opposite sides (63 & 65) of said film roll and respective annular lips (59 & 61) circumferentially extending from said disks to radially confine an outermost convolution (47) of the film roll to prevent said outermost convolution from contacting an interior wall (73) of said cassette shell, is characterized in that:
 - each of said lips (59 & 61) includes an

A pair of rigid identical spreader surfaces 79 and 81 are fixed to the cassette half 9 at separate locations inwardly of the film passage slit 25 as shown in FIG. 2. The respective spreader surfaces 79 and 81 deflect opposite limited portions 59' and 61' of the annular lips 59 and 61 axially away from each other to an axial dimension slightly exceeding the film width. See FIG. 2. In essence, the deflected portions 59' and 61' of the annular lips 59 and 61 are axially spaced sufficiently to prevent those portions of the lips from radially confining corresponding portions of the outermost convolution 47 of the film roll 37. As indicated in FIG. 2, the remaining portions of the two lips 59 and 61 are maintained in place by inner semi-circular flat surfaces 83 and 85 of the cassette shell 3. The flat surfaces 83 and 85 abut the respective disks 55 and 56, except in the vicinity of the spreader surfaces 79 and 81. Thus, the remaining portions of the two lips 59 and 61 continue to radially confine the outermost convolution 47.

As shown in FIG. 2, the annular free end section 77 of each of the annular lips 59 and 61, at the deflected portions 59' and 61' of the two lips, bears against the respective spreader surfaces 79 and 81. Since the annular free end section 77 of each of the lips has a gentle curve to it as best seen in FIG. 4, very little wear occurs between the free end section and either of the spreader surfaces 79 and 81. The relief angle A_2 of the annular free end section 77 of each of the lips is useful during assembly of the film cassette 1, to position either of the spreader surfaces 79 and 81 relative to an annular free end section.

When the spool core 23 is initially rotated in the unwinding direction U, the two flanges 51 and 53 may remain substantially stationary and the film roll 37, since its inner end 39 is attached to the spool core, tends to expand radially or clock-spring to ensure a non-slipping relation between the outermost convolution 47 of the film roll and the annular lips 59 and 61 of the flanges. Then, rotation of the spool core 23 in the same direction will similarly rotate the two flanges 51 and 53. As a result, the two spreader surfaces 79 and 81 will deflect successive portions 59' and 61' of the annular lips 59 and 61 axially away from each other as the respective portions are rotated past the spreader surfaces. The deflected portions 59' and 61' of the two lips 59 and 61 are returned to their original non-flexed condition by the semi-circular flat surfaces 83 and 85 of the cassette shell 3. As can be appreciated from FIG. 3, the leading end 45 of the film roll 37 will be freed from the radial confinement of the two lips 59 and 61 in the vicinity of the two spreader surfaces 79 and 81, and it will be advanced against a pair of rigid

ally formed with the respective spreader surfaces. The two stripper-guide surfaces 87 and 89 operate to direct the leading end 45 into the film passage slit 25, thereby allowing succeeding portions of the outermost convolution 47 to be freed from corresponding portions of the two lips 59 and 61 as those portions of the lips are deflected by the two spreader surfaces 79 and 81. Consequently, continued rotation of the spool core 23 will thrust the film leader 43 from the inside to the outside of the cassette shell 3.

According to the invention, the annular constraining section 71 of each of the annular lips 59 and 61 provides an essentially radial contact between the two lips and the clock-springing film roll 37. This prevents any clock-springing of the film roll from generating an axial force against either of the flanges 51 and 53 which would severely increase the friction between the respective disks 55 and 57 and the semi-circular flat surfaces 83 and 85 of the cassette shell 3.

The invention has been described with reference to a preferred embodiment. However, it will be appreciated that variations and modifications can be effected within the ordinary skill in the art without departing from the scope of the invention. For example, the leading end 45 of the film roll 37 could initially be located within the film passage slit 25 rather than be radially confined by the annular lips 59 and 61 of the two flanges 51 and 53 as shown in FIG. 1. Also, the leading end 45 could be tapered to allow it to freely protrude from between the annular lips 59 and 61.

According to another example, the annular lips 59 and 61 need not be "Z"-shaped or "S"-shaped as shown in FIGS. 2 and 4. Instead, they may have a somewhat different shape. All that is necessary is that the annular lips provide essentially radial contact between themselves and the film roll, without allowing the clock-springing force of the film roll to generate an axial force against either of the flanges 51 and 53.

Claims

1. A film cassette (1) comprising a cassette shell (3) in which a spool (5) is arranged to rotate, a convoluted film roll (37) wound on said spool, and a pair of flanges (51 & 53) rotatable with said spool and having respective disks (55 & 57) overlying opposite sides (63 & 65) of said film roll and respective annular lips (59 & 61) circumferentially extending from said disks to radially confine an outermost convolution (47) of the film roll to prevent said outermost convolution from contacting an interior wall (73) of said cassette shell, is characterized in that:

each of said lips (59 & 61) includes an



annular constraining section (71) positioned at a predefined remote distance from one of said disks (55 & 57) and at a predetermined radial distance (R1) from said spool (5) to enable a lip to contact said outermost convolution (47) of the film roll (37) at a limited area remote from a disk, to radially confine the outermost convolution, and it includes an annular section (75) extending from said disk to said constraining section and positioned at a predetermined radial distance (R2) from said spool, greater than the first-mentioned radial distance (R1), to enable said lip to avoid contacting said outermost convolution substantially between the disk and the constraining section.

2. The film cassette (1) as recited in claim 1, wherein said annular section (75) of each of the lips (59 & 61) is inclined radially inwardly from one of said disks (55 & 57) toward said outermost convolution (47) of the film roll (37) to form an acute angle (A1) with the outermost convolution.
3. The film cassette (1) as recited in claim 2, wherein said annular constraining section (71) of each of the lips (59 & 61) is curved radially inwardly with respect to said film roll (37) to enable both of said lips to contact said outermost convolution (47) of the film roll in a substantially tangential manner and thereby limit the area of contact between the lips and the outermost convolution.
4. The film cassette (1) as recited in claim 3, wherein each of said lips (59 & 61) includes an annular free end section (77) inclined radially outwardly from said annular constraining section (71) of a lip and away from said outermost convolution (47) of the film roll (37).

Patentansprüche

1. Filmpatrone (1) fit einem Gehäuseteil (3), in dem eine Spule (5) drehbar gelagert ist, mit einer auf die Spule aufgewickelten Filmrolle (37) und mit zwei Flanschen (51, 53), die mit der Spule drehbar sind und entsprechende Scheiben (55, 57) aufweisen, die über entgegengesetzte Enden (63, 65) der Filmrolle und über entsprechende ringförmige Auskragungen (59, 61) hinausragen, die sich von den Scheiben weg erstrecken und in radialer Richtung eine äußerste Wicklung (47) der Filmrolle begrenzen und so verhindern, daß diese Wicklung mit einer Innenwand (73) des Patronengehäuseteils in Berührung gelangt, dadurch gekennzeichnet, daß

jede Auskragung (59, 61) einen ringförmigen, eine Einschnürung bildenden Abschnitt (71) aufweist, der in einem vorbestimmten größeren Abstand von einer der Scheiben (55, 57) und in einem vorbestimmten radialen Abstand (R1) von der Spule (5) so angeordnet ist, daß eine Auskragung in einem begrenzten Bereich im Abstand von einer Scheibe mit der äußersten Wicklung (47) der Filmrolle (37) in Berührung gelangen kann, um diese Wicklung radial zu begrenzen, und daß jede Auskragung einen ringförmigen Abschnitt (75) aufweist, der sich von der Scheibe zu dem eine Einschnürung bildenden Abschnitt (71) erstreckt und der in einem größeren vorbestimmten radialen Abstand (R2) von der Spule als der zuerst erwähnte radiale Abstand (R1) so angeordnet ist, daß die Auskragung im wesentlichen zwischen der Scheibe und dem eine Einschnürung bildenden Abschnitt (71) nicht mit der äußersten Wicklung in Berührung gelangt.

2. Filmpatrone (1) nach Anspruch 1, dadurch gekennzeichnet, daß der ringförmige Abschnitt (75) einer jeden Auskragung (59, 61) von einer der Scheiben (55, 57) aus zur äußersten Wicklung (47) der Filmrolle (37) hin radial nach innen geneigt ist und mit dieser Wicklung einen spitzen Winkel (A1) bildet.
3. Filmpatrone (1) nach Anspruch 2, dadurch gekennzeichnet, daß der ringförmige, eine Einschnürung bildende Abschnitt (71) einer jeden Auskragung (59, 61) bezüglich der Filmrolle (37) so radial nach innen gekrümmt ist, daß beide Auskragungen mit der äußersten Wicklung (47) der Filmrolle im wesentlichen tangential in Berührung gelangen und dadurch den Berührungsbereich zwischen den Auskragungen und der äußersten Wicklung begrenzen.
4. Filmpatrone (1) nach Anspruch 3, dadurch gekennzeichnet, daß jede Auskragung (59, 61) einen ringförmigen freien Endabschnitt (77) aufweist, der von dem ringförmigen, eine Einschnürung bildenden Abschnitt (71) einer Auskragung aus radial nach außen und von der äußersten Wicklung (47) der Filmrolle (37) weg geneigt ist.

Revendications

1. Chargeur (1) de film comprenant une enveloppe (3) dans laquelle tourne une bobine (5), un rouleau (37) de film enroulé en spirale sur ladite bobine, et une paire de joues (51 et 53) susceptible de tourner avec la bobine et présentant des disques (55 et 57) respectifs re-



couvrant les côtés opposés (63 et 65) dudit rouleau de film et des lèvres annulaires respectives (59 et 61) s'étendant à la circonférence desdits disques de manière à confiner la spire extérieure (47) du rouleau de film pour éviter que ladite spire extérieure ne vienne en contact avec la paroi interne (73) de ladite enveloppe, chargeur caractérisé en ce que :

chacune des lèvres (59 et 61) comprend une partie annulaire de contrainte (71) disposée à une distance déterminée du disque correspondant (55 et 57) et à une distance radiale prédéterminée (R1) de ladite bobine (5) pour permettre à ladite lèvre de venir en contact avec la spire externe (47) du rouleau de film (37) en une zone limitée distante du disque, afin de confiner radialement ladite spire externe, et en ce qu'il comprend une partie annulaire (75) reliant le disque à la partie annulaire de contrainte et disposée à une distance radiale (R2) prédéterminée de ladite bobine supérieure à la distance radiale (R1) mentionnée préalablement, pour permettre que ladite lèvre ne vienne pratiquement pas en contact avec ladite spire externe entre le disque et la partie annulaire de contrainte.

2. Chargeur (1) selon la revendication 1, dans lequel la section annulaire (75) de chaque lèvre (59 et 61) est inclinée radialement vers l'intérieur lorsqu'on s'éloigne du disque correspondant (55 et 57) vers la spire externe (47) du rouleau de film (37) afin de former un angle aigu (A1) avec la spire externe.

3. Chargeur (1) selon la revendication 2, dans lequel la partie annulaire de contrainte (71) de chaque lèvre (59 et 61) est incurvé radialement vers l'intérieur par rapport audit rouleau de film (37) pour permettre que les deux lèvres viennent en contact avec la spire externe (47) du rouleau de film pratiquement tangentiellement et ainsi limiter la zone de contact entre les lèvres et la spire externe.

4. Chargeur selon la revendication 3, dans lequel chacune des lèvres (59 et 61) comprend une partie libre d'extrémité (77) annulaire et inclinée radialement vers l'extérieur de ladite partie annulaire de contrainte (71) de la lèvre lorsqu'on s'éloigne de ladite spire externe (47) du rouleau de film (37).

