



- (51) **International Patent Classification:**
C08L 23/14 (2006.01) *C08F 2/00* (2006.01)
- (21) **International Application Number:**
PCT/EP2014/000374
- (22) **International Filing Date:**
11 February 2014 (11.02.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
13002102.5 22 April 2013 (22.04.2013) EP
- (71) **Applicants:** **ABU DHABI POLYMERS COMPANY LIMITED (BOROUGE)** [AE/AE]; Sheikh Khalifa Energy Complex, Corniche Road, P.O. Box 6925, Abu Dhabi (AE). **BOREALIS AG** [AT/AT]; IZD Tower, Wagramerstrasse 17-19, A-1220 Wien (AT).
- (72) **Inventors:** **HEDESIU, Cristian**; Innovention Center, SKEC, Boroque Tower, 11 th Floor, P.O. Box 6951, Abu Dhabi (AE). **ALASTALO, Kauno**; Karjapolku 4, FIN-06400 Porvoo (FI).
- (74) **Agent:** **KADOR & PARTNER**; Corneliusstrasse 15, 80469 München (DE).
- (81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *of inventorship (Rule 4.17(iv))*

Published:

— *with international search report (Art. 21(3))*

- (54) **Title:** MULTIMODAL POLYPROPYLENE COMPOSITION FOR PIPE APPLICATIONS

(57) **Abstract:** A multimodal propylene copolymer composition suitable for pipe applications comprising a multimodal propylene copolymer (U) with at least one comonomer selected from alpha-olefins with 2 or 4 to 8 carbon atoms in a total amount of 4.0 to 10.0 mole-%, wherein the composition has a melt flow rate MFR₂ (2.16 kg, 230 °C) of 0.05 to 1.00 g/10 min determined according to ISO 1133, a content of xylene cold solubles (XCS) of 4.0 to 17.0 wt.-% determined at 25 °C according to ISO 16152, and a polydispersity index PI of 2.5 to 4.0 Pa⁻¹ determined by rheological measurements according to ISO 6721-1 and ISO 6721-10.

