



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A63F 37/00	A1	(11) International Publication Number: WO 00/12187 (43) International Publication Date: 9 March 2000 (09.03.00)
(21) International Application Number: PCT/SG99/00088 (22) International Filing Date: 25 August 1999 (25.08.99) (30) Priority Data: 9803362-4 31 August 1998 (31.08.98) SG (71) Applicant (for all designated States except US): TECHNOCRACKER PTB LTD. [SG/SG]; 31 International Business Park, Creative Resource #02-04, Singapore 609921 (SG). (72) Inventors; and (75) Inventors/Applicants (for US only): YAP, Leong, Kheng [SG/SG]; 30 Dover Rise #14-05, Singapore 138687 (SG). NEO, Tiang, See [SG/SG]; Blk 152 Hougang Street 11 #04-66, Singapore 530152 (SG). (74) Agent: GREENE-KELLY, James, Patrick; Lloyd Wise, Tanjong Pagar, P.O. Box 636, Singapore 910816 (SG).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IN, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: SOUND PRODUCING APPARATUS (57) Abstract Sound producing apparatus (20) is disclosed which simulates a fire cracker. The apparatus comprises a selectively actuatable aerosol (24) which fills a chamber (35) with compressed fluid which, when a certain pressure is reached, blows off a cap (38) creating a shower of confetti (39) and a loud bang. In other embodiments, a plurality of elastomeric members filled with compressed air which are ruptured or a selectively operable compressed fluid container formed by the apparatus housing, are used to create a similar effect.		