

Description

The present invention relates generally to a cassette type recording and/or reproducing apparatus and, more particularly, to a cassette type recording and/or reproducing apparatus having a chassis capable of mounting a cassette on an upper part thereof. More particularly, this invention relates to a thin cassette recording apparatus having a chassis with a recess wherein the tape reels and the mode-changing mechanism are mounted within the recess. Still more particularly, this invention relates to a thin cassette recording apparatus wherein a recessed chassis and the arrangement of parts facilitates easy assembly primarily from a direction above the chassis.

In a conventional cassette type tape recorder, in which a cassette is mounted on an upper part of chassis to which a pair of left and right reel beds are attached, the reel beds are mounted above a chassis on an upper portion of an upper surface of the chassis. Gears to rotate the reel beds are mounted below the chassis on a lower part of the chassis. Hence, it is difficult to mount the cassette compactly on the upper surface of the chassis. Therefore, it is required to float the cassette with respect to the upper surface of the chassis. Consequently, it is difficult to achieve a thin structure for the cassette type recording and/or reproducing apparatus.

In addition, since the reel beds and gears must be assembled above and below the chassis respectively on the upper and lower portions of the chassis separately, a reduced assembly efficiency results.

The applicants have proposed a thin structure for a cassette type recording and/or reproducing apparatus in a pending United States Patent Application Serial No. 06/578,011 filed on February 8, 1984 (corresponding to document GB-A-2,136,191).

In the above-identified Patent Application, a chassis for mounting a cassette thereon is provided with two holes for the two reel beds and the two reel beds are supported on another chassis.

Nevertheless, it has remained a problem to provide a thin cassette-type recording apparatus wherein the parts are conveniently arranged and assembled in a chassis while the cassette remains quite thin and the functions of the apparatus are conveniently performed.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved cassette type recording and/or reproducing apparatus.

It is another object of the present invention to provide a cassette type recording and/or reproducing apparatus having a remarkably thin profile construction.

It is still another object of the present invention to provide a recessed chassis for a cassette-type recording apparatus to contain the reel beds and the mode-changing apparatus in the recess.

It is yet another overall object of this invention to provide a cassette-type recording apparatus having a recessed chassis and an arrangement of components which may facilitate assembly primarily from a direction above the chassis.

The above-described objects can be achieved by providing a cassette-type recording apparatus as defined in claim 1.

The actuation change means comprise drive means for respectively actuating selected ones of the reel means to operate the cassette in various modes.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the present invention may be obtained from the following description taken in conjunction with the attached drawings in which;

Fig. 1 is an overall exploded perspective view of a preferred embodiment of a cassette type recording and/or reproducing apparatus according to the present invention;

Fig. 2 is an exploded perspective view of an essential part of the cassette-type recording and/or reproducing apparatus shown in Fig. 1;

Fig. 3 is a top plan view of the essential part of the cassette-type recording and/or reproducing apparatus shown in Figs. 1 and 2;

Fig. 4 is a sectional view of the cassette-type recording and/or reproducing apparatus taken along line IV-IV in Fig. 3; and

Fig. 5 is a sectional view of the cassette-type recording and/or reproducing apparatus taken along line V-V in Fig. 3.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will hereinafter be made to the drawings in order to facilitate an understanding of the present invention.

Figs. 1 through 5 show a cassette tape recorder as a cassette-type recording and/or reproducing apparatus to which the present invention is applicable. The cassette tape recorder is an automatically-reversing type of a dual capstan system using a compact cassette.

As shown in Fig. 1, a magnetic tape 3 wound on a pair of reel hubs 1, 2 is housed in a cassette,

designated generally by the reference numeral 4. The cassette 4 is horizontally mounted for recording and playback on an upper part of a chassis 6 cooperating with recording and reproducing components (not shown) as a part of an overall apparatus. The chassis 6 is structurally adapted to cooperate with a drive mechanism for rotating the reel hubs for the respective tape reels in the cassette in a forward or in a reverse direction, at various speeds, to record and playback information on the tape 3.

The upper part or top surface of the chassis 6 contains a pair of left and right capstans 7, 8, pinch rollers 9, 10, reel beds 11, 12, and a magnetic head 13. The pair of left and right reel hubs 1, 2 are respectively engaged with the corresponding reel beds 11, 12. The magnetic tape 3 is extended through the capstans 7, 8 and the magnetic head 13. A plurality of operating buttons 14 for a playback or record mode, a fast forward mode, a rewind mode, a stop mode, and so on are attached to a side surface of the chassis 6 to control the mode of operation of the cassette 4.

An actuation device 16 for actuating the pair of capstans 7, 8 to rotate in mutually reverse directions and for selectively actuating the pair of reel beds 11, 12 is installed on a lower part or bottom surface of the chassis 6. A change in the direction of rotation of the pair of reel beds 11, 12 is accomplished by a gear change mechanism 17 installed at an intermediate space between the reel beds 11, 12 and on the upper part of the chassis 6. The gear change mechanism 17 comprises a plurality of gears 27, 28, 29, and 30.

When the playback button, included among the buttons 14, is depressed with the cassette 4 mounted on the chassis 6, the pinch roller 9 is pressed into contact with the capstan 7 and the left reel bed 11 is actuated to rotate in a counterclockwise direction. With the magnetic tape 3 running normally to wind on the left reel hub 1, a normal playback, or normal recording is caused on the tape 3 by the magnetic head 13. When the end of the tape 3 is reached during the normal run, the pinch roller 9 is separated from the capstan 7. After actuation of the reel bed 11 has ceased, the other pinch roller 10 is pressed into contact with the other capstan 8. At this time, the right reel bed 12 is actuated to rotate in a clockwise direction and the magnetic tape 3 runs in a reverse direction to wind on the other or right reel hub 2. Consequently, a reverse playback or a reverse recording is caused on the tape 3 by the magnetic head 13. When a fast forward or a rewind button among the operation buttons 14 is depressed, a fast forward or rewind of the magnetic tape 3 is caused with the reel beds 11, 12 selectively actuated to rotate at a high speed, i.e. at a speed higher than used for normal or reverse re-

cording or playback.

The rotation actuation device 16, as shown in Fig. 1, comprises a drive pulley 18 actuated by means of a motor, to be described later, a pair of capstan pulleys 19, 20 attached to a lower end of the capstans 7, 8, and a belt 23 wound about an intermediate pulley 21 and a direction change pulley 22. A Fast Forward and Rewind (FR) drive gear 24 is integrally and coaxially mounted on an upper part of the intermediate pulley 21. Furthermore, a Normal and Reverse (NR) drive gear 25 actuated via a torque limiter (not shown) is also coaxially mounted on an upper portion of the FR drive gear 24. The gear change mechanism 17 is provided with the Normal and Reverse (NR) gears 27, 28 and Fast Forward and Rewind (FR) gears 29, 30. A pair of reel axles 31, 32 are respectively installed on the upper portions of centers of the reel beds 11, 12, respectively. A pair of reel bed gears 33, 34 are respectively installed on the peripheries of the reel beds 11, 12.

The structure of the chassis 6 and the mounting states of the reel beds 11, 12 and gears 27 through 30 will be described with reference to Fig. 2 through Fig. 5.

As shown in Fig. 2, the chassis 6 is made of a metallic plate. An upper surface 6a of the chassis 6 has a recess 36 substantially in the form of an ellipse (as best seen in Fig. 3) at substantially a center portion of the upper surface 6d and another recess 37 substantially in the form of a trapezoid at a rear portion of the upper surface 6a with respect to the side surface on which the plurality of operating buttons 14 are mounted. These recesses are formed by a pressing or drawing process. It should be noted that the recesses 36, 37 act to reinforce the chassis 6 so that the chassis 6 becomes extremely rigid through the pressing of the recesses 36, 37.

The reel beds 11, 12 and gears 27 through 30 are mounted on the upper portion of the chassis 6 and within the recess 36 so as to be positioned on left and right sides and at a center position within the recess 36. The upper surfaces 11a, 12a of the reel beds 11, 12 and the upper surfaces 27a through 30a of the gears 27 through 30 are located at substantially the same level as, or lower than, the upper surface 6a of the chassis 6, as can be seen in Figs. 2, 4, and 5. In addition, a cover plate 38 (as best seen in Figs. 1, 2, and 3), substantially in a double concave shape, is screwed substantially on the same plane as the upper surface 6a of the chassis 6 at an upper portion of a center portion of the recess 36, as seen in Fig. 5. The cover plate 38 is used to cover the above-described gears 27 through 30. The pair of capstans 7, 8 is mounted within the rearward, generally-trapezoidal recess 37.

As shown in Fig. 4, the reel bed 11 is rotatably mounted on an outer periphery of a supporting pole 40 which is installed on the upper portion of a recess 36 in the chassis 6. At this time, the reel bed 11 is inserted into the recess 36 with its center opening penetrated by the supporting pole 40.

The other reel bed 12 is rotatably mounted on an outer periphery of a supporting pole 44 which is installed on the upper portion of a casing 43 of the motor 42 attached from a lower side of the chassis at an opening 41 installed in the recess of the chassis 6. At this time, the other reel bed 12 is inserted into the recess 36 with its center hole penetrated by the supporting pole 44. A suitable structure for the motor 42 is exemplified in the United States Patent Application Serial No. 06/578,011 filed on February 8, 1984 by the same applicants, which application corresponds to the document GB-A-2,136,191.

As shown in Figs. 3 and 5, a supporting lever 47 is mounted on a supporting pole 46 mounted coaxially on an outer periphery of the NR drive gear 25 placed below the chassis 6 so as to enable the lever 47 to swing on the supporting pole 46. A supporting pin 48 installed on an upper portion of a tip of the supporting lever 47 projects toward an upper portion of the recess 36 from the opening 49 of the recess 36 of the chassis 6. The NR gear 27 is rotatably supported on the outer periphery of the supporting pin 48. At this time, the one NR gear 27 is inserted into the recess 36 from the upper direction of the chassis 6 during assembly. The other NR gear 28 is rotatably supported on the outer periphery of the supporting pin 50 fixed on the upper portion of the recess 36 of the chassis 6, as seen in Figs. 2 and 3. At this time, the other NR gear 28 is inserted onto the supporting pin 50 hereinto from the upper part of the chassis 6. The other NR gear 28 is always engaged with the reel bed gear 33 of the one reel bed 11. The one NR gear 27 can be engaged with or disengaged from the other NR gear 28 and reel bed gear 34 of the other reel bed 12, while the one NR gear 27 is always engaged with the NR drive gear 25.

In addition, the FR gears 29, 30 are rotatably mounted on mounting pins 53, 54 mounted on the lower part of a tip of a supporting lever 52 arranged within the recess 36 of the chassis 6. The supporting lever 52 is inserted onto a supporting pin 55 fixed on the upper part of the recess 36 of the chassis 6 via an elongated hole 56 during the assembly, is free to swing around the supporting pin 55 and is movable in the elongated direction of the elongated hole 56. The FR gear 29 comprises a wide gear projected from the opening 57 of the recess 36 of the chassis 6 toward a lower direction of the recess 36 and is detachably engaged with the reel bed gear 34 of the reel bed 12 and the FR

drive gear 24. In addition, the other FR gear 30 is always meshed with the FR gear 29 so as to engage detachably with the reel bed gear 33 of the one reel bed 11.

As shown in Figs. 2, 3 and 5, the cover plate 38 has three holes 59 each located substantially at a vertex of an isosceles triangle formed by the cover plate 38. On the other hand, on the upper part of the recess 36, two supporting pins 50, 55 extend vertically from the NR gear 28 and the elongated hole 56, respectively, while another supporting pin 58 extends vertically from the upper surface of the recess 36. In addition, three female threaded holes 60 are provided on upper central portions of the three supporting pins 50, 55, 58, respectively. When the screws 61 are fitted into the corresponding female threaded holes 60 via the corresponding holes 59 in the cover plate 38, the cover plate 38 is positioned horizontally with respect to the recess 36 and detachably screwed to the chassis 6.

As shown in Figs. 4 and 5, the cassette 4 denoted by a dot-and-dash line is mounted horizontally on the chassis 6. When the reel hubs 1, 2 are engaged with the reel axes 31, 32 of the reel beds 11, 12 and the magnetic tape 3 is set so as to pass about the capstans 7, 8 and in contact with the magnetic head 13, the cassette 4 can be brought in close contact with the upper surface 6a of the chassis 6. Consequently, the entire tape recorder can be remarkably compacted especially for its height. At this time, as shown in Fig. 5, an extended portion 4a, which is trapezoidally-shaped and located at the rear surface of the cassette, is fitted to the recess 37 of the chassis 6.

Since, in the above-described construction, the reel beds 11, 12 and the plurality of gears 27 through 30 can be assembled on the upper portion of the chassis 6 within the recess 36 from a single direction, i.e. from above the upper part of the chassis 6, the reel beds 11, 12 and gears 27 through 30 can be assembled extremely simply. In addition, since a single cover plate 38 can serve to prevent the NR gears 27, 28 inserted from the upper direction and attached to the supporting pins 48, 50 from drawing out toward the upper direction as well as to prevent the FR gears 29, 30 inserted from the upper direction and attached to the supporting pin 55 via the supporting lever 52 from drawing out toward the upper direction, it is not necessary to attach washers for preventing the gears from drawing out toward the upper direction to the individual upper ends of the supporting pins 48, 50, 55. Hence, the number of parts to be used for assembly and the labor time required therefor can be reduced remarkably. In addition, a mere removal of the single cover plate 38 screwed to the upper surface of the chassis can facilitate the re-

placement of the gears 27 through 30 and achieve better service.

The change of rotation in the direction of the reel beds 11, 12 by means of the gear change mechanism 17 will be described below with reference to Fig. 3.

When the magnetic tape 3 is in the normal playback or record mode, the NR gear 27 is meshed with the NR gear 28 as denoted by a solid line and the NR drive gear 25 actuates the reel bed 11 to rotate in a counterclockwise direction as viewed from Fig. 3 via the NR gears 27, 28 and the reel bed gear 33. On the other hand, when the magnetic tape 3 is in a reverse playback or record mode, the NR gear 27 is meshed with the reel bed gear 34 as denoted by a dot-and-dash line and the NR drive gear 25 actuates the other reel bed 12 to rotate in a clockwise direction via the NR gear 27 and the reel bed gear 34. When the magnetic tape 3 is in the fast forward mode, the FR gears 29, 30 are respectively meshed with the FR drive gear 24 and reel bed gear 33 as denoted by solid lines, and the FR drive gear 24 actuates the one reel bed 11 to rotate in the counterclockwise direction via these gears 29, 30, 33 at a high speed. When the magnetic tape 3 is in the rewind mode, the FR gear 29 is meshed with the FR drive gear 24 and the reel bed gear 34 as denoted by the dot-and-dash line, so as to actuate the other reel bed 12 to rotate at a high speed via these gears 29, 34.

Since according to the present invention recesses are formed on the upper surface of the chassis and the pair of left and right reel beds and associated gears to actuate these reel beds are attached on the upper surface of the one recess in a direction from above the chassis, the cassette can be mounted on the upper surface of the chassis with the entire surface of the cassette brought in close contact with the upper surface of the chassis. Consequently, the entire cassette tape recorder of cassette-type recording and/or reproducing apparatus can remarkably be compacted. In addition, since the reel beds and gears can be assembled only on the upper side of the chassis from a direction from above the chassis, the assembly of the reel beds and gears can be carried out in a very simple manner as compared with the conventional structure in which the reel beds and gears are assembled separately on the upper and lower surfaces of the chassis. Therefore, an easy assembly operation can be achieved. The recesses formed on the upper surface of the chassis also provide a reinforcement structure for the chassis. Therefore, the chassis becomes very rigid.

As described in the above embodiment, the single cover plate 38 serves to prevent draw out of the plurality of gears 27 through 30 so that the number of parts to be used for the assembly of the

cassette type recording and/or reproducing apparatus and labor time required to assembly can remarkably be achieved.

The present invention is applicable to the other types of cassette type recording and/or reproducing apparatus such as cassette-type Video Tape Recorders (VTR's) as well as to the cassette tape recorder.

It will clearly be appreciated by those skilled in the art that the foregoing description is made in terms of the preferred embodiment.

Claims

1. A cassette type recording apparatus in which a cassette is mountable on a chassis for recording or playback, the chassis (8) having an upper surface (8a) on which said cassette is mountable, the apparatus comprising :
 - a pair of reel means (11, 12) provided with a pair of respective reel axles (31, 32); and
 - operation mode selecting means (17) for selectively transmitting the rotation to said reel means (11, 12) characterized in that
 - said upper surface defines a substantially planar un-recessed portion, and a recessed portion (36) in which are lodged, without projecting beyond the plane of the un-recessed portion, said reel pair means (11, 12) and the operation mode selecting means (17);
 - whereby a cassette can be operatively engaged with said reel axles (31, 32) with the cassette housing mounted in close contact with the un-recessed portion of the chassis without contacting the reel pair means (11, 12) or said operation mode selecting means (17).
2. The cassette tape recording apparatus according to claim 1, wherein said operation mode selecting means (17) comprises : (a) first drive means (27, 28) installed at an intermediate position between said reel means (11, 12) for actuating one of said reel means (11) to rotate in a recording mode; and (b) second drive means (29, 30) installed at an intermediate position between said reel means for actuating one of said reel means (11) to rotate in a fast forward mode.
3. The cassette type recording apparatus according to claim 2, wherein each of said reel means (11, 12) includes a reel gear (33, 34) on an outer periphery thereof and wherein said first drive means includes a first gear (27) means meshed with one reel gear (33) of said reel means (11) and said second drive means includes a second gear means (24) meshed with one reel gear (33) of said reel means (11).



placement of the gears 27 through 30 and achieve better service.

The change of rotation in the direction of the reel beds 11, 12 by means of the gear change mechanism 17 will be described below with reference to Fig. 3.

When the magnetic tape 3 is in the normal playback or record mode, the NR gear 27 is meshed with the NR gear 28 as denoted by a solid line and the NR drive gear 25 actuates the reel bed 11 to rotate in a counterclockwise direction as viewed from Fig. 3 via the NR gears 27, 28 and the reel bed gear 33. On the other hand, when the magnetic tape 3 is in a reverse playback or record mode, the NR gear 27 is meshed with the reel bed gear 34 as denoted by a dot-and-dash line and the NR drive gear 25 actuates the other reel bed 12 to rotate in a clockwise direction via the NR gear 27 and the reel bed gear 34. When the magnetic tape 3 is in the fast forward mode, the FR gears 29, 30 are respectively meshed with the FR drive gear 24 and reel bed gear 33 as denoted by solid lines, and the FR drive gear 24 actuates the one reel bed 11 to rotate in the counterclockwise direction via these gears 29, 30, 33 at a high speed. When the magnetic tape 3 is in the rewind mode, the FR gear 29 is meshed with the FR drive gear 24 and the reel bed gear 34 as denoted by the dot-and-dash line, so as to actuate the other reel bed 12 to rotate at a high speed via these gears 29, 34.

Since according to the present invention recesses are formed on the upper surface of the chassis and the pair of left and right reel beds and associated gears to actuate these reel beds are attached on the upper surface of the one recess in a direction from above the chassis, the cassette can be mounted on the upper surface of the chassis with the entire surface of the cassette brought in close contact with the upper surface of the chassis. Consequently, the entire cassette tape recorder of cassette-type recording and/or reproducing apparatus can remarkably be compacted. In addition, since the reel beds and gears can be assembled only on the upper side of the chassis from a direction from above the chassis, the assembly of the reel beds and gears can be carried out in a very simple manner as compared with the conventional structure in which the reel beds and gears are assembled separately on the upper and lower surfaces of the chassis. Therefore, an easy assembly operation can be achieved. The recesses formed on the upper surface of the chassis also provide a reinforcement structure for the chassis. Therefore, the chassis becomes very rigid.

As described in the above embodiment, the single cover plate 38 serves to prevent draw out of the plurality of gears 27 through 30 so that the number of parts to be used for the assembly of the

cassette type recording and/or reproducing apparatus and labor time required to assembly can remarkably be achieved.

The present invention is applicable to the other types of cassette type recording and/or reproducing apparatus such as cassette-type Video Tape Recorders (VTR's) as well as to the cassette tape recorder.

It will clearly be appreciated by those skilled in the art that the foregoing description is made in terms of the preferred embodiment.

Claims

1. A cassette type recording apparatus in which a cassette is mountable on a chassis for recording or playback, the chassis (6) having an upper surface (6a) on which said cassette is mountable, the apparatus comprising :
 - a pair of reel means (11, 12) provided with a pair of respective reel axles (31, 32); and
 - operation mode selecting means (17) for selectively transmitting the rotation to said reel means (11, 12) characterized in that
 - said upper surface defines a substantially planar un-recessed portion, and a recessed portion (36) in which are lodged, without projecting beyond the plane of the un-recessed portion, said reel pair means (11, 12) and the operation mode selecting means (17);
 - whereby a cassette can be operatively engaged with said reel axles (31, 32) with the cassette housing mounted in close contact with the un-recessed portion of the chassis without contacting the reel pair means (11, 12) or said operation mode selecting means (17).
2. The cassette tape recording apparatus according to claim 1, wherein said operation mode selecting means (17) comprises : (a) first drive means (27, 28) installed at an intermediate position between said reel means (11, 12) for actuating one of said reel means (11) to rotate in a recording mode; and (b) second drive means (29, 30) installed at an intermediate position between said reel means for actuating one of said reel means (11) to rotate in a fast forward mode.
3. The cassette type recording apparatus according to claim 2, wherein each of said reel means (11, 12) includes a reel gear (33, 34) on an outer periphery thereof and wherein said first drive means includes a first gear (27) means meshed with one reel gear (33) of said reel means (11) and said second drive means includes a second gear means (24) meshed with one reel gear (33) of said reel means (11).



4. The cassette type recording apparatus according to claim 1, which further comprises a cover plate (38) installed on said recessed portion of the chassis so as to cover said operation mode selecting means (17), while leaving said reel means (11, 12) uncovered.

5. The cassette type recording apparatus according to claim 3, which further comprises rotation actuation means (16) including first and second drive gears (24, 25) coaxially mounted on each other and which are capable of meshing with said first and second gear means (27, 28; 29, 30, 34).

6. The cassette type recording and reproducing apparatus according to claim 1, wherein said reel means (11, 12) are mounted in said recessed portion (36) for mating with a pair of reel hubs on the cassette.

7. The apparatus according to claim 1, wherein the recessed portion (36) is substantially shaped as an ellipse.

8. The apparatus according to claim 1, which further comprises another recess (37) on the surface of said recessed portion (36) on which a magnetic head (13) and pinch rollers (9, 10) are mounted.

9. The apparatus according to claim 6, wherein said reel beds (11, 12) and said operation mode selecting means (17) are mounted in said recessed portion (36) in a direction from above said chassis.

10. The apparatus according to claim 1, wherein said chassis means includes a plate (6) and said recessed portion is a recess (36) defined about at the center portion of an upper surface (6a) of said plate (6), said reel means (11, 12) and said operation mode selecting means (17) being mounted within said recess so that upper surfaces (27a, 28a, 29a, 30a) thereof are located at substantially the same level as, or lower than, an upper surface (6a) of said chassis means (6).

Patentansprüche

1. Kassettenrekorder mit einem Chassis (6), auf dem eine Kassette zur Aufnahme oder Wiedergabe angeordnet werden kann, wobei das Chassis (6) eine Oberseite (6a) aufweist, auf der die Kassette aufgelegt werden kann, mit zwei Spulenwickelrichtungen (11, 12) die mit zwei entsprechenden Spulenwellen

(31, 32) ausgestattet sind,

sowie mit einer Betriebsart-Wähleinrichtung (17) für die selektive Übertragung der Drehbewegung auf die Spulenwickelrichtungen (11, 12),

dadurch gekennzeichnet,

daß die Oberseite des Chassis (6) einen im wesentlichen ebenen vertiefungsfreien Abschnitt aufweist sowie einen vertieften Abschnitt (36), in welchem die beiden Spulenwickelrichtungen (11, 12) und die Betriebsart-Wähleinrichtung (17) so aufgenommen sind, daß sie nicht über die Ebene des vertiefungsfreien Abschnitts hinausragen,

so daß eine Kassette mit den genannten Spulenwellen wirkungsmäßig in Eingriff stehen kann, während der Kassettengehäuse in engem Kontakt mit dem vertiefungsfreien Abschnitt des Chassis angeordnet ist, ohne die beiden Spulenwickelrichtungen (11, 12) oder die Betriebsart-Wähleinrichtung (17) zu berühren.

2. Kassettenrekorder nach Anspruch 1, bei dem die Betriebsart-Wähleinrichtung (17) aufweist:

(a) in einer Zwischenposition zwischen den Spulenwickelrichtungen (11, 12) angeordnete erste Antriebsmittel (27, 28) für den Drehantrieb einer der Spulenwickelrichtungen (11) derart, daß diese sich im Aufnahmemodus dreht, und

(b) in einer Zwischenposition zwischen den Spulenwickelrichtungen (11, 12) angeordnete zweite Antriebsmittel (29, 30) für den Drehantrieb einer der Spulenwickelrichtungen (11) derart, daß diese sich im Schnellvorlauf-Modus dreht.

3. Kassettenrekorder nach Anspruch 2, bei dem jede der Spulenwickelrichtungen (11, 12) an ihrem Außenumfang ein Spulenzahnrad (33, 34) aufweist,

bei dem die ersten Antriebsmittel ein erstes Zahnrad (27) umfassen, das mit dem Spulenzahnrad (33) einer der Spulenwickelrichtungen (11) kämmt,

und bei dem die zweiten Antriebsmittel ein zweites Zahnrad (24) umfassen, das mit dem Spulenzahnrad (33) einer der Spulenwickelrichtungen (11) kämmt.

4. Kassettenrekorder nach Anspruch 1, bei dem ferner eine Abdeckplatte (38) vorgesehen ist, die in dem vertieften Abschnitt des Chassis so montiert ist, daß sie die Betriebsart-Wähleinrichtung (17) abdeckt, während die Spulenwickelrichtungen (11, 12) freigelassen werden.



5. Kassettenrekorder nach Anspruch 3, bei der ferner Drehantriebsmittel (16) vorgesehen sind mit einem ersten und einem zweiten Antriebszahnrad (24, 25), die koaxial zueinander angeordnet sind und mit der ersten und mit der zweiten Zahnradanordnung (27, 28, 29, 30, 34) in Eingriff bringbar sind.

6. Kassettenrekorder nach Anspruch 1, bei dem die Spulenwickelrichtungen (11, 12) in dem vertieften Abschnitt (16) so montiert sind, daß sie sich in zwei Spulennaben der Kassette einpassen.

7. Kassettenrekorder nach Anspruch 1, bei dem der vertiefte Abschnitt (36) im wesentlichen die Form einer Ellipse hat.

8. Kassettenrekorder nach Anspruch 1, bei dem auf derselben Fläche, in der sich der vertiefte Abschnitt (36) befindet, eine weitere Vertiefung (37) vorgesehen ist, in der ein Magnetkopf (13) und Andruckrollen (9, 10) montiert sind.

9. Kassettenrekorder nach Anspruch 6, bei dem die Spulenwickelpasen (11, 12) und die Betriebsart-Wähleinrichtung (17) in dem vertieften Abschnitt (36) von oberhalb des Chassis montiert werden.

10. Kassettenrekorder nach Anspruch 1, bei dem das Chassis eine Platte (6) umfaßt, und bei dem der vertiefte Abschnitt eine etwa im zentralen Bereich der Oberseite (6a) der Platte (6) ausgebildete Vertiefung (36) darstellt, wobei die Spulenwickelrichtungen (11, 12) und die Betriebsart-Wähleinrichtung (17) in dieser Vertiefung so montiert sind, daß ihre Oberseiten (27a, 28a, 29a, 30a) im wesentlichen in der gleichen Höhe wie die Oberseite des Chassis (6) oder tiefer liegen als diese.

Revendications

1. Appareil d'enregistrement du type à cassette dans lequel une cassette peut être montée sur un châssis pour enregistrement ou lecture, le châssis (6) ayant une surface supérieure (6a) sur laquelle ladite cassette peut être montée, l'appareil comportant :

une paire de moyens de bobine (11, 12) pourvue d'une paire d'axes de bobine respectifs (31, 32); et

des moyens de sélection de mode de fonctionnement (17) destinés à transmettre de manière sélective la rotation aux dits moyens de bobine (11, 12), caractérisé en ce que ladite surface supérieure définit une partie

non renforcée sensiblement plane, et une partie renforcée (36) dans laquelle sont logés, sans dépasser au-delà du plan de la partie non renforcée, lesdits moyens de bobine (11, 12) et les moyens de sélection de mode de fonctionnement (17);

une cassette pouvant être engagée de manière opérationnelle avec lesdits axes de bobine (31, 32) avec le boîtier de cassette monté en contact avec la partie non renforcée du châssis sans contact avec les moyens de bobine (11, 12) ou les moyens de sélection de mode de fonctionnement (17).

2. Appareil d'enregistrement du type à cassette selon la revendication 1, dans lequel lesdits moyens de sélection de mode de fonctionnement (17) comportent : (a) des premiers moyens d'entraînement (27, 28) installés dans une position intermédiaire entre lesdits moyens de bobine (11, 12) afin d'actionner un desdits moyens de bobine (11) de façon à tourner dans un mode d'enregistrement; et (b) des seconds moyens d'entraînement (29, 30) installés dans une position intermédiaire entre lesdits moyens de bobine afin d'actionner un desdits moyens de bobine (11) de façon à tourner dans un mode d'avance rapide.

3. Appareil d'enregistrement du type à cassette selon la revendication 2, dans lequel chacun desdits moyens de bobine (11, 12) comprend un pignon de bobine (33, 34) sur une périphérie extérieure de celui-ci et dans lequel lesdits premiers moyens d'entraînement comprennent un premier pignon (27) en prise avec un pignon de bobine (33) desdits moyens de bobine (11) et lesdits seconds moyens d'entraînement comprennent un deuxième pignon (24) en prise avec un pignon de bobine (33) desdits moyens de bobine (11).

4. Appareil d'enregistrement du type à cassette selon la revendication 1, qui comporte en outre une plaque de recouvrement (38) installée sur ladite partie renforcée du châssis de façon à recouvrir lesdits moyens de sélection de mode de fonctionnement (17), tout en laissant lesdits moyens de bobine (11, 12) non recouverts.

5. Appareil d'enregistrement du type à cassette selon la revendication 3, qui comporte en outre des moyens d'actionnement en rotation (16) comprenant des premier et deuxième pignons d'entraînement (24, 25) montés coaxialement l'un sur l'autre et qui sont capables de venir en prise avec lesdits premier et deuxième pignons (27, 28; 29, 30, 34).



6. Appareil d'enregistrement et de reproduction du type à cassette selon la revendication 1, dans lequel lesdits moyens de bobine (11, 12) sont montés dans ladite partie renforcée (36) afin de correspondre à une paire de moyeux de bobine sur la cassette. 5
7. Appareil selon la revendication 1, dans lequel la partie renforcée (36) est sensiblement en forme d'ellipse. 10
8. Appareil selon la revendication 1, qui comporte en outre un autre renforcement (37) sur la surface de ladite partie renforcée (36) sur lequel sont montés une tête magnétique (13) et des galets de pincement (9, 10). 15
9. Appareil selon la revendication 6, dans lequel lesdits supports de bobine (11, 12) et lesdits moyens de sélection de mode de fonctionnement (17) sont montés dans ladite partie renforcée (36) par le dessus dudit châssis. 20
10. Appareil selon la revendication 1, dans lequel lesdits moyens de châssis comprennent une plaque (6) et ladite partie renforcée est un renforcement (36) défini autour de la partie centrale d'une surface supérieure (6a) de ladite plaque (6), lesdits moyens de bobine (11, 12) et lesdits moyens de sélection de mode de fonctionnement (17) étant montés à l'intérieur dudit renforcement de sorte que des surfaces supérieures (27a, 28a, 29a, 30a) se trouvent sensiblement au même niveau ou plus bas qu'une surface supérieure (6a) dudit châssis (6). 25
30
35

40

45

50

55