

(19) World Intellectual Property Organization
International Bureau



G00002

(43) International Publication Date
20 June 2002 (20.06.2002)


PCT

(10) International Publication Number
WO 02/48019 A1

- (51) International Patent Classification⁷: **B67D 1/08** (71) Applicant (for all designated States except US):
HEINEKEN TECHNICAL SERVICES B.V. [NL/NL];
2e Weteringplantsoen 21, NL-1017 ZD Amsterdam (NL).
- (21) International Application Number: PCT/NL01/00847
- (22) International Filing Date: 21 November 2001 (21.11.2001) (72) Inventors; and
(75) Inventors/Applicants (for US only): **VAN DER KLAUW, Guido, Petrus, Johannes** [NL/NL]; Elzenhof 28, NL-2382 EV Zoeterwoude (NL). **BAX, Bart, Jan** [NL/NL]; Molenstraat 11a, NL-2513 BH The Hague (NL). **VAN DUUREN, Marius, Corstiaan** [NL/NL]; Limes 80, NL-3176 TE Poortugaal (NL). **PAAUWE, Arie-Maarten** [NL/NL]; Fuut 7, NL-2678 XK De Lier (NL).
- (25) Filing Language: Dutch
- (26) Publication Language: English
- (30) Priority Data: 1016687 23 November 2000 (23.11.2000) NL
- (61) Related by addition to earlier applications or grants:
CU Not furnished (ICA)
Filed on Not furnished
KP Not furnished (ICA)
Filed on Not furnished
- (74) Agent: **PRINS, A.W.**; Verenigde, Nieuwe Parklaan 97, NL-2587 BN The Hague (NL).
- (81) Designated States (national): AE, AG, AL (utility model), AM (provisional patent), AT (utility model), AU, AZ, BA, BB, BG (utility model), BR (utility model), BY

[Continued on next page]

(54) Title: TAPPING ROD



(57) Abstract: A tapping rod (2) with a beverage valve (16), a gas valve (14) cooperating therewith, and a collar (24), while in or on the collar a connecting device (26) is fitted, which connecting device comprises a pressure body (30) for opening the beverage valve (16) and the gas valve (14), wherein: the pressure body (30) comprise or defines at least one first beverage channel (50) for bringing, with the beverage valve in open position, the inner space of a keg, in particular a riser of the tapping rod, into fluid communication with a beverage dispensing line; the pressure body comprises or defines at least one gas channel (48) for bringing, with the gas valve in open position, the inner space of the keg into fluid communication with a gas supply line.



162162

WO 02/48019 A1

(utility model), BZ (utility model), CA, CH, CN (utility model), CO, CR (utility model), CU (inventor's certificate), CZ (utility model), DE (utility model), DK (utility model), DM, DZ, EC, EE (utility model), ES (utility model), FI (utility model), GB, GD, GE (utility model), GH (utility certificate), GM, HR (consensual patent), HU (utility model), ID, IL, IN, IS, JP (utility model), KE (utility model), KG (provisional patent), KP (inventor's certificate), KR (utility model), KZ (provisional patent), LC, LK, LR, LS (utility model), LT, LU, LV, MA, MD (utility model), MG, MK, MN, MW, MX (utility model), MZ, NO, NZ, OM, PH, PL (utility model), PT (utility model), RO, RU (utility model), SD, SE, SG, SI, SK (utility model), SL (utility model), TJ (utility model), TM (provisional patent), TR (utility model), TT (utility certificate), TZ, UA (utility model), UG (utility certificate), US,

UZ (provisional patent), VN (utility model), YU (petty patent), ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI utility model (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.