

SPECIFICATION

TITLE OF THE INVENTION

INTEGRALLY MOLDED SURFACE FASTENER

BACKGROUND OF THE INVENTION

1. Field of the Invention :


This invention relates to a surface fastener molded integrally of synthetic resin comprising a pair of upper and lower engaging members in which a plurality of rows of hook elements are integrally molded of synthetic resin on surfaces of respective engaging base plates and which adopt the same structures to facilitate the manufacture and the control of products and to ensure uniform distribution of engaging strength and durability.

2. Description of Prior Art :

The usual surface fastener is known as a so-called velvet type fastener comprising a pair of male and female tapes, wherein engaging element of male tape is formed as hook-like projection cutting a part of a loop in the fastener made of knitted cloth, or engaging element of male tape is formed as hook-like, mushroom-like, anchor-like projection in the fastener molded integrally of synthetic resin, and engaging element of female tape is mainly formed of a loop of a loop knitted cloth.

As stated above, the other engaging element or female element is formed of the loop of the loop knitted cloth to provide high engaging ability, however, the female element has weaker strength

This Sheet Has Been Replaced



and is too flexible. As a result, the female element has not been used as the industrial material since it does not meet the demand of positioning function and the durability.

The conventional surface fasteners made of synthetic resin are disclosed for examples in United States Patent No. 2499898, Japanese Utility Model Unexamined Publication No. S 52-71808, and No. H 2-127205. Each of these surface fasteners comprises a pair of upper and lower (or male and female) engaging members which are respectively molded integrally of synthetic resin, so that these fasteners provide excellent positioning function and high strength of engaging elements in comparison with using female members of loop knitted clothes.

However, the above-mentioned surface fasteners comprise male and female engaging elements of mainly mushroom-shape. When the engaging element has a mushroom shape, the construction of the engaging element provides engaging strength weaker than that of the engaging element of hook-shape. When engaging and disengaging of the male and female elements are repeated, the engaging strength falls off in a short time, so that the fastener will be hardly usable.

A precedent surface fastener comprising a pair of male and female engaging elements of the same hook shape is proposed by this inventor to solve the above-mentioned problems of the conventional surface fastener (Japanese Utility Application No. H 4-27364). This surface fastener is composed of first and second engaging members which are respectively provided with a plurality of rows of hook elements. The hook elements of first and second engaging members are oriented in the mutually opposite directions and the pitch of hook elements

This Sheet Has Been Replaced 1



on the first engaging member is set at twice as much of the pitch of hook elements of the second engaging member.

In order to engage hook elements of first engaging member surely with hook elements of second engaging member, it is required to guide and engage a hook element of the first engaging member between a pair of hook elements of the second engaging member in the row direction. During this guiding, hook elements of the first engaging member should be elastic-deformed separating mutually. In order to allow the elastic deformation in the mutually separating direction, it is considered to increase the pitch between hooks on both first and second engaging member, however the density of the hook elements becomes rough so that the engaging strength deteriorates inevitably. The above-mentioned prior surface fastener is developed on general investigation of the above-mentioned problems. Since hook elements are engaged with each other to provide remarkably high engaging strength and stable form and to prevent its strength from decreasing in repeated engagement, the surface fastener can be used as suitable industrial materials.

The above-mentioned integrally molded surface fastener of this construction has the above-mentioned excellent qualities. But on

further investigation of this construction, it is found to be unsatisfactory.

That is, this surface fastener is composed of first and second engaging members of different constructions, so that it is required to form respective engaging members independently in manufacturing of the surface fastener. It is moreover required to classify first and second engaging members completely for the stock control of products and to



confirm the combination and the number of combined first and second engaging members in ordering and receiving the order of products.

Further, since it is required to confirm that one is the first engaging member and the other is the second engaging member to attach both products, attaching work will be rather complicated.

SUMMARY OF THE INVENTION

It is therefore an object of this invention to provide a novel surface fastener comprising a pair of engaging members which are respectively integrally molded together with hook elements of the same structures to ensure high engaging strength and sufficient durability to be used repeatedly, to promote making efficiency, and to provide easy controlling and attaching works in the stock and shipment.

In order to accomplish the above-mentioned object, the surface fastener of this invention comprises a pair of upper (male) and lower (female) engaging members, in which a plurality of rows of hook elements are molded integrally with engaging base plates. The hook element is composed of a raised portion SP having a back face ba extending with a gentle slope from the surface of the engaging base plate and a front face fr extending straight from the engaging base plate, and a hook-like engaging portion FP extending forwardly from the end of the raised portion SP wherein the sectional area of the hook element is gradually increased from the end of the hook-like engaging portion FP to the root rt of the raised portion SP. Every row of hook elements of each engaging member is arranged to have a plurality of desired units including two hook elements and a spacing without a hook element in order. The

This Sheet Has Been Replaced



desired unit is repeated in every row to provide a desired hook element arrangement on each engaging member. Then, adjacent hook elements are mutually shifted by a predetermined pitch, and preferably, adjacent rows of hook elements of each engaging member are oriented in the mutually opposite directions.

Hook elements on upper and lower engaging base plates are formed as wavy shapes on the beach and are arranged oppositely as shown in FIG. 1 and FIG. 2. In engagement of fastener, two hook elements of the upper engaging member confront opposing two hook elements of the lower engaging member as being shifted by one pitch. One hook element is pressed onto mating two hook elements while the tip face of the hook-like engaging portion FP of one hook element is contacted with the tip face of the hook-like engaging portion FP of one of the two mating

hook elements and with the back face ba of the other mating hook element adjacent in row direction, to open these mating hook elements and is smoothly guided between the mating hook elements and engaged since the spacings are arranged between respective set of two hook elements to allow easy elastic deformation of the hook elements. And the mating hook elements are deformed in the same way, so that the confronting hook elements of both engaging members are engaged more surely.

Accordingly, all hook elements of the upper and lower engaging members are mutually engaged uniformly and smoothly to ensure desired engaging strength without being rough or rugged when engaged.

To disengage the engaged surface fastener, a disengaging force beyond a locking force of mating engaging members is applied to the



engaged surface fastener, so that the tip ends of the engaged hook-like engaging portion FP are twisted slightly sideward and simultaneously opened in the mutually separating direction to provide easy disengagement.

Further objects and advantages of the invention will be apparent from the detailed description hereinbelow set forth, together with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustrative view showing an engaging principle of integrally molded surface fastener according to this invention;

FIG. 2 is a plan view showing an arrangement of the integrally molded surface fastener of a first embodiment of this invention;

FIG. 3 is a side view showing every row of engaging elements of the surface fastener;

FIG. 4 is a plan view showing another arrangement of the integrally molded surface fastener of a second embodiment of this invention; and
FIG. 5 is a side view showing every row of engaging elements of the surface fastener of the second embodiment.

DETAILED DESCRIPTION

Firstly, the engaging principle of the surface fastener of this invention will be illustrated with reference to FIG. 1.

As stated above, a first feature of this invention is that upper and lower engaging members 2, 3 of the surface fastener 1 have the same structure.




FIG. 1

A second feature of this invention is that a hook element of specific shape is adopted as an engaging element. The shape of the hook element comprises, as well as the precedent proposed hook shape, a raised portion SP having a back face ba extending with a gentle slope from a flat base plates 21, 31 and a vertically standing front face fr, a hook-like engaging portion FP extending forwardly from the end of the raised portion SP, and ribs c formed on the both sides of the raised portion SP. Each hook element 4 has a sectional area which increases gradually from the tip end of the hook-like engaging portion FP to the root d of the raised portion SP. Accordingly, in this embodiment, the hook element 4 has the maximum area at the root d thereof. However, said area may be the same from the tip end of the hook-like engaging portion FP to the root d of the raised portion SP, or the front face fr may be formed to have an arcuate shape, so that this invention has various modifications. And the rib c is not an essential component of this invention.

A third feature of this invention is that two hook elements 4, 4 with a predetermined pitch and a spacing 5 which occupies the length of two pitches and wherein a hook element 4 is not disposed, are successively arranged in a row on a base plate, and this unit arrangement is successively repeated in the longitudinal direction.

The first feature is to form upper (male) and lower (female) engaging members as the same structure in the manufacture of a surface fastener molded integrally so as to provide easy forwarding and stocking work and so as to ensure easy attachment of the surface fastener.

The second feature is further to ensure easy molding, reliable

This Sheet Has Been Replaced



engaging and disengaging, and sufficient durability for repeated use.

The third feature is furthermore to provide reliable engaging of opposed upper and lower hook elements 4 by disposing spacing 5 which makes respective two hook elements 4, 4 to be easily elastic-deformed in the separable direction even if the positions of the opposed hook elements 4 do not mutually match in the row direction as shown in FIG. 1 (a) and (b) when the hook element 4 of the one engaging member is inserted between the two hook elements of the opposite engaging member.

This invention is characterized by the above-mentioned three features, however, a further aspect of this invention is now described.

The adjacent rows of hook elements which are arranged on respective surfaces of engaging base plate 21, 31, are oriented in the mutually reverse directions, whereby being prevented from having orientation in engaging strength in the row direction.

A surface fastener 1 of this invention is an integrally molded article of synthetic resin materials. As shown in both figures 1(a) and 1(b), the upper and lower engaging members 2 and 3 have the same structure respectively. A plurality of rows of the hook elements 4 are linearly arranged and protrude on the surfaces of the engaging base plates 21, 31 at the above-mentioned regular arrangement.

According to the first embodiment shown in FIG. 2 and FIG. 3, the hook elements 4 are repeatedly arranged by the same patterns of every six rows A, a, B, b, C, c. Three rows A, B, C of hook elements 4 are oriented in the same direction, and other three rows a, b, c of hook elements 4 are oriented in the reverse direction relative to

This Sheet Has Been Replaced



the rows A, B, C of hook elements 4. Of course, every row of hook elements 4 is repeatedly arranged in order at the above-mentioned unit arrangement including two hook elements 4 of predetermined hook pitch and a spacing 5 of two hook pitches. Every one pair of adjoining rows A, a ; B, b ; C, c of hook elements 4 are respectively shifted by one second ($1/2$) of one hook pitch, and an adjoining pair of rows c, A ; a, B ; b, C of hook elements 4 is arranged at positions shifted by three seconds ($3/2$) of one hook pitch in the same direction.

When one of two engaging members having the same structure is rotated by 180 degrees in the same plane and the surfaces having projected hook elements 4 are pressed toward each other, the hook elements 4 of the two engaging members are mutually engaged as follows;

When hook elements 4 having vertical cross sections of wavy shapes on the beach are arranged as mentioned above on upper and lower engaging base plates 21, 31, the hook elements 4 of the upper and lower engaging members 2 and 3 are engaged in the face-to-face relation as shown in FIG. 1 and FIG. 2. During engagement, a set of two hook elements 4, 4 of the upper engaging member 2 is shifted by one pitch relative to a set of two hook elements 4, 4 of the lower engaging member 3. While the tip face of the hook-like engaging portion FP of one hook element 4 is contacted with the tip face of the hook-like engaging portion FP of the one of the mating hook elements 4, 4 and with the back face ba of the other mating hook element 4 adjoined in the same row, the one hook element is pressed and is guided smoothly between the adjacent mating hook elements 4, 4 due to the spacing 5

This Sheet Has Been Replaced



to provide reliable engagement between the upper and lower engaging members.

Thus, the hook elements of the whole hook surfaces of the upper and lower engaging members 2, 3 are uniformly and smoothly engaged to ensure desired engaging strength without being rough.

In case of disengaging the engaged surface fastener 1, when a force stronger than the engaging force between both engaging members 2 and 3 is applied to both engaging members 2 and 3 in the separating direction, the tip ends of the engaged hook-like engaging portions FP are twisted slightly sideward and simultaneously opened in the separating direction to provide easy disengagement.

FIG. 4 shows an arrangement pattern of hook elements of a second embodiment of this invention. FIG. 5 is a side view showing every row of hook elements of the second embodiment.

According to this second embodiment, the arrangement of the hook elements 4 repeats the same patterns at every six rows A, D, B, D, C, D and the hook elements 4 of the D-rows are disposed always in the same pattern and with the hook being oriented in the same direction. The hook elements 4 of the other A, B, C-rows are arranged between the D-rows and oriented in the reverse direction relative to the D-rows. Two hook elements 4, 4 of three rows A, B, C are arranged as a whole at an obliquely figured textile. Of course, in this example, two hook elements 4, 4 of predetermined pitches respectively and a spacing 5 of two pitchlengths are repeatedly arranged in order as stated above.

When two engaging members of the above-mentioned structure are used as upper and lower surface fastener 1, it is possible to ensure



reliable engaging strength as well as the above-mentioned first embodiment and further to provide easy engaging and disengaging of the surface fastener. As stated hereinabove, in accordance with this invention, advantageous results can be obtained as follows;

Since a pair of engaging members of surface fastener have the same structures of integrally molded article, it is possible to ensure high engaging strength and sufficient durability for repeated use, to promote high manufacturing efficiency, and to provide easy controlling and attaching work in the stocking and shipment. Since the hook elements are rationally arranged on the engaging members, the surface fastener can be uniformly engaged with each other to provide uniform strength throughout the surfaces.

Since the hook element has a specific shape of a generally wavy cross section and the hook elements of the first and second engaging members are oriented in the reverse directions relative to each other, the engaging and disengaging operation of the surface fastener can be smoothly carried out without damaging the hook elements.

Accordingly, the surface fastener of this invention may be widely used in various fields and especially in the industrial material field which requires strong and uniform engagement.

This Sheet Has Been Replaced



CLAIM:

1. A surface fastener molded integrally of synthetic resin characterized by a pair of upper and lower engaging members (2, 3) which are respectively molded integrally and provided with a plurality of rows of hook elements on engaging base plates (21, 31), each of said

hook element (4) having a raised portion (SP) having a back face (ba) extending with a gentle slope from said engaging base plate and a front face (fr), and a hook-like engaging portion (FP) extending from the end of said raised portion (SP) forwardly, wherein two hook elements (4, 4) and a spacing (5) without a hook element which occupies a length of twice as long as a pitch of said hook elements (4,4)

are successively arranged in order in every row on each engaging member (2, 3) and adjacent rows of hook elements (4) are mutually shifted by predetermined pitches.

2. A surface fastener molded integrally of synthetic resin according to claim 1, ~~characterized~~ in that adjacent rows of hook elements (4) of each engaging member (2, 3) are oriented in mutually opposite directions.

3. A surface fastener molded integrally of synthetic resin according to claim 1, ~~characterized~~ in that the sectional area of said hook element (4) is increased gradually from the tip end of said hook-like engaging portion (FP) to the root (d) of said raised portion (SP).

