



- (51) **International Patent Classification:**
C09D 163/00 (2006.01) *C09D 183/04* (2006.01)
- (21) **International Application Number:**
PCT/US2013/029802
- (22) **International Filing Date:**
8 March 2013 (08.03.2013)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
13/415,925 9 March 2012 (09.03.2012) US
- (71) **Applicant:** PPG INDUSTRIES OHIO, INC. [US/US];
3800 West 143rd Street, Cleveland, Ohio 44111 (US).
- (72) **Inventor:** MOWRER, Norman R.; 6720 Bentley Trail,
Cumming, Georgia 30040 (US).
- (74) **Agents:** MEYERS, Diane R. et al.; PPG Industries, Inc.,
One PPG Place, 39th Floor, Pittsburgh, Pennsylvania
15272 (US).
- (81) **Designated States** (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,

ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.

- (84) **Designated States** (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii))*
- *as to the applicant's entitlement to claim the priority of the
earlier application (Rule 4.17(iii))*

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))*

(54) **Title:** EPOXY SILOXANE COATING COMPOSITIONS

(57) **Abstract:** Epoxy-polysiloxane based coating and flooring compositions exhibiting improved flexibility, and excellent weather-ability and corrosion resistance after curing are described. The epoxy-polysiloxane polymer coating composition may be prepared by combining a polysiloxane, an epoxide resin material and a cure system including a blend of compounds selected from a dialkoxy functional aminosilane, a trialkoxy functional aminosilane, and an amino functional polysiloxane resin, where the blend has an average alkoxy functionality value ranging from 2.0 to 2.8

