

PATENT SPECIFICATION**1,194,226**

DRAWINGS ATTACHED.

Date of Application (No. 29351/67) and filing Complete Specification: 26 June, 1967.

Application made in United States of America (No. 587,095) on 17 Oct., 1966.

Complete Specification Published: 10 June, 1970.



1,194,226

Index at acceptance:—G4 H(1A, 1B, 1D, 2A, 3X, 6A, 6B, 6D, 6E, 6F, 7B, 7R, 9X, 13D, 14A, 14B, 14X).

International Classification:—G 06 k 15/18.

COMPLETE SPECIFICATION.**Information Display Method and System.**

We, TEXAS INSTRUMENTS INCORPORATED, a Corporation organised according to the laws of the State of Delaware, United States of America, of 13500 North Central Expressway, Dallas, Texas, United States of America, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

This invention relates to a display system capable of large screen, real time projection and, more particularly, to the storage of information on a rotating system synchronised with a rotating light reflection system with modulation of light being dependent upon the stored information.

Large screen displays of alpha-numeric information have heretofore been carried out by selectively energizing a matrix of lamps or by selectively controlling the positions of movable elements of contrasting reflectivity where the elements are mounted in a planar matrix. Further, a television type raster scan laser display has previously been provided wherein fibre optics are employed.

Small screen cathode ray tube type digital data displays heretofore have solved the image storage problem either of two ways: (1) they store the x, y co-ordinates of each display point in a magnetic core "refresh" memory which is cycled fast enough to prevent flicker, or (2) they use an image storage tube. The magnetic core storage technique has limited the maximum display image complexity to a few thousand points. The storage tube approach has resulted in frequent erasures and loss of data or blurring of dynamic data.

The present invention is directed to an improved and yet simplified system which is capable of the display of alpha-numeric in-

formation as well as more generalised information.

The present invention provides a system for producing an information display in the form of an image having a plurality of co-ordinate positions, said system comprising: rotatable storage means for storing data defining the information to be displayed and having a predetermined storage address for each of the co-ordinate positions of the image, means for reproducing the data stored at each storage address of the storage means as the storage means is rotated, means for producing a light beam modulated in accordance with the reproduced data as the storage means is rotated, a multi-faceted mirror mounted for rotation and in predetermined relation with respect to said storage means, and said light beam-producing means being so arranged as to provide a modulated light beam incident upon the facets of the mirror as it is rotated and reflectable therefrom for scanning the light beam onto the corresponding co-ordinate positions of the image so as to produce a visible image on a display surface.

The image may be computer generated or otherwise digitally stored.

Simplified image storage and synchronized beam deflection are provided by a rotating magnetic memory element preferably attached to a multi-facet scanning mirror. Every image point is stored digitally in the magnetic element refresh memory eliminating restrictions on image complexity or format. The display image may also be interrogated by a computer for updating purposes so that it is not necessary for a computer to "remember" what is being displayed.

More particularly, a system for producing a display on a screen is provided wherein a

[Price 5s. 0d.]

storage drum is employed for storage of information to be displayed. A multi-faceted mirror is mounted for rotation in predetermined relation with respect to said drum, preferably mechanically locked to the drum. A plurality of sources produce light beams which are incident on said mirror in a selected pattern and are reflected to sweep the screen. Modulators individually modulate the beams in accordance with information signals from the drum. Preferably a plurality of laser sources of different color contribute to each beam.

A relatively low bit rate from the drum is matched to the bit rate required to continuously refresh the multi-point multi-color display by reading from magnetic drum tracks in parallel. The output from each track controls the intensity of an associated light beam. A multi-beam light modulator modulates light beams from one or more laser beams with one modulator being required for each primary color.

For a more complete understanding of the present invention and for further objects and advantages thereof, reference may now be had to the following description taken in conjunction with the accompanying drawings in which:

Figure 1 is a diagram prepared in block form illustrating one embodiment of the present invention;

Figure 2 is a diagram of an optical system for one embodiment of the invention;

Figure 3 is an isometric view of one form of light modulator;

Figure 4a illustrates a modified form of modulator;

Figure 4b illustrates another modulator that may be found to be suitable;

Figure 5 illustrates an installation involving the invention of Figure 1; and

Figure 6 illustrates the PCU unit 35 of Figure 1.

Referring now to Figure 1, this embodiment of the display system utilizes light beams from a laser source unit 10. The light beams are modulated in a modulator bank 11 and are reflected from a multi-faceted mirror 12.

Preferably, the mirror 12 will be mounted on a shaft 13 which is common to a multi-track memory drum 14. Information stored on drum 14 is employed for control of the modulators in bank 11 so that the display on screen 15 will be responsive to and representative of the information stored on drum 14.

The mirror 12 in practice will have a diameter of the order of the diameter of the drum 14. Each beam then scans the viewing screen 15 by action of the multi-faceted scanning mirror 12. In the embodiment shown in Figure 1, the mirror 12 has 32 facets uniformly disposed around the periphery thereof.

Each facet of the mirror 12 performs a horizontal scan of the screen 15 as it rotates with the drum 14. Vertical scanning is accomplished by mounting each facet tilted at a slightly different angle with respect to the axis of rotation.

While only one light beam is indicated in Figure 1, a greater number, of the order of sixteen, for example, will be employed with the 32-facet scanning mirror. In such case, the modulated beams give a vertical resolution of 512 lines which may be identical with the horizontal resolution. The use of multiple scanned beams of light allows beam deflection to be performed by a relatively simple low speed device such as the mirror 12. This also greatly reduces the bandwidth of information which must be handled by a single light beam.

Each light beam impinging the mirror 12 may comprise a composite of different colors from three different color sources for producing a full color display. In a simple alpha-numeric display, a single source would be required for each beam and only 7 beams and beam modulators would be required in parallel operation to portray alpha-numeric information. In the description which follows it is to be understood that a 512 by 512 data point display will be provided on screen 15 and that it will be produced in full color through the use of sixteen three-component beams operated in parallel. This requires forty-eight data tracks on drum 14 and a like number of modulators.

In Figure 1 the information to be displayed may be applied to the system from a tape input unit 30 by way of an interface module 31 and a channel selector 32. Alternatively, information to be displayed may be generated by a computer 33 which is coupled to selector 32 by way of an interface unit 34. The information is then fed to a programmed control unit (PCU) 35. Data from the PCU 35 is applied by way of encoders 36 and amplifiers 37 to read-write head 38 on drum 14. Read channels 39 lead from head 38 to read amplifiers 40 which drive decoders 41. A real select matrix 42 couples the decoder 41 back to the PCU 35.

Drum address channels 45 lead from PCU 35 to address decoder 46. Decoder 46 activates the head selector drivers 47 which are coupled to the input unit 48 of drum 14.

Channels, 49a, 50a and 51a lead from timing tracks 49, 50 and 51 on drum 14 to clock drivers 53. Drivers 53 energize sector counter 54 and thus control comparator 55. Comparator 55 is coupled by channels 56 to the address decoders 46. Decoders 46 are coupled by channels 57 to the read select matrix 42.

Information derived from drum 14 is applied from the output of the decoders 41

to modulator drivers 60 to control the intensities of the several light beams.

The generation and control of the production of one light beam 61 has been illustrated in Figure 1. A laser 62 such as the 6328 angstrom neon-helium gas laser having a red output beam 63 is employed in conjunction with a second laser 64 such as the 4880-5145 angstrom argon ion laser which has blue and green output beams 65. The red beam 63 is transmitted by way of a modulator 66 to a beam combiner 67. A beam divider 68 separates the green and blue beams from laser 64 and applies them to a green beam modulator 69 and a blue beam modulator 70, respectively. The green beam and the blue beam are then combined with the red beam in the beam combiner 67 to form the multi-color beam 61.

The modulators 66, 69 and 70 are controlled by the modulator drivers 60. The beam modulation of each of the three primary colors is thus independently controlled in dependence upon signal information stored on drum 14.

A suitable optical system for producing and modulating one beam is illustrated diagrammatically in Figure 2. Laser 62 is a neon-helium laser having an output beam 63 which passes through a beam splitter 63a so that one laser may be employed effectively to generate more than one beam. Part 63b of the beam 63 passes through a converging lens 63c and a collimating lens 63d to the red modulator 66. The modulated output beam passes through a polarizer 66a and thence to a combining prism 67. The beam from the prism 67 passes through a projection lens 68 to the scan mirror 12.

The laser 64 is an argon-ion laser having blue and green beams 65 which pass through a beam splitting mirror 65a. A portion of the light from the mirror 65a passes through a separation prism 65b. The green beam 65c from prism 65d is reflected from a mirror 65d through a converging lens 65e and a collimating lens 65f from which it passes to the green light modulator 69. The output beam from modulator 69 passes through a polarizer 69a and is reflected from mirrors 69b and 69c to the adding prism 67.

The blue light beam 65g passes through converging lens 65h and collimating lens 65i to the blue modulator 70. The output beam from modulator 70 passes through a polarizer 70a to the adding prism 67.

Beam modulator 66, in one form, is shown in Figure 3. It comprises a transverse field, Pockle's-effect unit constructed from a 45-degree Z-cut crystal of potassium dihydrogen phosphate (KDP). With such a 45-degree Z-cut orientation, a transverse electric field is applied perpendicular to the direction of light propagation utilizing the α_{63} electro-

optic coefficient of KDP for amplitude modulation.

Modulator 66 is formed of two crystals 100 and 101 of KDP. The crystals 100 and 101 are identical in orientation. They are positioned between the collimating lens 63d and the polarizer 66a. Crystal 100 is provided with electrodes 102 and 103. Crystal 101 is provided with electrodes 104 and 105. The crystals 100 and 101 are arranged in tandem with their optical axes orthogonal. Their optical axes are normal to the respective electrode crystal faces. Preferably, index matching oil junctions are used between the crystals 100 and 101, lens 63d and polarizer 66a.

Driver amplifier 107, included in the modulator driver 60 of Figure 1, is coupled by way of conductor 109 to electrode 101 and by way of conductor 110 to electrode 102. Driver 107 is also connected by way of conductor 111 to electrode 105 and by way of conductor 112 to electrode 104. By this means, the modulator may be controlled in dependence upon information stored on drum 14. Modulator 66 is a polarization modulator with linearly polarized light from laser 62 passing down the longitudinal axes of the crystals 100 and 101. Under the influence of the variable electric field applied along the optical axes of the crystals 100 and 101, a variable amount of elliptical polarization is produced in the emerging light beam. The polarizer 66a oriented perpendicular to the polarization of the incident beam 63b converts the varying elliptically polarized light into linearly polarized amplitude modulated light. By selecting the initial bias voltage on the modulator, almost no light will be allowed to pass. As is understood in the art, the bias voltage is determined by the polarizer quality, by the degree of light beam collimation and by the electro-optic crystal alignment. An applied signal can allow from 0 to nearly 100 per cent of the incident light to pass. As further understood, the voltage required to vary the modulator output from a minimum to a maximum is commonly referred to as the half-wave retardation voltage. This corresponds to the voltage required to change the relative phase shift between the orthogonal polarized components into which the incident light is decomposed upon entering the crystal by one-half wave length.

Figure 4a illustrates one form of a multi-beam light modulator. The modulator includes a beam splitter 130 which is a plate of plane, parallel-polished fused silica. The plate 130 is cemented to a prism 131. The surface between plate 130 and prism 131 is coated with a low-loss multi-layer dielectric coating whose transmission is graded from 6% at the lower end 130a to 50% at the upper end 130b. The incident beam 132

enters the plate 130 at the lower end. The plurality of beams are incident on the face of plate 130 opposite the coating at an angle greater than the critical angle and thus they undergo total internal reflection. Because of the gradation in coating, beams of equal intensity pass through prism 131 with uniform spacing.

A single electro-optic crystal 133 is positioned to receive the light beams from the prism 131. Spaced electrodes on opposite sides of the crystal 133 are then employed to vary the electrical polarization of the light passing therethrough. Thus the beams emerging from an analyzer 134 may be of intensity dependent upon the modulator voltages applied to the crystal 133. The prism 131 serves to eliminate glass-to-air reflection losses and protects the dielectric coating on the plate 130. Multi-layer coatings of the type above described are well known and routinely prepared by manufacturing companies.

It should be appreciated that other types of beam splitters and modulators may be employed.

An alternative means of modulating an array of light beams involves the use of an ultrasonic light modulator of the type shown in Figure 4b. This device consists of a piezoelectric transducer 135, which generates a travelling ultrasonic stress wave under the control of an applied electrical signal. This stress wave changes the index of refraction, through the stress-optic effect, of a light modulating medium such as water or fused silica body 136 mounted with one end in contact with an absorber 137. The resulting effect is, for a sinusoidal drive signal, similar to that produced by a ruled diffraction grating. Light will be diffracted from an incident light beam 138 at an angle determined by the light modulation drive frequency. Diffracted beam 138b and undiffracted beam 138a will thus be controlled by the acoustic waves through element 136. Diffracted light intensity is determined by drive level. Sixteen modulated light beams such as beam 138b may thus be produced by driving the ultrasonic light modulator with 16 different carrier frequencies each of whose amplitude is controlled to be proportional to the desired beam intensity. Typically 16 carrier frequencies might be equally disposed between 50 and 82 megacycles each modulated at a maximum rate of 1 megacycle.

In Figure 5 an installation involving the present invention is illustrated wherein the mirror 12 is mounted on the storage drum shaft 13, both of which are mounted in a cabinet 140.

The optics of the system are indicated generally as including a director 141 for the blue and green beams and director 142 for

the red beam. The blue and green beams are reflected by mirrors 143 and 144 as to pass through modulators 145 and 146 with the red beam passing through the modulator 147. Mirrors 148 direct the beams through prisms 149 and lens 150 to a mirror 151. Light is reflected from the mirror 151 on to the mirror 12 which causes the beam to sweep through the aperture defined by an opening 152 in housing 140.

The PCU 35 preferably is a high-speed logical unit operating on and from information contained in its core memory. With proper programming, the PCU 35 is capable of (1) handling the transfer and routing of information between a keyboard, control switches, input/output registers, and the display drum, (2) performing locally such tasks as character and vector generation, (3) examining and logically modifying data or control action, (4) reconstituting compressed data, and (5) performing the general "house-keeping" duties for the display system. All directions for operations may be stored in the memory. The PCU 35 can perform any task that can be logically described to it within the limitation of time and memory capacity. All programs need not be stored in the PCU 35 at one time. New programs can be read from storage as they are needed.

In Figure 6, the PCU 35 has been shown in its relationship to the input units 30 and 33 and to the line 35a leading to encoder, line 42a leading to the read select matrix 42 and line 45 leading to both the address decoder 46 and the comparator 55.

The PCU has a first input register 200 through which input information may be supplied from a trackball input unit 203. The trackball unit 203 may convert coordinate information into a form which may be employed in the PCU 35.

The trackball is a manual input device. To the operator, it appears as the top of a small ball protruding through the top of the panel. The ball may be rolled by finger pressure in any direction proportionally controlling the position of a "locator symbol" on the screen. This input combines sensitivity with actions that are natural to an operator.

The locator symbol, which is controlled by the trackball, is provided to indicate a particular point of interest on the display screen and also to have the address at this point available for computational purposes. A suitable locator symbol circuit operates from the trackball and when activated sends its signals directly to the modulator drivers so that no PCU time is wasted in positioning the locator. When required, the PCU can read the trackball address and thus indicate precisely where the locator symbol is positioned on the screen.

A second input register 201 is employed in connection with a keyboard and function

switch unit 204. The switch 32 and registers 200 and 201 are connected to an A register 202. The A register 202 is connected to an output register 205 which leads to the interface modules 31 and 34. The A register also has an output leading to a zero detector 206 and a further output channel leading to a status display register 207 which actuates lamp drivers 208 on an inquiry console 209.

10 A fourth output from the A register 202 extends to the input section of a memory indicated generally by the reference numeral 210. The memory 210 has an input section, a core memory section 216, an output section and an address unit. The output section of the memory 210 is coupled to the A register 202 and to the channel 35a and to an instruction register 220. Instruction register 220 has (i) an operation code (OP) section, 15 (ii) a repetition counter (C) section which indicates how many times a green command is to be repeated, (iii) an indirect address bit (I) register, and (iv) an address (Q) register for the addresses of the commands.

25 An operation decoder 211 is connected between instruction register 220 and sequencer 214. A repetition comparator 213 is connected between instruction register 220 and sequencer 214 with a repetition counter 212 being connected between sequencer 214 and comparator 213. The sequencer 214 feeds the output control line 45. An N register 215 is connected to unit 220. The address section of the memory 214 is connected both 35 to the register 215 and to the instruction register 220. The line 42a is connected both to the address section of memory 210 and to its input section.

40 Thus, Figure 6 shows the internal configuration and data flow of the PCU 35. It will be seen that there are three input registers 200, 201 and 202. Registers 200 and 201 are standard registers which read information from the input units 203 and 204. 45 The output register 205 sends 24 bits to the interface unit leading to the computer 33. All input/output transfers and arithmetic logical operation take place in the A register 202.

50 The PCU 35 may also load information into a status display register 207. The logical condition of the bit positions in this register is indicated by lights on the inquiry console 209. This permits the program in the PCU 35 to communicate with the console operator without disrupting the displayed image. Status lamps on console 209 may light permanently marked indicators indicating conditions such as "Display 55 Ready", "Keyboard Ready" and "Operator Intervention Required". Other positions light lamps over the function keys and indicate which of the functions are available at a given point in a program.

65 The instruction the PCU 35 will perform

is determined by the contents clocked from the memory into Instruction register 220. The first six bits of the command word form an operational code which is decoded by the operation decoder 211. The next five bits 70 form the repetition count. If these bits are not already zero, the order will be repeated, toggling repetition counter 212 for each repetition until coincidence is detected by the repetition comparator 213. The last 12 75 bits form the address portion of the command. The 13th bit is the indirect address bit. If this bit is non-zero when a command is clocked into the Instruction register, the memory cycle will be repeated, although only 80 the last 13 bits of the new word will be loaded into the Instruction register. If the 13th bit is still non-zero, this cycle will repeat until a non-direct address is found.

85 All control signals go to a sequencer block 214 which furnishes timing and operational signals to all units. The N register 215 holds the address of the next command to be clocked into the Instruction register. On normal commands it acts as a counter and 90 is toggled by one. On branch commands it is reset from the address portion of the Instruction register.

95 The contents of the A, Instruction and N registers may be displayed with lamps on the front panel of the PCU 35 for troubleshooting and diagnostic purposes. The regular clock may be switched off from counter 54, Figure 1, and the program may be stepped 100 by a manual pushbutton. A series of switches (not shown) may permit insertion of data directly into the A, Instruction and N registers.

105 The PCU memory 210 may be of the type commercially available. Preferably it will be a 4096-word by 24-bit core storage unit with a 2-microsecond full-cycle time and a 1-microsecond half-cycle time. The memory preferably will contain data protection features which prevent data in the cores from 110 being destroyed by power failures or normal turn-off. During the execution of core-to-drum and drum-to-core transfers, the memory operates under the control of the memory drum unit. In this mode the memory 115 uses the half-cycle mode.

The clock rate for the PCU is 1.06 megacycle derived from the drum bit clock.

120 Thus there is provided a large-screen, real-time, projection display system which may be employed for on-line operation with a digital computer. In a preferred embodiment, the display is generated by modulating and deflecting coherent light from a red and a blue-green laser to produce a 512- by 512- 125 point, multicolor display.

All 262,144 points of an image are digitally stored and reproduced 60 times a second to generate a flicker-free display image. The scanning used ensures linearity and color 130

registration. The resolution can readily be increased to 1024 by 1024 points if a particular application warrants. The update rate is limited only by the information transfer rate of the associated computer and can exceed one million bits per second.

A general purpose digital computer is rendered compatible through programmed control unit PCU 35 which connects to the computer input/output channel in the same manner as other input/output equipments. The control unit performs character generation, vector generation, formatting, buffering, and other display-computer intercommunication functions.

A 1-watt r.f.-pumped, ring-discharge argon laser may be used as the blue and green light source. The wavelengths of the 400-milliwatt blue line and the 250-milliwatt green line in the argon laser are 4880 angstroms and 5145 angstroms, respectively. An r.f.-pumped krypton ion laser optimized for 6470 angstrom operation may be used as the red source. A 1-watt krypton laser may produce 330 milliwatts at 6470 angstroms. Alternatively, four Spectra-Physics Model 125, 6328-angstrom neon-helium lasers may be used for the red primary source. Their combined output power is in excess of 300 milliwatts. The greater optical complexity inherent in this arrangement would be partially compensated by the higher visibility factor of the 6328-angstrom line and the proven reliability of the neon-helium laser.

Having described the invention in connection with certain specific embodiments thereof, it is to be understood that further modifications may now suggest themselves to those skilled in the art and it is intended to cover such modifications as fall within the scope of the appended claims.

WHAT WE CLAIM IS:—

1. A system for producing an information display in the form of an image having a plurality of co-ordinate positions, said system comprising: rotatable storage means for storing data defining the information to be displayed and having a predetermined storage address for each of the co-ordinate positions of the image, means for reproducing the data stored at each storage address of the storage means as the storage means is rotated, means for producing a light beam modulated in accordance with the reproduced data as the storage means is rotated, a multi-faceted mirror mounted for rotation and in predetermined relation with respect to said storage means, and said light beam-producing means being so arranged as to provide a modulated light beam incident upon the facets of the mirror as it is rotated and reflectable therefrom for scanning the light beam onto the corresponding co-ordinate positions of the image so as to produce a visible image on a display surface.

2. A system as set forth in Claim 1, wherein said multi-faceted mirror is rigidly connected to the storage means for rotation therewith.

3. A system as set forth in Claim 2, wherein said light beam-producing means is effective to produce a plurality of individually modulated light beams which are incident upon the facets of the mirror as it is rotated and are reflectable therefrom to sweep different paths on the display surface, and the modulation of each light beam is dependent upon the data reproduced from the storage means.

4. A system as set forth in Claim 3, wherein successive facets on said mirror are tilted at different angles relative to the axis of rotation therefor so as to cause the same set of modulated light beams to sweep the display surface along spaced paths determined by said angles.

5. A system as set forth in any preceding claim, wherein said light-beam producing means comprises at least one laser and at least one light modulator.

6. A system as set forth in Claim 5, wherein said at least one light modulator comprises a separate optical body, and a variable electric field applying means associated with said separate optical body for controlling the light transmission there-through, the energization and de-energization of said variable electric field applying means being dependent upon the data reproduced from the storage means.

7. A system as set forth in Claim 6, wherein said separate optical body includes a pair of electro-optic crystals of the same orientation, said crystals being arranged in end-to-end relationship with their longitudinal optical axes in alignment; and said variable electric field applying means includes a first pair of electrodes respectively mounted on opposite sides of one of said crystals, and a second pair of electrodes respectively mounted on opposite sides of the other crystal so as to be offset from the first pair of electrodes; and said variable electric field applying means controls the light transmission through said pair of electro-optic crystals by varying the polarization of the light beam incident to said pair of electro-optic crystals as the light beam travels within said separate optical body.

8. A system as set forth in Claim 6, wherein said separate optical body includes a planar beam splitter, a prism having an inclined surface disposed adjacent to and parallel to said beam splitter, a dielectric coating between said beam splitter and the inclined surface of said prism, said dielectric coating securing said beam splitter to said prism and having a variable light transmission factor which progressively increases

registration. The resolution can readily be increased to 1024 by 1024 points if a particular application warrants. The update rate is limited only by the information transfer rate of the associated computer and can exceed one million bits per second.

A general purpose digital computer is rendered compatible through programmed control unit PCU 35 which connects to the computer input/output channel in the same manner as other input/output equipments. The control unit performs character generation, vector generation, formatting, buffering, and other display-computer intercommunication functions.

A 1-watt r.f.-pumped, ring-discharge argon laser may be used as the blue and green light source. The wavelengths of the 400-milliwatt blue line and the 250-milliwatt green line in the argon laser are 4880 angstroms and 5145 angstroms, respectively. An r.f.-pumped krypton ion laser optimized for 6470 angstrom operation may be used as the red source. A 1-watt krypton laser may produce 330 milliwatts at 6470 angstroms. Alternatively, four Spectra-Physics Model 125, 6328-angstrom neon-helium lasers may be used for the red primary source. Their combined output power is in excess of 300 milliwatts. The greater optical complexity inherent in this arrangement would be partially compensated by the higher visibility factor of the 6328-angstrom line and the proven reliability of the neon-helium laser.

Having described the invention in connection with certain specific embodiments thereof, it is to be understood that further modifications may now suggest themselves to those skilled in the art and it is intended to cover such modifications as fall within the scope of the appended claims.

WHAT WE CLAIM IS:—

1. A system for producing an information display in the form of an image having a plurality of co-ordinate positions, said system comprising: rotatable storage means for storing data defining the information to be displayed and having a predetermined storage address for each of the co-ordinate positions of the image, means for reproducing the data stored at each storage address of the storage means as the storage means is rotated, means for producing a light beam modulated in accordance with the reproduced data as the storage means is rotated, a multi-faceted mirror mounted for rotation and in predetermined relation with respect to said storage means, and said light beam-producing means being so arranged as to provide a modulated light beam incident upon the facets of the mirror as it is rotated and reflectable therefrom for scanning the light beam onto the corresponding co-ordinate positions of the image so as to produce a visible image on a display surface.

2. A system as set forth in Claim 1, wherein said multi-faceted mirror is rigidly connected to the storage means for rotation therewith.

3. A system as set forth in Claim 2, wherein said light beam-producing means is effective to produce a plurality of individually modulated light beams which are incident upon the facets of the mirror as it is rotated and are reflectable therefrom to sweep different paths on the display surface, and the modulation of each light beam is dependent upon the data reproduced from the storage means.

4. A system as set forth in Claim 3, wherein successive facets on said mirror are tilted at different angles relative to the axis of rotation therefor so as to cause the same set of modulated light beams to sweep the display surface along spaced paths determined by said angles.

5. A system as set forth in any preceding claim, wherein said light-beam producing means comprises at least one laser and at least one light modulator.

6. A system as set forth in Claim 5, wherein said at least one light modulator comprises a separate optical body, and a variable electric field applying means associated with said separate optical body for controlling the light transmission there-through, the energization and de-energization of said variable electric field applying means being dependent upon the data reproduced from the storage means.

7. A system as set forth in Claim 6, wherein said separate optical body includes a pair of electro-optic crystals of the same orientation, said crystals being arranged in end-to-end relationship with their longitudinal optical axes in alignment; and said variable electric field applying means includes a first pair of electrodes respectively mounted on opposite sides of one of said crystals, and a second pair of electrodes respectively mounted on opposite sides of the other crystal so as to be offset from the first pair of electrodes; and said variable electric field applying means controls the light transmission through said pair of electro-optic crystals by varying the polarization of the light beam incident to said pair of electro-optic crystals as the light beam travels within said separate optical body.

8. A system as set forth in Claim 6, wherein said separate optical body includes a planar beam splitter, a prism having an inclined surface disposed adjacent to and parallel to said beam splitter, a dielectric coating between said beam splitter and the inclined surface of said prism, said dielectric coating securing said beam splitter to said prism and having a variable light transmission factor which progressively increases



along the extent of the dielectric coating such that a light beam incident on said beam splitter is transformed into a plurality of light means of equal intensity and passing through said prism with uniform spacing therebetween, and an electro-optical crystal positioned for receiving the light beams from said prism; and said variable electric field applying means is operably connected to said electro-optic crystal for controlling the light transmission therethrough by varying the polarization of the light beams.

9. A system as set forth in Claim 5, wherein said at least one light modulator comprises an acoustic light modulator including a light modulating medium, means for inducing ultra-sonic stress waves in the medium in response to an electrical signal, and means for modulating the electrical signal to provide a plurality of frequencies, the amplitude of each frequency being individually modulated in accordance with different data reproduced from the storage means.

10. A system as set forth in any preceding claim, wherein said light-beam producing means comprises a plurality of lasers of different colours and a plurality of light modulators corresponding thereto so as to form each said modulated light beam by a combination of separate laser beams of different colours, and the data reproduced from the storage means is related to the different colours of the lasers.

11. A system as set forth in any preceding claim, wherein said storage means comprises a rotatable drum.

12. A method of displaying an image from information data stored on a storage means which provides a memory element, said method comprising: rotating the memory element and a multi-faceted mirror rigidly connected thereto, retrieving information data stored on said memory element, modulating at least one light beam in dependence upon and in synchronism with the retrieved information data, and directing the modulated light beam onto said mirror for reflection to a display surface.

13. A method as set forth in Claim 12, wherein the information data retrieved from said memory element includes a plurality of information signals such that a plurality of light beams are modulated thereby, and directing the plurality of modulated light beams onto said mirror.

14. A method as set forth in Claim 12, wherein the information data retrieved from said memory element includes colour dependent information signals stored on different locations of said memory element such that at least two colour components of said light beam are separately modulated by the colour dependent information signals.

15. A system for producing an informa-

tion display in the form of an image having a plurality of co-ordinate positions, said system comprising: rotatable storage means for storing data defining the information to be displayed and having a predetermined storage address for each of the co-ordinate positions of the image; means for reproducing the data stored at each storage address of the storage means as the storage means is rotated; means for producing a light beam modulated in accordance with the reproduced data as the storage means is rotated; said light beam-producing means comprising a light modulating medium, means for directing a coherent light beam through the light modulating medium, means for generating ultrasonic waves in the medium in response to an electrical signal, and means for applying to the ultrasonic wave-generating means an electrical signal representative of the reproduced data as the storage means is rotated and the amplitude of which is modulated so that the light beam directed through the light modulating medium will have an intensity corresponding to the amplitude of the electrical signal; a multi-faceted mirror mounted for rotation and in predetermined relation with respect to said storage means; and said light beam-producing means being so arranged as to provide a modulated light beam incident upon the facets of the mirror as it is rotated and reflectable therefrom for scanning the light beam onto the corresponding co-ordinate positions of the image so as to produce a visible image on a display surface.

16. A system as set forth in Claim 15, wherein said electrical signal-applying means is effective for applying an electrical signal to the ultrasonic wave-generating means that has a plurality of frequencies each individually amplitude modulated so as to divide the light beam into a corresponding plurality of independently modulated light beams.

17. A system as set forth in Claim 16, wherein at least two light modulating mediums are provided, said coherent light beam-directing means being effective to direct a coherent light beam through each of the light modulating mediums, the coherent light beams being of different colours, said ultrasonic wave-generating means being effective to generate ultrasonic waves in each of the mediums in response to electrical signals, said electrical signal-applying means being effective to apply an electrical signal to each of the ultrasonic wave-generating means that have a corresponding plurality of frequencies each individually amplitude modulated so as to divide each of the light beams into a corresponding plurality of independently modulated light beams, and means for combining corresponding light beams split from each of the coherent light



beams to produce a corresponding plurality of multi-coloured light beams.

18. A method as set forth in either of Claims 13 or 14, wherein the light beam modulation is accomplished by passing a coherent light beam through an acoustic modulating medium, and inducing ultrasonic stress waves in the modulating medium disposed at an angle to the light beam wherein the ultrasonic stress waves have a plurality of different wavelengths each individually amplitude modulated so that the light beam will be divided into a separate light beam for each discrete frequency with the intensity of the separate light beams being dependent upon the amplitude of the corresponding ultrasonic stress waves.

19. A system for producing an information display substantially as herein described with reference to Figure 1 of the accompanying drawings or modified as described with reference to any of Figures 2 to 6 of the accompanying drawings.

20. A method of displaying an image substantially as herein described with reference to Figure 1 either alone or taken with any other figure of the accompanying drawings.

ABEL & EMRAY,
Chartered Patent Agents,
Northumberland House,
303-306 High Holborn,
London, W.C.1.

Printed for Her Majesty's Stationery Office by Burgess & Son (Abingdon), Ltd.—1970.
Published at The Patent Office, 25 Southampton Buildings, London, WC2A 1AY,
from which copies may be obtained.

