(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
27 February 2003 (27.02.2003)

PCT

(10) International Publication Number
WO 2003/017341 A3

(51) International Patent Classification[7]: H01L 21/02, 21/288

(21) International Application Number: PCT/US2002/026191

(22) International Filing Date: 15 August 2002 (15.08.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/932,236 16 August 2001 (16.08.2001) US

(71) Applicant *(for all designated States except US)*: MICRON TECHNOLOGY, INC. [US/US]; 8000 South Federal Way, Boise, WA 83716 (US).

(72) Inventor: YANG, Haining; 501 Maloney Road, Apt.H14, Poughkeepsie, NY 12603 (US).

(74) Agent: LATWESEN, David, G.; Wells, St. John, 601 West First Avenue, Suite 1300, Spokane, WA 99208 (US).


(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*
— *with amended claims*

[Continued on next page]

(54) Title: METHODS OF FORMING METAL-COMPRISING MATERIALS AND CAPACITOR ELECTRODES; AND CAPACITOR CONSTRUCTIONS



(57) Abstract: The invention includes a method of forming a metal-comprising mass for a semiconductor construction. A semiconductor substrate is provided, and a metallo-organic precursor is provided proximate the substrate. The precursor is exposed to a reducing atmosphere to release metal from the precursor, and subsequently the released metal is deposited over the semiconductor substrate. The invention also includes capacitor constructions, and methods of forming capacitor constructions.

WO 2003/017341 A3

(88) Date of publication of the international search report: 19 February 2004

Date of publication of the amended claims: 15 April 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.