

Cosmetic and dermatological oxygen carrier system

The invention relates to an oxygen carrier system suitable to apply gaseous oxygen in cosmetic and dermatologic forms of application onto the skin.

5

It is known to use perfluorocarbon compounds as oxygen carriers in cosmetic forms of application. WO 94/0098 describes asymmetric lamellar aggregates consisting of perfluorocarbons and phospholipids with a phosphatidylcholin content of at least 30 percent in weight. In modern cosmetic formulations, silicone oils are increasingly
10 being used in order to accomplish certain advantageous properties, such as light weight, no stickiness, richness. Such formulations can, however, incorporate only small concentrations of the known oxygen carrier systems which do not exceed 5 percent in weight because a higher percentage will then lead to stability problems in the formulations. Lower concentrations of such known oxygen carrier systems
15 require correspondingly lower oxygen content in the formulation and correspondingly in respect of the effectiveness for the skin.

Another disadvantage of the known systems is the fact that relatively high concentrations of the carrier system of 10 to 40 percent in weight are required in
20 silicone oil-free formulations in order to ensure oxygen release quantities over longer periods of time of 8 to 40 weeks.

An object of the invention is the provision of a new oxygen carrier system that can be used at will in silicone oil-containing cosmetic or dermatologic formulations
25 without stability problems for the formulation and where its effectiveness is markedly increased as far as oxygen release is concerned.

In accordance with the invention, the cosmetic and dermatologic oxygen carrier system is characterised in that it consists of a liquid perfluorinated or partially
30 fluorinated hydrocarbon or hydrocarbon mixture with a moiety of 0.1 - 10 percent in weight, a liquid silicon polymer or silicone polymer mixture with a moiety of 10 - 85

percent in weight and an oil or water base with a moiety of 5 - 25 percent in weight, with all weight percentages being related to the total weight of the carrier system.

In an advantageous embodiment, the oxygen carrier system is loaded with an initial
5 oxygen content of 150 - 950 mbar O₂

Preferably, the initial oxygen content is 250 to 400 mbar O₂ already in the presence of moieties of 2 - 5 percent in weight of perfluorinated hydrocarbon.

10 In another advantageous embodiment, the oxygen carrier system is loaded four weeks after the loading with an oxygen content of 5 - 40 percent by volume of the initial oxygen content, preferably 15 - 25 percent by volume.

The oxygen loading of a system according to the invention is in general done as
15 follows: after the preparation of the carrier system, oxygen gas with a partial pressure of 180 to 600 mbar is bubbled through the entire composition while stirring with 200 - 400 r.p.m. and at ambient temperature (18 - 25° C) over a period of 15 to 100 minutes, preferably 20 to 40 minutes followed by its incorporation into the respective cosmetic or dermatologic formulation.

20

While with the known oxygen carrier systems with phospholipids or with sphingomyelins (Cerasomes) which belong to the phospholipids, after an initial drop of the O₂ concentration after 24 h by about 30 - 50 %, in the weeks thereafter a continuous drop of the concentration down to an equilibrium with the oxygen of
25 the air occurs after 26 weeks, the carrier systems according to the invention maintain, after the 24 h drop by 30 to 50 %, the O₂ concentration in the weeks thereafter over an essentially longer period of time and with higher moieties of 25 to 40 %. After 8 weeks, measurements resulted in O₂ concentrations of 5 to 15 % for the carrier system of the invention when compared to the initial content which then
30 continue to remain approximately constant.

This means that an increased oxygen offer with a comparable concentration of the perfluorocarbons is available for a longer period of time and can thus be supplied to the skin cells. It is known that it is specifically the surface area of the skin up to a depth of 0.4 mm where most of the oxygen is absorbed not via the blood but via the
5 oxygen of the air.

Advantageously, the oxygen carrier system of the invention can in addition contain tocopherol or a tocopherol derivative with a moiety of 0,01 - 1.5 percent by weight, related to the overall weight of the carrier system. Thus, a further improvement of
10 the effectiveness in respect of the stability of the system in silicone oil-containing cosmetic formulations is accomplished. Suitable tocopherol derivatives are for instance tocopheryl acetate, tocopheryl palmitate, tocopheryl succinate, tocopheryl propionate, tocopheryl oleate, tocopheryl linolate or tocopheryl sorbate which may also be used as a mixture of the same or with tocopherol.

15 The oxygen carrier system according to the invention may surprisingly be incorporated in cosmetic or dermatologic formulations, in particular in those with silicone oils or silicone polymers, in concentration of up to 40 percent in weight without impairing the stability of the cosmetic or dermatologic formulation.

20 The liquid silicone polymer in the carrier system according to the invention on an oil base is advantageously a cyclic silicone oil or a mixture of cyclic silicone oils with other silicone oils.

The liquid silicone polymer in a carrier system on a water base is advantageously
25 an aqueous suspension of silicone elastomers in combination with a methylpolysiloxane.

Particularly preferred are organosiliconeoxide polymers, such as methylpolysiloxanes as, for instance, BAR-SIL® 2001 (from Barnet, Englewood
30 Cliffs, USA) or fluorosilicones which contain at least one trifluoroalkyl group in monomers, such as Gransil®, e.g. Gransil® FLD-55 (from Grant Ind., Inc., Elmwood Park, USA). The preferred silicone elastomer emulsion is the

dimethicone/vinyldimethicone cross polymer (and) CI2-12 Pareth-12 with a viscosity of about 5,000 mPa.s.

Other suitable silicone polymers are polydimethylcyclsiloxanes (e.g. 5 cyclopentasiloxanes), mixtures of cyclopentasiloxanes with cyclohexasiloxanes (e.g. DC® 345), mixtures of cyclopentasiloxanes with high viscous Dimethiconol (e.g. DC® 1501), mixtures of polydimethylsiloxanes with viscosities ranging from 0,65 – 60,000 mm²s (e.g. DC® 200 Fluids).

10 The oil base of the carrier system is advantageously a vegetable oil, an ester, such as dicaprylyl carbonate (Cetiol CC), isodecyl neopentanoate (e.g. DUV VCI 10), neopentyl glycol diheptanoate (e.g. Lexfeel® 7), trimethylolpropane tricaprylate/tricaprate (e.g. Lexfeel®21) or a mixture thereof. Synthetic oils are particularly preferred.

15

The oxygen carrier is preferably a perfluorinated hydrocarbon, in particular perfluodecalin, F-butyltetrahydro-furane, perfluorotributylamine, perfluoromethylcyclopentane, perfluoro-1,3-dimethylcyclohexane, perfluoroperhydro-benzyl-decaline, perfluoroperhydrophenanthrene, perfluorooctyl-bromide, Bis-fluoro- 20 (butyl)ethene or C₆-C₉-perfluoroalkanes.

The moiety of the perfluorinated hydrocarbon or hydrocarbon mixture is preferably in the range of 1.5 to 6 percent by weight, related to the overall weight of the carrier system.

25

The moiety of the silicone polymer in the carrier system is advantageously 15 to 35 percent by weight.

Moreover, the carrier system contains advantageously at least one gelling agent 30 with a viscosity in the range of 120,000 Pa.s to 300,000 Pa.s, in particular in a carrier system on an oil base.

Particularly preferred are gels, such as mineral oil-free gels with hydrogenated polyisobuten as base, for instance Versagel® (from Penreco, Dickinson, USA) or organic, modified montmorillonites, such as bentone gel.

- 5 The use of thickening agents in the carrier system is also preferred.

The following are preferably used as water thickening agents: xanthan gum, ammonium acryloyldimethyl laurate/VP copolymer, ammonium acryloyldimethyl laurate/Beheneth-25, methylacrylate copolymer (e.g. Aristoflex® AVC or HMB),
 10 homo- and copolymers of acrylic acid and polyalkenylpolyethers (e.g. Carbopol®-thickening agent) with a high molecular weight.

Different benton gels are suited as oil thickening agents, for instance C12-15 Alkyl Benzoate(and)Stearalkonium Hectorite (and)Propylene Carbonate, Isodecane(and) Disteardimonium Hectorite(and)Propylene Carbonate, Cyclopenta-
 15 siloxane(and)Disteardimonium Hectorite(and)SD Alcohol which can also be used in mixtures.

Thickening agents, such as hydrogenated polyisobuten (e.g. Versagel® ME 1600) with a viscosity of about 143,000 mPa.s (Brookfield Viscosimeter, 25 °C, Spindle T-
 20 C, 5 r.p.m.) can also be used.

The oxygen carrier system according to the invention can be incorporated into any cosmetic or dermatologic formulation, for instance such a topical formulation can have the form of a cream, a lotion, a self-tanning agent, a sun protection
 25 formulation for use before, during and after exposure to sun, of a mask, a gel, a spray.

In a cosmetic formulation, the moiety of the oxygen carrier system may amount to 1 to 25 percent by weight in relation to the overall weight of the formulation,
 30 preferably to 6 to 10 %.

In a dermatologic formulation, the moiety of the oxygen carrier system may amount to 3 to 40 percent by weight, preferably to 6 to 35 % in relation to the overall weight of the formulation.

- 5 The cosmetic or dermatologic formulations into which the oxygen carrier system of the invention can be incorporated may contain common inactive ingredients, carriers and active ingredients, e.g. inactive ingredients and carriers, such as water, preservatives, colorants, pigments with a colouring effect, thickening agents, fragrances, monovalent and polyvalent alcohols, esters, electrolytes, gelling agents, 10 polar and non-polar oils, polymers, copolymers, emulsifiers, waxes , stabilisers.

Particularly suited are formulations which contain moieties of silicone oils > 5 %, preferably 6 - 70 %, in particular 6 - 35 %. The oxygen carrier system of the invention can be incorporated into such formulations without the risk of an instability of the 15 formulation. All common silicone oils qualify as silicone oils in the formulation.

Cosmetic active ingredients include, inter alia, inorganic and organic sunscreen agents, free radical scavengers, moisturisers, vitamins, enzymes, active ingredients from plants, antioxidants, antiphlogistic natural active ingredients, disintegration products from yeasts or plant substances, manufactured by means of an ultrasound 20 disintegration method pursuant to WO 94/13783, kaolin as well as kaolin modified with SiO₂ pursuant to WO 94/17588 and dihydroxyacetone. Another active ingredient for such a formulation with the oxygen carrier system according to the invention is a special preparation with a high factor of protection against free radicals which contains a product produced from the bark of Quebracho blanco by extraction and 25 subsequent enzymatic hydrolysis which contains at least 90 percent by weight of proanthocyanidine oligomers and not more than 10 percent by weight of gallic acid, in micro-capsules, and a silkworm extract produced by extraction which extract contains the peptide cecropine, amino acids and a vitamin mixture and a non-ionic, cationic or anionic hydrogel or mixture of hydrogels, and one or more phospholipids, and water. 30 This special preparation can also contain superoxide dismutase and cyclodextrine.

Furthermore, the invention relates to a method for preparation of a cosmetic oxygen carrier system characterised in that at least one part of a liquid silicone polymer is incorporated while stirring at 20 to 100 r.p.m. into at least one part of the oil or water base at a temperature ranging from 18 to 26 °C, adding in addition while stirring at 10 to 80 r.p.m. a liquid perfluorinated or partially perfluorinated hydrocarbon or a hydrocarbon mixture stirring it for 3 to 30 minutes, adding, if appropriate, further constituents or remaining moieties of the mentioned constituents while stirring at 40 to 150 r.p.m. and homogenising the mixture for 20 to 150 seconds at maximally 3,000 r.p.m.

10

Advantageously, the carrier system is loaded in the procedure with gaseous oxygen up to a partial pressure of 150 to 950 mbar O₂.

The invention relates moreover to the use of a cosmetic oxygen carrier system consisting of a liquid perfluorinated or partially fluorinated hydrocarbon or hydrocarbon mixture with a moiety of 0.1 - 10 percent in weight, a liquid silicon polymer with a moiety of 35 - 85 percent in weight, an oil or water base with a moiety of 5 - 25 percent in weight, and, if appropriate, a tocopherol or tocopherol derivative with a moiety of 0.01 to 1.5 percent by weight with all weight percentages being related to the total weight of the carrier system in topical formulations, in particular in those with silicone oil contents of 5 to 25 percent by weight, related to the overall weight of the topical formulation.

The topical formulation advantageously has the form of a cream, a lotion, a self-bronzing agent, a sun protection formulation for use before, during and after exposure to sun, of a mask, a gel, a spray.

The invention will be described below in greater details by way of examples. All data are in percent by weight unless stated otherwise.

Example 1 Preparation of the oxygen carrier system (SiOx I) on an aqueous base

Composition in percent by weight:

	(A) Dimethicone	20
5	(B) Trifluoromethyl C1-4 Alkyl Dimethicone	35
	(C) Perfluorodecalin	5
	(D) Tocopherol	0.4
	(E) Dimethicone/Vinyldimethicone Crosspolymer	
	(and) Cl2-14 Pareth-12	25
10	(F) Water	14.6

While stirring, the relevant amount of (B) is slowly added to (A) at ambient temperature, and stirring is continued for a few minutes. While stirring, (C) is added, and stirring is continued for about 20 to 30 minutes. Thereafter, (E) is successively added while also slowly stirring, then (D) and finally (F). The mixture is homogenised at about 2,500 r.p.m. for 50 seconds. All steps were carried out at about 21 - 25°C.

Thereafter, gaseous oxygen with 400 mbar is bubbled through the mixture for 30 minutes while stirring at 280 r.p.m. The obtained oxygen contents are measured with an Oxi 3000 (WTW GmbH, Weilheim, Germany).

Example 2 Preparation of the oxygen carrier system (SiOx II) on an oil base

Composition in percent by weight:

	(A) Cyclopentasiloxane	10
25	(B) Dicapryl Carbonate	10
	(C) Perfluorodecalin	2
	(D) Tocopherol	0.5
	(E) Hydrogenated Polyisobutene (and)	
	Ethylene/Propylene/Styrene Copolymer (and)	
30	Butylene/-Ethylene/-Styrene Copolymer	
	(Versagel® ME1600)	40
	(F) Bentone Gel	37.5

While stirring at 400 to 500 r.p.m., the relevant amount of (B) is slowly added to (A), and stirring is continued for a few minutes. (C) is added at 900 to 1,000 r.p.m., and

stirring is continued for about 20 to 30 minutes. Thereafter, (D) is added, then (E) and finally (F). The mixture is homogenised at about 2,700 to 2,800 r.p.m. for 40 seconds. All steps were carried out at about 20 - 24°C.

- 5 Thereafter, gaseous oxygen with 450 mbar is bubbled through the mixture for 35 minutes while stirring at 300 r.p.m.

Example 3 Body Foam (Mousse) I

	Water	up to 100 %
10	Squalane	0.01
	Butylene Glycol	2.0
	Glycerol	2.0
	PPG-5 Ceteth-20	1.0
	Decyl Glucoside	3.0
15	SiOx I of Example 1; 160 mbar O ₂	6.0

The constituents were mixed at ambient temperature in the order as stated above and then transferred into a pump bottle with a special pump for mousse.

20 **Example 4 Body Foam (Mousse) II**

The same constituents as in Example 3 and in addition 6 % of silicone oil were processed in the same way into a body foam.

25 **Example 5 Self-Tanning Agent I O/W**

Phase A

	Water	up to 100 %
30	Dihydroxyacetone	5.0
	Glycerol	2.0

Phase B

	Dimethicone	6.0
	Dimethicone/Vinyldimethicone Crosspolymer	

(and) Cl2-14 Pareth-12	25
Cyclopentasiloxane Dimethiconol	2.0
Octyldodecyl Stearoyl Stearate	2.5

Phase C

5 Preservative	0.5
Fragrance	0.5

Phase D

SiOx II of Example 2; 210 mbar O ₂	10
---	----

10 **Example 6 Self-tanning agent II (example for comparison)**

Phase A

Water	up to 100
Dihydroxyacetone	5.0
Glycerol	2.0

15

Phase B

Dimethicone	6.0
Dimethicone/Vinyldimethicone Crosspolymer	
(and) Cl2-14 Pareth-12	5

20 Cetiole CC	20
Octyldodecyl Stearoyl Stearate	2.5

Phase C

Preservative	0.5
--------------	-----

25 Fragrance	0.5
--------------	-----

Asymmetric lamellar aggregates pursuant to

WO94/0098 5

When attempting to increase the content of the aggregates mentioned last as oxygen carriers (180 mbar O₂) to more than 5 %, the formulation became unstable

30 and a phase separation occurred.

Example 7 Body gel

Water	up to 100
35 Glycerol	5
Dimethicone	15

	Propylene Glycol	10
	Carbomere	2
	Triethanolamine	2
	Preservative	0.5
5	Fragrance	0.2
	SiOx I of example 1; 254 mbar O ₂	20

The constituents were successively added to each other and homogeneously mixed by stirring.

10

Example 8 Skin fluid serum

	Water	up to 100
	Glycerol	3
15	Propylene Glycol	5
	Carbomere	1
	Silicone	10
	Triethanolamine	1
	Preservative	0.5
20	Fragrance	0.2
	SiOx I of example 2; 215 mbar O ₂	15

The constituents were successively added to each other and homogeneously mixed by stirring.

25

Claims

1. Cosmetic and dermatologic oxygen carrier system which comprises a liquid perfluorinated or partially fluorinated hydrocarbon or hydrocarbon mixture with a moiety of 0.1 - 10 % by weight, a liquid silicone polymer or silicone polymer mixture with a moiety of 10 - 85% by weight and an oil or water base with a moiety of 5 – 25% by weight, with all weight percentages being related to the total weight of the carrier system.
2. Oxygen carrier system according to Claim 1, wherein the carrier system is loaded with an initial oxygen content of 150 - 950 mbar O₂.
3. Oxygen carrier system according to Claim 1, wherein the carrier system is loaded four weeks after the loading with an oxygen content of 25 – 40% by volume of the initial oxygen content.
4. Oxygen carrier system according to Claim 1, wherein it contains tocopherol or a tocopherol derivative with a moiety of 0.01 - 1.5% by weight.
5. Oxygen carrier system according to Claim 1, wherein the moiety of the liquid silicone polymer ranges from 15 – 35% by weight.
6. Oxygen carrier system according to Claim 1, wherein the carrier system contains at least one gelling or thickening agent or mixture thereof.
7. Oxygen carrier system according to Claim 1, wherein the oil base of the carrier system is a vegetable oil, an ester or a mixture thereof.
8. Oxygen carrier system according to Claim 1, wherein in that the oxygen carrier is perfluorodecaline.

9. Oxygen carrier system according to Claim 1, wherein the moiety of the perfluorinated hydrocarbon or hydrocarbon mixture ranges from 1.5 – 6% by weight.

5 10. Oxygen carrier system according to Claim 1, wherein the carrier system is present in a cosmetic formulation with a moiety of 1 to 25% by weight, related to the overall weight of the formulation, preferably with a moiety of 6 to 10%.

11. Oxygen carrier system according to Claim 1, wherein the carrier system is
10 present in a cosmetic formulation which comprises a silicone oil with a moiety of 3 to 70%, related to the overall weight of the formulation, preferably with a moiety of 6 to 35%.

12. Oxygen carrier system according to Claim 1, wherein the carrier system is
15 present in a dermatologic formulation with a moiety of 3 to 40% by weight, preferably 6 to 35% by weight, related to the overall weight of the formulation.

13. Procedure for the preparation of a cosmetic oxygen carrier system according to claim 1 characterised in that at least one part of a liquid silicone polymer is
20 incorporated while stirring at 20 to 100 r.p.m. into at least one part of the oil or water base at a temperature ranging from 18 to 26 °C, adding in addition while stirring at 10 to 80 r.p.m. a liquid perfluorinated or partially perfluorinated hydrocarbon or a hydrocarbon mixture and stirring it for 3 to 30 minutes, adding, optionally, further constituents for the carrier system or remaining moieties of the mentioned
25 constituents while stirring at 40 to 150 r.p.m. and homogenising the mixture for 20 to 150 seconds at maximally 3,000 r.p.m. 10 to 40 minutes.

14. Procedure according to Claim 13 wherein the carrier system is treated with gaseous oxygen with a partial pressure of 180 to 600 mbar.

15. Use of a cosmetic oxygen carrier system comprising a liquid perfluorinated or partially perfluorinated hydrocarbon or hydrocarbon mixture with a moiety of 0.1 - 10 percent by weight, a liquid silicone polymer with a moiety of 35 – 85% by weight, an oil or water base with a moiety of 5 – 25% by weight, all weight percentages
5 being related to the overall weight of the carrier system, in topical formulations, in particular in those with silicone oil contents of 5 – 25% by weight, related to the overall weight of the topical formulation.
16. Use according to Claim 15 wherein the topical formulation has the form of a
10 cream, a lotion, a self-tanning agent, a sun protection formulation for use before, during and after the exposure to sun, of a mask, a gel, a spray.