

[060623U1-QF-168APP1 WO TW TH CL]

COMMUNICATIONS METHOD AND APPARATUS USING PHYSICAL ATTACHMENT POINT
IDENTIFIERS

FIELD OF THE INVENTION

[0001] This invention relates to communications system and, more particularly, to methods and apparatus for routing messages based on physical layer information in wireless, e.g., cellular, communications networks.

BACKGROUND OF INVENTION

[0002] The Open System Interconnection (OSI) reference model is useful in explaining various communications and routing operations. The OSI reference model includes 7 layers with the application layer being the top most layer and the Physical Layer being the lowest layer. The physical layer is the layer which deals with actual physical connections and attributes of the physical connections in the system. Above the physical layer is a Data Link layer, sometimes referred to as the link layer. The link layer (Layer 2 in the OSI model) is sometimes described as a technology specific transfer layer. Above the link layer is the network layer (OSI Layer 3) where network routing and relaying is supported. The network layer is sometimes referred to as the packet layer. It is at the network layer that routing of messages/packets through the network is performed, e.g., on one or more paths. Different addressing may be used for directing messages and signals at the different levels. For example, a network address such as an IP address, maybe used for routing messages/packets at the network layer level. MAC addresses maybe use for controlling routing of messages at the data link layer level. At the lowest level of the OSI model, the physical level, one or more physical identifiers have a relationship to an actual physical attribute or characteristic of a source or destination device. An understanding of the different communication layers and different addressing techniques used for each of the layers will facilitate an understanding of the present invention.

[0003] Communications systems frequently include a plurality of network nodes which are coupled to access nodes through which end nodes, e.g., mobile devices, are coupled to the network. Network nodes may be arranged in a hierarchy. End nodes

typically communicate with access nodes directly through connections that have been established with said access nodes. Such systems usually rely on the existence of a bidirectional communications link between an access node and an end node to support two way communications between an end node and an access node. Note that in such systems the end node normally does not know the network layer address of a target destination access node but may be cognizant of information that it can receive over broadcast channels which typically can include physical layer identifier that are normally not used in such systems for message routing. This approach results in handoff delays and packet loss when the end node is only able to maintain one single bidirectional communications link at the time.

[0004] It should then be appreciated that there is a need for methods and apparatus that allows an end node that has no current uplink communications link to a target access node to communicate with said target access node via another access node with which the end node has a current uplink communications link even when said end node does not know the network address of the target access node..

[0005] In some systems end nodes are capable of maintaining multiple bidirectional communications links with different access nodes at the same time. However, such systems typically require the end nodes to send messages intended for a specific access node, with which an end node has a connection, over the link that is directly connected to that specific access node. This approach, in some cases, is inefficient since links, especially when they are wireless links, tend to fluctuate in terms of quality (e.g., delay and loss characteristics). As a result the link to the target destination access node may not be the best link available to the end node at the time a message to said target destination access node needs to be sent. Typically this limitation is overcome by resorting to network layer communications that can be routed via multiple hops due to the use of network layer addresses (e.g., IP addresses). This approach of using network layer addresses is also inefficient especially when the messaging has to do with link layer specific functions, since network layer messages tend to be much larger than link layer messages in some systems. Such inefficient signaling is not well suited for communications over resource restricted air links.

[0006] It should then be appreciated that there is also a need for a method that allows an end node to send messages over any of its available wireless communications links independently of the access node the message is intended. It would be desirable if such messages could be sent, at least in some embodiments, without having to resort to inefficient network layer communications, e.g., communications involving the use of network layer addresses, such as IP layer addresses, for routing information to the destination access node.

SUMMARY OF THE INVENTION

[0007] The present invention is directed to methods and apparatus for routing messages between an end node and an access node via another access node. The methods and apparatus of the invention support the use of physical layer identification information when identifying a remote, e.g., adjacent, access node as a message destination. Thus, when a connection identifier based on one or more physical layer identifiers is available to a wireless terminal, e.g., from one or more downlink signals received from a destination access node, the wireless terminal can use the connection identifier corresponding to the destination node to route a message via an access node with which it has an established uplink connection.. Such connection identifier information can be used even when other addressing information, e.g., network layer address information, associated with the destination access node, may not be available to the wireless terminal.

[0008] Various novel features are directed to end node methods of receiving broadcast information from an access node and determining a physical attachment point identifier, for example a connection identifier corresponding to the access node. Other features are directed to the sending of signals to one access node including a connection identifier corresponding to another access node. The connection identifier is based on one or more pieces of information which provide information relating to a physical layer attachment point. Thus, in accordance with the invention physical layer information can be used as a connection identifier.

[0009] In accordance with the invention, access nodes store information mapping connection identifiers which are based on physical layer identification information to one or more higher level addresses. The mapping information is stored in the access nodes. Access nodes include mapping information for connections identifiers corresponding to physical layer attachment points which are local to the access node in addition to connection identifiers corresponding to physical layer attachment points of other, e.g., neighboring, access nodes. This allows routing between physically adjacent base stations to be performed based on physical layer connection identifiers without the need for a wireless terminal to transmit a link layer or network layer address over the air when sending a message which is to be delivered to a neighboring access node via an existing connection with an access node currently serving the wireless terminal.

[0010] Thus various features of the invention are directed to end node methods of receiving signals from access nodes indicating an identifier to access node address resolution failure and causing said end node to send neighbor notification messages for the establishment of new access node neighbors.

[0011] While some features are directed to wireless terminal methods and apparatus, as well as to novel messages of the invention stored in a wireless terminal, other features are directed to novel access node methods and apparatus. The invention is also directed to data storage devices, e.g., memory devices, which store one or more of the novel messages of the present invention.

[0012] While various embodiments have been discussed in the summary above, it should be appreciated that not necessarily all embodiments include the same features and some of the features described above are not necessary but can be desirable in some embodiments. Numerous additional features, embodiments and benefits of the present invention are discussed in the detailed description which follows.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] Fig. 1 illustrates a network diagram of an exemplary communications system implemented in accordance with the present invention.

[0014] Fig. 2 illustrates an exemplary end node implemented in accordance with the present invention.

[0015] Fig. 3 illustrates an exemplary access node implemented in accordance with the present invention.

[0016] Fig. 4 illustrates an exemplary Connection Identifier implemented according to this invention.

[0017] Fig. 5 illustrates an exemplary message using the Connection Identifier of Fig 4 implemented according to this invention.

[0018] Fig. 6 illustrates exemplary signaling performed in accordance with the present invention when an end node maintains a bidirectional connection to one access node and wants to communicate with another access node.

[0019] Fig. 7 illustrates exemplary signaling performed in accordance with the present invention when an end node maintains bidirectional connections with multiple access nodes.

[0020] Fig. 8 illustrates exemplary signaling performed in accordance with the present invention when an end node triggers a neighbor discovery process between two access nodes.

[0021] Fig. 9 illustrates an exemplary PID to higher level address resolution table which may be used for mapping between (to/from) PIDs and corresponding higher level addresses.

DETAILED DESCRIPTION:

[0022] The methods and apparatus of the present invention for routing messages based on physical layer information, e.g., physical layer indentifiers, which can be used to support communications sessions with one or more end nodes, e.g., mobile devices. The method and apparatus of the invention can be used with a wide range of communications systems. For example the invention can be used with systems which support mobile communications devices such as notebook computers equipped with modems, PDAs, and a wide variety of other devices which support wireless interfaces in the interests of device mobility.

[0023] Fig. 1 illustrates an exemplary communication system 100 implemented in accordance with the present invention, e.g., a cellular communication network, which comprises a plurality of nodes interconnected by communications links. Exemplary communications system 100 is, e.g., a multiple access spread spectrum orthogonal frequency division multiplexing (OFDM) wireless communications system. Nodes in the exemplary communication system 100 exchange information using signals, e.g., messages, based on communication protocols, e.g., the Internet Protocol (IP). The communications links of the system 100 may be implemented, for example, using wires, fiber optic cables, and/or wireless communications techniques. The exemplary communication system 100 includes a plurality of end nodes 144, 146, 144', 146', 144'', 146'', which access the communication system via a plurality of access nodes 140, 140', 140''. The end nodes 144, 146, 144', 146', 144'', 146'' may be, e.g., wireless communication devices or terminals, and the access nodes 140, 140', 140'' may be, e.g., base stations. The base stations may be implemeneted as wireless access routers. The exemplary communication system 100 also includes a number of other nodes 104, 106, 110, and 112, used to provide interconnectivity or to provide specific services or functions. Specifically, the exemplary communication system 100 includes a Server 104, used to support transfer and storage of state pertaining to end nodes. The Server node 104 may be, for example, an AAA server, or it may be a Context Transfer Server, or it may be a server including both AAA server functionality and Context Transfer server functionality.

[0024] The Fig. 1 exemplary system 100 depicts a network 102 that includes the Server 104 and the node 106, which are connected to an intermediate network node 110 by a corresponding network link 105 and 107, respectively. The intermediate network node 110 in the network 102 also provides interconnectivity to network nodes that are external from the perspective of the network 102 via network link 111. Network link 111 is connected to another intermediate network node 112, which provides further connectivity to a plurality of access nodes 140, 140', 140'' via network links 141, 141', 141'', respectively.

[0025] Each access node 140, 140', 140'' is depicted as providing connectivity to a plurality of N end nodes (144, 146), (144', 146'), (144'', 146''), respectively, via corresponding access links (145, 147), (145', 147'), (145'', 147''), respectively. In the exemplary communication system 100, each access node 140, 140', 140'' is depicted as using wireless technology, e.g., wireless access links, to provide access. A radio coverage area, e.g., communications cell, 148, 148', 148'' of each access node 140, 140', 140'', respectively, is illustrated as a circle surrounding the corresponding access node.

[0026] The exemplary communication system 100 is subsequently used as a basis for the description of various embodiments of the invention. Alternative embodiments of the invention include various network topologies, where the number and type of network nodes, the number and type of access nodes, the number and type of end nodes, the number and type of Servers and other Agents, the number and type of links, and the interconnectivity between nodes may differ from that of the exemplary communication system 100 depicted in Fig. 1.

[0027] In various embodiments of the present invention some of the functional entities depicted in Fig. 1 may be omitted or combined. The location or placement of these functional entities in the network may also be varied.

[0028] Fig. 2 provides a detailed illustration of an exemplary end node 200, e.g., wireless terminal such as a mobile node, implemented in accordance with the present

invention. The exemplary end node 200, depicted in Fig. 2, is a detailed representation of an apparatus that may be used as any one of the end nodes 144, 146, 144', 146', 144'', 146'', depicted in Fig. 1. In the Fig. 2 embodiment, the end node 200 includes a processor 204, a wireless communication interface 230, a user input/output interface 240 and memory 210 coupled together by bus 206. Accordingly, via bus 206 the various components of the end node 200 can exchange information, signals and data. The components 204, 206, 210, 230, 240 of the end node 200 are located inside a housing 202.

[0029] The wireless communication interface 230 provides a mechanism by which the internal components of the end node 200 can send and receive signals to/from external devices and network nodes, e.g., access nodes. The wireless communication interface 230 includes, e.g., a receiver module 232 with a corresponding receiving antenna 236 and a transmitter module 234 with a corresponding transmitting antenna 238 used for coupling the end node 200 to other network nodes, e.g., via wireless communications channels. In some embodiments, the transmitter module 234 includes an orthogonal frequency division multiplexing (OFDM) transmitter.

[0030] The exemplary end node 200 also includes a user input device 242, e.g., keypad, and a user output device 244, e.g., display, which are coupled to bus 206 via the user input/output interface 240. Thus, user input/output devices 242, 244 can exchange information, signals and data with other components of the end node 200 via user input/output interface 240 and bus 206. The user input/output interface 240 and associated devices 242, 244 provide a mechanism by which a user can operate the end node 200 to accomplish various tasks. In particular, the user input device 242 and user output device 244 provide the functionality that allows a user to control the end node 200 and applications, e.g., modules, programs, routines and/or functions, that execute in the memory 210 of the end node 200.

[0031] The processor 204 under control of various modules, e.g., routines, included in memory 210 controls operation of the end node 200 to perform various signaling and processing as discussed below. The modules included in memory 210 are executed on startup or as called by other modules. Modules may exchange data,

information, and signals when executed. Modules may also share data and information when executed. In the Fig. 2 embodiment, the memory 210 of end node 200 of the present invention includes a signaling/control module 212 and signaling/control data 214.

[0032] The signaling/control module 212 controls processing relating to receiving and sending signals, e.g., messages, for management of state information storage, retrieval, and processing. Signaling/control data 214 includes state information, e.g., parameters, status and/or other information relating to operation of the end node. In particular, the signaling/control data 214 includes configuration information 216, e.g., end node identification information, and operational information 218, e.g., information about current processing state, status of pending responses, etc. The module 212 accesses and/or modify the data 214, e.g., updating the configuration information 216 and/or the operational information 218.

[0033] The message generation module 251 is responsible for generating messages for various operations of the end node 200. Neighbor notification message 280 and signaling message 281 are exemplary messages generated according to this invention.

[0034] The link selection module 213 is responsible for selecting a link, e.g., the best link, from the plurality of links available to end node 200 for the transmission of the next message ready to be transmitted by end node 200. The link selection algorithm is based on various link quality parameters including at least some of but not limited to link latency, link channel conditions, link error rate, and link transmission power requirements.

[0035] The physical layer attachment point identifier (PID) determination module 270 is responsible for determining the PID corresponding to broadcast signals received from an access node. The PID determination module 270 includes a cell identification module 271, a carrier identification module 272, and a sector identification module 273. In some but not all embodiments, a combination of a cell identifier, carrier identifier and sector identifier are used as physical attachment point

identifiers. Each of these identifier elements corresponds to physical layer identification information. For example, the cell identifier identifies a physical cell or cell type. The carrier identifier identifies the physical carrier, e.g., the carrier frequency or tone block while the sector identifier identifies a sector in a corresponding cell. Not all of this information need be used to implement a PID and the particular element of a PID may vary depending on the system implementation. For example, in a system which does not use sectorized cells there would be no need for a sector ID. Similarly, in a single carrier system there may be no need for a carrier ID. Making a PID determination, in one exemplary system, includes the steps of operating the cell identification module 271 for the determination of a cell identifier, operating the carrier identification module 272 for the determination of a carrier identifier and operating the sector identification module 273 for the determination of a sector identifier. Thus, it should be appreciated that different signals which pass through a single physical transmitter element, e.g., antenna, can correspond to different physical layer attachment points, e.g., where each of the different physical layer attachment points may be uniquely identified at least within a local area, by a combination of physical identifiers. For example, it should be appreciated that a combination of an antenna or sector identifier in combination with a first carrier identifier might be used to identify a first physical layer attachment point while a second carrier identifier in combination with the same antenna or sector identifier may be used to identify a second physical layer attachment point.

[0036] The physical layer attachment point identifiers (PIDs) information 260 is a list of PIDs, (PID1 261, PID2 262) which are PIDs determined using the PID determination module 260. One exemplary implementation of a physical layer attachment point identifiers (PIDs) may be a connection identifier (CID) which may be included in messages when sending and/or receiving messages. Particular exemplary CIDs are discussed further below.

[0037] Memory 210 also includes a neighbor notification module 290, a message transmission control module 292, and a link establishment module 294. The neighbor notification module 290 is used for transmitting a neighbor notification, e.g., a neighbor notification message 280, to access nodes. Message transmission control

module 292 is used for controlling the transmitter module 234. Link establishment module 294 is used for establishing a wireless communications links with access nodes.

[0038] Fig. 3 provides a detailed illustration of an exemplary access node 300 implemented in accordance with the present invention. The exemplary access node 300, depicted in Fig. 3, is a detailed representation of an apparatus that may be used as any one of the access nodes 140, 140', 140'' depicted in Fig. 1. In the Fig. 3 embodiment, the access node 300 includes a processor 304, memory 310, a network/internetwork interface 320 and a wireless communication interface 330, coupled together by bus 306. Accordingly, via bus 306 the various components of the access node 300 can exchange information, signals and data. The components 304, 306, 310, 320, 330 of the access node 300 are located inside a housing 302.

[0039] The network/internetwork interface 320 provides a mechanism by which the internal components of the access node 300 can send and receive signals to/from external devices and network nodes. The network/internetwork interface 320 includes, a receiver module 322 and a transmitter module 324 used for coupling the node 300 to other network nodes, e.g., via copper wires or fiber optic lines. The wireless communication interface 330 also provides a mechanism by which the internal components of the access node 300 can send and receive signals to/from external devices and network nodes, e.g., end nodes. The wireless communication interface 330 includes, e.g., a receiver module 332 with a corresponding receiving antenna 336 and a transmitter module 334 with a corresponding transmitting antenna 338. The interface 330 is used for coupling the access node 300 to other network nodes, e.g., via wireless communication channels.

[0040] The processor 304 under control of various modules, e.g., routines, included in memory 310 controls operation of the access node 300 to perform various signaling and processing. The modules included in memory 310 are executed on startup or as called by other modules that may be present in memory 310. Modules may exchange data, information, and signals when executed. Modules may also share data and information when executed.

[0041] In the Fig. 3 embodiment, the memory 310 of the access node 300 of the present invention includes a signal generation module 314 for the generation of signals, a packet routing module 350 responsible for the routing of signals and messages, a mapping module 312 that is responsible for mapping PIDs to network layer addresses, an address resolution table 311 including PID to IP address mappings 317. Memory 310 also includes an end node identification module 351 identifying end nodes with which the access node 300 is in communications with, uplink resource allocation information 340 responsible for allocating uplink resources to end nodes, including resources allocated to an end node X 341 and, downlink resource allocation information 345 responsible for allocating downlink resources to end nodes, including resources allocated to an end node X 346.

[0042] Referring now briefly to Fig. 9, Fig. 9 illustrates an address resolution table 311' which may be used as the address resolution table 311 shown in Fig. 3. The address resolution table 311' includes PIDs 902, 904, 906, 908, 910, 912 and information indicating the corresponding IP addresses 903, 905, 907, 909, 911 and 913, respectively. The PIDs are each unique locally, e.g., the PIDs of immediately adjacent cells are unique from one another. Note that the content of the PIDs may vary depending on the physical characteristics of the access node and number of physical layer attachment points supported by the access node to which the PID corresponds. In the Fig. 9 example, PIDs 902, 904 correspond to a first access node (AN 1) which supports two sectors which use the same carrier. Accordingly, in the case of AN 1, it is sufficient for the PID to include a cell identifier and a sector type identifier to uniquely identify the physical layer attachment points in the cell. PIDs 906, 908, 910 correspond to a cell which supports multiple carriers and multiple sectors. Accordingly, the PIDs for access node 2 are implemented as CIDs in the same manner as used in various exemplary embodiments discussed further herein. PID 912 corresponds to a third access node which includes a single sector and uses a single carrier. Accordingly, it is sufficient for PID 6 which corresponds to the third access node to include just a cell identifier although additional physical layer identification, e.g., a sector and/or carrier identifier. The inclusion of such additional information may be desirable where, from a processing perspective, consistent PID formats across multiple cells is desirable.

[0043] Referring now to Fig. 4, Fig. 4 illustrates an exemplary Connection Identifier (CID) 400 implemented according to this invention. CID 400 includes a Slope 410, which is a cell Identifier, a Sector 420 which is a Sector Identifier and a Carrier 430, which is a carrier frequency identifier also known as tone block identifier.

[0044] In an exemplary communication system using OFDM technology, in the physical layer, the spectrum is divided into a number of tones and reused in cells and sectors in neighboring geographical areas. In order to improve the interference characteristics, the tones used in each cell/sector hop over time, and different cells and sectors in neighboring geographical areas use different hopping sequences, which specify how the tones shall hop. The hopping sequences are generated using a predetermined function controlled with two input variables, namely, the cell identifier, e.g., slope value, and a sector identifier. The sector identifier may be implemented as a sector type identifier that indicates which of a plurality of possible sector types a particular sector corresponds to. In one embodiment, the slope value is an integer from 1 to 112, and the sector identifier value is an integer from 0 to 5. Neighboring cells and sectors use different pairs of slope and sector identifier so that the generated hopping sequences are different. In one embodiment, all the sectors in a cell use the same slope value but different sector identifiers, and neighboring, e.g., physically adjacent, cells use different slope values.

[0045] Furthermore, the exemplary OFDM communication system, in some embodiments, uses multiple carriers or tone blocks, so that the available tones are grouped into multiple tone blocks. Tones in a tone block are preferably contiguous. In one exemplary system, hopping of the tones in a given tone block is limited to that tone block. That is, the hopping sequences are such that the tones can hop within the tone block but cannot hop across multiple tone blocks. Tone blocks are indexed with a carrier identifier. In one embodiment, the carrier identifier is an integer 0, 1, or 2.

[0046] When an end node sets up a connection to get wireless networking services, the entity on the network side is an access node, e.g., a base station in a cell/sector, and the connection is defined with respect to a single tone block. Therefore, in the above exemplary OFDM communication system, a combination of slope, sector

identifier and carrier identifier can be used as a locally unique identifier that identifies the connection for the wireless terminal. The combination is thus a connection identifier based on one or more physical layer identifiers. In one embodiment, multiple wireless terminals can have connections with the same base station cell/sector on the same tone block. Those connections normally will share the same connection identifier since they are connected to the same physical layer attachment point as defined by the combination of cell, sector and tone block. . The combination of the connection identifier and a wireless terminal identifier can be used to indicate a communication connection with a particular wireless terminal.

[0047] In general, the connection identifier is a number or a combination of numbers that locally uniquely identifies a connection. In various embodiments, the number or numbers are physical layer characteristic parameters. In another embodiment, e.g., an exemplary embodiment of a CDMA communication system, the connection identifier can be the combination of a pseudo noise (PN) sequence offset and another parameter, e.g., a carrier identifier if multiple carriers are used.

[0048] Fig. 5 illustrates an exemplary message 500, in accordance with the present invention, which uses the Connection Identifier of Fig. 4. Exemplary message 500 is a link layer message which includes a CID destination/source address. The CID destination/source address is an optional field in link layer messages in accordance with some embodiments of the present invention. Link layer message 500 includes a Link Layer Control (LLC) Type field 510 identifying the type of Message Body 530 included in the message 500. CID 520 is a Connection ID in the form of the Connection ID 400 of Fig 4. In one embodiment of this invention the CID field 520 identifies a destination physical attachment point when sent from an end node to an access node in accordance with the invention and identifies a source physical attachment when sent from an access node to an end node in accordance with the invention.

[0049] Fig. 6 illustrates an exemplary communications method and corresponding signaling performed in accordance with various exemplary embodiments of the invention. In Fig.6 end node 630 communicates with access node 620 via access node 610 without a wireless uplink link between end node 630 and access node 620 and

without the end node having to know an IP address of the access node 620. The signaling is illustrated in the context of exemplary system 100 illustrated in Fig. 1. Access Nodes 610 and 620 are similar to access nodes 140, 140' and 140'' of system 100 in Fig 1 and they are implemented according to the access node 300 of Fig'3. The End Node 630 is similar to end node 144, 146, 144', 146', 144'' and 146'' of system 100 in Fig 1, and it is implemented according to end node 200 in Fig 2.

[0050] In Fig 6, end node 630 maintains a bidirectional link with access node 610, which means that it can send messages to and receive message from access node 610. End node 630 in Fig 6, although inside the transmission range of access node 620, does not have an uplink with access node 620. This means that while end node 630 can receive and process broadcast information sent by access node 620 (e.g., broadcast messages 640), end node 630 can not send messages to access node 620 over the air and access node 620 can not receive and process messages sent to it by end node 630 over the air interface. In one embodiment of this invention this may be because end node 630 and access node 620 do not have sufficient timing synchronization. Due to certain limitations, e.g., limited hardware capability, end node 630 may not be able to establish an uplink connection with access node 620 while end node 630 currently has a bidirectional connection with access node 610. In one embodiment, the uplinks used by access node 610 and access node 620 are in different carriers, e.g., the frequency band of the uplink used by access node 610 is different from the frequency band of the uplink used by access node 620. If end node 630 can only generate uplink signal in one band at a given time, for example, because end node 630 only has one radio frequency (RF) chain due to cost considerations, then end node 630 cannot simultaneously maintain two uplink connections in two separate frequency bands. In another embodiment where the uplinks used by access nodes 610 and 620 are in the same band, the two uplinks may not be time synchronized, because the two access nodes are not time synchronized or because of the difference in the propagation delay for the signal to reach access nodes 610 and 620 from the end node 630. If end node 630 can generate just one uplink signal according to one timing synchronization scheme at a time, for example, because end node 630 has a single digital processing chain limited to one timing scheme at a time, then end node 630 cannot simultaneously maintain two uplink connections, when the connections are not sufficiently timing synchronized with one another.

[0051] End node 630 receives broadcast signal(s) 640 which are transmitted by access node 620. The signal(s) 640, according to the embodiment of this invention, are sufficient to determine the Connection ID, similar to CID 400 of Fig 4, corresponding to the specific physical attachment of access node 620 that transmits broadcast signal 640. The signals or signals 640 may include beacon and/or pilot signals which may be transmitted over one or more symbol transmission time periods.

[0052] End node 630 transmits a message 650 to access node 610. In an exemplary embodiment of this invention, said message 650 is the same as, or similar to, exemplary message 500 of Fig 5. The CID field, equivalent to CID 520 of Fig 5, of said message 650 is set to the connection identifier that identifies the physical attachment point of access node 620 that broadcasted signal 640. Said message 650 is thus destined for access node 620 although it is sent to access node 610. Note that since end node 630, in the Fig. 6 example, does not have an uplink with access node 620 it can not send message 650 directly to said access node 620.

[0053] Access node 610 receives message 650 and examines the CID field, corresponding to CID 520 of Fig 5, of message 650 and realizes, from the stored CID to link layer identification information that it does not identify one of its own physical attachment points. In such a case, access node 610 searches its memory for said CID of message 650 to find a mapping to a corresponding higher layer identifier for access node 620 (e.g., an IP address).

[0054] For example, a base station which includes multiple sectors operating under a single link layer controller and/or multiple carriers used under a single link layer controller may have multiple CIDs corresponding to a link layer identifier corresponding to a single link layer controller. In embodiments where separate link layer controllers are used for each sector and/or carrier, different link layer identifiers may be used for each for the different sector and/or carriers. In some embodiments, there is a one to one mapping between physical attachment points and link layers but this is not necessary and there may be several physical attachment points operating under a single link layer. Thus, multiple physical layer identifiers may correspond to

the same link layer link identifier but each physical layer identifier connection identifier normally maps to , at most, a single link layer link identifier.

[0055] Assuming a mapping to a higher layer address is found, access node 610 encapsulates at least part of message 650 into a network layer message 660 which includes a destination address set to the identifier of access node 620 and transmits said message 660 to access node 620. According to this invention message 660 also includes an end node 630 identifier, said identifier being, depending on the embodiment, one of an end node 630 IP address, end node 630 Network Access Identifier (NAI) and a temporary identifier. Access node 620 receives said message 660 and extracts the encapsulated part of message 650 from it. Access node 620 inspects the CID field of the extracted encapsulated part of message 650 and recognizes that the CID field identifies one of its own physical attachments points.

[0056] Access node 620 sends message 670 which includes at least part of message 650 received encapsulated in message 660 by access node 620. Said message 670 also includes an end node 630 identifier similar to the one included in message 660. Access node 610 then receives message 670 and by examining the end node identifier included determines that the message 670 encapsulates a message 680 destined to end node 630. Access node 610 then sends message 680 which includes at least part of the message 670. According to this invention message 680 includes the CID of the physical attachment point of access node 620 that broadcasts signal 640.

[0057] End node 630 receives message 680 from access node 610 but by examining the CID field included in said message 680, e.g., by comparing it to stored CID information, it determines that message 680 is originated from access node 620 in response to message 650 sent to it earlier.

[0058] Fig. 7 illustrates exemplary signaling performed in accordance with various embodiments of the invention. The signaling is illustrated in the context of exemplary system 100 illustrated in Fig. 1. End node 710 is a simplified depiction of end node 200 of Fig 2 and it is the same as, or similar to, to the end nodes 144, 146, 144', 146', 144'', 146'' of system 100 in Fig 1. Access Nodes 740 and 750 are similar to

access nodes 140, 140' and 140'' of system 100 in Fig 1 and they are implemented using access node 300 of Fig 3. In Fig 7, end node 710 includes a message generation module 720 and a link selection module 730. The message generation module 720 of Fig. 7, can be used by applications running in end node 710 to generate messages for their purposes. For example a connection control protocol application maybe included and active in end node 710 allowing the end node 710 to communicate with access nodes for the purpose of creating, disconnecting and/or modifying links between end node 710 and one or both of access nodes 740, 750. Another example is a quality of service (QoS) application which may be included in end node 710. The QoS application when present can modify QoS characteristics of the various links of end node 710. Link selection module 730 of Fig 7 measures various metrics for the quality of connections including link latency, link channel conditions, link error rate, and link transmission power requirements to determine, e.g., on a message by message basis or at a particular point in time, which of the available links is the most appropriate for the transmission of the next message.

[0059] The resulting link quality information can, and in various embodiments is, used to determine which of the plurality of simultaneous links to which a message should be transmitted at a particular point in time.

[0060] In Fig. 7, end node 710 maintains bidirectional links with access nodes 740 and 750, which means that it can send messages to and received message from access node 740 and 750. In this embodiment of the invention the message generation module 720 of end node 710 generates message 759 with ultimate destination access node 740. Message 759 is first sent in link selection module 730 of end node 710. Link selection module 730 selects the link between the links to access nodes 740 and 750 over which the next message is to be transmitted. The link determination function is based on link characteristics including at least one of link latency, link channel conditions, link error rate, and link transmission power requirements.

[0061] In the exemplary embodiment of this invention depicted in Fig. 7, the link selection module 730 selects the link to access node 740 and transmits message 760 over it. Message 760 includes at least some part of message 759 and, in some

embodiment of the invention, includes additional fields used for the transmission of a message over the link between end node 710 and access node 740. For example, the additional fields are, in some embodiments, link framing fields. Since the ultimate destination of message 759 and 760 is access node 740, access node 740 receives message 760, processes the received message and responds, e.g., by transmitting message 765 to end node 710. Message 765 is received by end node 710 and delivered to the message generation module as message 766. Message generation module 720, generates a second message 769 with the ultimate destination being the access node 740. Message 769 is sent to link selection module 730 which selects the link over which message 769 is to be transmitted. In this embodiment of the invention the link to access node 750 is selected and message 770 is transmitted to access node 750. Message 770 includes at least a part of message 769 and in some embodiments of this invention includes additional fields used for the transmission of the message over the link between end node 710 and 750. For example, the additional fields are, in some embodiments link framing fields.

[0062] In one embodiment of this invention the link selection module 730 adds an identifier, e.g., a physical attachment point identifier, of access node 740 together with at least a part of message 769 in comprising message 770, because the link selected by link selection module 730 for the transmission of message 770 does not correspond to the ultimate destination of message 770, which is access node 740. In another embodiment of this invention the link selection module adds the identifier of the ultimate destination of message 760 and 770 before it transmits said messages 760 and 770, independently from which link is selected for their transmission. In a further embodiment of this invention messages 759, 769 include the identifier of their ultimate destination. For example in an example of the exemplary embodiment of Fig. 7 the identifier of the ultimate destination corresponds to access node 740.

[0063] In one exemplary embodiment of this invention, message 770 is implemented according to message 500 of fig 5, where CID field 520 identifies access node 740. Access node 750, receives message 770 and processes it. By examining the ultimate destination of message 770, e.g., a physical attachment point identifier in the CID field 520 of message 500 of fig 5, access node 750 determines that message 770 is

not intended for itself but for some other node identified by the ultimate destination identifier (e.g., a CID in the CID field). The Access node 750 looks up the physical attachment point identifier (PID) included in message 770 in its address resolution table (see address resolution table 311 in access node 300 of fig 3) to find the network address (e.g., IP Address) corresponding to the PID included in message 770.

[0064] Access node 750 encapsulates at least a part of message 770 in an appropriate network layer header and transmits message 775 to access node 740. Message 775 includes at least: a part of message 770, and at least some of the IP address of access node 740. In addition the message 775 may in various embodiments include some or all of the following: the IP address of access node 750, the PID of access node 740 included in message 770, the PID of access node 750 over which message 770 was received, end node 710 identifier and session identifiers for the encapsulation (also called tunneling) of messages between access node 750 and access node 740. Access Node 740 receives message 775 which it recognizes as a message intended for itself from the destination PID included in message 775.

[0065] In one embodiment of this invention access node 740 responds by transmitting message 780 which includes at least part of message 775. Access node 750 receives message 780, which includes end node 710 identifier and sends message 785 to end node 710. Message 785 includes at least part of message 780. End node 710 receives message 785 and forwards message 786 to message generation module 720.

[0066] In another embodiment of this invention access node 740 responds by transmitting, to end node 710, message 780' including at least part of message 775. Message 780' is transmitted over the direct link between access node 740 and end node 710.

[0067] Fig. 8 illustrates exemplary signaling performed in accordance with exemplary embodiments of the invention where an end node is used as part of a neighbor discovery and CID routing information update process. The signaling is illustrated in the context of an exemplary system such as the system 100 illustrated in Fig. 1. End node 810 is a simplified depiction of end node 200 of Fig 2 and it is the

same as or similar to the end nodes 144, 146, 144', 146', 144'', 146'' of system 100 in Fig 1. Access Nodes 840 and 850 are the same as or similar to access nodes 140, 140' and 140'' of system 100 in Fig 1 and they may be implemented, e.g., using access nodes of the type illustrated in Fig 3. In the Fig. 8 example end node 810 has a bidirectional communications link with access node 840, allowing it to send messages to, and receive message from access node 840.

[0068] In Fig. 8, end node 810 generates and transmits message 860 to access node 840. Message 860 includes an identifier that identifies access node 850 as the destination of said message. Access node 840 receives message 860 and attempts to resolve the access node 850 identifier included in said message to a network address, by searching its address resolution table, e.g., address resolution table 311 of access node 300 of Fig 3. In the Fig. 8 example access node 840 fails to resolve said identifier. Access node 840 then transmits message 865 to end node 810. Message 865 includes an indication that routing of a message was not possible due to a resolution failure.

[0069] In one embodiment of this invention end node 810 at this point establishes a bidirectional communications link with access node 850 by exchanging a variety of messages shown as double arrowed message 870 in Fig 8. However, this is not necessary if a bidirectional link already exists with access node 850. In another example in which the invention is used, end node 810 already has a bidirectional link with access node 850 in addition to the link with access node 840

[0070] Using the link with access node 850, the end node 810 transmits a new neighbor notification message 875 to access node 850. Message 875 includes at least an identifier of access node 840 and the network layer address of access node 840. In this way, the access node 850 is supplied with both an identifier, e.g., PID of access node 840 and a corresponding link layer address, e.g., MAC address which the access node 850 can address and store for future resolution of physical layer to network layer identifier. In one embodiment of this invention the access node 840 identifier is a physical attachment point identifier; in another embodiment of this invention it is a link layer identifier. The network layer identifier of access node 840 is known to end node

810 from communication messages 897 communicated to end node 810 during or after the establishment of the link with access node 840.

[0071] In an alternative embodiment of this invention end node 810 sends message 875' instead of message 875. Message 875' has the same or similar message content to message 875 but is sent to access node 850 via access node 840, instead of access node 850 directly. Access node 840 then routes message 875' as message 875" to access node 850. Note that unlike message 860, message 875' is a network layer message including the access node 850 network address as its destination. The network address of access node 850 is known to end node 810 from communication messages 899 communicated during or after the establishment of the link with access node 850. For this reason, access node 840 can route message 875" to access node 850 using a network address of access node 850 e.g., IP address, without having to perform a CID to address resolution operation.

[0072] Access node 850 receives message 875 and sends new neighbor creation message 880 to the network address of access node 840, retrieved from message 875. Message 880 includes connection identifier to network layer address mappings for access node 850. In another embodiment of this invention, message 880 includes link layer identifiers to network layer address mappings for access node 850. In another embodiment of this invention message 880 includes additional neighbor information used for the accommodation of end node handoffs, including but not limited to tunnel address and tunnel session identifiers for packet redirection between access nodes 840 and 850, access node 850 capabilities with respect to quality of service, loading, protocols, and applications supported. Access node 840 receives message 880 and stores information included in message 880 in its memory e.g., for future use in CID to network address resolution operations. Access node 840 responds with message 882 acknowledging the reception of said information included in message 880.

[0073] In one embodiment of this invention access node 840 includes in message 882 some of connection identifier to network layer address mappings for access node 850, link layer identifiers to network layer address mappings for access node 850, neighbor information used for the accommodation of end node handoffs,

including but not limited to tunnel address and tunnel session identifiers for packet redirection between access nodes 840 and 850, and or information indicating capabilities of access node 840 with respect to quality of service, loading, protocols, and applications supported. Access node 840 receives message 880 and stores information included in message 880 in its memory, or e.g., for future use in routing messages. In this particular embodiment of the invention messages 883 and 884 are not used.

[0074] In another embodiment of this invention access node 840 message 882 includes an acknowledgement of the reception of the information included in message 880. In this embodiment of the invention access node 840 sends message 883 including at least some of connection identifier to network layer address mappings for access node 850, link layer identifiers to network layer address mappings for access node 850, neighbor information used for the accommodation of end node handoffs, including but not limited to tunnel address and tunnel session identifiers for packet redirection between access nodes 840 and 850, access node 840 capabilities with respect to quality of service, loading, protocols, and applications supported. Access node 850 receives message 883 and stores the information included in message 883 in its memory, e.g., for future use. Access node 850 responds with message 884 acknowledging the reception of said information.

[0075] Following the exchanges of neighboring information and identifier to address mappings between access node 840 and 850 via message 880, 882 and optionally 883 and 884, end node 810 sends message 890 to access node 840. Like message 860, in one embodiment of the invention message 890 is also the same as or similar to message 500 of Fig 5. Message 890 identifies as its ultimate destination access node 850. Access node 840, receives message 890, searches its memory for a mapping between the access node 850 identifier and a network address for said node 850 and finds said network address in its address resolution table which was earlier populated by message 880. Access node 840 encapsulates message 890 according to information in the resolution table and sends it to access node 850 in the form of message 891. Access node 850 responds with message 892 again using information in its address resolution table and message 891. Access node 840 sends message 893 to end node 810 including at least part of message 892 received from access node 850

completing the communication exchange between end node 810 and access node 850 via access node 840.

[0076] In the above described manner, through the use of messages from end node 810, access nodes 840 and 850 are provided with address and/or PID information about each other that can be used in routing subsequently received messages. Accordingly, as access nodes are added to the network, end nodes can serve to discover their presence from broadcast signals and notify access nodes of new neighbors. As part of the notification process sufficient address information is distributed to facilitate network PID based routing of messages after the notification process has been completed.

[0077] In various embodiments nodes described herein are implemented using one or more modules to perform the steps corresponding to one or more methods of the present invention, for example, signal processing, message generation and/or transmission steps. Thus, in some embodiments various features of the present invention are implemented using modules. Such modules may be implemented using software, hardware or a combination of software and hardware. Many of the above described methods or method steps can be implemented using machine executable instructions, such as software, included in a machine readable medium such as a memory device, e.g., RAM, floppy disk, etc. to control a machine, e.g., general purpose computer with or without additional hardware, to implement all or portions of the above described methods, e.g., in one or more nodes. Accordingly, among other things, the present invention is directed to a machine-readable medium including machine executable instructions for causing a machine, e.g., processor and associated hardware, to perform one or more of the steps of the above-described method(s).

[0078] Numerous additional variations on the methods and apparatus of the present invention described above will be apparent to those skilled in the art in view of the above description of the invention. Such variations are to be considered within the scope of the invention. The methods and apparatus of the present invention may be, and in various embodiments are, used with CDMA, orthogonal frequency division multiplexing (OFDM), or various other types of communications techniques which may

be used to provide wireless communications links between access nodes and mobile nodes. In some embodiments the access nodes are implemented as base stations which establish communications links with mobile nodes using OFDM and/or CDMA. In various embodiments the mobile nodes are implemented as notebook computers, personal data assistants (PDAs), or other portable devices including receiver/transmitter circuits and logic and/or routines, for implementing the methods of the present invention.

WHAT IS CLAIMED IS:

- 1 1. A communication method for use in a system including an end node, a first
2 access node and a second access node, the method comprising:
3 operating said end node to receive broadcast information from said second
4 access node;
5 operating said end node to determine a physical attachment point identifier from
6 said broadcast information; and
7 operating said end node to transmit a first signal including said physical
8 attachment point identifier to said first access node.
- 1 2. The communications method of claim 1, wherein transmitting said first signal
2 includes transmitting said signal over a wireless communication link.
- 1 3. The communications method of claim 2, wherein said end node is within a
2 broadcast coverage area into which said first and second access nodes each broadcast
3 signals.
- 1 4. The communications method of claim 2, wherein said end node has a bi-
2 directional communications link with said first access node and at least an uplink with
3 said second access node.
- 1 5. The communications method of claim 2, wherein said end node has a bi-
2 directional communications link with said first access node and does not have an uplink
3 with said second access node.
- 1 6. The communications method 2, wherein said broadcast information includes a
2 plurality of beacon signals.
- 1 7. The method of claim 6, wherein said step of operating said end node to
2 determine a physical attachment point identifier includes determining from said
3 received beacon signals:
4 a first identifier which is a cell identifier.

1 8. The method of claim 7, wherein said step of operating said end node to
2 determine a physical attachment point identifier further includes:
3 determining from said received beacon signals a second identifier, said second
4 identifier being a carrier identifier.

1 9. The method of claim 8, wherein said step of operating said end node to
2 determine a physical attachment point identifier further includes:
3 determining from said received beacon signals a third identifier, said third
4 identifier being a sector identifier.

1 10. The method of claim 6, wherein said step of operating said end node to
2 determine a physical attachment point identifier includes determining from said
3 received beacon signals at least two of the following three identifiers corresponding to
4 said second access node; i) a cell identifier, ii) a carrier identifier and iii) a sector
5 identifier; and
6 wherein said step of transmitting a first signal includes communicating a physical
7 attachment point identifier including said at least two determined identifiers to said first
8 access node.

1 11. The method of claim 10, further comprising:
2 operating said end node to receive from said first access node a signal including
3 a message source identifier, said message source identifier including at least said two
4 determined identifiers corresponding to said second access node.

1 12. The method of claim 10, wherein said physical attachment point identifier
2 identifies a physical connection point at said second access node, said physical
3 attachment point identifier being unique within overlapping end node reception areas.

1 13. The method of claim 1, wherein said first and second access nodes are base
2 stations; and
3 wherein operating the end node to transmit includes operating the end node to
4 transmit OFDM signals.

- 1 14. The method of claim 10, further comprising:
2 operating said first access node to receive said first signal;
3 operating said first access node to determine a network layer address
4 corresponding to the physical attachment point identifier included in said first signal;
5 and
6 operating the first access node to transmit a packet including said determined
7 network layer address as a destination address and including at least some information
8 obtained from said first signal.
- 1 15. The method of claim 14, wherein said packet further includes an end node
2 identifier identifying said end node which transmitted said first signal.
- 1 16. The method of claim 15, wherein said first signal is a first message which does
2 not include an end node identifier, said first signal being communicated using uplink
3 signaling resources dedicated to said end node, the method further comprising:
4 operating said first access node to determine said end node identifier
5 corresponding to the first signal; and
6 wherein said first access node includes said determined end node identifier in
7 said transmitted packet.
- 1 17. The method of claim 16, further comprising:
2 operating the first access node to receive a packet from said second access node,
3 said received packet including said end node identifier and said physical attachment
4 point identifier.
- 1 18. The method of claim 17, further comprising:
2 operating said first access node to transmit a signal to said end node, said signal
3 including said physical attachment point identifier and at least some information
4 obtained from the packet received from said second access node.
- 1 19. The method of claim 18, wherein said signal transmitted to said end node is
2 transmitted using a communications resource dedicated to said end node and does not
3 include an end node identifier.

1 20. A wireless terminal comprising:
2 a first receiver module for receiving broadcast information from a second access
3 node;
4 a physical attachment point identifier determination module for determining a
5 physical attachment point identifier from said broadcast information; and
6 a first transmitter module for transmitting a first signal including said physical
7 attachment point identifier to a first access node.

1 21. The wireless terminal of claim 20, wherein said transmitter is a wireless
2 transmitter for transmitting said first signal as an OFDM signal over a wireless
3 communication link.

1 22. The wireless terminal of claim 21, wherein said wireless terminal is within a
2 broadcast coverage area into which first and second access nodes each broadcast
3 signals; and
4 wherein said end node has a bi-directional communications link with said first
5 access node and does not have an uplink with said second access node.

1 23. The wireless terminal of claim 21, wherein said broadcast information includes a
2 plurality of beacon signals, and
3 wherein said physical attachment point identifier determination module includes
4 a cell identifier determination module for determining a first identifier from one or more
5 of said received beacon signals, said first identifier being a cell identifier.

1 24. The wireless terminal of claim 23, wherein said physical attachment point
2 identifier determination module further includes a carrier identifier determination
3 module for determining a second identifier from one or more of said received beacon
4 signals, said second identifier being a carrier identifier.

1 25. The wireless terminal of claim 24, wherein said identifier determination module
2 further includes a sector identifier module for determining a third identifier from one or
3 more of said received beacon signals, said third identifier being a sector identifier.

1 26. A method of operating a first access node, the method comprising:

2 receiving a first signal from an end node;
3 determining a network layer address corresponding to a physical attachment
4 point identifier included in said first signal; and
5 transmitting a packet including said determined network layer address as a
6 destination address and including at least some information obtained from said first
7 signal.

1 27. The method of claim 26, wherein said packet further includes an end node
2 identifier identifying said end node which transmitted said first signal.

1 28. The method of claim 27, wherein said first signal is a first message which does
2 not include an end node identifier, said first signal being communicated using uplink
3 signaling resources dedicated to said end node, the method further comprising:
4 determining said end node identifier corresponding to the first signal; and
5 including said determined end node identifier in said transmitted packet.

1 29. The method of claim 28, further comprising:
2 receiving a packet from a second access node, said received packet including
3 said end node identifier and said physical attachment point identifier.

1 30. The method of claim 29, further comprising:
2 transmitting a signal to said end node, said signal including said physical
3 attachment point identifier and at least some information obtained from the packet
4 received from said second access node.

1 31. The method of claim 30, wherein said signal transmitted to said end node is
2 transmitted using a communications resource dedicated to said end node and does not
3 include an end node identifier.

1 32. A base station, comprising:
2 a receiver module for receiving from a wireless terminal a first signal including a
3 physical attachment point identifier;

4 an address resolution table including information mapping at least one physical
5 attachment point identifier to a network layer address;
6 a mapping module for determining from the address resolution table a network
7 layer address corresponding to the physical attachment point identifier included in said
8 first signal; and
9 a network interface module for transmitting a packet including said determined
10 network layer address as a destination address and including at least some information
11 obtained from said first signal.

1 33. The base station of claim 32, further including:
2 a signal generation module for generating said packet including said determined
3 network layer address and for including in said packet an end node identifier identifying
4 said wireless terminal which transmitted said first signal.

1 34. The base station of claim 33, wherein said first signal is a first message which
2 does not include an end node identifier;
3 said base station further including:
4 a memory including stored resource allocation information identifying
5 end nodes to which uplink resources have been allocated;
6 an end node identification module for determining an end node identifier
7 corresponding to an end node to which an uplink resource used to communicate
8 said received first signal was dedicated; and
9 wherein said signal generation module includes said determined end
10 node identifier in said transmitted packet.

1 35. The base station of claim 34, further comprising:
2 a packet routing module for routing packets including said end node identifier
3 and said physical attachment point identifier as a function of said physical attachment
4 point identifier.

1 36. The base station of claim 35, further comprising:

2 a transmission module for transmitting signals to said end node which include
3 said physical attachment point identifier and at least some information obtained from
4 one or more packets received from another access node.

1 37. The base station of claim 36, wherein said memory further includes downlink
2 resource allocation information; and
3 wherein said signal transmitted to said end node is transmitted using a downlink
4 communications resource dedicated to said end node and does not include an end node
5 identifier.