

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 July 2002 (18.07.2002)

PCT

(10) International Publication Number
WO 02/056052 A3

(51) International Patent Classification⁷: **G01S 11/10**, 5/14

(21) International Application Number: PCT/US01/49992

(22) International Filing Date: 29 October 2001 (29.10.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/244,109 27 October 2000 (27.10.2000) US
10/044,194 26 October 2001 (26.10.2001) US

(71) Applicant: **QUALCOMM INCORPORATED** [US/US];
5775 Morehouse Drive, San Diego, CA 92121-1714 (US).

(72) Inventor: **VAYANOS, Alkinoos, H.**; 1037 Diamond
Street, San Diego, CA 92109 (US).

(74) Agents: **WADSWORTH, Philip, R.** et al.; Qualcomm In-
corporated, 5775 Morehouse Drive, San Diego, CA 92121-
1714 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,

GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI,
SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA,
ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,
TG).


Published:
— with international search report

(88) Date of publication of the international search report:
30 May 2003

(15) Information about Correction:
Previous Correction:
see PCT Gazette No. 07/2003 of 13 February 2003, Sec-
tion II

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR ESTIMATING VELOCITY OF A TERMINAL IN A WIRELESS COMMUNI-
CATION SYSTEM



(57) Abstract: Techniques to estimate the velocity of a terminal in a wireless communication system. Movement by the terminal results in a Doppler shift in the frequency of each transmitted signal received at the terminal. In one method, the positions of the terminal, a base station, and each of two or more satellites are initially determined. A residual rate of a change of pseudo-range may also be determined for each satellite, e.g., based on (1) an estimated baseband frequency error that includes the Doppler frequency shift due to the terminal's movement and (2) an estimated Doppler frequency shift due to movement by the satellite. A set of equations is then formed based on the determined positions of the terminal, the base station, and the satellites and the determined residual rates of change of pseudo-ranges for the satellites. The velocity of the terminal may thereafter be estimated based on the set of equations.



WO 02/056052 A3