

ARTICULATED BRACELET WITH LIMITED BENDING

The present invention concerns a non-extensible articulated bracelet, in particular for a watch, including a plurality of decorative annular elements which are sensitive to compression or shocks, said decorative elements being strung onto a central core formed by an inner chain of links connected to each other by pivoting axes
5 and designed to co-operate with each other and with the decorative elements to prevent any accidental compression or shock from breaking said elements.

The invention concerns more particularly a bracelet of this type wherein the decorative elements are made of a material having very high resistance to abrasion, but lower resistance to shocks, such as ceramic based composites.

10 Non-extensible bracelets having a central core, made of a base material with an essentially mechanical function, completely or partially masked by a decorative outer element made of free links made of a more noble material have already been disclosed in various documents of the prior art, certain of which also have the object of preventing excessive bending likely to damage the outer element.

15 French Patent No. 2 502 916 discloses a watch bracelet formed of an inner chain onto which decorative elements, open on the wrist side, are freely strung on. The inner chain is formed of solid links each including a stud portion and a slot portion to allow them to be fitted inside each other and keeping them assembled by means of a pin. The face of the stud opposite the slot has a certain inclination in order to limit the
20 range of movement of an inner link with respect to the next link to fit the natural curve of the wrist. Because of the play which must necessarily exist between each decorative element, when the bracelet is bent a decorative element may not cover the corresponding link of the inner chain perfectly and may be damaged when the bracelet is bent.

25 In order to overcome the aforecited drawback European Patent No. 0 549 979 proposes a device wherein the decorative elements are enveloping, leaving free a central passage provided laterally with stops and they are positioned precisely above each link by blocking bars. The opposite faces of the decorative elements have complementary rounded shapes but no means are provided, on the inner chain, able
30 to limit the range of movement thereof, which does not eliminate the risk of breakage by excessive bending.

The non-extensible bracelet disclosed in European Patent No. 0 736 480 includes a relatively complex articulation device between two successive links including two pins connected by linking elements which also determine the authorised
35 bending angle, each enveloping decorative element being held on this articulation

device by an insert passing through said element and being held snap fitted by the pins.

The object of the present invention is to overcome the drawbacks of this prior art by providing a non-extensible articulated bracelet, wherein the links of an inner
5 chain co-operate with each other and with the decorative elements strung onto them to prevent or limit the risk of said decorative elements being compressed when the bracelet is bent or in the event of an accidental shock, for example by dropping to the ground a watch fitted with such a bracelet.

The present invention therefore concerns a bracelet formed of enveloping
10 decorative elements mounted on a non-extensible articulated inner chain formed of links the particular shape of which, by co-operating with the structures of the passages through the decorative elements, allows the angular range of movement of a link with respect to the next link to be limited to an angle α in a vertical plane passing through the longitudinal line of symmetry X-X' of the bracelet.

15 Each decorative element includes, on a part of the depth of the through passage, on the one hand a central rib, and on the other hand two lateral edges connecting the cap, i.e. the visible part, to feet made as an overthickness on the bottom, said feet forming two symmetrical grooves with respect to the line X-X'.

Each link includes a central slot which is complementary to the rib of a
20 decorative element and the bottom of which forms a bridge through which a pin hole passes. The bridge connects two symmetrical coupling elements, the main body of which has a width substantially smaller than the distance between the central rib and a lateral edge. Each coupling element has at one end a lateral arm provided with a pin
hole, extending beyond the main body over a distance corresponding to the thickness
25 of one edge and forming with the bridge a recess which is complementary to an extension of the opposite end, through which a pin hole also passes. The edges of the pin holes or the edges of the recesses and extensions are provided with blocking means limiting the bending angle of a link with respect to the next link.

According to a first embodiment, the blocking means are formed at each end of
30 the pin hole of the bridge by two annular stops having vertical shoulders which co-operate with annular stops provided at the ends facing the holes of the two extensions, said stops having shoulders forming an angle of less than 180° one being vertical on the cap side, the other being inclined at an angle α on the bottom side.

According to another embodiment the blocking means are formed at the end of
35 each extension by a lug bent at an angle α on the bottom side, said lug co-operating with a recess of complementary shape, provided on the bottom side in the thickness of each coupling element and joining an edge of the recess.

It will also be observed that the presence of feet between the bottom and the edges and the rib allow a certain play enabling bending slightly greater than the value α to be absorbed, without exerting any stress on the decorative element.

Other advantages and features of the invention will appear more clearly upon
5 reading the following description of embodiment examples given by way of illustrative and non-limiting example, with reference to the annexed drawings, in which:

- Figure 1 is a blown up perspective view of the assembly of links with two decorative elements;
- Figure 2 is a top view of a link of the inner chain;
- 10 - Figure 3 is a cross-section along the line III-III of Figure 2;
- Figure 4 is a top view of another embodiment of a link of the inner chain;
- Figure 5 is a cross-section along the line V-V of Figure 4;
- Figure 6 is a cross-section of a decorative element, onto which a link is strung, at line VI-VI of Figure 1;
- 15 - Figure 7A is a cross-section, along the line VII-VII of Figure 6, of four bracelet elements arranged flat;
- Figure 7B shows the four bracelet elements of Figure 7A in a bent position;
- Figure 8A is a cross-section, along the line VIII-VIII of Figure 6, of four bracelet elements arranged flat;
- 20 - Figure 8B shows the four bracelet elements of Figure 8A in a bent position;
- Figure 9A shows, along an identical cross-section to that of Figure 8A, four bracelet elements having other decorative elements; and
- Figure 9B shows the four bracelet elements of Figure 9A in a bent position.

Figure 1 shows in blown up perspective a portion of bracelet formed of two
25 decorative elements 10 and 10a and three links 20, 20a and 20b aligned along a line of symmetry X-X', intended to be assembled by pivoting pins 4 and 5. First bracelet element 1 is shown with link 20a set in place in the direction X-X', in through passage 12 of decorative element 10a. In order to assemble second bracelet element 3, link 20 is engaged in link 20a, they are assembled by means of pin 4, then the following
30 decorative element 10 is strung on, again in direction X-X. In the same way, the preceding process is repeated by engaging link 20b in link 20 and assembling them by means of pivoting pin 5.

Decorative element 10, which has the general shape of a flattened ring, is shown in partially torn away view to show more clearly the particular structure of
35 through passage 12 from its front face 6 to its back face 8. It is delimited at its top portion, i.e. the visible portion, by a cap 13, at its bottom portion, which is in contact with a user's wrist by a bottom 15, these two portions being joined by rounded edges

14. From substantially half of its depth and up to its back face 8, through passage 12 has on the one hand a central rib 16 joining the inner wall of cap 13 and a foot 17 made as an overthickness on the inner wall of bottom 15, and on the other hand over each side an edge 18 joining cap 13 and a foot 19 made as an overthickness on
5 bottom 15 in the same manner. Foot 17 of rib 16 delimits with feet 19 of edges 18 two symmetrical grooves 11 with respect to axis X-X'. This symmetrical structure appears more clearly in the cross-section shown in Figure 6. Figure 6 also shows that rib 16, edges 18 and feet 17, 19 greatly contribute to reinforcing decorative element 10 at the zones of support for coupling elements 21, 31, while having the possibility of keeping
10 sufficient play on the one hand between the inner surface of bottom 15 and the opposite surface of main body 21, 31 of a link, and on the other hand between each edge 18 and the edges of the main body, while the bracelet elements are aligned perfectly along axis X-X' as a result of the co-operation of rib 16 and slot 2.

In the example shown, decorative element 10 has been given the simplest
15 geometrical shape, but it is obvious that it may be given a different aesthetic appearance, for example by making the cap in a convex manner. Likewise, front and back faces 6 and 8 may have complementary enveloping shapes, as appears for example in the cross-sections of Figures 7A and 7B. This decorative element may be made in a single piece with any type of material, but one of the objects of the invention
20 is to be able to use materials having an attractive appearance, good abrasion and scratch resistance, but yet less resistance to compression and shocks. A material of this type is for example a ceramic material which easily allows the desired shape to be obtained by moulding and sintering.

With reference now also to Figures 2 and 3, a link 20 of the inner chain will be
25 described hereinafter. As can be seen, each link has a symmetrical structure on either side of a central slot 2 having as width the thickness of central rib 16 of a decorative element 10. The bottom of this slot 2 forms a bridge 7 which connects two coupling elements 21 and 31 and through which a pin hole 9 passes. Each coupling element 21, 31 is formed of a main body 22, 32 having a substantially smaller width than the
30 space between central rib 16 and a lateral edge 18 of a decorative element 10. Each coupling element 21, 31 has, at one end a lateral arm 28, 38 extending transversely beyond main body 22, 32 over a length substantially equal to the thickness of an edge 18 of a decorative element 10, so that the vertical surface 28a, 38a turned towards the other end of main body 22, 32 rests on an edge 18 when a decorative element 10 is
35 strung onto link 20. Pin holes 29, 38 aligned with pin hole 9 of bridge 7 pass through arms 28, 38 which delimit with said bridge 7 a substantially rectangular recess 23, 33

of complementary shape to an extension 24, 34 of the opposite end of main body 22, 32. The two extensions 24 and 34 are provided with pin holes 25 and 35 in alignment.

In the example shown in Figures 1 to 3 and 7A to 8B, the blocking means allowing the bending of a link with respect to the following link to be limited to an angle α are formed on the one hand at each end of pin hole 9 of bridge 7 and at the opposite ends of pin holes 25, 35 of extensions 24, 34 of the other end of main body 21, 31. These blocking means consist, at bridge 7, of an annular stop 37 (respectively 27) having vertical shoulders 37a, 37b at 180°, and at extensions 24, 34 of an annular stop 36 (respectively 26) having a vertical shoulder 36a on the side of cap 13 and a shoulder 36b inclined at an angle α on the side of bottom 15, the angular distance between these two shoulders 36a, 36b being less than 180°. The value of angle α obviously depends on the width of the bracelet elements and on the size of the wrist on which it has to be put, but it can be indicated by way of example that a mean value of 18° is entirely suitable. Thus, as shown in Figures 7A and 8A, when the bracelet is arranged flat, the shoulder 36a of a link 20 is in contact with the shoulder 37b of the following link 20', while shoulders 36b and 37b form an angle α . Conversely when the bracelet is bent, shoulders 36b and 37b are in contact and shoulders 36a and 37a form an angle α . In a similar manner, this blocking device can be provided at the ends of other pin holes.

As is seen in particular in Figures 8A and 8B, front and back faces 6 and 8 of decorative elements 10 have complementary rounded shapes extending beyond the links which they cover, so that the portions forming the cap also cover the inner chain when the bracelet is bent. In order to allow range of movement for the bottom when the bracelet is bent, main body 22, 32 includes a hollow portion 41 after pin hole 25, 35. As can be seen in Figures 9A and 9B which correspond, along the same cross-section as Figures 8A and 8B, to another simpler embodiment wherein the caps do not cover each other, it may also be necessary to keep hollow portions 41.

With reference now to Figures 4 and 5, an alternative embodiment of a link of the inner chain is shown, which differs from that which has just been described as regards the blocking means which are no longer formed by stops at the pin holes. In this variant, the blocking means are formed, for each coupling element 21, 22, by a lug 30 bent at an angle α towards the bottom 15 and located in the prolonged portion of each extension 23, 34. This lug 30 is provided to have a range of movement of amplitude α in a recess 40, of complementary shape to lug 30 and arranged in the thickness of the main body at the edge of recesses 23, 33.

The links which have just been described can be obtained by known techniques such as machining a metal blank or sandwiching a form cut out from a thin sheet of metal.

It goes without saying that various simple variants and modifications within the
5 grasp of those skilled in the art also fall within the scope of the present invention.




CLAIMS

1. Bracelet formed of enveloping decorative elements (10) provided with through passages (12) delimited on the one hand by a cap (13) and on the other hand by a bottom (15) and provided over a portion of their depth, in the median portion with a central rib (16) and over the sides with two lateral edges (18) connecting the cap (13) to feet (17, 19) made as an overthickness on the bottom (15), said feet (17, 19) forming two symmetrical grooves (11) with respect to the line X-X', said elements being mounted on a non-extensible articulated chain, extending longitudinally along a line of symmetry X-X', formed of links (20) housed one after the other in the through passages (12) and assembled by hinges in which are engaged pivoting pins (4, 5) after each decorative element (10) is set in place, characterised in that each link (20) includes a central slot (2) which is complementary to the rib (16) of a decorative element (10) and the bottom of which forms a bridge (7) through which a pin hole (9) passes, said bridge (7) connecting two symmetrical coupling elements (21, 32) the main body (22, 32) of which has a width substantially smaller than the distance between the central rib (16) and an edge (18), each coupling element (21, 31) having at one end a lateral arm (28, 38), provided with a pin hole (29, 39) extending beyond the main body (22, 32) over a distance corresponding to the thickness of one edge (18) and forming with the bridge (7) a recess (23, 33) which is complementary to an extension (24, 34) of the opposite end, provided with a pin hole (25, 35), the edges of said pin holes (9, 25, 28, 35, 38) or the edges of the recesses (23, 33) and the extensions (24, 34) being provided with blocking means allowing the angular range of movement of a link with respect to the following link to be limited to an angle α in the vertical plane passing through the line X-X'.

2. Bracelet according to claim 1, characterised in that the blocking means are formed, at each end of the pin hole (9) of the bridge (7) by two annular stops (27, 37) having vertical shoulders at 180° and co-operating with annular stops (26, 36) provided at the opposite ends of the pin holes (25, 35) of the two extensions (24, 34), said stops forming an angle of less than 180° , one shoulder being vertical on the cap (13) side and the other shoulder being inclined at an angle α on the bottom (15) side.

3. Bracelet according to claim 1, characterised in that the blocking means are formed at the end of each extension (24, 34) by a lug (30) bent at an angle α on the bottom (15) side, said lug (30) co-operating with a recess (40) of complementary shape provided on the bottom (15) side in the thickness of each coupling element (21, 31) and joining an edge of the recess (23, 33).



4. Bracelet according to claim 1, characterised in that the feet (17, 19) of a decorative element (10) allow a certain play to be arranged between the bottom of the through passage (12) and the hinges of the pivoting pins (4; 5).

5. Bracelet according to claim 1, characterised in that the decorative elements are made in a single piece of a hard material such as ceramics.