

S P E C I F I C A T I O N

TITLE OF THE INVENTION

Operation type electronic component

5 FIELD OF TECHNOLOGY

The present invention relates to an operation type electronic component with built-in push switch driven by rotating operation and push operation of an operating knob, which operation type electronic component being a component mainly used in remote controllers of various
10 electronic appliances or in portable electronic devices.

BACKGROUND TECHNOLOGIES

A rotary encoder with built-in push switch, which is an embodiment of a prior art operation type electronic component with push switch, is described hereunder referring to Figs. 9 through 13.

15 A prior art rotary encoder with built-in push switch comprises, as shown in Fig.9 (cross sectional view) and Fig.10 (partially cutaway top view), a movable member 1 affixed movable to a base board 2 in holding part 1C, a rotary contact wheel 3 attached revolvable on the movable member 1 and disposed at the middle part of the base board 2, and a
20 switch 4 disposed at a rear part of base board 2 (at the right in Figs. 9-10).

The rotary contact wheel 3 is provided at the bottom surface with contact plates 3A disposed in a radial arrangement for accepting contacts from elastic contact reeds 5 of the base board 2, and held
25 revolvable at the central hole 3B by a pillar 1A of the movable member 1, with the top covered with an operating knob 6 that rotates together.

As shown in a perspective view of Fig.11, the base board 2

comprises a hole 2A provided in a side part for holding the movable member 1 movable, a hollow 2C having a stop wall 2B for fixing the switch 4, elastic contact reeds 5 for generating electric signal by having contact with the bottom surface of rotary contact wheel 3, and terminals 7 for taking the generated electric signal out.

A coil spring 8, which is positioned by an extrusion 2D located on the base board 2 at a rear part, pushes a side of the movable member 1 in horizontal direction so that push rod 1B of the movable member 1 is usually kept off the switch 4. Switch 4 is, as shown in Fig.9, fixed in the hollow 2C of base board 2 with the rear end touching to the stop wall 2B, and a button 4A facing to the push rod 1B of movable member 1.

The operation of the above prior art rotary encoder having push switch is described in the following.

The rotary contact wheel 3 rotates with the pillar 1A of movable member 1 as the axis when the knob 6 attached on the rotary contact wheel 3 is rotated by a force given in tangential direction indicated with an arrow F in Fig.10. The radial contact plates 3A disposed on the bottom surface of rotary contact wheel 3 slide on the elastic contact reeds 5 of base board 2, and pulse signals are generated. The pulse signals are outputted through the terminals 7, thus it works as a rotary encoder.

While the operating knob 6 is being rotated, a pushing force is also given to the knob, but the spring force of said twisted coil spring 8 prevents the push rod 1B of movable member 1 from pushing the button 4A of switch 4.

When the operating knob 6 is pressed in the direction of an arrow

G in Fig.10 with more force than the force due to the coil spring 8, the entire part of the movable member 1 including the rotary contact wheel 3 is moved to the direction of an arrow H with the holding part 1C of movable member 1, or a hole 2A of the base board 2, as the axis of movement, causing the push rod 1B of movable member 1 push the button 4A to actuate the switch 4. As soon as the force given to the knob 6 is withdrawn, the force of twisted coil spring 8 pushes the movable member 1 back to the original position.

The above described prior art rotary encoder having push switch employs an independent completed switch for the switch 4 that works on a push of the operating knob 6, and comprises the coil spring 8 disposed at a rear part of the base board 2 for preventing the push rod 1B of movable member 1 from pushing the switch 4 while the operating knob 6 is being rotated, as well as for restoring the movable member 1 to the original position when the pushing operation on the operating knob 6 is finished. These result in a higher cost and an increased body size of a rotary encoder having push switch.

In the general trends towards the more compact and lower price of electronic appliances, those electronic components to be incorporated in such appliances are likewise requested to be compact yet have advanced functions, coming in low price. A means to meet the requirement is to make the components available on an automatic production line. A popular solution is introduction of an insert-shaping technique, wherein contact points, terminals and other conductive members are formed on a hoop of metal sheet to be inserted into a resin molded base board, for the later assembly on an automatic assembly machine.

Now in the following, a method of manufacturing a base board containing contacts, terminals and other conductive members is described with reference to Fig.12, using the above mentioned prior art rotary encoder having push switch as the vehicle.

5 Fig.12 illustrates a metal sheet hoop showing a set of conductive members formed on the metal sheet and a resin molded base board with the set of conductive members inserted therein. Numeral 9 denotes an electro-conductive metal sheet hoop provided with frame alley 9A, and 10 conductive members stamped in flat sheet form with each of the members
10 remaining connected with the frame alley 9A at connecting sections 9B. Numeral 2 denotes a resin molded base board with the conductive members 10 inserted therein.

In the next step, the base board 2 undergoes a cutting at the joints 10A of conductive members 10, and then the conductive members
15 10 are formed to become elastic contact reeds 5. Then, the sections 9B connecting with the frame alley 9A are cut at cutting lines 9C, and the terminals 7 are bent downward to complete a base board 2 as shown in Fig.11.

The cut surface 11 of electro-conductive metal sheet 9 is exposed
20 out of the surface of base board 2 in the above prior art method. When a rotary encoder 12 having push switch 12 assembled with the above base board 2 is mounted on a circuit board 14 with a part of the operating knob 6 extruding out of outer casing 13, and the cut surface is positioned at a vicinity of the operating knob 6, a static electricity
25 generated while the operating knob 6 is rotated with a finger discharges to the cut surface 11. The discharge affects the signals to be outputted from a rotary encoder having push switch 12, producing possible causes

of erroneous operation of an apparatus.

In prior art methods, therefore, the cut surface 11 had to be covered with a separate metal board 15 electrically coupled with a ground sector 16 of apparatus by means of soldering etc., whenever there is a possibility of the electrostatic problem.

This is a substantial drawback that results in an extra parts count and additional assembly steps.

DISCLOSURE OF THE INVENTION

The present invention is intended to solve the above described problems the prior arts had, and to present an operation type electronic component which has a simple structure enabling the reduction of the total dimensions and cost, wherein the grounding work is completed at a same time with a mounting work.

An operation type electronic component according to the present invention comprises a switch which is constituted by providing a dome shape moving contact point on a fixed contact point prepared on base board, and an L-shaped actuator disposed between the switch and a movable member; wherein the elastic force of the dome shape moving contact point is utilized to prevent the movable member from actuating the switch while an operating knob is being rotated, the elastic force is also used to return the movable member to the original position after a push operation to the knob is finished. Further, according to the present invention, the conductive members and the grounding member which are provided on a same metal sheet are fixed in a resin mold base board by means of an insert-shaping technique, and then the electrical coupling between the conductive members and the grounding member is broken; thus the grounding member is placed between the conductive

members and the knob.

With the above described constitution, the total number of constituent parts including the parts constituting the switch is reduced, which enables the reduction of cost and the overall size of an operation type electronic component, furthermore the static electricity generated at the knob is always discharged to a nearest electro-conductive substance, viz. the grounding member.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig.1 is a cross sectional view showing a rotary encoder having push switch according to an embodiment of an operation type electronic component of the present invention, Fig.2 a partially cutaway top view of the above rotary encoder, Fig.3 a perspective view of the key part of the above rotary encoder, viz. base board, Fig.4 a perspective view of the key part of the above rotary encoder, viz. L-shaped actuator, Fig.5 a cross sectional view of the key part of the above rotary encoder showing how the L-shaped actuator is attached to the base board, Fig.6 a cross sectional view of the above rotary encoder showing when the knob is being pushed, Fig.7 a top view of metal sheet hoop showing the conductive members and grounding member formed on the hoop, and these members after insert-molded in a resin mold base board, Fig.8 a cross sectional side view of the above rotary encoder having push switch mounted in a casing. Fig.9 is a cross sectional view showing a prior art rotary encoder having push switch, Fig.10 a partially cutaway top view of the above rotary encoder, Fig.11 a perspective view of the key part of the above rotary encoder, viz. the base board, Fig.12 a top view of prior art metal sheet hoop showing the conductive members formed on the hoop and these members after insert-molded in a resin mold base

board, Fig.13 a cross sectional side view of the above rotary encoder having push switch mounted in a casing.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An operation type electronic component according to an embodiment of the present invention is described below using a rotary encoder having push switch as the vehicle, referring to Fig.1 through Fig.8. In the drawings, those constituent parts having the same functions as those of the above described prior art are given with the same symbols, and explanation to which is omitted.

Fig.1 is a cross sectional view showing a rotary encoder having push switch according to an embodiment of an operation type electronic component of the present invention, Fig.2 a partially cutaway top view of the above rotary encoder, Fig.3 a perspective view of the key part of the above rotary encoder, viz. base board, Fig.4 a perspective view of the key part of the above rotary encoder, viz. L-shaped actuator, Fig.5 a cross sectional view of the key part of the above rotary encoder showing how the L-shaped actuator is attached to the base board, Fig.6 a cross sectional view of the above rotary encoder showing when the knob is being pushed, Fig. 7 a top view of metal sheet hoop showing the conductive members and grounding member formed on the hoop, and these members after insert-molded in a resin mold base board, Fig.8 a cross sectional side view of the above rotary encoder having built-in push switch mounted in a casing.

As shown in Fig.1 and Fig.2, a rotary encoder having built-in push switch according to the present invention comprises a movable member 21 affixed movable to a base board 22 at holding part 21B, a rotary contact wheel 3 affixed revolvable on the movable member 21 and

disposed at the middle part of the base board 22, and a switch 23 disposed at a rear part of base board 22 (at the right in Figs. 1-2). This constitution is similar to that of the prior art.

5 The rotary contact wheel 3 is provided at the bottom surface with contact plates 3A disposed in a radial arrangement for accepting the contact from elastic contact reeds 5 of the base board 22, and held revolvable at the central hole 3B by a pillar 21A of the movable member 21 with the top covered with an operating knob 6 that rotates together. This constitution is similar to that of the prior art, too.

10 As shown in perspective view of Fig. 3, the base board 22 comprises a hole 22A for holding the movable member 21 movable, elastic contact reeds 5 for generating electric signal by having contact with the bottom surface of rotary contact wheel 3, and terminals 7 for taking the generated electric signal out. Within a hollow 22B of the base board 15 22, a pair of fixed contact points 23A and 23B for switch 23 are provided, and switch terminals 23C and 23D electrically coupled respectively with these contact points at an outer circumferential part. A pit 22C for affixing the L-shaped actuator 24 is provided in a central part of base board 22 at an outskirts of the hollow 22B. The L-shaped actuator 20 24 for actuating the switch 23 is comprised of arms of board form 24A and 24B, approximately rectangular to each other, and a holding pivot 24C located at the crossing part, as shown in Fig. 4.

A method of assembling a rotary encoder having built-in push switch according to the present embodiment is described in the following.

25 A domed movable contact point 23E is attached on the outer fixed contact point 23A disposed in the hollow 22B located at a rear part of base board 22, covering the inner fixed contact point 23B, and then a flexible

film 23F for dust-free is applied over the domed movable contact point to complete a switch 23.

The L-shaped actuator is affixed in the pit 22C of base board 22 in the following method. The holding pivot 24C is pushed into the
5 pit 22C of base board 22 at the enlarged part 22D (see Fig.2 and Fig.3) with the arm 24A of L-shaped actuator 24 perpendicular to the base board 22, and the arm 24B facing to switch 23, upon reaching the floor 22E of pit the holding pivot 24C is made to go horizontally in order to bring the entire body of L-shaped actuator 24 towards the switch 23.
10 The holding pivot 24C goes beyond a small bump 22F to be fixed into a cavity 22H formed by the pit floor 22E and a ceiling wall 22G, as shown with an arrow line in Fig.5. In this way the L-shaped actuator 24 is held movable with the holding pivot 24C as the axis. The bottom surface of arm 24B keeps touching with the top of the domed movable
15 contact 23E of said switch 23 via the flexible film 23F.

The movable member 21 is coupled with the base board 22 by inserting the holding part 21B of movable member 21 provided at an end into a hole 22A from underneath which is provided in the base board 22 at an end, then an extrusion 21D at the end of an arm 21C located
20 in a rear end of the movable member 21 will touch to an end of arm 24A of said L-shaped actuator 24. The rotary contact wheel 3 is attached revolvable to the movable member 21 at pillar 21A, and then the operating knob 6 is mounted to complete a rotary encoder with built-in push switch according to the present embodiment.

25 Now in the following, the operation of a rotary encoder with built-in push switch according to the present embodiment is described.

Pulse signals are generated by rotating the operating knob 6

with a force in the straight line direction as indicated with an arrow J in Fig.2; by the rotation of rotary contact wheel 3 with the pillar 21A of movable member 21 as the center of rotation the radial contact plates 3A disposed on the bottom surface of rotary contact wheel 3 slide
5 on the elastic contact reeds 5 of base board 22 to generate the pulse signals. The pulse signals are led to the outside through the terminals 7 providing a function as a rotary encoder. This operation is similar to that in the prior art.

During the above rotating operation of knob 6, although an
10 element of the force given to the knob in the push-in direction, or the force given to the movable member 21, reaches the domed movable contact point 23E of switch 23 via the arm 21C of movable member 21 and the L-shaped actuator 24, the switch 23 is not put into operation because the elastic force of domed movable contact 23E is set to be
15 strong enough to resist the element of force.

When the operating knob 6 is pressed in the direction as indicated by an arrow K in Fig.2 and Fig.6 with a force strong enough to overcome the force due to the elastic force of said domed movable contact 23E of switch 23, the rotary contact wheel 3 and the entire movable member
20 21 move to the direction as indicated by an arrow L with the holding part 21B of movable member 21, viz. the hole 22A of base board 22, as the axis. Then, the extrusion 21D provided at the end of arm 21C of movable member 21 pushes the end of arm 24A of L-shaped actuator 24 making the L-shaped actuator 24 rotate in the direction shown by an
25 arrow M in Fig.6 around the holding pivot 24C. The end tip of arm 24B pushes the top of the domed movable contact point 23E of switch 23 firmly downward. As the result, the domed movable contact point 23E is

reversed with snapping action, and the fixed contact point 23A and the fixed contact point 23B, or the switch terminals 23C and 23D, are shortcircuited as shown in Fig.6.

As soon as the push-in force given to the knob 6 is withdrawn,
5 the arm 24B of L-shaped actuator 24 is pushed up by the elastic restoring force of the domed movable contact point 23E, and movable member 21, rotary contact wheel 3, and knob 6 are pushed back to the original position as shown in Fig.1 and Fig.2.

The force needed to push the knob 6 in depends on the elastic
10 restoring force of the domed movable contact point 23E, and the relationship between the push-in force and the push-in stroke of the knob 6 are adjustable through adjustment of the location at which the arm 21C of movable member 21 presses the arm 24A of L-shaped actuator 24, and the location at which the arm 24B presses the domed movable
15 contact point 23E of switch 23. When the arm 21C is provided at a rear end of movable member 21 and the extrusion 21D at the end of the arm is made to press the extreme end of arm 24A of L-shaped actuator 24, as in the present embodiment, the push-in stroke becomes the largest.

A method of manufacturing the base board 22 according to the
20 present invention is shown in Fig.7. Where, numeral 25 denotes a hoop of electro-conductive metal sheet on which a gathering of the conductive members 10 and the grounding part 26 as well as the fixed contact points 23A and 23B for switch tied with the frame 25A and the conductive members 10 by means of the connecting sections 25B is continually stamped.
25 Numeral 22 denotes a resin-molded base board in which the conductive members 10, the grounding part 26, and the fixed contact points 23A and 23B for switch are inserted.

In the base board 22 thus formed, the conductive members 10, the elastic contact reeds 5, and the terminals 7 are shaped in the same way as in the prior art. And then, the connecting sections 25B of the grounding part 26 are cut at the cutting places 25C; of which a plate 5 26A to work as a lightning rod is bent upward, while plates 26B to become grounding terminals are bent downward, and the fixed contact points 23A and 23B for the switch are separated by cutting the cutting section 25D; and a base board 22 as shown in Fig.3 is completed.

A rotary encoder with built-in push switch made with the base 10 board 22 is mounted on an apparatus as shown in Fig.8, where the grounding terminals 26B are electrically coupled with a circuit board 14 of the apparatus at the ground sector 16, furthermore the grounding part 26 is located at a place closest to the outer surface of apparatus casing 13. By so mounting, the lightning rod 26A of grounding part 15 26 becomes an electro-conductive substance located closest to the operating knob 6, therefore the static electricity always jumps onto the lightning rod 26A and escapes to the grounding wire through the grounding terminals 26B. Thus the grounding is ensured without providing the metal board 15, which was indispensable with the prior 20 arts.

In Fig.3 and Fig.8 both describe the present embodiment, the plate to become lightning rod 26A of grounding part 26 is bent upward, while the plates to become the grounding terminals 26B downward; however, it is of course possible to dispose the plates for lightning rods 26A 25 up in the right and left, whereas the plate for grounding terminal 26B down in the middle.

Furthermore, according to the present constitution, as the

output terminals 7, the grounding terminals 26B, and the switch terminals 23C/23D are taken out to be formed and disposed in a same direction with almost equivalent dimensions, while the grounding part is built in a rotary encoder having push switch, the accuracy of terminal arrangement is high enough to undergo the automatic assembly, which enables to further reduce the number of steps for assembling an apparatus.

In the above embodiment, descriptions have been made using a rotary encoder having built-in push switch, which being an embodiment of the operation type electronic component, as the vehicle. However, it is of course possible to apply the above base board manufacturing method to the manufacture of normal operation type electronic components having no push switch.

USABILITY IN THE INDUSTRY

According to the present invention, a switch is constituted with fixed contact points provided on the base board of an operation type electronic component and a dome shaped movable contact point placed over the fixed contact points, and an L-shaped actuator is disposed between the switch and a movable member having an operating knob; thereby the movable member is prevented from putting the switch into operation during rotating operation of the knob by making use of the elastic force of the dome shaped movable contact point of switch, meanwhile the same elastic force is utilized for returning the movable member to the original position as soon as the push-in operation of knob is over. The conductive members and the grounding parts stamped in a same metal sheet are once fixed in a resin molded base board by means of an insert-molding method, and then electrically separated

afterwards; this brings about a grounding part positioned between the conductive members and the operating knob.

By taking the above described constitution, the total number of constituent components including those of the switch are reduced enabling to reduce the cost and the overall size of an operation type electronic component. Furthermore, by simply mounting a base board prepared through the above method on a circuit board of an apparatus an operation type electronic component is presented, wherein the static electricity generated from operating knob always escapes to the grounding part which is an electro-conductive substance located closest to the knob.

CLAIMS

1. An operation type electronic component comprising:

a rotary contact wheel having operating knob;

a base board in which a conductive member having an elastic
5 reed at one end for generating electrical signal by elastically
contacting with said rotary contact wheel and a terminal at the other
end for taking said electrical signal out is molded;

a movable member which holds said rotary contact wheel
revolvable and is coupled with said base board at an end part so as
10 movable in parallel with the surface of the base board;

a switch comprised of a fixed contact point molded at an end
part of said base board and a dome shaped movable contact point placed
over the fixed contact point; and

an L-shaped actuator which is comprised of a first arm
15 perpendicular to the surface of said base board and touching with an
edge of said movable member and a second arm extending from said first
arm in parallel with the surface of said base board towards said switch
to have contact with the dome shaped movable contact point of the switch,
and is attached revolvable to said base board with the crossing section
20 of said first and second arms as the pivot for actuating said switch.

2. The operation type electronic component of claim 1, wherein
an extrusion is provided at a certain part on outer circumference of
said movable member for contacting with said first arm at an end point
of said L-shaped actuator.

25 3. The operation type electronic component of claim 1, wherein
said L-shaped actuator is attached to the base board by first inserting
said pivot positioned at the crossing section of said L-shaped actuator





vertically into a pit provided in said base board and then lightly pushing in horizontal direction towards said switch.

4. The operation type electronic component of claim 2, wherein said L-shaped actuator is attached to the base board by first inserting
5 said pivot positioned at the crossing section of said L-shaped actuator vertically into a pit provided in said base board and then lightly pushing in horizontal direction towards said switch.

5. An operation type electronic component comprising:
a resin mold body in which a conductive member comprised of
10 a contact point and a terminal is housed;

an operating knob for switching the electrical signal to be generated at said conductive member; and

PART OF THIS SHEET HAS BEEN
REPLACED

a grounding electro-conductive substance insert-molded within said resin mold body so as to be positioned between the outer
15 circumference of said operating knob and said conductive member.

6. The operation type electronic component of claim 5, wherein said conductive member and said grounding electro-conductive substance are formed on a same metal material to be insert-molded in said resin mold body, and then said conductive member and said grounding
20 electro-conductive substance are electrically separated after being molded in said resin mold body.

7. The operation type electronic component of claim 5, wherein said terminal of said conductive member and a terminal of said grounding electro-conductive substance are coming out of the resin mold body in
25 a same directional arrangement with approximately the same length.

8. The operation type electronic component of claim 6, wherein said terminal of said conductive member and a terminal of said grounding



P13914

electro-conductive substance are coming out of the resin mold body in a same directional arrangement with approximately the same length.

