COMMUNICATIONS MODULE FOR ALTERNATE PATH GRAVEL PACKING, AND METHOD FOR COMPLETING A WELLBORE

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application 61/423,914, filed December 16, 2010.

BACKGROUND OF THE INVENTION

[0002] This section is intended to introduce various aspects of the art, which may be associated with exemplary embodiments of the present disclosure. This discussion is believed to assist in providing a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as admissions of prior art.

Field of the Invention

[0003] The present disclosure relates to the field of well completions. More specifically, the present invention relates to wireless communication and control systems within a wellbore. The application further relates to the remote actuation of tools in connection with wellbores that have been completed using gravel-packing.

Discussion of Technology

[0004] In the drilling of oil and gas wells, a wellbore is formed using a drill bit that is urged downwardly at a lower end of a drill string. After drilling to a predetermined depth, the drill string and bit are removed and the wellbore is lined with a string of casing. An annular area is thus formed between the string of casing and the formation. A cementing operation is typically conducted in order to fill or “squeeze” the annular area with cement. The combination of cement and casing strengthens the wellbore and facilitates the isolation of certain areas of the formation behind the casing.

[0005] It is common to place several strings of casing having progressively smaller outer diameters into the wellbore. The process of drilling and then cementing progressively smaller strings of casing is repeated several times until the well has reached total depth. The final string of casing, referred to as a production casing, is cemented into place and perforated. In some instances, the final string of casing is a liner, that is, a string of casing that is not tied back to the surface.

[0006] As part of the completion process, a wellhead is installed at the surface. The wellhead controls the flow of production fluids to the surface, or the injection of fluids into the wellbore. Fluid gathering and processing equipment such as pipes, valves and separators are also provided. Production operations may then commence.

[0007] It is sometimes desirable to leave the bottom portion of a wellbore open. In open-hole completions, a production casing is not extended through the producing zones and

perforated; rather, the producing zones are left uncased, or "open." A production string or "tubing" is then positioned inside the wellbore extending down below the last string of casing and across a subsurface formation.

[0008] There are certain advantages to open-hole completions versus cased-hole completions. First, because open-hole completions have no perforation tunnels, formation fluids can converge on the wellbore radially 360 degrees. This has the benefit of eliminating the additional pressure drop associated with converging radial flow and then linear flow through particle-filled perforation tunnels. The reduced pressure drop associated with an open-hole completion virtually guarantees that it will be more productive than an unstimulated, cased hole in the same formation.

[0009] Second, open-hole techniques are oftentimes less expensive than cased hole completions. For example, the use of gravel packs eliminates the need for cementing, perforating, and post-perforation clean-up operations.

[0010] A common problem in open-hole completions is the immediate exposure of the wellbore to the surrounding formation. If the formation is unconsolidated or heavily sandy, the flow of production fluids into the wellbore may carry with it formation particles, e.g., sand and fines. Such particles can be erosive to production equipment downhole and to pipes, valves and separation equipment at the surface.

[0011] To control the invasion of sand and other particles, sand control devices may be employed. Sand control devices are usually installed downhole across formations to retain solid materials larger than a certain diameter while allowing fluids to be produced. A sand control device typically includes an elongated tubular body, known as a base pipe, having numerous slotted openings. The base pipe is then typically wrapped or otherwise encompassed with a filtration medium such as a screen or wire mesh. This is referred to as a sand screen.

[0012] To augment sand control devices, particularly in open-hole completions, it is common to install a gravel pack. Gravel packing a well involves placing gravel or other particulate matter around the sand control device after the sand control device is hung or otherwise placed in the wellbore. To install a gravel pack, a particulate material is delivered downhole by means of a carrier fluid. The carrier fluid with the gravel together forms a gravel slurry. The slurry dries in place, leaving a circumferential packing of gravel. The gravel not only aids in particle filtration but also helps maintain formation integrity.

[0013] In an open-hole gravel pack completion, the gravel is positioned between a sand screen that surrounds a perforated base pipe and a surrounding wall of the wellbore. During production, formation fluids flow from the subterranean formation, through the gravel, through the screen, and into the inner base pipe. The base pipe thus serves as a part of the production string.

[0014] In some cases, a gravel pack is placed along a completion interval in a cased hole. This is particularly advantageous in unconsolidated sandstone formations. In this instance, a sand screen surrounding a perforated base pipe is placed within the wellbore along the subsurface formation, and a gravel pack is installed between the sand screen and the surrounding perforated production casing. The resulting gravel pack restricts the invasion of sand and fines.

[0015] A problem historically encountered with gravel-packing is that an inadvertent loss of carrier fluid from the slurry during the delivery process can result in premature sand bridges being formed at various locations along open-hole intervals. For example, in an inclined production interval or an interval having an enlarged or irregular borehole, a poor distribution of gravel may occur due to a premature loss of carrier fluid from the gravel slurry into the formation. The fluid loss may then cause voids to form in the gravel pack. Thus, a complete gravel-pack from bottom to top is not achieved, leaving the wellbore exposed to sand and fines infiltration.

[0016] The problem of sand bridging has been addressed through the use of alternate path technology, or "APT." Alternate path technology employs shunt tubes (or shunts) that allow the gravel slurry to bypass sand bridges or selected areas along a wellbore. Such alternate path technology is described, for example, in U.S. Pat. No. 5,588,487 entitled "Tool for Blocking Axial Flow in Gravel-Packed Well Annulus," and PCT Publication No. WO2008/060479 entitled "Wellbore Method and Apparatus for Completion, Production, and Injection," each of which is incorporated herein by reference in its entirety. An additional reference which discuss alternate path technology is M.D. Barry, *et al*., "Open-hole Gravel Packing with Zonal Isolation," SPE Paper No. 110,460 (November 2007).

[0017] In connection with alternate path sand screens, it has been proposed to utilize control lines and sensors. U.S. Pat. No. 7,441,605 entitled "Optical Sensor Use in Alternate Path Gravel Packing with Integral Zonal Isolation" offers devices and methods for monitoring wellbore conditions while conducting hydrocarbon production within an open-hole wellbore along multiple zones. There, a production tubing string assembly is provided with a plurality of packers ostensibly suitable for sealing between multiple individual zones downhole. The packers are set using hydraulic fluid pressure present within the bore of the production tubing string. In addition to the packers, the production tubing string includes production nipples having perforated screens for the removal of debris from produced fluids. One or more fiber optic sensor lines are disposed upon the outside of the screens. The sensor lines are disposed through the packers using a pass-through system to provide unbroken sensing line(s) to the surface of the wellbore. This allows temperature, pressure, or other wellbore conditions to be monitored at the surface in each of the individual zones of interest. In

addition, hydraulic control lines are disposed upon the outside of the screen to facilitate post-deployment fiber optic installation.

[0018] There are additional references that discuss control lines, including fiber optic lines, in an open-hole completion. These include U.S. Pat. No. 7,243,715; U.S. Pat. No. 7,431,085; U.S. Pat. No. 6,848,510; U.S. Pat. No. 6,817,410; and U.S. Pat. No. 6,681,854. However, these references require a physical path to provide communication from the surface to a downhole location, or vice versa. In subsea or extended reach wells, the complexity and reliability of such completions becomes a concern.

[0019] Therefore, a need exists for an improved sand control system that provides not only alternate flow path technology for gravel packing, but also an improved communication and control system. Further, a wireless system is needed in connection with sand control operations, particularly with alternate path sand screens.

SUMMARY OF THE INVENTION

[0020] A communications module for downhole operations is provided herein. The communications module has utility in connection with the production of hydrocarbon fluids from a wellbore. The wellbore may be completed with production casing, or may be an open-hole wellbore. The wellbore has a lower end defining a completion interval, which may extend through one, two, or more subsurface intervals.

[0021] In one embodiment, the communications module provides an inner mandrel. The inner mandrel is preferably dimensioned in accordance with a base pipe of a sand control device. Preferably, the inner body is fabricated from a non-metallic material such as ceramic or plastic.

[0022] The communications module may also comprise an outer shroud. The outer shroud is circumferentially disposed about the inner mandrel. The outer shroud preferably does not function as a filtering medium, but freely permits the flow of formation fluids there through. The outer shroud may be either concentric or eccentric to the inner mandrel.

[0023] The communications module also includes at least one alternate flow channel. The alternate flow channel represents one or more shunt tubes that are configured to provide a route for gravel slurry during a gravel packing operation. The gravel slurry will first flow in the annulus between the communications module and the surrounding wellbore. After that, the fluid phase in the slurry leaks off into the nearby reservoir formation or sand screens, and an annular pack is deposited in the annulus surrounding the communications module. Slurry will then bypass the communications module through alternate flow channels to provide gravel packing below the communications module.

[0024] The alternate flow channels may be, for example, a longitudinal annulus between outer and inner mandrels. The alternate flow channels may contain both transport tubes and packing tubes, where packing tubes are equipped with flow ports opening to the wellbore

annulus for slurry exit. The alternate flow channels may also be, for example, transport tubes disposed between the inner mandrel and the surrounding outer shroud. Alternatively still, the alternate flow channels may be a longitudinal annulus between an outer shroud and an inner mandrel.

[0025] The communications module also has a transmitter-receiver. The transmitter-receiver (i) receives a signal, and (ii) in response to the received signal, sends a separate instruction signal. The communications module further has an electrical circuit. Generally, the electrical circuit is programmed to (i) receive a signal and, in response to the received signal, deliver an actuating command signal.

[0026] In addition, the communications module includes a control line. The control line is configured to reside entirely within the subsurface completion interval of the wellbore and is not tied to the surface. The control line serves to convey an actuating command signal to a downhole tool. The downhole tool may be, for example, a sliding sleeve, a valve, or a packer. The control line operates in response to the command signal provided by the pre-programmed electrical circuit.

[0027] The communications module is configured to connect to a tubular joint in the wellbore. In one aspect, the tubular joint comprises a joint of a sand control device. The sand control device will have a sand screen equipped with alternate path channels.

[0028] In one embodiment, the transmitter-receiver is configured to (i) receive a signal from a downhole carrier and, (ii) in response to the received signal, send a separate instruction signal to the pre-programmed electrical circuit to actuate a downhole tool.

[0029] In one aspect, the communications module further comprises a sensing device. The sensing device may be a pressure gauge, a flow meter, a temperature gauge, a sand detector, an in-line tracer analyzer, a compaction strain detector, or combinations thereof. The sensing device is in electrical communication with the electrical circuit. Optionally, the electrical circuit is programmed to send a command signal to the control line to actuate the downhole tool in response to a selected reading by the sensing device.

[0030] In another aspect, the electrical circuit receives and records readings from the sensing device. The electrical circuit is pre-programmed to send a signal to the transmitter-receiver conveying the recorded readings. The transmitter-receiver, in turn, is programmed to (i) receive the recorded readings from the electrical circuit and, (ii) in response to the received recorded readings, wirelessly transmit the recorded readings to the downhole carrier.

[0031] A method for completing a wellbore is also disclosed herein. The method has utility in connection with the production of hydrocarbon fluids from a wellbore. The wellbore has a lower end defining a completion interval. The completion interval may extend through one, two, or more subsurface intervals.

[0032] In one embodiment, the method includes connecting a communications module to a tubular joint. The communications module may be in accordance with the communications module described above. The module will at least include alternate flow channels configured to provide an alternate flow path for a gravel slurry to partially bypass the communications module during a gravel packing procedure. This means that after gravel is packed in the annulus between the communications module and the surrounding wellbore, most slurry will bypass the communications module to provide gravel packing below the communications module.

[0033] The module will also have a control line. Beneficially, the control line is configured to reside entirely within the completion interval of the wellbore. The control line conveys an actuating command signal to a downhole tool within the wellbore.

[0034] The method will also include running the communications module and the connected tubular joint into the wellbore. The tubular joint may comprise a joint of a sand control device. The sand control device will have a sand screen with alternate flow channels. Alternatively, the tubular joint may be a packer with alternate path channels that can be set within the wellbore before a gravel packing operation begins. The communication module may also be built or embedded in a tubular joint.

[0035] The method also includes positioning the communications module and the tubular joint in the completion interval of the wellbore. Thereafter, the method includes injecting a gravel slurry into an annular region formed between the communications module and the surrounding wellbore as well as between the tubular joints and the surrounding wellbore. The gravel slurry travels through the at least one alternate flow channel in the tubular joints to allow the gravel slurry to at least partially bypass any premature sand bridges or zonal isolation in the annulus. In this way, gravel packing below the communications module is provided.

[0036] Preferably, the wellbore is completed for the production of hydrocarbon fluids. The method further includes producing production fluids from at least one subsurface interval along the completion interval of the wellbore for a period of time.

[0037] In one embodiment, the control line contains an electrical line. In this instance, the method may further comprise sending a signal from the electrical circuit through the electrical line to actuate the downhole tool. The downhole tool may be, for example, a sliding sleeve, a packer, or a valve.

[0038] The method preferably operates in conjunction with a downhole carrier. The downhole carrier is essentially an information tag that is pumped, dropped, or otherwise released into the wellbore. Information may flow from the downhole carrier to the transmitter-receiver, or from the transmitter-receiver to the downhole carrier. In either event,

the information is beneficially exchanged within the wellbore during wellbore operations without need of an electric line or a working string.

[0039] In one aspect, the transmitter-receiver is programmed to (i) receive a wireless signal from the downhole carrier and, (ii) in response to the received signal, send a separate instruction signal to the pre-programmed electrical circuit to actuate the downhole tool.

[0040] The communications module may include a sensing device. The sensing device may be, for example, a pressure gauge, a flow meter, a temperature gauge, a sand detector, a strain gauge such as a compaction strain detector, or an in-line tracer analyzer. The sensing device is in electrical communication with the electrical circuit. In this instance, the method further includes recording a reading by the sensing device in the electrical circuit. The electrical circuit may then send a signal from the electrical circuit to the control line to actuate the downhole tool in response to a selected reading by the sensing device. Alternatively, the electrical circuit may send its signal to the transmitter-receiver, which in turn sends a signal containing the recorded readings to the downhole carrier.

[0041] A separate method for actuating a downhole tool in a wellbore is also provided herein. The wellbore again has a lower end defining a completion interval. The completion interval may be an open-hole portion.

[0042] In one embodiment, the method includes running a communications module and a connected tubular joint into the wellbore. The communications module may be in accordance with the communications module described above. The module will at least include alternate flow channels configured to permit a gravel slurry to partially bypass the blocked annulus adjacent to the communications module during a gravel packing procedure. In this way, gravel packing is provided below the communications module. The module will also have a control line configured to reside entirely within the open-hole (or other) portion of the wellbore. The control line conveys an actuating command signal to a downhole tool within the wellbore.

[0043] The method also includes positioning the communications module and the tubular joint in the completion interval of the wellbore. Preferably, the tubular joint is part of a sand control device with alternate path channels. The sand control device will have a filtering screen. The method will then further include injecting a gravel slurry into an annular region formed between the sand control device and the surrounding wellbore. The sand control device will also have at least one alternate flow channel to allow the gravel slurry to at least partially bypass the joint of the sand control device during the gravel packing operation in case the downstream annulus is blocked by premature sand bridge or a zonal isolation device.

[0044] After the communications module and the tubular joint are positioned, the method includes releasing a first downhole carrier into the wellbore. The downhole carrier is

essentially an information tag that is pumped, dropped, or otherwise released into the wellbore. In this arrangement, the downhole carrier emits a first frequency signal. Thus, information flows from the downhole carrier to the transmitter-receiver within the wellbore. This may take place during wellbore operations without need of an electric line or a working string.

[0045] The method also includes sensing the first frequency signal at the transmitter-receiver. In response to the first frequency signal, a first instruction signal is sent from the transmitter-receiver to the electrical circuit.

[0046] The method further includes sending a first command signal from the electrical circuit. This is done in response to the first instruction signal to actuate a downhole tool. Actuating the downhole tool may comprise (i) moving a sliding sleeve to close off production from a selected zone within the completion interval, (ii) moving a sliding sleeve to open up production from a selected zone within the completion interval, (iii) or setting a packer.

[0047] Preferably, the communications module employs RFID technology. In such an embodiment, the pre-programmed electrical circuit is an RFID circuit. Further, the downhole carrier is an RFID tag that emits a radio-frequency signal, while the transmitter-receiver is an RF antenna.

[0048] Alternatively, the communications module employs acoustic technology. In such an instance, the downhole carrier comprises an acoustic frequency generator. The transmitter-receiver then comprises an acoustic antenna that receives acoustic signals from the downhole carrier, and in response sends an electrical signal to the pre-programmed electrical circuit.

[0049] In one embodiment, the method utilizes a second downhole carrier. In this instance, the method includes releasing a second downhole carrier into the wellbore. The second downhole carrier emits a second frequency signal. The second frequency signal is also sensed at the transmitter-receiver. In response to the second frequency signal, a second instruction signal is sent from the transmitter-receiver to the electrical circuit. Then, in response to the second instruction signal, a second command signal is sent from the electrical circuit to actuate a downhole tool.

[0050] The present disclosure also provides a method for monitoring conditions in a wellbore. The wellbore has a lower end defining a completion interval. The completion interval may be along a section of production casing, or within an open-hole portion. Monitoring takes place during hydrocarbon production operations after a gravel packing operation has been conducted.

[0051] In one embodiment, the method includes running a communications module and a connected tubular joint into the wellbore. The communications module may be in accordance with the communications module described above. The module will at least

include alternate flow channels configured to permit the gravel slurry to partially bypass the communications module during a gravel packing procedure. In this way, gravel packing is provided below the communications module.

[0052] The communications module will also have a control line. Beneficially, the control line is configured to reside entirely within the open-hole portion of the wellbore. The control line conveys an actuating command signal to a downhole tool within the wellbore.

[0053] The method also includes positioning the communications module and the tubular joint in the open-hole portion of the wellbore. Preferably, the tubular joint is part of a sand control device. The sand control device will have a filtering screen, and will also have at least one alternate flow channel. The method will then further include injecting a gravel slurry into an annular region formed between the sand control device and the surrounding open-hole portion of the wellbore. The sand control device will also have at least one alternate flow channel to allow the gravel slurry to at least partially bypass the joint of the sand control device during the gravel packing operation.

[0054] The method further includes producing hydrocarbon fluids from the open-hole portion of the wellbore. During production, the method includes sensing a downhole condition. The downhole condition may be, for example, temperature, pressure, flow rate, or other parameters. Sensing takes place using a sensing device that is in electrical communication with an electrical circuit. The method then includes sending readings of the sensed downhole conditions from the sensing device to the electrical circuit.

[0055] The method also includes the steps of:

releasing a downhole carrier into the wellbore;

sending the readings from the electrical circuit to the transmitter-receiver;

sending the readings from the transmitter-receiver to the downhole carrier;

retrieving the downhole carrier from the wellbore; and

downloading the recorded readings from the downhole carrier for analysis.

[0056] Different means may be employed for releasing the downhole carrier. In one instance, releasing the downhole carrier comprises releasing the downhole carrier from the open-hole portion of the wellbore at or below the communications module. This arrangement may include the use of a separate information tag. Thus, the method may include pumping a tag from a surface into the wellbore, the tag emitting a first frequency signal, sensing the first frequency signal at the transmitter-receiver, and in response to sensing the first frequency signal, releasing the downhole carrier into the wellbore.

[0057] Alternatively, releasing the downhole carrier may mean pumping the downhole carrier from a surface into the wellbore and down to the communications module.

BRIEF DESCRIPTION OF THE DRAWINGS

[0058] So that the manner in which the present inventions can be better understood, certain illustrations, charts and/or flow charts are appended hereto. It is to be noted, however, that the drawings illustrate only selected embodiments of the inventions and are therefore not to be considered limiting of scope, for the inventions may admit to other equally effective embodiments and applications.

[0059] Figure 1 is a cross-sectional view of an illustrative wellbore. The wellbore has been drilled through three different subsurface intervals, each interval being under formation pressure and containing fluids.

[0060] Figure 2 is an enlarged cross-sectional view of an open-hole completion of the wellbore of Figure 1. The open-hole completion at the depth of the three illustrative intervals is more clearly seen.

[0061] Figure 3A provides a cross-sectional view of a sand control device, in one embodiment. Shunt tubes are seen outside of a sand screen to provide an alternative flowpath for a particulate slurry.

[0062] Figure 3B provides a cross-sectional view of a sand control device, in an alternate embodiment. Shunt tubes are seen internal to a sand screen to provide an alternative flowpath for a particulate slurry.

[0063] Figure 4A is a cross-sectional view of a wellbore having a jointed sand control device therein. Transport tubes extend along the sand screen.

[0064] Figure 4B is a cross-sectional view of one of the sand control devices of Figure 4A, taken across line 4B-4B of Figure 4A. Transport tubes and packing tubes are seen external to a sand screen.

[0065] Figure 5A is a perspective view of a communications module in accordance with the present inventions, in one embodiment. The communications module has a pre-programmed electrical circuit and a communication device for transmitting or receiving commands from a downhole carrier.

[0066] Figure 5B is a cross-sectional view of the communications module of Figure 5A, taken across line 5B-5B. An optional motor and associated control line are shown, along with transport tubes and packing tubes for transporting gravel slurry.

[0067] Figure 6 is a perspective view of a communications module, in an alternate embodiment. Here, the communications module employs radio-frequency identification tags. The pre-programmed electrical circuit is an RFID circuit, and the communication device is an RFID antennae that communicates with an RFID tag.

[0068] Figure 7 is a flowchart that provides steps that may be used, in one embodiment, for completing a wellbore. The wellbore has a lower end defining an open-hole portion. The method uses a communications module having alternate flow channels.

[0069] Figure 8 is a flowchart that provides steps that may be used, in one embodiment, for actuating a downhole tool in a wellbore. The wellbore has a lower end defining an open-hole portion.

[0070] Figure 9 is flowchart that provides steps for a method for monitoring conditions in a wellbore. The wellbore has a lower end defining an open-hole portion.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

Definitions

[0071] As used herein, the term "hydrocarbon" refers to an organic compound that includes primarily, if not exclusively, the elements hydrogen and carbon. Hydrocarbons generally fall into two classes: aliphatic, or straight chain hydrocarbons, and cyclic, or closed ring hydrocarbons, including cyclic terpenes. Examples of hydrocarbon-containing materials include any form of natural gas, oil, coal, and bitumen that can be used as a fuel or upgraded into a fuel.

[0072] As used herein, the term "hydrocarbon fluids" refers to a hydrocarbon or mixtures of hydrocarbons that are gases or liquids. For example, hydrocarbon fluids may include a hydrocarbon or mixtures of hydrocarbons that are gases or liquids at formation conditions, at processing conditions or at ambient conditions (15° C and 1 atm pressure). Hydrocarbon fluids may include, for example, oil, natural gas, coal bed methane, shale oil, pyrolysis oil, pyrolysis gas, a pyrolysis product of coal, and other hydrocarbons that are in a gaseous or liquid state.

[0073] As used herein, the term "fluid" refers to gases, liquids, and combinations of gases and liquids, as well as to combinations of gases and solids, and combinations of liquids and solids.

[0074] As used herein, the term "subsurface" refers to geologic strata occurring below the earth's surface.

[0075] The term “subsurface interval” refers to a formation or a portion of a formation wherein formation fluids may reside. The fluids may be, for example, hydrocarbon liquids, hydrocarbon gases, aqueous fluids, or combinations thereof.

[0076] As used herein, the term "wellbore" refers to a hole in the subsurface made by drilling or insertion of a conduit into the subsurface. A wellbore may have a substantially circular cross section, or other cross-sectional shape. As used herein, the term "well", when referring to an opening in the formation, may be used interchangeably with the term "wellbore."

[0077] The term “tubular member” refers to any pipe, such as a joint of casing, a portion of a liner, or a pup joint.

[0078] The term "sand control device" means any elongated tubular body that permits an inflow of fluid into an inner bore or a base pipe while filtering out sand, fines and granular debris from a surrounding formation.

[0079] The term "alternate flow channels" means any collection of manifolds and/or shunt tubes that provide fluid communication through or around a downhole device such as a sand screen, a packer, or a communications module, to allow a gravel slurry to at least partially bypass the device in order to obtain full gravel packing of an annular region below the device.

Description of Specific Embodiments

[0080] The inventions are described herein in connection with certain specific embodiments. However, to the extent that the following detailed description is specific to a particular embodiment or a particular use, such is intended to be illustrative only and is not to be construed as limiting the scope of the inventions.

[0081] Certain aspects of the inventions are also described in connection with various figures. In certain of the figures, the top of the drawing page is intended to be toward the surface, and the bottom of the drawing page toward the well bottom. While wells commonly are completed in substantially vertical orientation, it is understood that wells may also be inclined and or even horizontally completed. When the descriptive terms "up and down" or "upper" and "lower" or "below" are used in reference to a drawing or in the claims, they are intended to indicate relative location on the drawing page or with respect to claim terms, and not necessarily orientation in the ground, as the present inventions have utility no matter how the wellbore is orientated.

[0082] **Figure 1** is a cross-sectional view of an illustrative wellbore **100**. The wellbore **100** defines a bore **105** that extends from a surface **101**, and into the earth's subsurface **110**. The wellbore **100** is completed to have an open-hole portion **120** at a lower end of the wellbore **100**. The wellbore **100** has been formed for the purpose of producing hydrocarbons for commercial sale. A string of production tubing **130** is provided in the bore **105** to transport production fluids from the open-hole portion **120** up to the surface **101**.

[0083] The wellbore **100** includes a well tree, shown schematically at **124**. The well tree **124** includes a shut-in valve **126**. The shut-in valve **126** controls the flow of production fluids from the wellbore **100**. In addition, a subsurface safety valve **132** is provided to block the flow of fluids from the production tubing **130** in the event of a rupture or catastrophic event above the subsurface safety valve **132**. The wellbore **100** may optionally have a pump (not shown) within or just above the open-hole portion **120** to artificially lift production fluids from the open-hole portion **120** up to the well tree **124**.

[0084] The wellbore **100** has been completed by setting a series of pipes into the subsurface **110**. These pipes include a first string of casing **102**, sometimes known as

surface casing or a conductor. These pipes also include at least a second **104** and a third **106** string of casing. These casing strings **104**, **106** are intermediate casing strings that provide support for walls of the wellbore **100**. Intermediate casing strings **104**, **106** may be hung from the surface, or they may be hung from a next higher casing string using an expandable liner or liner hanger. It is understood that a pipe string that does not extend back to the surface is normally referred to as a "liner."

[0085] In the illustrative wellbore arrangement of **Figure 1**, intermediate casing string **104** is hung from the surface **101**, while casing string **106** is hung from a lower end of casing string **104**. The lower casing string **106** terminates at **134**. Additional intermediate casing strings (not shown) may be employed. The present inventions are not limited to the type of casing architecture used.

[0086] Each string of casing **102**, **104**, **106** is set in place through cement **108**. The cement **108** isolates the various formations of the subsurface **110** from the wellbore **100** and each other. The cement **108** extends from the surface **101** to a depth "**L**" at a lower end of the casing string **106**. It is understood that some intermediate casing strings may not be fully cemented.

[0087] An annular region **204** is formed between the production tubing **130** and the surrounding string of casing **106**. A packer **206** seals the annular region **204** near the lower end "**L**" of the casing string **106**.

[0088] In many wellbores, a final casing string known as production casing is cemented into place at a depth where subsurface production intervals reside. For example, a production liner (not shown) may be hung from the lower end **134** of intermediate casing string **106**. The production liner would extend substantially down to a lower end **136** (not shown in **Figure 1**, but shown in **Figure 2**) of the open-hole portion **120** of the wellbore **100**. However, the illustrative wellbore **100** is completed as an open-hole wellbore. Accordingly, the wellbore **100** does not include a final casing string along the open-hole portion **120**.

[0089] In the illustrative wellbore **100**, the open-hole portion **120** traverses three different subsurface intervals. These are indicated as upper interval **112**, intermediate interval **114**, and lower interval **116**. Upper interval **112** and lower interval **116** may, for example, contain valuable oil deposits sought to be produced, while intermediate interval **114** may contain primarily water or other aqueous fluid within its pore volume. This may be due to the presence of native water zones, high permeability streaks, natural fractures connected to an aquifer, or fingering from injection wells. In this instance, there is a probability that water will invade the wellbore **100**. In addition, undesirable condensable fluids such as hydrogen sulfide gas or acid gases may invade the wellbore **100**.

[0090] Alternatively, upper **112** and intermediate **114** intervals may contain hydrocarbon fluids sought to be produced, processed and sold, while lower interval **116** may contain

some oil along with ever-increasing amounts of water. This may be due to coning, which is a rise of near-well hydrocarbon-water contact. In this instance, there is again the possibility that water will invade the wellbore **100**.

[0091] Alternatively still, upper **112** and lower **116** intervals may be producing hydrocarbon fluids from a sand or other permeable rock matrix, while intermediate interval **114** may represent a non-permeable shale or otherwise be substantially impermeable to fluids.

[0092] In any of these events, it is desirable for the operator to isolate selected zones or intervals. In the first instance, the operator will want to isolate the intermediate interval **114** from the production string **130** and from the upper **112** and lower **116** intervals so that primarily hydrocarbon fluids may be produced through the wellbore **100** and to the surface **101**. In the second instance, the operator will eventually want to isolate the lower interval **116** from the production string **130** and the upper **112** and intermediate **114** intervals so that primarily hydrocarbon fluids may be produced through the wellbore **100** and to the surface **101**. In the third instance, the operator will want to isolate the upper interval **112** from the lower interval **116**, but need not isolate the intermediate interval **114**. Solutions to these needs in the context of an open-hole completion are provided herein, and are demonstrated more fully in connection with the proceeding drawings.

[0093] In connection with the production of hydrocarbon fluids from a wellbore having an open-hole completion, it is not only desirable to isolate selected intervals, but also to limit the influx of sand particles and other fines. In order to prevent the migration of formation particles into the production string **130** during operation, sand control devices **200** have been run into the wellbore **100**. These are described more fully below in connection with **Figure 2** and with **Figures 4A** and **4B**.

[0094] Referring now to **Figure 2**, **Figure 2** is an enlarged cross-sectional view of the open-hole portion **120** of the wellbore **100** of **Figure 1**. The open-hole portion **120** and the three intervals **112**, **114**, **116** are more clearly seen. The upper **210'** and lower **210''** packer assemblies are also more clearly visible proximate upper and lower boundaries of the intermediate interval **114**, respectively. Finally, the sand control devices **200** along each of the intervals **112**, **114**, **116** are shown.

[0095] The sand control devices **200** contain an elongated tubular body referred to as a base pipe **205**. The base pipe **205** typically is made up of a plurality of pipe joints. The base pipe **205** (or each pipe joint making up the base pipe **205**) typically has small perforations or slots to permit the inflow of production fluids.

[0096] The sand control devices **200** also contain a filter medium **207**. The filter medium typically defines a metallic material wound or otherwise placed radially around the base pipes **205**. The filter medium **207** is preferably a combination of wire-mesh screens or wire-

wrapped screens fitted around the base pipe **205**. The mesh or screens serve as filters **207** to prevent the inflow of sand or other particles into the slotted (or perforated) pipe **205** and the production tubing **130**.

[0097] In addition to the sand control devices **200**, the wellbore **100** includes one or more packer assemblies **210**. In the illustrative arrangement of **Figures 1** and **2**, the wellbore **100** has an upper packer assembly **210'** and a lower packer assembly **210''**. However, additional packer assemblies **210** or just one packer assembly **210** may be used. The packer assemblies **210'**, **210''** are uniquely configured to seal an annular region (seen at **202** of **Figure 2**) between the various sand control devices **200** and a surrounding wall **201** of the open-hole portion **120** of the wellbore **100**.

[0098] Concerning the packer assemblies themselves, each packer assembly **210'**, **210''** contains at least two packers. These represent an upper packer **212** and a lower packer **214**. Each packer **212**, **214** has an expandable portion or element fabricated from an elastomeric or a thermoplastic material capable of providing at least a temporary fluid seal against the surrounding wellbore wall **201**.

[0099] It is understood that the packer assemblies **210'**, **210''** are merely illustrative; the operator may choose to use only a single packer. In either instance, it is preferred that the packer be able to withstand the pressures and loads associated with a gravel packing process. Typically, such pressures are from about 2,000 psi to 3,000 psi.

[0100] The upper **212** and lower **214** packer elements are set shortly before a gravel pack installation process. The packer elements **212**, **214** are preferably set by mechanically shearing a shear pin and sliding a release sleeve along an inner mandrel. Upward movement of the shifting tool (not shown) allows the packers **212**, **214** to be activated in sequence. The lower packer **214** is activated first, followed by the upper packer **212** as the shifting tool is pulled upward through the respective inner mandrels.

[0101] An intermediate swellable packer element **216** may also optionally be provided in the packer assemblies **210'**, **210''**. The swellable packer element **216** assists in long term sealing. The swellable packer element **216** may be bonded to the outer surface of the mandrel **211**. The swellable packer element **216** is allowed to expand over time when contacted by hydrocarbon fluids, formation water, or any chemical which may be used as an actuating fluid. As the packer element **216** expands, it forms a fluid seal with the surrounding zone, e.g., interval **114**. In one aspect, a sealing surface of the swellable packet element **216** is from about 5 feet (1.5 meters) to 50 feet (15.2 meters) in length; and more preferably, about 3 feet (0.9 meters) to 40 feet (12.2 meters) in length.

[0102] The use of a packer (or optionally, a multi-packer assembly) in a gravel-packing completion helps to control and manage fluids produced from different zones. In this

respect, a packer allows the operator to seal off an interval from either production or injection, depending on well function.

[0103] The packers will incorporate alternate flow channels to bypass gravel slurry during a gravel packing operation. In addition, the sand control devices **200** will have alternate flow channels. **Figures 3A** and **3B** provide cross-sectional views of sand screens with alternate flow channels, in different embodiments.

[0104] First, **Figure 3A** provides a cross-sectional view of a sand control device **200A**, in one embodiment. In **Figure 3A**, a slotted (or perforated) base pipe **205** is seen. This is in accordance with base pipe **205** of **Figures 1** and **2**. The central bore **105** is shown within the base pipe **205** for receiving production fluids during production operations.

[0105] An outer mesh **220** is disposed immediately around the slotted or perforated base pipe **205**. The outer mesh **220** preferably comprises a wire mesh or wires helically wrapped around the base pipe **205**, and serves as a screen. In addition, shunt tubes **225** are placed radially and equidistantly around the outer mesh **220**. This means that the sand control device **200A** provides an external embodiment for the shunt tubes **225**. The shunt tubes serve as alternate flow channels for delivering gravel slurry past any annular zone isolation or premature sand bridges which might form.

[0106] The configuration of the sand control device **200A** may be modified. In this respect, the shunt tubes **225** may be moved internal to the screen **220**.

[0107] **Figure 3B** provides a cross-sectional view of a sand control device **200B**, in an alternate embodiment. In **Figure 3B**, the slotted (or perforated) base pipe **205** is again seen. This is in accordance with base pipe **205** of **Figures 1** and **2**. The central bore **105** is shown within the base pipe **205** for receiving production fluids during production operations.

[0108] Shunt tubes **225** are placed radially and equidistantly around the base pipe **205**. The shunt tubes **225** reside immediately around the base pipe **230**, and within a surrounding screen **220**. This means that the sand control device **200B** provides an internal embodiment for the shunt tubes **225**.

[0109] An annular region **215** is created between the base pipe **205** and the surrounding outer mesh or screen **220**. The annular region **215** accommodates the inflow of production fluids in a wellbore. The outer mesh **220** is supported by a plurality of radially extending support ribs **222**. The ribs **222** extend through the annular region **215**.

[0110] **Figure 4A** presents a cross-sectional side view of a wellbore **400**. The wellbore **400** is generally in accordance with wellbore **100**. **Figure 4A** shows primarily the lower portion of the wellbore **400**, which has been completed as an open-hole. The open-hole portion extends down to the lower end **136**.

[0111] Sand control devices **200** have been set along the lower portion **120** of the wellbore **400**. The sand control devices **200** are jointed together. In addition, a single

packer **450** is provided along the sand control devices **200**. The packer **450** has been set against the surrounding wellbore wall **201**.

[0112] **Figure 4B** is a cross-sectional view of one of the sand control devices **200** of **Figure 4A**, taken across line **4B-4B**. In this view, a slotted or perforated base pipe **205** for the sand control device **200** is seen. The base pipe **205** defines a central bore **105** through which production fluids may flow. A sand screen **220** is disposed immediately around the base pipe **205**. The sand screen **220** may include multiple wire segments, mesh screen, wire wrapping, or other filtering medium to prevent a predetermined particle size.

[0113] The wellbore **400** has not yet undergone gravel packing. In order to transport gravel slurry in a gravel packing operation, shunt tubes **425** are provided along each of the sand screens **220**. In this embodiment, the shunt tubes **425** represent a combination of transport tubes **425a** and packing tubes **425b**. The transport tubes **425a** transport slurry down the annulus between the sand screens **220** and the wellbore wall **201**, while the packing tubes **425b** serve as arteries to deliver slurry into the annulus for gravel packing.

[0114] It is understood that the communication module and methods herein are not confined by the particular design and arrangement of sand screens **200** and shunt tubes **425** unless specifically indicated by the claims. Further information concerning the use of external shunt tubes is found in U.S. Pat. No. 4,945,991 and U.S. Pat. No. 5,113,935. Further information on internal shunt tubes is found at U.S. Pat. No. 5,515,915 and U.S. Pat. No. 6,227,303.

[0115] The control of downhole equipment has historically been accomplished through mechanical manipulation using a working string., Alternatively, downhole equipment has been actuated through the application of hydraulic pressure, or through a hydraulic or electrical control line that runs from the surface. However, it is difficult to utilize these traditional means when a gravel pack is in place. Therefore, it is desirable to have an autonomous tool that resides along an open-hole portion or other completion interval of a wellbore that can activate downhole equipment. Further, it is desirable to employ a communications module within a wellbore that accommodates alternate flow channels for a gravel packing operation, and that can activate downhole equipment without the need for control lines and cables that are run from the surface down to the sand screens.

[0116] **Figure 5A** is a perspective view of a communications module **500** in accordance with the present inventions, in one embodiment. The communications module **500** first has an inner mandrel **510**. The inner mandrel **510** defines a bore **505** therein. Production fluids flow through the bore **505** en route to the surface **101**.

[0117] The inner mandrel **510** has an inner diameter. The inner diameter is configured to generally match the inner diameter of the slotted or perforated base pipe of a sand screen, such as any of sand screens **200**. The inner mandrel **510** of the communications

module **500** threadedly connects to the base pipe of a joint of sand screen **200**. In this way, fluid communication is provided between the inner mandrel **510** and the base pipe.

[0118] The communications module **500** also has an outer shroud **520**. The outer shroud **520** is preferably fabricated from a metal screening material. The screening material does not function as a filtering medium, but simply protects components associated with the communications module **500**.

[0119] The outer shroud **520** defines an inner bore **515**. In the illustrative arrangement of **Figure 5A**, the bore **515** of the outer shroud **520** is eccentric to the bore **505** of the inner mandrel **510**. In this way, alternate flow channels can be accommodated. In the view of **Figure 5A**, two transport tubes **525a** are seen as the alternate flow channels.

[0120] **Figure 5B** is a cross-sectional view of the communications module **500** of **Figure 5A**. The view is taken across line **5B-5B** of **Figure 5A**. In this view, the two transport tubes **525a** are visible. In addition, two packing tubes **525b** are seen. The packing tubes **525b** receive slurry from the transport tubes **525a** during a gravel packing operation, and then deliver the slurry into the annulus within the wellbore through a plurality of openings along the packing tube **525b**.

[0121] When connecting the communications module **500** with a sand control device **200**, the transport tubes will be aligned. Thus, transport tubes **525a** of **Figure 5A** will line up with the transport tubes **425a** of **Figure 4A** for slurry delivery. Of course, it is understood that other arrangements for alternate flow channels may be employed. In this respect, the alternate flow channels may be either an external shunt application (such as shown in **Figure 3A**) or an internal shunt application (such as shown in **Figure 3B**).

[0122] The communications module **500** also has a communications line **530**. In the arrangement of **Figures 5A** and **5B**, the communications line **530** runs along and within the bore **505** of the inner mandrel **510**. However, the communications line **530** may optionally be disposed external to the inner mandrel **510**.

[0123] The communications line **530** may carry hydraulic fluid such as water or a light oil. In that instance, the communications line **530** serves as a hydraulic control line. Alternatively, the communications line **530** may have one or more electrically conductive lines, or fiber optic cables. In these instances, the communications line **530** may be considered as an electrical control line. In either embodiment, the communications line **530** operates to actuate a downhole tool (not shown in **Figure 5A**) by either delivering fluid or an electrical signal as a command.

[0124] The downhole tool may be, for example, a packer. Alternatively, the downhole tool may be a sliding sleeve along a mandrel or production tubing. Alternatively still, the downhole tool may be a valve or other inflow control device.

[0125] In order to deliver fluid or a signal to the downhole tool, the communications module **500** includes a pre-programmed electrical circuit. Such a circuit is shown schematically at **540** in both of **Figures 5A** and **5B**. The pre-programmed electrical circuit **540** may be designed to send a signal that actuates a hydraulic motor in response to receiving an actuation signal. An illustrative hydraulic motor is seen at **550**. Alternatively, the pre-programmed electrical circuit **540** may be designed to send an electrical signal (including, for example, a fiber optic light signal) in response to receiving an actuation signal. In one aspect, the pre-programmed electrical circuit **540** is further programmed to send the signal following a predetermined period of time, or in response to sensing a certain condition such as a downhole temperature, pressure, or strain.

[0126] The communications module **500** also includes a transmitter-receiver. An illustrative transmitter-receiver is shown at **560**. The illustrative transmitter-receiver **560** is a transceiver, meaning that the device **560** incorporates both a transmitter and a receiver which share a common circuitry and housing. The transmitter-receiver receives a signal provided through a downhole carrier **565**, and then sends its own signal to the pre-programmed electrical circuit **540**.

[0127] The downhole carrier **565** is designed to send a signal to the transmitter-receiver **560**. Thus, at a designated time, the operator may drop the downhole carrier **565** into the wellbore, and then pump it downhole. The downhole carrier **565** is shown in **Figure 5A** moving into the inner mandrel **510** in the direction indicated by Arrow "**C**." The downhole carrier **565** will ultimately pass through the bore **505** of the communications module **500**. There, the communications module **500** will be wirelessly sensed by the transmitter-receiver **560**. The transmitter-receiver **560**, in turn, will send a wired or wireless signal to the pre-programmed electrical circuit **540**.

[0128] The transmitter-receiver **560** may be tuned to send different signals in response to signals that it receives from downhole carriers **565** having different frequencies. Thus, for example, if the operator wishes to slide a sleeve, it may drop a first downhole carrier **565** emitting a signal at a first frequency, which prompts the transmitter-receiver **560** to send a first signal to the pre-programmed electrical circuit **540** at its own first frequency, which then actuates the sleeve through the appropriate hydraulic or electrical command. Later, the operator may wish to re-operate the sleeve again or set an annular packer. The operator then drops a second downhole carrier **565** emitting a signal at a second frequency, which prompts the transmitter-receiver **560** to send a second signal to the pre-programmed electrical circuit **540** at its own second frequency, which then actuates the packer or the sleeve through the appropriate hydraulic or electrical command.

[0129] In one preferred embodiment, the communications module operates through radio-frequency identification technology, or RFID. **Figure 6** is a perspective view of a

communications module **600**, in an alternate embodiment, wherein the communications module **600** employs RFID components.

[0130] The communications module **600** of **Figure 6** includes an inner mandrel **610**. The inner mandrel **610** defines a bore **605** therein. Production fluids flow through the bore **605** en route to the surface **101**.

[0131] The inner mandrel **610** has an inner diameter. The inner diameter is configured to generally match the inner diameter of a base pipe **205** of a sand screen, such as any of sand screens **200**. The inner mandrel **610** of the communications module **600** threadedly connects to the base pipe of a joint of sand screen **200**. In this way, fluid communication is provided between the inner mandrel **610** and the base pipe (such as the perforated base pipe **205** seen in **Figure 2** and **Figure 4B**).

[0132] The communications module **600** also has an outer shroud **620**. The outer shroud **620** is preferably fabricated from a metal screening material. The screening material does not function as a filtering medium, but simply protects components within the communications module **600**.

[0133] The outer shroud **620** defines an inner bore **615**. The bore **615** of the outer shroud **620** is substantially concentric to the bore **605** of the inner mandrel **610**. In this way, external alternate flow channels can be accommodated. In the view of **Figure 6A**, two transport tubes **618** are partially seen as the alternate flow channels.

[0134] The communications module **600** also has a communications line **630**. In the illustrative arrangement of **Figure 6**, the communications line **630** runs along and within the bore **615** of the outer shroud **620**. Thus, the communications line **630** is placed outside of the inner mandrel **610**. It is understood that the communications line **630** may optionally be disposed internal to the inner mandrel **610**.

[0135] The communications line **630** functions in the same way as communications line **530** of **Figures 5A** and **5B**. In this respect, the communications line **630** may carry hydraulic fluid such as water or a light oil. In that instance, the communications line **630** serves as a hydraulic control line. Alternatively, the communications line **630** may have one or more electrically conductive lines, or fiber optic cables. In these instances, the communications line **630** may be considered as an electrical control line. In either embodiment, the communications line **630** conveys an actuating signal to downhole tool by either delivering fluid under pressure or by delivering an electrical command signal.

[0136] In order to deliver fluid or a signal to the downhole tool, the communications module **600** includes an RFID circuit. Such a circuit is shown somewhat schematically at **640**. The RFID circuit **640** may be designed to send a signal that actuates a hydraulic motor in response to receiving an actuation signal. This causes the motor to pump fluid through the control line **630** under pressure. Alternatively, the RFID circuit **640** may be designed to

send an electrical signal (including, for example, a fiber optic light signal) in response to receiving an actuation signal.

[0137] The communications module **600** also includes a transmitter-receiver. In this embodiment, the transmitter-receiver is an RF antenna. An illustrative RF antenna is shown at **660**. The illustrative antennae **660** is a coil wrapped around or within the base pipe **610**. The base pipe **610** is fabricated from a non-metallic material such as ceramic or plastic to accommodate the metallic coil. The RF antenna **660** receives a signal provided through a downhole carrier **665**, and then sends its own signal to the pre-programmed RFID circuit **640**.

[0138] In the RFID embodiment of **Figure 6**, the downhole carrier **665** is a radio-frequency ("RFID") tag. The RFID tag **665** is designed to send a signal to the RF antenna **660**. Generally, the RFID tag **665** consists of an integrated circuit that stores, processes and transmits the RF signal to the receiving antenna **660**.

[0139] At a designated time, the operator may drop an RFID tag **665** into the wellbore, and then pump it or otherwise allow it to drop from the surface downhole. The tag **665** is shown in **Figure 6** moving into the inner mandrel **610** in the direction indicated by Arrow "**C**." The tag **665** will ultimately pass through the bore **605** of the communications module **600**. There, the RFID tag **665** will be wirelessly sensed by the RF antenna **660**. The RF antenna **660**, in turn, will send a wired or wireless signal to the pre-programmed RFID circuit **640**.

[0140] The communications module **600** (or RFID module) may have other components. For example, the module **600** may include the hydraulic motor **550** of **Figure 5A**. The module **600** may also include devices for sensing conditions downhole such as pressure gauges, temperature gauges, strain gauges, flow meters, in-line tracer analyzers, and sand detectors. The RFID circuit **640** may actuate a downhole device such as a sliding sleeve or a packer or a valve in response to readings made by such sensing devices.

[0141] The communications module **600** will also have a battery (not shown). The battery provides power for the RFID circuit. The battery may also provide power to the sensing equipment and any hydraulic motor.

[0142] It is also noted that the flow of information could be reversed. In this respect, information sensed by sensing equipment and sent to the RFID circuit **640** may be sent to the RF antenna **660**, and then communicated to the RFID tag **665**. The tag **665** is then pumped back to the surface **101** and retrieved. Information received and carried by the tag **665** is downloaded and analyzed.

[0143] In yet another embodiment, the transmitter-receiver that is used in a communications module is an acoustic transponder. In this arrangement, the transmitter-receiver may receive acoustic signals and, upon detecting a predetermined acoustic frequency, send an electrical signal.

[0144] Based upon the downhole tools described above, novel methods for completing an open-hole (or other) wellbore may be provided herein. The methods may utilize the above described communications module in various embodiments for completing a wellbore (method **700**), for actuating a downhole tool (method **800**) or for monitoring wellbore conditions (method **800**) (all described below), or all three.

[0145] **Figure 7** provides a method **700** for completing a wellbore. The wellbore has a lower end defining a completion interval. The completion interval may be either a cased hole portion or an open-hole portion.

[0146] The method **700** first includes connecting a communications module to a tubular joint. This is seen at Box **710**. The communications module may be in accordance with any of the communications modules described above. The module will at least include alternate flow channels configured to permit a gravel slurry to partially bypass the communications module during a gravel packing procedure.

[0147] The module will also have a control line. The control line is configured to reside entirely within the open-hole portion of the wellbore. The control line conveys an actuating command signal to a downhole tool within the wellbore.

[0148] The method **700** will also include running the communications module and the connected tubular joint into the wellbore. This is provided at Box **720**. The tubular joint may comprise a joint of a sand control device. The sand control device will have a sand screen and alternate flow channels. Alternatively, the tubular joint may be a packer that can be set within the completion interval before a gravel packing operation begins. Such a packer will also have alternate flow channels so that gravel may be packed in the annulus below the packer.

[0149] The method **700** also includes positioning the communications module and the tubular joint in the producing portion of the wellbore. This is seen at Box **730**. The producing portion may be an open-hole portion, or a portion of a cased wellbore that is perforated. Thereafter, the method includes injecting a gravel slurry into an annular region formed between the communications module and the surrounding wellbore. This is shown at Box **740**. The gravel slurry also travels through the at least one alternate flow channel to allow the gravel slurry to partially bypass the communications module. In this way, the completions interval is gravel-packed below the communications module.

[0150] Preferably, the wellbore is completed for the production of hydrocarbon fluids. The method **700** further includes producing production fluids from the completion interval. The producing step is provided at Box **750**. In one aspect, the completion interval may be at least one subsurface interval of an open-hole portion in the wellbore.

[0151] In one embodiment, the control line contains an electrical line. In this instance, the method **700** may further comprise sending a command signal from the electrical circuit

through the electrical line to actuate the downhole tool. This is seen at Box **760**. The downhole tool may be, for example, a sliding sleeve, a valve, or a packer.

[0152] The method **700** operates in conjunction with a downhole carrier. The downhole carrier is essentially an information tag that is pumped, dropped, or otherwise released into the wellbore. Information may flow from the downhole carrier to the transmitter-receiver, or from the transmitter-receiver to the downhole carrier. In the first aspect, the transmitter-receiver is programmed to (i) receive a signal from the downhole carrier and, (ii) in response to the received signal, send a separate instruction signal to the programmed electrical circuit to actuate the downhole tool. In the second aspect, the transmitter-receiver receives information from the electrical circuit and sends it to the downhole carrier. In either event, the information is beneficially exchanged within the wellbore during wellbore operations without need of an electric line or a working string.

[0153] The method **700** also optionally includes setting a packer in the producing portion of the wellbore. This is provided at Box **770**. The packer has a sealing element to provide a seal of the annulus between the sand control device and the surrounding formation. This enables the isolation of a selected interval. The packer is preferably set before the step of injecting a gravel slurry in Box **740**.

[0154] The communications module may also include a sensing device. The sensing device may be, for example, a pressure gauge, a flow meter, a temperature gauge, a strain gauge, a sand detector, or an in-line tracer analyzer. The sensing device is in electrical communication with the electrical circuit. In this instance, the method **700** further includes recording a reading by the sensing device in the electrical circuit. This is provided at Box **780**.

[0155] The electrical circuit may send a signal from the electrical circuit to the control line to actuate the downhole tool in response to a selected reading by the sensing device. This is shown at Box **790A**. Alternatively, the electrical circuit may send its signal to the transmitter-receiver, which in turn transmits a wireless signal containing the recorded readings to the downhole carrier. This is shown at Box **790B**.

[0156] A more detailed progression of steps for Box **790B** is as follows:

record a reading by the sensing device in the electrical circuit;

send a signal from the electrical circuit to the transmitter-receiver conveying the recorded readings;

receive the signal with the recorded readings from the electrical circuit at the transmitter-receiver;

wirelessly transmit the recorded readings from the transmitter-receiver to the downhole carrier; and

deliver the downhole carrier to a surface for data analysis.

[0157] A separate method for actuating a downhole tool is also provided herein. **Figure 8** is a flow chart showing steps for a method **800** for actuating a downhole tool in a wellbore, in one embodiment. The wellbore again has a lower end defining a completion interval. The completion interval is preferably an open-hole portion.

[0158] In one embodiment, the method **800** includes running a communications module and a connected tubular joint into the wellbore. This is seen at Box **810**. The communications module may be in accordance with the communications module described above. The module will at least include alternate flow channels configured to permit a gravel slurry to bypass the communications module during a gravel packing procedure. The module will also have a control line configured to reside entirely within the open-hole portion of the wellbore. The control line conveys an actuating command signal to a downhole tool within the wellbore.

[0159] The method **800** also includes positioning the communications module and the tubular joint in the open-hole portion of the wellbore. Preferably, the tubular joint is part of a sand control device. The sand control device will have a filtering screen, and will also have at least one alternate flow channel. The method **800** will then further include injecting a gravel slurry into an annular region formed between the sand control device and the surrounding open-hole portion of the wellbore. This is seen at Box **830**. The sand control device will also have at least one alternate flow channel to allow the gravel slurry to at least partially bypass the joint of the sand control device during the gravel packing operation.

[0160] After the communications module and the tubular joint are positioned, the method **800** includes releasing a first downhole carrier into the wellbore. This is provided at Box **840**. The downhole carrier is essentially an information tag that is pumped, dropped, or otherwise released into the wellbore. In this arrangement, the downhole carrier emits a first frequency signal. Thus, information flows from the downhole carrier to the transmitter-receiver within the wellbore. This may take place during wellbore operations without need of an electric line or a working string extending from the surface.

[0161] The method **800** also includes sensing the first frequency signal at the transmitter-receiver. This is shown at Box **850**. In response to the first frequency signal, a first instruction signal is sent from the transmitter-receiver to the electrical circuit. This is indicated at Box **860**.

[0162] The method **800** further includes sending a first command signal from the electrical circuit. This is done in response to the first instruction signal, and is for the purpose of actuating a downhole tool. The command signal step is provided at Box **870**. Actuating the downhole tool may comprise, for example, (i) moving a sliding sleeve to close off production from a selected interval within the open-hole portion, (ii) moving a sliding sleeve to open up production from a selected interval within the open-hole portion, (iii) or

setting a packer. The packer is preferably set before the step of injecting a gravel slurry in Box **830**.

[0163] Preferably, the communications module employs RFID technology. In such an embodiment, the pre-programmed electrical circuit is an RFID circuit. Further, the downhole carrier is an RFID tag that emits a radio-frequency signal, while the transmitter-receiver is an RF antenna.

[0164] Alternatively, the communications module employs acoustic technology. In such an instance, the downhole carrier comprises an acoustic frequency generator. The transmitter-receiver then comprises an acoustic antenna that receives acoustic signals from the downhole carrier, and in response sends an electrical signal to the pre-programmed electrical circuit.

[0165] In one embodiment, the method **800** may utilize a second downhole carrier. In this instance, the method **800** includes releasing a second downhole carrier into the wellbore. This is provided at Box **880**. The second downhole carrier emits a second frequency signal. The second frequency signal is sensed at the transmitter-receiver. In response to the second frequency signal, a second instruction signal is sent from the transmitter-receiver to the electrical circuit. Then, in response to the second instruction signal, a second command signal is sent from the electrical circuit to actuate a downhole tool. These additional steps are seen collectively in Box **890**.

[0166] In connection with the method **800**, it is preferred that the tubular joint connected to the inner mandrel is a joint of a sand control device. This joint will also have at least one alternate flow channel. The method **800** may then further include injecting a gravel slurry into an annular region formed between the sand control device and the surrounding wellbore. During the injection process, a portion of the gravel slurry travels through the at least one alternate flow channel to allow the gravel slurry to partially bypass the joint of the sand control device. In this way, the completions interval is gravel-packed below the communications module.

[0167] The present disclosure finally provides a method for monitoring conditions in a wellbore. The wellbore again has a lower end defining a completion interval. The completion interval is preferably an open-hole portion. Monitoring takes place during hydrocarbon production operations after a gravel packing operation has been conducted.

[0168] **Figure 9** provides a flow chart showing steps for a method **900** for monitoring wellbore conditions. In one embodiment, the method **900** includes running a communications module and a connected tubular joint into the wellbore. This is seen at Box **905**. The communications module may be in accordance with the communications module described above. The module will at least include alternate flow channels configured to permit the gravel slurry to partially bypass the communications module during a gravel

packing procedure. The module will also have a control line configured to reside entirely within the open-hole portion (or other completion interval) of the wellbore. The control line conveys an actuating command signal to a downhole tool within the wellbore. Further, the module will have an inner mandrel defining a bore through which production fluids may flow.

[0169] In support of the monitoring method **900**, the communications module will also have a sensing device. The sensing device may sense for temperature, pressure, flow rate, or other fluid or formation conditions. The sensing device is in electrical communication with a programmed electrical circuit. The electrical circuit may record readings taken by the sensing device.

[0170] The method **900** also includes positioning the communications module and the tubular joint in the producing portion of the wellbore. This is provided at Box **910**. Preferably, the tubular joint is part of a sand control device. The sand control device will have a filtering screen, and will also have at least one alternate flow channel. The method **900** will then further include placing a gravel pack along a substantial portion of the producing portion of the wellbore. This is shown at Box **915**.

[0171] The method **900** also includes producing hydrocarbon fluids from the wellbore. This is seen at Box **920**. The method **900** also includes sensing a downhole condition. This is noted at Box **925**. The sensing is done by the sensing device during production operations. Sensing takes place using a sensing device that is in electrical communication with an electrical circuit.

[0172] The method **900** further includes sending readings from the sensing device to the electrical circuit. This is provided at Box **930**. From there, readings are sent from the electrical circuit to a transmitter-receiver. This is given at Box **935**.

[0173] In the method **900**, a downhole carrier is employed. Thus, the method **900** also includes releasing a downhole carrier into the wellbore. This is demonstrated at Box **940**. The downhole carrier is preferably an RFID tag that emits or receives a radio-frequency signal. In this instance, the pre-programmed electrical circuit is an RFID circuit, and the transmitter-receiver is an RF antenna.

[0174] Different means may be employed for releasing the downhole carrier. The downhole carrier may be released from the surface. In this instance, the operator may pump the downhole carrier down into the wellbore, or it may sink gravitationally. Alternatively, releasing the downhole carrier comprises releasing the downhole carrier from a receptacle in the open-hole portion of the wellbore at or below the communications module. This latter arrangement may include the use of a separate information tag. Thus, the method may include pumping a tag from the surface into the wellbore, the tag emitting a first frequency signal, sensing the first frequency signal at the transmitter-receiver, and in response to sensing the first frequency signal, releasing the downhole carrier into the wellbore.

[0175] In either instance, the downhole carrier passes through the inner mandrel or otherwise comes into close proximity with the transmitter-receiver along the inner mandrel. The readings are then sent to the downhole carrier. Thus, the method **900** further includes the step of transmitting the readings from the transmitter-receiver to the downhole carrier. This is provided at Box **945**. The transmitting step of Box **945** is done wirelessly.

[0176] It is desirable to obtain the readings at the surface for analysis. Since there is no electric or fiber optic line extended from the gravel pack to the surface, the downhole carrier must be retrieved. Therefore, the method **900** includes the step of retrieving the downhole carrier from the wellbore. This is indicated at Box **950**. Then, the method **900** includes downloading the recorded readings for analysis. This is shown at Box **955**.

[0177] While it will be apparent that the inventions herein described are well calculated to achieve the benefits and advantages set forth above, it will be appreciated that the inventions are susceptible to modification, variation and change without departing from the spirit thereof. Improved methods for completing a wellbore are provided so as to seal off one or more selected subsurface intervals. An improved communications module is also provided. The inventions permit an operator to control a downhole tool or monitor a downhole condition wirelessly.

CLAIMS

What is claimed is:

1. A communications module for downhole operations along a completion interval of a wellbore, comprising:

an inner mandrel;

at least one alternate flow channel along the inner mandrel to provide a route for gravel slurry to partially bypass the communications module during a gravel packing operation and enable gravel packing below the communications module;

a transmitter-receiver for (i) receiving a signal, and (ii) in response to the received signal, sending a separate instruction signal;

an electrical circuit programmed to (i) receive a signal and, in response to the received signal, deliver an actuating command signal; and

a control line configured to reside entirely within the completion interval of the wellbore, the control line conveying the actuating command signal provided by the electrical circuit;

wherein the communications module is configured to connect to a tubular joint in a wellbore.

2. The communications module of claim 1, wherein the at least one alternate flow channel comprises at least one transport tube or longitudinal bypass annulus.

3. The communications module of claim 1, wherein the completion interval represents an open-hole portion of the wellbore.

4. The communications module of claim 3, wherein:

the communications module further comprises an outer shroud circumferentially disposed about the inner mandrel, the outer shroud permitting the flow of fluids there through; and

the at least one transport tube resides (i) in a bore of the outer shroud between the inner mandrel and the outer shroud, or (ii) outside of the outer shroud.

5. The communications module of claim 3, wherein the tubular joint comprises a joint of a sand control device.

6. The communications module of claim 1, wherein:

the transmitter-receiver is pre-programmed to (i) receive a wireless signal emitted from a downhole carrier and, (ii) in response to the received signal, send a separate instruction signal to the electrical circuit to actuate a downhole tool.

7. The communications module of claim 1, wherein the communications module further comprises a sensing device.

8. The communications module of claim 7, wherein:

the sensing device comprises a pressure gauge, a flow meter, a temperature gauge, a sand detector, a strain gauge, an in-line tracer analyzer, or combinations thereof; and

the sensing device is in electrical communication with the electrical circuit.

9. The communications module of claim 8, wherein the electrical circuit is programmed to send a command signal to the control line to actuate a downhole tool in response to a selected reading by the sensing device.

10. The communications module of claim 8, wherein:

the electrical circuit receives and records readings from the sensing device;

the electrical circuit is programmed to send a signal to the transmitter-receiver conveying the recorded readings; and

the transmitter-receiver is programmed to (i) receive the recorded readings from the electrical circuit and, (ii) in response to the received recorded readings, wirelessly transmit the recorded readings to a downhole carrier.

11. The communications module of claim 6, wherein:

the pre-programmed electrical circuit is an RFID circuit;

the downhole carrier is an RFID tag that emits a radio-frequency signal; and

the transmitter-receiver is an RF antenna.

12. The communications module of claim 6, wherein:

the downhole carrier comprises an acoustic frequency generator; and

the transmitter-receiver comprises an acoustic antenna that receives acoustic signals from the downhole carrier, and in response sends the instruction signal to the pre-programmed electrical circuit to actuate the downhole tool.

13. The communications module of claim 6, wherein:

the control line contains a hydraulic fluid; and

the communications module further comprises a hydraulic motor configured to provide pressure to the hydraulic fluid to actuate the downhole tool in response to the command signal from the pre-programmed electrical circuit.

14. The communications module of claim 6, wherein:

the control line contains an electrical line; and

the electrical circuit is programmed to send an electrical command signal through the electrical line to actuate the downhole tool.

15. The communications module of claim 1, wherein the downhole tool comprises a sliding sleeve, a packer, a valve, or combinations thereof.

16. The communications module of claim 3, wherein the tubular joint comprises a zonal isolation packer also having at least one alternate flow channel.

17. A method for completing a wellbore, the wellbore having a lower end defining a completion interval, and the method comprising:

connecting a communications module to a tubular joint, the communications module comprising:

at least one alternate flow channel configured to permit a gravel slurry to partially bypass the communications module during a gravel packing procedure, and

a control line configured to reside entirely within the wellbore for conveying an actuating command signal to a downhole tool;

running the communications module and the connected tubular joint into the wellbore;

positioning the communications module and the tubular joint in the wellbore; and

injecting a gravel slurry into an annular region formed between the communications module and the surrounding wellbore, while providing that a portion of the gravel slurry travels through the at least one alternate flow channel to allow the gravel slurry to partially bypass the communications module and provide gravel packing below the communications module.

18. The method of claim 17, wherein the communications module further comprises:

an inner mandrel; and

an outer shroud circumferentially disposed about the inner mandrel, the outer shroud permitting the flow of fluids there through.

19. The method of claim 17, wherein the communications module further comprises:

a transmitter-receiver for (i) receiving a signal, and (ii) in response to the received signal, sending a separate instruction signal; and

an electrical circuit programmed to (i) receive a signal and, in response to the received signal, deliver an actuating command signal.

20. The method of claim 19, wherein:

the completion interval defines one or more zones of interest along an open-hole portion of the wellbore;

the wellbore is completed for fluid production; and

the method further comprises producing production fluids from at least one subsurface interval along the open-hole portion of the wellbore for a period of time.

21. The method of claim 18, wherein:

the tubular joint comprises a joint of a sand control device also having at least one alternate flow channel;

the inner mandrel is dimensioned to connect to a base pipe of a sand control device; and

injecting a gravel slurry further comprises injecting the slurry into an annular region formed between the sand control device and the surrounding wellbore, while providing that a portion of the gravel slurry travels through the at least one alternate flow channel to allow the gravel slurry to at least partially bypass the joint of the sand control device.

22. The method of claim 19, wherein:

the transmitter-receiver is programmed to (i) receive a wireless signal from a downhole carrier and, (ii) in response to the received signal, send a separate instruction signal to the electrical circuit to actuate the downhole tool.

23. The method of claim 22, wherein:

the control line contains an electrical line; and

the method further comprises sending a command signal from the electrical circuit through the electrical line to actuate the downhole tool.

24. The method of claim 19, wherein the communications module further comprises a sensing device.

25. The method of claim 24, wherein:

the sensing device comprises a pressure gauge, a flow meter, a temperature gauge, a sand detector, a strain gauge, an in-line tracer analyzer, or combinations thereof; and

the sensing device is in electrical communication with the electrical circuit.

26. The method of claim 25, further comprising:

recording a reading by the sensing device in the electrical circuit; and

sending a signal from the electrical circuit to the control line to actuate the downhole tool in response to a selected reading by the sensing device.

27. The communications module of claim 26, wherein:

the control line contains a hydraulic fluid;

the communications module further comprises a hydraulic motor; and

sending a signal from the electrical circuit to the control line comprises sending a signal from the electrical circuit to the hydraulic motor to provide pressure to the hydraulic fluid, thereby actuating the downhole tool in response to the command signal from the electrical circuit.

28. The method of claim 27, further comprising:

recording a reading by the sensing device in the electrical circuit;

sending a signal from the electrical circuit to the transmitter-receiver conveying the recorded readings;

receiving the signal with the recorded readings from the electrical circuit at the transmitter-receiver;

wirelessly transmitting the recorded readings from the transmitter-receiver to the downhole carrier; and

delivering the downhole carrier to a surface for data analysis.

29. The method of claim 17, wherein the downhole tool comprises a sliding sleeve or a packer, or a valve.

30. A method for actuating a downhole tool in a wellbore, the wellbore having a lower end defining a completion interval, and the method comprising:

running a communications module and a connected tubular joint into the wellbore, the communications module comprising:

a pre-programmed electrical circuit,

a transmitter-receiver,

at least one alternate flow channel configured to allow a gravel slurry to partially bypass the communications module during a gravel packing procedure and permit gravel packing below the communications module, and

a control line configured to reside entirely within the wellbore for conveying an actuating signal to a downhole tool;

positioning the communications module and the tubular joint in the wellbore;

releasing a first downhole carrier into the wellbore, the downhole carrier emitting a first frequency signal;

wirelessly sensing the first frequency signal at the transmitter-receiver;

in response to the first frequency signal, sending a first instruction signal from the transmitter-receiver to the electrical circuit; and

in response to the first instruction signal, sending a first command signal from the electrical circuit to actuate a downhole tool.

31. The method of claim 30, wherein the communications module further comprises:

an inner mandrel; and

an outer shroud circumferentially disposed about the inner mandrel, the outer shroud permitting the flow of fluids there through.

32. The method of claim 30, wherein:

the pre-programmed electrical circuit is an RFID circuit;

the downhole carrier is an RFID tag that emits a radio-frequency signal; and

the transmitter-receiver is an RF antenna.

33. The method of claim 30, wherein:

the downhole carrier comprises an acoustic frequency generator; and

the transmitter-receiver comprises an acoustic antenna that receives acoustic signals from the downhole carrier, and in response sends an electrical signal to the pre-programmed electrical circuit.

34. The method of claim 30, wherein:

the control line contains a hydraulic fluid; and

the communications module further comprises a hydraulic motor configured to provide pressure to the hydraulic fluid to actuate the downhole tool in response to the first command signal from the pre-programmed electrical circuit.

35. The method of claim 30, wherein:

the control line contains an electrical line; and

sending a first command signal from the electrical circuit to actuate the downhole tool comprises sending an electrical command signal through the electrical line to actuate the downhole tool.

36. The method of claim 30, wherein actuating the downhole tool comprises (i) moving a sliding sleeve to close off production from a selected zone within the completion interval, (ii) moving a sliding sleeve to open up production from a selected zone within the completion interval, (iii) setting a packer, or (iv) manipulating a valve.

37. The method of claim 30, wherein:

the tubular joint comprises a joint of a sand control device also having at least one alternate flow channel; and

the method further comprises injecting a gravel slurry into an annular region formed between the sand control device and the surrounding wellbore, while providing that a portion of the gravel slurry travels through the at least one alternate flow channel to allow the gravel slurry to bypass any premature sand bridges.

38. The method of claim 30, further comprising:

releasing a second downhole carrier into the wellbore, the second downhole carrier emitting a second frequency signal;

sensing the second frequency signal at the transmitter-receiver;

in response to the second frequency signal, sending a second instruction signal from the transmitter-receiver to the electrical circuit; and

in response to the second instruction signal, sending a second command signal from the electrical circuit to actuate a downhole tool.

39. A method for monitoring conditions in a wellbore, the wellbore having a lower end defining a completion interval, the method comprising:

running a communications module and a connected tubular joint into the wellbore, the communications module comprising:

a pre-programmed electrical circuit,

a transmitter-receiver,

a sensing device in electrical communication with the electrical circuit, and

at least one alternate flow channel configured to allow a gravel slurry to partially bypass the communications module during a gravel packing procedure;

positioning the communications module and the tubular joint along the completion interval of the wellbore;

placing a gravel pack along a substantial portion of the completion interval of the wellbore;

producing hydrocarbon fluids from the completion interval of the wellbore;

sensing a downhole condition during production operations;

sending readings of the sensed downhole conditions from the sensing device to the electrical circuit;

sending the readings from the electrical circuit to the transmitter-receiver;

releasing a downhole carrier into the wellbore;

transmitting the readings from the transmitter-receiver to the downhole carrier;

retrieving the downhole carrier from the wellbore; and

downloading the recorded readings for data analysis.

40. The method of claim 39, wherein the completion interval is along a section of perforated production casing.

41. The method of claim 39 wherein the completion interval is along an open-hole portion of the wellbore.

42. The method of claim 39, wherein:

the pre-programmed electrical circuit is an RFID circuit;

the downhole carrier is an RFID tag that receives a radio-frequency signal; and

the transmitter-receiver is an RF antenna.

43. The method of claim 39, wherein releasing the downhole carrier comprises releasing the downhole carrier from the wellbore at or below the communications module.

44. The method of claim 43, further comprising:

pumping a tag from a surface into the wellbore, the tag emitting a first frequency signal;

sensing the first frequency signal at the transmitter-receiver; and

in response to sensing the first frequency signal, releasing the downhole carrier into the wellbore.

45. The method of claim 39, wherein releasing a downhole carrier comprises pumping, releasing, or dropping the downhole carrier from a surface into the wellbore and down to the communications module.

46. The method of claim 39, wherein:

the tubular joint comprises a joint of a sand control device also having at least one alternate flow channel; and

the step of placing a gravel pack comprises injecting a gravel slurry into an annular region formed between the sand control device and the surrounding wellbore, while providing that a portion of the gravel slurry travels through the at least one alternate flow channel to allow the gravel slurry to at least partially bypass any premature sand bridges.

47. The method of claim 39, wherein the tubular joint comprises a zonal isolation packer also having at least one alternate flow channel.