

02 MAR 2000

-1-

METHOD AND ARRANGEMENT TO ESTIMATE TRANSMISSION**CHANNEL CHARACTERISTICS**

The present invention relates to a method to estimate a transmission
5 channel characteristic as defined in the non-characteristic part of claim 1, a
transmission channel characteristic estimating arrangement able to perform this
method as defined in the non-characteristic part of claim 8, and a related remote
terminal as defined in the non-characteristic part of claim 9.

Such a method to estimate a transmission channel characteristic and
10 related equipment are already known in the art, e.g. from the *United States
Patent US 4,105,995*, entitled '*Digitally Controlled Transmission Impairment
Measurement Apparatus*'. Typically, the operator needs knowledge of certain
channel characteristics of a transmission channel between a central office and a
remote terminal to be able to guarantee a certain service to a subscriber that has
15 installed the remote terminal. The presence of line imperfections such as bridged
taps, line attenuation, ageing effects, disturbers like radio frequency interference,
and so on, has to be estimated by the operator before a certain quality of service
can be guaranteed. To estimate all basic parameters necessary to characterise a
transmission channel for its ability to carry data traffic, US 4,105,995 describes a
20 portable microprocessor controlled apparatus that measures specified
parameters for a telephone channel. The known apparatus for channel
characteristic estimation either consists of two units to be connected respectively
to both ends of the transmission channel, or of a single unit to be connected to a
single end of the transmission channel. The latter embodiment of the known
25 channel characteristic estimating apparatus requires manual loop-back at the
end of the transmission channel whereto the apparatus is not coupled.
Summarising, US 4,105,995 describes dedicated transmission channel test
equipment enabling off-line measurement of channel characteristics. To apply
the known technique, transmission of user data over the transmission channel

has to be interrupted and test equipment has to be connected to the transmission channel either at one or at both sides of the channel.

It is an object of the present invention to provide a method for estimation of a transmission channel characteristic and related equipment similar to the
5 above described one, but which allows both on-line and off-line channel characteristic estimation without the necessity to connect dedicated test equipment to the transmission channel.

According to the invention, this object is achieved by the method to estimate a transmission channel characteristic defined by claim 1, the
10 transmission channel characteristic estimating arrangement defined by claim 8, and the remote terminal defined by claim 9.

Indeed, the remote terminal itself collects all information required to estimate the transmission channel characteristic of interest and sends this information back to the central office wherein the information is matched with a
15 simulation model of the transmission channel and remote terminal. The information collected by the remote terminal can be fed back in a multiplexed way simultaneously with user data so that the data traffic over the transmission channel does not have to be interrupted. The simulation model used in the central office for the matching process typically contains a number of
20 parameters, e.g. the location along the transmission line of a bridged tap, corresponding to the transmission channel characteristics of interest. During the matching process, the values of these parameters are determined.

It is to be noticed that the term 'comprising', used in the claims, should not be interpreted as being limitative to the means listed thereafter. Thus, the
25 scope of the expression 'a device comprising means A and B' should not be limited to devices consisting only of components A and B. It means that with respect to the present invention, the only relevant components of the device are A and B.

Similarly, it is to be noticed that the term 'coupled', also used in the
30 claims, should not be interpreted as being limitative to direct connections only.

Thus, the scope of the expression 'a device A coupled to a device B' should not be limited to devices or systems wherein an output of device A is directly connected to an input of device B. It means that there exists a path between an output of A and an input of B which may be a path including other devices or means.

An additional feature of the method according to the present invention is defined by claim 2.

Indeed, the remote terminal of an Asymmetric Digital Subscriber Line (ADSL) system operating in accordance with ANSI's T1.413 standard, issue 2 for instance automatically collects information concerning the attenuation of a set of carriers with equidistant frequencies as can be deduced from *paragraph 9.9.8.1 of the draft edition of issue 2 of ANSI's T1E1.413 standard, entitled 'Standards Project for Interfaces Relating to Carrier to Customer Connection of Asymmetric Digital Subscriber Line (ADSL) Equipment*. This information is collected for use in the bit rate selection process described in *paragraph 9.9.8.2 of the cited draft standard*, and for use in the bit allocation process described in *paragraph 9.9.14 of the cited draft standard*, but in addition is very useful for estimating certain transmission channel characteristics such as the position of a bridged tap along the line. A preferred embodiment of the present invention consequently makes use of this automatically collected information for transmission channel characterisation.

A further feature of the method according to the present invention is defined by claim 3.

Thus, by multiplexing the collected information that will be used for transmission channel characterisation with user data, a transmission channel can be characterised without interruption of the system. This is so because the remote terminal that is able to transmit the user data does not have to be replaced by test equipment.

Alternatively, as defined by claim 4, a transmission channel characteristic is estimated off-line.

Thus, by interrupting transfer of user data over the channel and bringing the system into a test phase, a transmission channel characteristic according to the present invention can also be estimated off-line without the requirement to connect dedicated test equipment to the channel.

5 A further feature of the method according to the present invention is defined by claim 5.

In this way, information indicative for the attenuation and phase rotation of carriers having different frequencies, such as is typically collected in a multi-carrier ADSL (Asymmetric Digital Subscriber Line) modem and used therein for
10 setting equaliser coefficients, can additionally be used for channel characterisation.

Yet another feature of the method according to the present invention is defined by claim 6.

In this way, information indicative for the noise affecting carriers having
15 different frequencies, such as is typically collected in a multi-carrier ADSL modem and used therein for allocation of bits to carriers, can additionally be used for channel characterisation.

Furthermore, as is indicated by claim 7, the present invention is very suitable for implementation in an Asymmetric Digital Subscriber Line (ADSL)
20 system, or any similar system, e.g. a Very High Speed Digital Subscriber Line (VDSL) system.

An additional advantageous feature of the arrangement for estimating a transmission channel characteristic according to the present invention is defined by claim 10.

25 Hence, information suitable for use in the transmission channel characterisation method can be collected over a certain time interval, and can be fed back to the central office as soon as this time interval has elapsed.

The above mentioned and other objects and features of the invention will become more apparent and the invention itself will be best understood by
30 referring to the following description of an embodiment taken in conjunction with

the accompanying drawing which is a functional block scheme of a telecommunication system wherein the method to estimate a transmission channel characteristic according to the present invention is applied.

In the figure, the central office CO and remote terminal RT of an Asymmetric Digital Subscriber Line (ADSL) system are drawn. The remote terminal RT in addition to traditional ADSL receiving circuitry that is supposed to form part of the receiver RX and traditional ADSL transmitting circuitry that is supposed to form part of the transmitter TX contains a channel information gathering unit INFO and channel information memory MEM. The central office CO on top of traditional ADSL transceiving circuitry, not drawn in the figure, contains a channel and modem matching unit MATCH.

The receiver RX in the remote terminal RT is coupled between an input/output port and an output terminal of this remote terminal RT, and further has an output coupled to the channel information gathering unit INFO. The transmitter TX in the remote terminal RT is coupled between an input terminal and the above mentioned input/output port of the remote terminal RT. To a second input terminal of the transmitter TX, the channel information memory MEM is coupled. An output of the channel information gathering unit INFO and an input of the channel information memory MEM are interconnected. A twisted pair telephone line CHANNEL serves as bi-directional physical communication medium between the remote terminal RT and the central office CO. The remote terminal RT is coupled to this telephone line CHANNEL via the above mentioned input/output port. In the central office CO, an input of the channel and modem matching unit MATCH is coupled to the telephone line CHANNEL.

In the drawn ADSL system digital data are transferred bi-directionally on top of telephone signals over the telephone line CHANNEL. At both the remote side and the central office side, a splitter separates received digital data from received telephone signals, applies the digital data to respectively the ADSL remote terminal RT or ADSL central office CO, and applies the telephone signals to respectively the customer's telephone apparatus or a POTS (Plain Old

Telephone Service) line-card. In the drawing, the splitters at the remote side and central office side, and the customer's telephone apparatus as well as the POTS line-card are not drawn because the present invention only has an impact on the ADSL central office CO and the ADSL remote terminal RT.

5 For the operator of the drawn system, one of the problems is how to guarantee a certain service to the customer at the time of installation or later without exact knowledge of the channel characteristics of the telephone line CHANNEL. Because of the frequent changes in disturbances (e.g. the presence of a radio amateur) and line faults (e.g. due to water logging), databases
10 containing information concerning the channel characteristics of telephone lines usually are outdated. Since the remote terminal RT of the drawn ADSL system automatically collects information that is useful for channel characteristic information, access to this information by the operator enables the operator to track changes in the channel characteristics.

15 The remote terminal RT in the figure is supposed to operate in accordance with Issue 2 of ANSI's T1E1.413 standard and consequently performs certain channel measurements such as a gain and phase measurement for each carrier transferred over the telephone line CHANNEL and a signal to noise ratio (SNR) measurement for each carrier. The so obtained information is used for setting
20 parameters of a time domain equaliser and frequency domain equaliser which typically forms part of the ADSL receiver RX and for allocating data bits to carriers in the ADSL transmitter TX. According to the invention, the channel information gathering unit INFO collects the measured information and the information is temporarily stored in the channel information memory MEM. Thereafter, the
25 ADSL transmitter TX reads the channel information out of the channel information memory MEM and sends the information to the central office CO so that it is available at the operator's side for channel estimation purposes.

 In the central office CO, the channel and modem matching unit MATCH
 uses a simulation model of the telephone line CHANNEL and remote terminal RT
30 and matches the received information with this simulation model. The simulation

model contains a number of parameters like the line attenuation, the length of the telephone line, length and location of bridged taps, water logging, and so on. By matching the simulation model with the information received from the remote terminal RT, the channel and modem matching unit MATCH determines
5 the values for the different parameters in the simulation model. These parameter values are an estimation of the channel characteristics where the operator can rely on to guarantee a certain service to the customer.

Since the measurements can be done by the remote terminal RT on-line, the channel characteristics can be monitored in time so that each time the
10 customer wants to install a new service, recent channel characteristic estimations are available to the operator allowing the operator to give quality guarantees concerning the newly installed service. The permanently available channel characteristic estimations moreover enable the operator to take appropriate measures in case of quality loss, to monitor changes to the customer's in-house
15 network that may affect the quality of service, and to fast evaluate complaints of the customer concerning the quality of service.

It is noticed that the channel information gathering unit INFO, that is coupled to an output terminal of the ADSL receiver RX in the above described embodiment, may be integrated within this ADSL receiver RX. Indeed, since an
20 ADSL receiver RX that operates in accordance with the specifications of ANSI's T1E1.413 Issue 2 standard collects channel information at initialisation for use in the bit allocation algorithm and for setting equaliser taps, channel information gathering equipment INFO may in certain embodiments of the invention be integrated in the receiver circuitry RX.

25 Another remark is that although the embodiment of the present invention illustrated by the drawing contains a channel information memory MEM, provision of such a channel information memory MEM is not an absolute requirement for implementation of the present invention. Indeed, without the channel information memory MEM, the channel information collected by the
30 remote terminal RT would be fed back instantly to the central office CO, whereas

with a channel information memory MEM, the channel information can be collected during a certain time interval and can be fed back at certain time instants in between the time intervals wherein the channel information is collected. When providing a channel information memory MEM, the collected
5 channel information may be sent automatically at regular time intervals to the central office CO or may be sent to the central office CO upon request of the latter one.

Also a remark is that the channel and remote terminal matching unit MATCH may form part of the central office CO, as is the case for the
10 embodiment of the invention drawn in the figure, but alternatively may be a separate unit connected to an operator terminal of the central office CO.

Yet another remark is that applicability of the present invention is not limited to any particular physical communication medium in between the central office CO and the remote terminal RT or any particular physical layer transport
15 protocol. Thus, instead of a twisted pair telephone line, a coaxial cable, an optical fibre, a radio link, a satellite connection, or even a hybrid transmission medium such as a hybrid coax/optical fibre link may serve as communication medium between the central office CO and remote terminal RT, and evidently, instead of the Asymmetric Digital Subscriber Line (ADSL) protocol, any other
20 physical layer protocol, e.g. the VDSL (Very High Speed Digital Subscriber Line) protocol, or the Hybrid Fibre Coax (HFC) protocol may be adopted in the system wherein the present invention is implemented.

Furthermore, a remark is that embodiments of the present invention are described above in terms of functional blocks. From the functional description of
25 these blocks it will be obvious for a person skilled in the art of designing electronic devices how embodiments of these blocks can be manufactured with well-known electronic components. A detailed architecture of the contents of the functional blocks hence is not given for most of them.

While the principles of the invention have been described above in
30 connection with specific apparatus, it is to be clearly understood that this

-9-

description is made only by way of example and not as a limitation on the scope of the invention.



CLAIMS

1. Method to estimate a transmission channel characteristic of a transmission channel (CHANNEL) between a central office station (CO) and a
5 remote terminal (RT),

CHARACTERISED IN THAT said method comprises the steps of:

- a. collecting in said remote terminal (RT) channel information;
- b. transferring said channel information from said remote terminal (RT) to said central office station (CO);
- 10 c. matching said channel information with a channel and remote terminal simulation model whose parameters define said channel characteristic; and as a result of said matching:
- d. determining values for said parameters of said channel and remote terminal simulation model.

15

2. Method to estimate a transmission channel characteristic according to claim 1,

CHARACTERISED IN THAT said channel information is automatically collected by said remote terminal (RT) for operational purposes.

20

3. Method to estimate a transmission channel characteristic according to claim 1 or claim 2,

CHARACTERISED IN THAT said remote terminal (RT) collects said channel information on-line.

25

4. Method to estimate a transmission channel characteristic according to claim 1 or claim 2,

CHARACTERISED IN THAT said remote terminal (RT) collects said channel information off-line during a test phase.

30



-11-

5. Method to estimate a transmission channel characteristic according to any of claims 2 to 4,

CHARACTERISED IN THAT said channel information comprises gain and phase distortion measurements at a number of frequencies, collected by said
5 remote terminal (RT) for equaliser setting.

6. Method to estimate a transmission channel characteristic according to any of claims 2 to 5,

CHARACTERISED IN THAT said channel information comprises noise
10 measurements at a number of frequencies, collected by said remote terminal (RT) for allocating bits to carriers, said carriers being used for transmission of data from said remote terminal (RT) to said central office station (CO).

7. Method to estimate a transmission channel characteristic according to
15 any of the preceding claims,

CHARACTERISED IN THAT said transmission channel (CHANNEL) is a Digital Subscriber Line, said central office station (CO) is a Digital Subscriber Line central office, said remote terminal (RT) is a Digital Subscriber Line modem, and said channel information is information collected at initialisation of an
20 Asymmetric Digital Subscriber Line system to enable either one of selection of downstream and upstream bit-rates, equaliser setting and allocation of data bits to carriers.

8. Transmission channel characteristic estimating arrangement for
25 estimating a transmission channel characteristic of a transmission channel (CHANNEL) between a central office station (CO) and a remote terminal (RT),

CHARACTERISED in that said arrangement comprises:

a. information collecting means (INFO) in said remote terminal (RT), adapted to collect channel information;



b. information transferring means (TX) in said remote terminal (RT) coupled to said information collecting means (INFO), said information transferring means (TX) being adapted to transfer said channel information from said remote terminal (RT) to said central office station (CO);

5 c. information and model matching means (MATCH) adapted to match said channel information with a channel and remote terminal simulation model whose parameters define said channel characteristic; and

10 d. parameter value determining means, integrated with said information and model matching means (MATCH) and adapted to determine values for said parameters of said channel and remote terminal simulation model.

9. Remote terminal (RT) suitable for communication with a central office station (CO) via a transmission channel (CHANNEL) there between,

CHARACTERISED IN THAT said remote terminal (RT) comprises:

15 a. information collecting means (INFO) adapted to collect channel information;

20 b. information transferring means (TX) coupled to said information collecting means (INFO), said information transferring means (TX) being adapted to transfer said channel information from said remote terminal (RT) to said central office station (CO) to be matched there with a channel and remote terminal simulation model whose parameters define a transmission channel characteristic for said transmission channel and whose values are determined as a result of said matching.

25 10. Remote terminal (RT) according to claim 9,

CHARACTERISED IN THAT said remote terminal (RT) further comprises memory means (MEM), coupled between said information collecting means (INFO) and said information transferring means (TX), and adapted to memorise said channel information collected over a time interval.