

REPLACED SHEETS		SG
☒	Description	: paged ... to paged ...
☒	Claim(s)	: paged ... to paged ...
☒	Drawing(s)	: paged ... to paged ...
☒	Abstract	: paged ... to paged ...
DATE OF RECEIPT		

This Sheet Has Been Replaced

COMPOSITIONS COMPRISING PENTAFLUOROBUTANE AND USE OF THESE COMPOSITIONS



The invention relates to compositions comprising pentafluorobutane and to the use of these compositions, especially as cleaning and/or drying agents for solid surfaces.

5 Completely halogenated chlorofluorinated hydrocarbons (CFCs), in particular 1,1,2-trichloro-1,2,2-trifluoroethane (CFC-113), are widely used as solvents in industry for degreasing and cleaning various surfaces, particularly for solid components of complicated shape
10 which are difficult to clean. In addition to their use in electronics in cleaning soldering fluxes in order to remove the pickling flux which adheres to printed circuits, they are also conventionally used for degreasing metal components or for cleaning mechanical components of
15 high quality and of high precision. In these various applications, CFC-113 is most often used in combination with other organic solvents, preferably in the form of azeotropic or pseudoazeotropic compositions having substantially the same composition in the vapour phase
20 and in the liquid phase, so that they can be easily employed at reflux.

Compositions based on CFC-113 are also conventionally used as desiccating agents, in order to remove the water adsorbed at the surface of solid components.
25

However, CFC-113, as well as other completely halogenated chlorofluoroalkanes, is today suspected of being involved in the destruction of the stratospheric ozone layer.

30 Consequently, there is currently an urgent need to find new compositions which do not have a harmful influence on the ozone layer.

To this end, a certain number of azeotropic compositions based on hydrofluoroalkanes have recently
35 been proposed. In particular, Patent Application EP-A-0,512,885 (Elf Atochem) proposes an azeotropic composition comprising, by weight, 93 to 99% of 1,1,1,3,3-pentafluorobutane (HFA-365mfc) and from 7 to 1% of methanol.



One of the objectives of the present invention is to provide other compositions, optionally forming azeotropes or pseudoazeotropes, which are particularly effective when they are used as cleaning agents in solvent cleaning processes. A further subject of the invention is such compositions having properties particularly suited to cleaning printed circuit boards. Another objective of the invention is to provide such compositions which do not have a destructive effect with respect to the ozone layer, compositions which can consequently be used as replacements for solvents based on completely halogenated chlorofluoroalkanes.

The present invention consequently relates to compositions comprising 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene.

1,2-Dichloroethylene exists in two isomeric forms, cis-1,2-dichloroethylene and trans-1,2-dichloroethylene. For the purposes of the present invention, 1,2-dichloroethylene is understood to mean, without distinction, one or the other isomer or a mixture of these. Nevertheless, trans-1,2-dichloroethylene is the preferred isomer.

The 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene contents in the compositions according to the invention can vary within wide limits, depending on the use envisaged.

The compositions according to the invention generally contain at least 45% by weight of 1,1,1,3,3-pentafluorobutane. They advantageously contain at least 50% by weight thereof. In a particularly preferred way, they contain at least 60% thereof. They can contain up to 90% by weight thereof. Most often, they contain at most 85% by weight thereof, preferably at most 80% by weight.

The compositions according to the invention contain from 10 to 55% by weight of 1,2-dichloroethylene. They preferably contain from 15 to 50% thereof. In a particularly preferred way, they contain from 20 to 40% thereof.

Advantageously, the compositions according to the



invention additionally contain an alkanol chosen from methanol, ethanol, propanol and isopropanol. As a general rule, the amount of alkanol present in the compositions according to the invention does not exceed 15% of the weight of the composition. Preferably, they contain from 0.5 to 10% thereof.

Various additives can optionally be present in the compositions according to the invention. The compositions according to the invention can thus contain stabilizing agents, surface-active agents or any other additives making it possible to improve the behaviour of the compositions according to the invention during their use. The nature and the amount of these additives depend on the use envisaged and are easily defined by those skilled in the art. As a general rule, the amount of additives present in the compositions according to the invention does not exceed approximately 20% of the weight of the composition, most often not more than 10%.

Preferred compositions according to the invention are those which contain 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene in proportions in which they form an azeotrope or a pseudoazeotrope.

Particularly preferred compositions according to the invention are those which contain 1,1,1,3,3-pentafluorobutane, 1,2-dichloroethylene and an alkanol chosen from methanol and ethanol in proportions in which they form a ternary azeotrope or pseudoazeotrope.

Fundamentally the thermodynamic state of a fluid is defined by four interdependent variables: the pressure (P), the temperature (T), the composition of the liquid phase (X) and the composition of the gas phase (Y). An azeotrope is a specific system containing at least two components in which, at a given temperature and a given pressure, X is exactly equal to Y. A pseudoazeotrope is a system containing at least two components in which, at a given temperature and a given pressure, X is substantially equal to Y. In practice, this means that the constituents of such azeotropic or pseudoazeotropic systems cannot be easily separated by distillation and



consequently their composition remains substantially constant in solvent cleaning operations, as well as in operations for recovering spent solvents by distillation.

For the purposes of the present invention,
5 pseudoazeotrope is understood to mean a mixture of two or a number of constituents whose boiling point (at a given pressure) differs from the boiling point of the azeotrope by at most 0.2°C.

1,1,1,3,3-Pentafluorobutane and 1,2-dichloro-
10 ethylene form a binary azeotrope or pseudoazeotrope when their mixture consists essentially of 56% to 82% by weight of 1,1,1,3,3-pentafluorobutane and of 44 to 18% by weight of 1,2-dichloroethylene. A preferred composition forming an azeotrope or pseudoazeotrope consists of 60 to
15 78% by weight of 1,1,1,3,3-pentafluorobutane and of 40 to 22% by weight of 1,2-dichloroethylene. At a pressure of 1022 mbar, the binary composition consisting essentially of approximately 70% by weight of 1,1,1,3,3-pentafluorobutane and of approximately 30% by weight of 1,2-di-
20 chloroethylene constitutes an azeotrope whose boiling point is approximately 36.3°C. This composition is very particularly advantageous.

1,1,1,3,3-pentafluorobutane, 1,2-dichloroethylene and methanol form a ternary azeotrope or pseudoazeotrope
25 when their mixture consists essentially of 62 to 68% by weight of 1,1,1,3,3-pentafluorobutane, of 28 to 34% by weight of 1,2-dichloroethylene and of 2 to 7% by weight of methanol. At atmospheric pressure, the ternary composition consisting essentially of approximately 64.9% by
30 weight of 1,1,1,3,3-pentafluorobutane, approximately 31.5% by weight of 1,2-dichloroethylene and approximately 3.6% by weight of methanol constitutes an azeotrope whose boiling point is approximately 32°C. This composition is very particularly advantageous.

35 1,1,1,3,3-Pentafluorobutane, 1,2-dichloroethylene and ethanol form a ternary azeotrope or pseudoazeotrope when their mixture consists essentially of 64 to 68% by weight of 1,1,1,3,3-pentafluorobutane, of 30 to 35% by weight of 1,2-dichloroethylene and of 1 to 3% by weight



of ethanol. At atmospheric pressure, the ternary composition consisting essentially of approximately 66.1% by weight of 1,1,1,3,3-pentafluorobutane, approximately 32.3% by weight of 1,2-dichloroethylene and approximately 1.6% by weight of ethanol constitutes an azeotrope whose boiling point is approximately 34°C. This composition is very particularly advantageous.

The compositions according to the invention have a suitable boiling point for replacing compositions based on CFC-113 in existing cleaning equipment. As regards its impact on the environment, 1,1,1,3,3-pentafluorobutane appears particularly advantageous, since it has a zero destructive potential for ozone. The compositions according to the invention are additionally inert towards the various types of surfaces to be treated, whether they are metal, plastic or glass.

The compositions according to the invention can consequently be used in the same applications and according to the same techniques as the prior compositions based on CFC-113. In particular, the compositions according to the invention can be used as cleaning agents, solvents, degreasing agents, defluxing agents or desiccating agents. The ternary compositions containing an alkanol appear particularly advantageous, in particular those where the constituents are present in proportions in which they form an azeotrope or pseudoazeotrope.

The invention consequently also relates to the use of the compositions according to the invention as cleaning agents, as degreasing agents for solid surfaces, as cleaning agents for printed circuit boards contaminated by a pickling flux and residues from this flux, or as desiccating agents for removing the water adsorbed at the surface of solid objects.

The examples below, without implied limitation, illustrate the invention in a more detailed way.

Example 1

A glass apparatus consisting of a 50 ml distillation flask surmounted by a reflux condenser was used to

reveal the existence of binary azeotropic or pseudoazeotropic compositions between 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene. The temperature of the liquid is measured using a thermometer inserted into the flask.

5 20.9 g of pure 1,1,1,3,3-pentafluorobutane were heated at a pressure of 1022 mbar until boiling and then small amounts of trans-1,2-dichloroethylene, accurately weighed, were progressively introduced into the flask using a syringe, via a side tube.

10 Determination of the azeotropic composition was carried out by noting a change in the boiling temperature of the mixture according to its composition. The composition for which a minimum boiling point was observed is the azeotropic composition at the operating pressure.

15 The boiling temperatures obtained for different compositions of 1,1,1,3,3-pentafluorobutane (PFBA) and trans-1,2-dichloroethylene (DCEe) are collated in the table below. It is observed therein that the best estimation of the composition for which the boiling point is
20 minimum (36.3°C) is approximately 70% by weight of 1,1,1,3,3-pentafluorobutane and 30% by weight of trans-1,2-dichloroethylene. The boiling point is 36.5°C ± 0.2°C for a composition containing approximately 56 to 82% by weight of 1,1,1,3,3-pentafluorobutane, at a pressure of
25 1022 mbar.

This Sheet Has Been Replaced



TABLE I

PFBA, g	DCEe added, g (cumulative amt.)	DCEe Content		Boil. point, °C
		weight %	mol %	
20.9	0	0.00	0.00	40.8
	0.087	0.42	0.63	40.5
	0.211	1.00	1.52	40.3
	0.488	2.28	3.44	39.9
	0.826	3.80	5.69	39.4
	1.018	4.65	6.92	39.1
	1.302	5.86	8.69	38.8
	1.629	7.23	10.63	38.4
	1.891	8.30	12.14	38.1
	2.228	9.63	14.00	37.8
	2.627	11.16	16.10	37.7
	3.018	12.62	18.06	37.4
	3.570	14.59	20.69	37.1
	4.019	16.13	22.69	36.9
	4.577	17.90	24.98	36.7
	5.451	20.68	28.48	36.6
	5.939	22.13	30.26	36.5
	6.459	23.61	32.06	36.4
	7.331	25.97	34.88	36.4
	7.837	27.27	36.41	36.3
	9.120	30.38	39.98	36.3
	9.896	32.13	41.96	36.3
	10.578	33.60	43.59	36.4
	12.163	36.79	47.05	36.5
	13.899	39.94	50.38	36.5
	16.403	43.97	54.51	36.7
	20.529	49.55	59.99	37.1
	25.335	54.80	64.92	37.9
	28.117	57.36	67.26	38.2

This Sheet Has Been Replaced



Example 2

A solution containing 66.2% by weight of 1,1,1,3,3-pentafluorobutane, 29.8% by weight of trans-1,2-dichloroethylene and 4% by weight of methanol was prepared. This solution was subjected to a distillation at atmospheric pressure using a Vigreux column. The boiling temperature remained constantly equal to 32°C. The various fractions of the distillate, each representing from 5 to 20% of the weight of the initial solution, were withdrawn using a multi-limb distributor ("pig") and then analysed by gas phase chromatography. The results obtained are collated in Table II.

TABLE II

Fraction of the distillate		PFBA (weight %)	DCEe (weight %)	Methanol (weight %)
15	1 (5.7 weight % of the solution)	64.9	31.5	3.6
	2 (12.1 weight % of the solution)	65.1	31.2	3.7
	3 (16.5 weight % of the solution)	65.3	31.0	3.7
	4 (15.0 weight % of the solution)	65.6	30.7	3.7
	5 (10.3 weight % of the solution)	65.9	30.3	3.8
20	6 (14.0 weight % of the solution)	66.2	30.0	3.8

The virtually identical composition of the various fractions obtained shows the existence of a ternary azeotrope between 1,1,1,3,3-pentafluorobutane, trans-1,2-dichloroethylene and methanol, the estimated composition of which is 64.9% by weight of 1,1,1,3,3-pentafluorobutane, 31.5% by weight of trans-1,2-dichloroethylene and 3.6% by weight of methanol.

This Sheet Has Been Replaced



Example 3

A solution containing 66.2% by weight of 1,1,1,3,3-pentafluorobutane, 32.1% by weight of trans-1,2-dichloroethylene and 1.7% by weight of ethanol was prepared. This solution was subjected to a distillation at atmospheric pressure using a Vigreux column. The boiling temperature remained constantly equal to 34°C. The various fractions of the distillate, each representing approximately from 5 to 15% of the weight of the initial solution, were withdrawn using a multi-limb distributor ("pig") and then analysed by gas phase chromatography. The results obtained are collated in Table III.

This Sheet Has Been Replaced




TABLE III

15	Fraction of the distillate	PFBA (weight %)	DCEe (weight %)	Ethanol (weight %)
	1 (4.8 weight % of the solution)	66.1	32.4	1.5
	2 (16.7 weight % of the solution)	66.1	32.3	1.6
	3 (12.7 weight % of the solution)	66.1	32.3	1.6
20	4 (12.2 weight % of the solution)	66.3	32.1	1.6
	5 (12.1 weight % of the solution)	66.2	32.2	1.6
	6 (15.1 weight % of the solution)	66.2	32.2	1.6
	7 (10.5 weight % of the solution)	66.3	32.0	1.7

The virtually identical composition of the various fractions obtained reveals the existence of a ternary azeotrope between 1,1,1,3,3-pentafluorobutane, trans-1,2-dichloroethylene and ethanol, the estimated composition of which is 66.1% by weight of 1,1,1,3,3-

pentafluorobutane, 32.3% by weight of trans-1,2-dichloro-ethylene and 1.6% by weight of ethanol.

This Sheet Has Been Replaced



CLAIMS

1. Compositions comprising 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene.
2. Compositions according to Claim 1, characterized
5 in that they contain at least 50% by weight of 1,1,1,3,3-pentafluorobutane and from 15 to 50% by weight of 1,2-dichloroethylene.
3. Compositions according to Claim 1 or 2, characterized in that they additionally contain an alkanol
10 chosen from methanol, ethanol, propanol and isopropanol.
4. Compositions according to Claim 1 or 2, characterized in that they consist essentially of 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene in proportions for which they form a binary azeotrope or pseudoazeo-
15 trope.
5. Compositions according to Claim 4, characterized in that they consist essentially of 56% to 82% by weight of 1,1,1,3,3-pentafluorobutane and of 44 to 18% by weight of 1,2-dichloroethylene.
- 20 6. Compositions according to any one of Claims 1 to 3, characterized in that they consist essentially of 1,1,1,3,3-pentafluorobutane, 1,2-dichloroethylene and an alkanol in proportions for which they form a ternary azeotrope or pseudoazeotrope.
- 25 7. Compositions according to Claim 6, characterized in that they consist essentially of 62 to 68% by weight of 1,1,1,3,3-pentafluorobutane, of 28 to 34% by weight of 1,2-dichloroethylene and of 2 to 7% by weight of methanol.
- 30 8. Compositions according to Claim 6, characterized in that they consist essentially of 64 to 68% by weight of 1,1,1,3,3-pentafluorobutane, of 30 to 35% by weight of 1,2-dichloroethylene and of 1 to 3% by weight of ethanol.
9. Use of the compositions according to any one of
35 Claims 1 to 8 as cleaning agents.
10. Use of the compositions according to any one of Claims 1 to 8 as degreasing agents for solid surfaces.
11. Use of the compositions according to any one of Claims 1 to 8 as cleaning agents for printed circuit





boards contaminated by a pickling flux and residues from this flux.

12. Use of the compositions according to any one of Claims 1 to 8 as desiccating agents for removing the
5 water adsorbed at the surface of solid objects.

This Sheet Has Been Replaced



ABSTRACTCompositions comprising pentafluorobutane
and use of these compositions

The invention relates to compositions comprising 1,1,1,3,3-pentafluorobutane, 1,2-dichloroethylene and optionally a C1-C3 alkanol. These compositions can be used especially as solvents for cleaning and defluxing electronic components and for degreasing metals.

No figure.

- 1 -

REPLACEMENT SHEET

02 SEP 1996

COMPOSITIONS COMPRISING PENTAFLUOROBUTANE AND
USE OF THESE COMPOSITIONS

The invention relates to compositions comprising pentafluorobutane and to the use of these compositions, especially as cleaning and/or drying agents for solid surfaces.

- 5 Completely halogenated chlorofluorinated hydrocarbons (CFCs), in particular 1,1,2-trichloro-1,2,2-trifluoroethane (CFC-113), are widely used as solvents in industry for degreasing and cleaning various surfaces, particularly for solid components of complicated shape
- 10 which are difficult to clean. In addition to their use in electronics in cleaning soldering fluxes in order to remove the pickling flux which adheres to printed circuits, they are also conventionally used for degreasing metal components or for cleaning mechanical components of
- 15 high quality and of high precision. In these various applications, CFC-113 is most often used in combination with other organic solvents, preferably in the form of azeotropic or pseudoazeotropic compositions having substantially the same composition in the vapour phase
- 20 and in the liquid phase, so that they can be easily employed at reflux.

- Compositions based on CFC-113 are also conventionally used as desiccating agents, in order to remove the water adsorbed at the surface of solid components.
- 25

However, CFC-113, as well as other completely halogenated chlorofluoroalkanes, is today suspected of being involved in the destruction of the stratospheric ozone layer.

- 30 Consequently, there is currently an urgent need to find new compositions which do not have a harmful influence on the ozone layer.

- To this end, a certain number of azeotropic compositions based on hydrofluoroalkanes have recently
- 35 been proposed. In particular, Patent Application EP-A-0,512,885 (Elf Atochem) proposes an azeotropic composition comprising, by weight, 93 to 99% of 1,1,1,3,3-pentafluorobutane (HFA-365mfc) and from 7 to 1% of methanol.

REPLACEMENT SHEETS SG

- ☒ Description : paged ... to paged ...
☒ Claim(s) : paged ... to paged ...
☐ Drawing(s) : paged ... to paged ...
☒ Abstract : paged ... to paged ...

DATE OF RECEIPT ... 2/9/96 ...

02 SEP 1996

- 2 -

One of the objectives of the present invention is to provide other compositions, optionally forming azeotropes or pseudoazeotropes, which are particularly effective when they are used as cleaning agents in solvent cleaning processes. A further subject of the invention is such compositions having properties particularly suited to cleaning printed circuit boards. Another objective of the invention is to provide such compositions which do not have a destructive effect with respect to the ozone layer, compositions which can consequently be used as replacements for solvents based on completely halogenated chlorofluoroalkanes.

The present invention consequently relates to compositions comprising 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene.

1,2-Dichloroethylene exists in two isomeric forms, cis-1,2-dichloroethylene and trans-1,2-dichloroethylene. For the purposes of the present invention, 1,2-dichloroethylene is understood to mean, without distinction, one or the other isomer or a mixture of these. Nevertheless, trans-1,2-dichloroethylene is the preferred isomer.

The 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene contents in the compositions according to the invention can vary within wide limits, depending on the use envisaged.

The compositions according to the invention generally contain at least 45% by weight of 1,1,1,3,3-pentafluorobutane. They advantageously contain at least 50% by weight thereof. In a particularly preferred way, they contain at least 60% thereof. They can contain up to 90% by weight thereof. Most often, they contain at most 85% by weight thereof, preferably at most 80% by weight.

The compositions according to the invention contain from 10 to 55% by weight of 1,2-dichloroethylene. They preferably contain from 15 to 50% thereof. In a particularly preferred way, they contain from 20 to 40% thereof.

Advantageously, the compositions according to the

invention additionally contain an alkanol chosen from methanol, ethanol, propanol and isopropanol. As a general rule, the amount of alkanol present in the compositions according to the invention does not exceed 15% of the weight of the composition. Preferably, they contain from 0.5 to 10% thereof.

Various additives can optionally be present in the compositions according to the invention. The compositions according to the invention can thus contain stabilizing agents, surface-active agents or any other additives making it possible to improve the behaviour of the compositions according to the invention during their use. The nature and the amount of these additives depend on the use envisaged and are easily defined by those skilled in the art. As a general rule, the amount of additives present in the compositions according to the invention does not exceed approximately 20% of the weight of the composition, most often not more than 10%.

Preferred compositions according to the invention are those which contain 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene in proportions in which they form an azeotrope or a pseudoazeotrope.

Particularly preferred compositions according to the invention are those which contain 1,1,1,3,3-pentafluorobutane, 1,2-dichloroethylene and an alkanol chosen from methanol and ethanol in proportions in which they form a ternary azeotrope or pseudoazeotrope.

Fundamentally the thermodynamic state of a fluid is defined by four interdependent variables: the pressure (P), the temperature (T), the composition of the liquid phase (X) and the composition of the gas phase (Y). An azeotrope is a specific system containing at least two components in which, at a given temperature and a given pressure, X is exactly equal to Y. A pseudoazeotrope is a system containing at least two components in which, at a given temperature and a given pressure, X is substantially equal to Y. In practice, this means that the constituents of such azeotropic or pseudoazeotropic systems cannot be easily separated by distillation and

REPLACEMENT SHEET

02 SEP 1996

02 SEP 1996

- 4 -

consequently their composition remains substantially constant in solvent cleaning operations, as well as in operations for recovering spent solvents by distillation.

For the purposes of the present invention,
5 pseudoazeotrope is understood to mean a mixture of two or a number of constituents whose boiling point (at a given pressure) differs from the boiling point of the azeotrope by at most 0.2°C.

1,1,1,3,3-Pentafluorobutane and 1,2-dichloro-
10 ethylene form a binary azeotrope or pseudoazeotrope when their mixture consists essentially of 56% to 82% by weight of 1,1,1,3,3-pentafluorobutane and of 44 to 18% by weight of 1,2-dichloroethylene. A preferred composition forming an azeotrope or pseudoazeotrope consists of 60 to
15 78% by weight of 1,1,1,3,3-pentafluorobutane and of 40 to 22% by weight of 1,2-dichloroethylene. At a pressure of 1022 mbar, the binary composition consisting essentially of approximately 70% by weight of 1,1,1,3,3-pentafluorobutane and of approximately 30% by weight of 1,2-di-
20 chloroethylene constitutes an azeotrope whose boiling point is approximately 36.3°C. This composition is very particularly advantageous.

1,1,1,3,3-pentafluorobutane, 1,2-dichloroethylene and methanol form a ternary azeotrope or pseudoazeotrope
25 when their mixture consists essentially of 62 to 68% by weight of 1,1,1,3,3-pentafluorobutane, of 28 to 34% by weight of 1,2-dichloroethylene and of 2 to 7% by weight of methanol. At atmospheric pressure, the ternary composition consisting essentially of approximately 64.9% by
30 weight of 1,1,1,3,3-pentafluorobutane, approximately 31.5% by weight of 1,2-dichloroethylene and approximately 3.6% by weight of methanol constitutes an azeotrope whose boiling point is approximately 32°C. This composition is very particularly advantageous.

35 1,1,1,3,3-Pentafluorobutane, 1,2-dichloroethylene and ethanol form a ternary azeotrope or pseudoazeotrope when their mixture consists essentially of 64 to 68% by weight of 1,1,1,3,3-pentafluorobutane, of 30 to 35% by weight of 1,2-dichloroethylene and of 1 to 3% by weight

02 SEP 1996

- 5 -

of ethanol. At atmospheric pressure, the ternary composition consisting essentially of approximately 66.1% by weight of 1,1,1,3,3-pentafluorobutane, approximately 32.3% by weight of 1,2-dichloroethylene and approximately 1.6% by weight of ethanol constitutes an azeotrope whose boiling point is approximately 34°C. This composition is very particularly advantageous.

The compositions according to the invention have a suitable boiling point for replacing compositions based on CFC-113 in existing cleaning equipment. As regards its impact on the environment, 1,1,1,3,3-pentafluorobutane appears particularly advantageous, since it has a zero destructive potential for ozone. The compositions according to the invention are additionally inert towards the various types of surfaces to be treated, whether they are metal, plastic or glass.

The compositions according to the invention can consequently be used in the same applications and according to the same techniques as the prior compositions based on CFC-113. In particular, the compositions according to the invention can be used as cleaning agents, solvents, degreasing agents, defluxing agents or desiccating agents. The ternary compositions containing an alkanol appear particularly advantageous, in particular those where the constituents are present in proportions in which they form an azeotrope or pseudoazeotrope.

The invention consequently also relates to the use of the compositions according to the invention as cleaning agents, as degreasing agents for solid surfaces, as cleaning agents for printed circuit boards contaminated by a pickling flux and residues from this flux, or as desiccating agents for removing the water adsorbed at the surface of solid objects.

The examples below, without implied limitation, illustrate the invention in a more detailed way.

Example 1

A glass apparatus consisting of a 50 ml distillation flask surmounted by a reflux condenser was used to

reveal the existence of binary azeotropic or pseudoazeotropic compositions between 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene. The temperature of the liquid is measured using a thermometer inserted into the flask.

5 20.9 g of pure 1,1,1,3,3-pentafluorobutane were heated at a pressure of 1022 mbar until boiling and then small amounts of trans-1,2-dichloroethylene, accurately weighed, were progressively introduced into the flask using a syringe, via a side tube.

10 Determination of the azeotropic composition was carried out by noting a change in the boiling temperature of the mixture according to its composition. The composition for which a minimum boiling point was observed is the azeotropic composition at the operating pressure.

15 The boiling temperatures obtained for different compositions of 1,1,1,3,3-pentafluorobutane (PFBA) and trans-1,2-dichloroethylene (DCEe) are collated in the table below. It is observed therein that the best estimation of the composition for which the boiling point is
20 minimum (36.3°C) is approximately 70% by weight of 1,1,1,3,3-pentafluorobutane and 30% by weight of trans-1,2-dichloroethylene. The boiling point is 36.5°C ± 0.2°C for a composition containing approximately 56 to 82% by weight of 1,1,1,3,3-pentafluorobutane, at a pressure of
25 1022 mbar.

REPLACEMENT SHEET

02 SEP 1996

TABLE I

PFBA, g	DCEe added, g (cumulative amt.)	DCEe Content		Boil. point, °C
		weight %	mol %	
20.9	0	0.00	0.00	40.8
	0.087	0.42	0.63	40.5
	0.211	1.00	1.52	40.3
	0.488	2.28	3.44	39.9
	0.826	3.80	5.69	39.4
	1.018	4.65	6.92	39.1
	1.302	5.86	8.69	38.8
	1.629	7.23	10.63	38.4
	1.891	8.30	12.14	38.1
	2.228	9.63	14.00	37.8
	2.627	11.16	16.10	37.7
	3.018	12.62	18.06	37.4
	3.570	14.59	20.69	37.1
	4.019	16.13	22.69	36.9
	4.577	17.90	24.98	36.7
	5.451	20.68	28.48	36.6
	5.939	22.13	30.26	36.5
	6.459	23.61	32.06	36.4
	7.331	25.97	34.88	36.4
	7.837	27.27	36.41	36.3
	9.120	30.38	39.98	36.3
	9.896	32.13	41.96	36.3
	10.578	33.60	43.59	36.4
	12.163	36.79	47.05	36.5
	13.899	39.94	50.38	36.5
	16.403	43.97	54.51	36.7
	20.529	49.55	59.99	37.1
	25.335	54.80	64.92	37.9
	28.117	57.36	67.26	38.2

REPLACEMENT SHEET

02 SEP 1996

Example 2

A solution containing 66.2% by weight of 1,1,1,3,3-pentafluorobutane, 29.8% by weight of trans-1,2-dichloroethylene and 4% by weight of methanol was prepared. This solution was subjected to a distillation at atmospheric pressure using a Vigreux column. The boiling temperature remained constantly equal to 32°C. The various fractions of the distillate, each representing from 5 to 20% of the weight of the initial solution, were withdrawn using a multi-limb distributor ("pig") and then analysed by gas phase chromatography. The results obtained are collated in Table II.

TABLE II

Fraction of the distillate		PFBA (weight %)	DCEe (weight %)	Methanol (weight %)
15	1 (5.7 weight % of the solution)	64.9	31.5	3.6
	2 (12.1 weight % of the solution)	65.1	31.2	3.7
	3 (16.5 weight % of the solution)	65.3	31.0	3.7
	4 (15.0 weight % of the solution)	65.6	30.7	3.7
	5 (10.3 weight % of the solution)	65.9	30.3	3.8
20	6 (14.0 weight % of the solution)	66.2	30.0	3.8

The virtually identical composition of the various fractions obtained shows the existence of a ternary azeotrope between 1,1,1,3,3-pentafluorobutane, trans-1,2-dichloroethylene and methanol, the estimated composition of which is 64.9% by weight of 1,1,1,3,3-pentafluorobutane, 31.5% by weight of trans-1,2-dichloroethylene and 3.6% by weight of methanol.

REPLACEMENT SHEET

02 SEP 1996

02 SEP 1996

- 9 -

Example 3


A solution containing 66.2% by weight of 1,1,1,3,3-pentafluorobutane, 32.1% by weight of trans-1,2-dichloroethylene and 1.7% by weight of ethanol was prepared. This solution was subjected to a distillation at atmospheric pressure using a Vigreux column. The boiling temperature remained constantly equal to 34°C. The various fractions of the distillate, each representing approximately from 5 to 15% of the weight of the initial solution, were withdrawn using a multi-limb distributor ("pig") and then analysed by gas phase chromatography. The results obtained are collated in Table III.

TABLE III

15	Fraction of the distillate	PFBA (weight %)	DCEe (weight %)	Ethanol (weight %)
	1 (4.8 weight % of the solution)	66.1	32.4	1.5
	2 (16.7 weight % of the solution)	66.1	32.3	1.6
	3 (12.7 weight % of the solution)	66.1	32.3	1.6
20	4 (12.2 weight % of the solution)	66.3	32.1	1.6
	5 (12.1 weight % of the solution)	66.2	32.2	1.6
	6 (15.1 weight % of the solution)	66.2	32.2	1.6
	7 (10.5 weight % of the solution)	66.3	32.0	1.7

The virtually identical composition of the various fractions obtained reveals the existence of a ternary azeotrope between 1,1,1,3,3-pentafluorobutane, trans-1,2-dichloroethylene and ethanol, the estimated composition of which is 66.1% by weight of 1,1,1,3,3-

pentafluorobutane, 32.3% by weight of trans-1,2-dichloro-ethylene and 1.6% by weight of ethanol.



REPLACEMENT SHEET

02 SEP 1996

- 11 -



CLAIMS


1. Compositions comprising 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene.
2. Compositions according to Claim 1, characterized in that they contain at least 50% by weight of 1,1,1,3,3-pentafluorobutane and from 15 to 50% by weight of 1,2-dichloroethylene.
3. Compositions according to Claim 1 or 2, characterized in that they additionally contain an alkanol chosen from methanol, ethanol, propanol and isopropanol.
4. Compositions according to Claim 1 or 2, characterized in that they consist essentially of 1,1,1,3,3-pentafluorobutane and 1,2-dichloroethylene in proportions for which they form a binary azeotrope or pseudoazeotrope.
5. Compositions according to Claim 4, characterized in that they consist essentially of 56% to 82% by weight of 1,1,1,3,3-pentafluorobutane and of 44 to 18% by weight of 1,2-dichloroethylene.
6. Compositions according to any one of Claims 1 to 3, characterized in that they consist essentially of 1,1,1,3,3-pentafluorobutane, 1,2-dichloroethylene and an alkanol in proportions for which they form a ternary azeotrope or pseudoazeotrope.
7. Compositions according to Claim 6, characterized in that they consist essentially of 62 to 68% by weight of 1,1,1,3,3-pentafluorobutane, of 28 to 34% by weight of 1,2-dichloroethylene and of 2 to 7% by weight of methanol.
8. Compositions according to Claim 6, characterized in that they consist essentially of 64 to 68% by weight of 1,1,1,3,3-pentafluorobutane, of 30 to 35% by weight of 1,2-dichloroethylene and of 1 to 3% by weight of ethanol.
9. Use of the compositions according to any one of Claims 1 to 8 as cleaning agents.
10. Use of the compositions according to any one of Claims 1 to 8 as degreasing agents for solid surfaces.
11. Use of the compositions according to any one of Claims 1 to 8 as cleaning agents for printed circuit



- 12 -

boards contaminated by a pickling flux and residues from this flux.

12. Use of the compositions according to any one of Claims 1 to 8 as desiccating agents for removing the
5 water adsorbed at the surface of solid objects.



ABSTRACT

**COMPOSITIONS COMPRISING PENTAFLUOROBUTANE AND USE
OF THESE COMPOSITIONS**

The invention relates to compositions comprising 1,1,1,3,3-pentafluorobutane, 1,2-dichloroethylene and optionally a C1-C3 alkanol. These compositions can be used especially as solvents for cleaning and defluxing electronic components and for degreasing metals.

No figure.

