

# ULTRA LOW FREQUENCY TRANSDUCER AND LOUD SPEAKER COMPRISING SAME

## TECHNICAL FIELD

The present invention relates to ultra low frequency transducers for use as  
5 subwoofers for automotive speaker systems.

## BACKGROUND ART

In automotive speakers, space is extremely limited. The need to minimize  
the size of the speaker is constantly at battle with the need to maximize sound and  
performance of the speakers. This is especially true in the case of subwoofers, where  
10 ultra low frequency sounds are produced.

Speaker loudness is a function of the volume of air displaced by  
movement of the diaphragm, which is in turn a function of the stroke or excursion of the  
diaphragm and its diameter. The lower range of the typical stereo speaker or woofer  
only operates down to about 40-80 Hz. However, with modern recording techniques,  
15 musical recordings generate much lower signals to as low as 20 Hz or below. There is a  
need for a subwoofer that can satisfactorily reproduce these ultra low range signals.

## DISCLOSURE OF THE INVENTION

The present invention is directed to an ultra low frequency transducer  
comprising a concave diaphragm supported by a basket for axial movement. The  
20 diaphragm has a rectangular periphery supported in the rectangular front of the basket.  
The transducer further includes a driver assembly supported by the basket and  
comprising a permanent magnet and a reciprocally supported voice coil linked to the  
diaphragm. The voice coil is connected to a signal source. In this way, the driver  
assembly is adapted to convert signals from the signal source into reciprocating axial  
25 motion of the diaphragm to produce ultra low frequency sounds.

The present invention further comprises a loud speaker comprising the  
above-described ultra low frequency transducer supported inside an enclosure. In this  
loud speaker, the enclosure has a rectangular opening and the rectangular periphery of  
the diaphragm is about the same size as the opening.

30 Still further, the present invention comprises an ultra low frequency  
transducer comprising a basket having a front opening and a concave diaphragm. The  
diaphragm has a periphery sized to be supported in the front opening of the basket and is

supported therein for axial movement. A flexible surround is provided around the periphery of the diaphragm. A driver assembly, as described above, is supported by the basket.

#### BRIEF DESCRIPTION OF THE DRAWINGS

5                Figure 1 is a right frontal perspective view of the loud speaker of the present invention.

              Figure 2 is a front elevational view of the ultra low frequency transducer.

              Figure 3 is a longitudinal sectional view of the ultra low frequency transducer of the loud speaker of Figure 1.

10             Figure 4 is a rear perspective view of the basket of the ultra low frequency transducer.

#### BEST MODES FOR CARRYING OUT THE INVENTION

              The present invention is directed to an ultra low frequency transducer, that is, a transducer capable of effectively reproducing only about the lowest two octaves  
15    of music, from about 20 Hz to about 80 Hz. The transducer of the present invention has a concave diaphragm (or cone). The periphery of the diaphragm may be rectangular or square. Alternately, the periphery of the diaphragm may be round or oval. The rectangular shape maximizes the diaphragm area relative to the enclosure, which is also usually rectangular, and thus the air displacement in the speaker.

20             Turning now to the drawings in general and to Figure 1 in particular, there is shown therein a loud speaker in accordance with the present invention and designated generally by the reference numeral 10. The speaker 10 comprises an enclosure 12 with a frontal opening 14. The enclosure houses a transducer 16 with a diaphragm 18 having a periphery 20 sized to be substantially coextensive with the opening 14. As best shown in  
25    Figure 2, the frontal opening 14 of the enclosure preferably is rectangular and more preferably the opening is square. Similarly, the periphery 20 of the preferred diaphragm 18 is rectangular and more preferably is square and is about the same size as the frontal opening 14. As used herein, "rectangular" means a parallelogram with a right angle, and square means a rectangle with four equal sides. In those instances where the  
30    periphery of the diaphragm is round, the enclosure may be rectangular, square or cylindrical.

              With reference now also to Figures 3 and 4, the construction of the preferred transducer will be described. As indicated, and as best seen in Figure 3, the

diaphragm 18 is concave, that is, the inner aspect or body portion 22 is generally dome-shaped. As used herein, "concave" is relative to the front of the enclosure and denotes a shape in cross-section that has a depth. Thus, "concave" would include conical or frusto-conical.

5           The diaphragm 18 preferably is made of a special talc-filled polypropylene material that is very stiff and highly internally damped. The internal damping controls standing waves on the diaphragm, while the stiffness suppresses flex during large excursions. The preferred diaphragm is resistant to pollution, sunlight and moisture.

10           The diaphragm in a subwoofer is subject to a great deal of stress because of the high excursion. For this purpose, the diaphragm 18 is formed with reinforcing trusses, one of which is designated by the reference numeral 26 (Figure 2). Preferably, the trusses are contours formed into the diaphragm when it is made.

          In the preferred embodiment, the diaphragm 18 includes a surround 30  
15   extending around the periphery 20. The surround 30 conforms to the shape of the periphery of the diaphragm 18. The ideal configuration of the surround 30 is convex in cross-section. As used herein, "convex" is relative to the front of the speaker. The surround 30 preferably is made of a flexible, but shape-sustaining material, and usually is not the same as the more rigid material used for the main body 22 of the diaphragm 18.

20           In the preferred embodiment, the diaphragm edge is stepped down to form a platform or flange 32 to which the surround is glued. The stepped-down flange 32 adds to the rigidity of the diaphragm 18, and serves as a convenient point of attachment, usually by stitching, for the inner edge of the surround 30.

          To improve the performance and durability of the surround 30, the  
25   corners are provided with one or more radially oriented ribs or pleats, one of which is designated by the reference numeral 34. While the pleats 34 shown are outwardly extending, the pleats alternately may be depending grooves. Further, the number, spacing, width, and cross-sectional shape of the pleats may be varied. The pleats allow the surround to collapse and expand uniformly as the diaphragm 18 reciprocates. This  
30   reduces distortion and buckling of the surround 30, particularly at the corners in the case of a square or rectangular periphery.

          With continued reference to Figures 3 and 4, the transducer 16 comprises a frame or basket 36 that supports the components of the transducer. The basket 36 has a

front 38 and a rear 40 connected by a plurality of struts 41 therebetween. The front 38 preferably is provided with a planar edge 42 having a recess 44 adapted to receive an outer flange 46 on the surround 30. In this way, the periphery 20 of the diaphragm 18, by means of the flange 46 on the surround 30, is supported on the front 38 of the basket 36. Preferably, the basket is made of die cast aluminum. The cast aluminum basket is more rigid than stamped steel.

More particularly, in a manner that will be described hereafter, the diaphragm 18 is thereby supported on the basket 36 for axial, reciprocal movement inside the enclosure 12. Though not shown herein, a gasket may be attached over the flange 46 of the surround 30 and under the front edge 42 of the basket 36. A preferred gasket material is Rubatex brand, which is composed of foam rubber, chopped and glued, to provide an excellent seal to many surfaces.

As best seen in Figure 3, the center portion 48 of the diaphragm 18 preferably is frusto-conically shaped and extends inwardly. The diaphragm 18 is operatively associated with a suitable driver assembly 50, yet to be described, also supported by the basket 36. To that end, the open edge of the diaphragm center 48 is attached circumferentially to the closed end of a voice coil former 52 in a known manner. A Kapton brand voice coil former is preferred because it is lightweight, strong, and retains its shape at high temperatures.

While the surround 30 attached to the front 38 of the basket 36 is the upper support for the moving system, a spider 54 preferably provides the lower support. A progressive spider may be used to reduce stress on the glue joint at the former 52, and force it to the outer regions. The spider 54 also provides soft mechanical limiting and centering as it extends radially between the former 52 and adjacent annular section 56 of the basket 36.

A voice coil 58 is supported on the former 52 in a known manner. A longer voice coil 58 is desired as it gives the driver greater excursion capability to move more air and produce more low bass. A preferred coil for the present invention comprises a 4-layer round wire. The wire insulation and coil adhesives are designed to handle the heat associated with high power operation.

The coil 58 is attached by tinsel leads 59 which connect to terminals 60 supported on the annular section 56 of the basket 36. The external leads 61 connect the

terminals 60 to a signal source 61, such as the radio or disk player in an automobile (see Figure 1).

As the tinsel leads 59 must absorb the abuse of motion as well as transfer large currents to the voice coil 58, it will be desirable to use two braided leads. An annular cone brace 63 may be included to provide additional support for the cone, which must also endure repetitive wide excursions.

Preferably the transducer 16 comprises an inverted structural dome or dust cap 64 that extends across the body portion 20 of the diaphragm 18 and encloses the voice coil former 52. Integration of the concave body 22 of the diaphragm 18 with the concave dust cap 62 in a locking action is advantageous as it increases the rigidity of the diaphragm to further inhibit diaphragm flex. This integration creates a piston action that is more effective, especially at high sound pressure levels (SPL).

The voice coil former 52 is telescopically received over the pole piece 66. The pole piece 66 preferably is tubular, the hollow center forming a pole piece vent 68. The vent 68 will enhance the speaker's compliance by relieving pressure from under the dust cap 64. Otherwise, this pressure might impede diaphragm movement at low frequencies and generate noise as air rushes through the voice coil gap. This is especially important in long throw drivers. A screen 69 may be placed over the vent hole to keep foreign material from entering the inner motor structure.

The transducer preferably comprises a back plate 70 in form of an annular ring. More preferably, the pole piece 66 and the back plate 70 are integrally formed in one piece of metal to improve magnetic field strength as well as heat transfer. It is advantageous to dye the back plate 70 and pole piece 66 black to increase heat transfer. In the preferred practice of this invention, the back plate 70 is formed with a "bumped" portion 72 to allow the voice coil former 52 maximum movement without ever contacting the back plate. The lower windings can be damaged and cause driver failure if contact occurs.

A permanent magnet 74 is supported between the back plate 70 and a top plate 76. A suitable magnet is a ceramic ferrite magnet. The magnet 74 should be optimized for the performance of each driver assembly 50. The size of the magnet does not always relate to the amount of bass produced. Too large of a magnet structure can over dampen and restrict diaphragm motion, reducing efficiency and low response characteristics.

The top plate 76 engages the lower surface of the rear end 78 of the basket 36. Thus, the pole piece 66, back plate 70, magnet 74 and top plate 76 are rigidly attached to the basket 36, while the voice coil former 52 and attached diaphragm 18 are supported in the basket for axial, reciprocal movement. A soft rubberized magnet boot 79 is desirable in many applications, as it will protect the magnet 74 from chipping and adds to the appearance of the driver assembly 50.

The annular surface 80 of the magnet 74 and the annular surface 82 of the top plate 76 are spaced radially from the voice coil 58 providing a gap 84. When the coil 58 is energized by a signal from the signal source 62, a magnetic field is created in the gap 84 between the voice coil former 52 and the magnet 74 causing the former 52 and the diaphragm 18 linked to it to reciprocate axially and produce sound. The top plate 76 focuses the magnetic field in the gap 84. The top plate 76 may also be dyed black to improve heat transfer.

As shown in Figure 2, the pole piece 66 preferably is extended above the top plate 76 to create a more uniform magnetic field to provide linear diaphragm travel. This reduces distortion caused by nonlinear movement. The longer pole also helps keep the voice coil cooler by not allowing the upper coil windings to radiate heat across to each other. This is desirable because heat buildup can cause speaker failure.

Now it will be appreciated that, in the ultra low frequency transducer of this invention, the use of a square or rectangular diaphragm and surround maximizes air displacement in a square enclosure. As a result, the diaphragm size and thus the displacement volume are increased as compared to a conventional round diaphragm designs housed in square or rectangular enclosures. In addition, a contoured, pleated surround improves performance and durability in speakers of any size and shape.

Changes can be made in the combination and arrangement of the various parts and elements described herein without departing from the spirit and scope of the invention as defined in the following claims.

#### INDURSTRIAL APPLICABILITY

As will be apparent from the description, the invention is applicable in the field of sound transmission and amplification.

## CLAIMS

What is claimed is:

1. An ultra low frequency transducer comprising:

a basket having a rectangular front;

5 a concave diaphragm with a rectangular periphery sized to be supported in the front of the basket and supported for axial movement; and

10 a driver assembly supported by the basket comprising a permanent magnet and a reciprocally supported voice coil linked to the diaphragm, the voice coil connected to a signal source, whereby the driver assembly is adapted to convert signals from the signal source into reciprocating axial motion of the diaphragm to produce ultra low frequency sounds.

2. The transducer of claim 1 wherein the rectangular front of the basket and the rectangular periphery of the diaphragm are both square.

15 3. The transducer of claim 1 wherein the diaphragm further comprising a flexible surround around the periphery of the diaphragm.

4. The transducer of claim 3 wherein the surround is convex in cross-section.

20 5. The transducer of claim 4 wherein the surround is formed into at least one radially positioned pleat at each corner.

6. The transducer of claim 4 wherein the surround is formed into a plurality of radially positioned pleats at each corner.

7. The transducer of claim 6 wherein the pleats extend outwardly from the surround.

25 8. The transducer of claim 1 wherein the diaphragm is provided with a plurality of trusses.



9. A loud speaker comprising:  
an enclosure having a rectangular opening;  
an ultra low frequency transducer comprising:

5 a concave diaphragm with a rectangular periphery about the same  
size as the rectangular opening of the enclosure, wherein  
the diaphragm is supported for axial movement inside the  
enclosure; and

10 a driver assembly comprising a permanent magnet and a  
reciprocally supported voice coil linked to the diaphragm,  
the voice coil connected to a signal source, whereby the  
driver assembly is adapted to convert signals from the  
signal source into reciprocating axial motion of the  
diaphragm to produce ultra low frequency sounds.

15 10. The loud speaker of claim 9 wherein the rectangular opening in  
the enclosure and the rectangular periphery of the diaphragm are both square.

11. The loud speaker of claim 9 further comprising a rigid basket  
having a front and a rear, the front being rectangular and sized to support the rectangular  
periphery of the diaphragm.

20 12. The loud speaker of claim 11 wherein the diaphragm further  
comprises a flexible surround around the periphery of the diaphragm.

13. The loud speaker of claim 12 wherein the surround is convex in  
cross section.

14. The loud speaker of claim 13 wherein the surround is formed into  
at least one radially positioned pleat at each corner.

25 15. The loud speaker of claim 13 wherein the surround is formed into  
a plurality of radially positioned pleats at each corner.

16. The loud speaker of claim 17 wherein the pleats extend outwardly  
from the surround.



17. The loud speaker of claim 9 wherein the diaphragm is provided with a plurality of trusses.

18. An ultra low frequency transducer comprising:

a basket having a front opening;

a concave diaphragm with a periphery sized to be supported in the front opening of the basket and supported for axial movement;

a flexible surround around the periphery of the diaphragm; and

a driver assembly supported by the basket comprising a permanent magnet and a reciprocally supported voice coil linked to the diaphragm, the voice coil connected to a signal source, whereby the driver assembly is adapted to convert signals from the signal source into reciprocating axial motion of the diaphragm to produce ultra low frequency sounds.

19. The transducer of claim 18 wherein the surround is convex in cross-section.

20. The transducer of claim 19 wherein the surround is formed into at least one radially oriented pleat.

21. The transducer of claim 20 wherein the surround is formed into a plurality of radially positioned pleats positioned circumferentially about the surround.

22. The transducer of claim 21 wherein the pleats extend outwardly from the surround.

23. The transducer of claim 22 wherein the periphery of the diaphragm is round.

24. The transducer of claim 18 wherein the periphery of the diaphragm is round.

