

A hook for a hearing aid

The present invention relates to a hook for a hearing aid, in particular a BTE-type hearing aid, 5 and a hearing aid utilizing such a hook.

BTE-type hearing aids generally have a hearing aid housing comprising a shell in which all of the electronics, including input and output transducers, of the hearing aid are typically located. The shell 10 is worn Behind The Ear, hence the abbreviation BTE. If the output transducer is located in the hearing aid housing, the output sound from the hearing aid is conducted via a sound tube to an earplug placed in an ear of the person wearing the hearing aid.

15 BTE-hearing aids generally have a hook-shaped part forming the transition from the hearing aid housing in which the sound output transducer is located to the sound tube. This hook-shaped part may be integrally formed with the shell of the hearing aid 20 housing. The hook has a curved shape, which may *inter alia* serve to hold the hearing aid in a correct position behind the ear of the wearer.

Often, however, in BTE-hearing aids the sound tube is not connected directly to the shell of the 25 hearing aid housing. Rather, a separate intermediate piece, commonly referred to as a hook, forms the transition between the shell of the hearing aid housing and the sound tube.

The hook is made from a material which is more 30 rigid than that of the sound tube in order to allow the sound tube to be readily attached thereto and removed therefrom. As the name hook indicates, it has a curved shape. The external shape of the hook is usu-

ally so that a smooth transition from the hook to the hearing aid housing, to which it is attached, is obtained. Thus, at the proximal end, where the hook is attached to the hearing aid housing, the external cross-section usually matches that of the hearing aid housing. The hook generally has a taper from the proximal end towards the distal end. Internally the hook has a sound passage extending from the proximal end to the distal end. This passage usually has a circular cross-section, with a constant diameter along the length.

In hearing aids it is well known that feed-back problems exist between the output transducer, and the input transducer. The feed-back is *inter alia* a problem because it limits the maximum gain achievable with the hearing aid.

The present invention bases itself on the realisation by the inventors that even though the output transducer and input transducer are located in the same housing, the hook attached to the shell of the hearing aid housing, or if the hearing aid has an integral housing, the hook-shaped part extending beyond the output transducer plays a role in these feedback problems.

On this background the present invention sets out to reduce the amount of feed-back between output and input transducers in hearing aids, in particular of the BTE-type. In this respect it should be noted that wherever the present description and claims makes reference to an input transducer, the use of more than one input transducer is not excluded. The skilled person will know that more than one input transducer is commonly used, e.g. in order to obtain

directionality, and that the number of input transducers is generally immaterial to the feed-back problems as discussed herein.

According to a first aspect of the invention,
5 this object is achieved by a hook for a hearing aid, said hook comprising a sound passage for transmitting the sound emanating from an output transducer of the hearing aid, characterized in that said hook comprises first and second materials with different
10 elastic properties.

By using two different materials, it is achieved that mechanical vibrations, in particular in the audible frequency range, are not transmitted from the hook to the input transducers in the hearing aid
15 housing.

According to a second aspect of the invention, this object is achieved by a hearing aid comprising a hook-shaped sound output part having a sound passage for transmitting the sound emanating from an output
20 transducer of the hearing aid, characterized in that said hearing aid comprises damping means for damping mechanical vibrations of the hook-shaped sound output part.

By the provision of such a damping means in
25 connection with the hearing aid, it is achieved that mechanical vibrations, in particular in the audible frequency range, are not transmitted from the hook-shaped sound output part to the input transducers in the hearing aid housing.

30 In a preferred embodiment of the first aspect of the invention, said first and second materials are provided as integral parts of the hook. Providing both materials as integral parts of the hook, rather

than e.g. one of them as a separate part to be mounted thereon or as a part of a hook assembly, is preferable in terms of manufacturing and storing.

Presently it is preferred to provide said one
5 of the materials as a section between a proximal end of said hook and a distal end of said hook. This allows simple manufacturing, e.g. by adhering parts of the hook together.

In a further preferred embodiment according to
10 the first aspect of the invention, said first material is a layer of adhesive material joining two parts of the hook. In this case the adhesive serves as a vibration damping material. Thus, no further parts of vibration damping material will be necessary.
15

In yet a further embodiment according to the first aspect of the invention, said first material is a rubber material. This is preferred, as it allows many design options, e.g. using the rubber itself as
20 adhesive between two parts of a hook made of a plastic material. Using a plastic material is preferable, because it allows the hook to have virtually the same properties as existing hooks. Hooks, which are interchangeable with existing hooks of existing hearing
25 aids may thus be made, thus allowing improvement of existing hearing aids.

In a most preferred embodiment according to the first aspect of the invention, of said first and second materials, the material of which the minor part
30 of the hook is made is provided as a material, which is softer than the material of which the major part of the hook is made. This allows the use of both the rubber and plastic materials referred to above.

In a first embodiment of the hearing aid according to the second aspect of the invention the damping means is provided as an integral part of the hook. Providing the damping material as an integral
5 part of the hook, rather than e.g. a separate part to be mounted thereon, as a part of a hook assembly, is preferable in terms of manufacturing and storing.

Alternatively, however, the damping means may be provided as a separate part between the hook and
10 the part of the hearing aid housing containing the output transducer. Thus rather than substituting the existing conventional hook of a used hearing aid with a hook with integral damping means according to the invention, a damping means could instead be inserted
15 between the existing hook and the housing of a hearing aid, without departing from the invention.

According to a further embodiment of the hearing aid according to the second aspect of the invention, however, the damping means is provided between
20 the part of the hearing aid housing in which the output transducer is located and the hook-shaped part. This allows the damping means to be provided as a separate piece, insertable between the hook and the hearing aid housing.

25 According to yet a further embodiment of the hearing aid according to the second aspect of the invention, the damping means is provided as a damping material, which is softer than the material of which the major part of the hook-shaped part and the hearing aid housing are made. This allows the use of both
30 the rubber and plastic materials referred to above.

The invention will now be described in greater detail based on non-limiting exemplary embodiments, illustrated in the drawings. On the drawings

fig. 1a shows a perspective view of a BTE hearing aid incorporating a hook according to the invention,

fig. 1b shows a different perspective view of the BTE hearing aid of fig. 1a,

fig. 2 shows a hearing aid housing of the hearing aid including the attached hook according to the invention, fig. 3a shows an exploded view of the hook according to the invention seen from a first angle,

fig. 3b shows an exploded view of the hook according to the invention seen from another angle,

fig. 4a shows a perspective view of a BTE hearing aid incorporating a damping means according to the invention, and

fig. 4b shows a different perspective view of the BTE hearing aid of fig. 4a.

Figs. 1a and 1b show a hearing aid 1 from different angles. The hearing aid 1 comprises four parts, namely a hearing aid housing 2, an earplug 3, a hook 4 and a sound tube 5. The hearing aid housing 2 may comprise all of the electronics of the hearing aid, including input and output transducers, signal processing means, switches, battery, etc.

To the hearing aid housing 2 the hook 4 is attached. The attachment of the hook 4 to the hearing aid housing 2 can be of a more or less permanent nature. That is to say, it may be detachable without the use of tools, or it may be in a mechanical engagement with the housing, necessitating the housing parts to be disassembled by means of tools in order

to replace or remove the hook. To the other end of the hook 4 one end of a sound tube 5 is attached. The other end of the sound tube 5 is attached to an earplug 3.

5 The sound tube 5, and in particular the earplug, are prone to be soiled from their use, and thus need to be replaceable. Consequently, the sound tube 5 is readily detachable from the hook 4, as well as from the earplug 3, without the use of any tools.

10 The hook 4, the sound tube 5 and the earplug 3 all include a sound passage so as to form a continuous sound passage for conducting sound from the transducer in the hearing aid housing to an output opening 6 in the earplug 3. Depending on the actual
15 location of the output transducer in the hearing aid housing 2, the hearing aid housing 2 may also include an internally arranged tubular member forming part of the sound passage from the output transducer to the sound output opening 6 of the earplug 3.

20 Fig. 2 shows the hook 4 and the hearing aid housing 2 in greater detail. As can be seen, the hook of the embodiment illustrated comprises three parts 4a, 4b, 4c. The three parts 4a, 4b, 4c are shown in greater detail in the exploded views of fig. 3a and
25 fig. 3b.

 The parts 4a and 4c are both made of a plastic material, preferably but not necessarily the same plastic material. The distal end of the hook 4, i.e. the end of the part 4a is provided with a sound tube
30 engaging and holding means 4d. In the illustrated example the sound tube engaging and holding means is provided as a circumferential barb 4d. As can best be seen from fig. 3b, the proximal end of the hook 4,

i.e. the end of the part 4c is provided with a housing engagement means. In the illustrated example the housing engagement means is an undercut in the form of a groove 4e, in which the shell parts of the hearing aid housing 2 engage, so as to secure the hook 4 to the hearing aid housing 2.

Between the part 4a and the part 4c the third part 4b is located. The third part 4b comprises a vibration damping material. The inclusion of such a vibration damping material in the hook 4 has been found to substantially reduce the feedback from the hook 4 to the input transducer. The vibration damping material is preferably a softer material than the material of which the parts 4a and 4c are made.

Preferably, the parts 4a and 4c are made of a transparent plastic material such as PMMA, PC, CP, PEX or the like or of an opaque plastic material such as ABS or POM or the like. Alternatively they could be made of metal such as aluminium or stainless steel. The softer vibration damping material of the third part 4b is preferably a rubber material such as silicone, butyl, EDPM, TPE or the like. Other damping materials than rubber may of course also be used.

It should be understood that the damping material can be integrated in the hook 4 in many different ways.

In the exploded views of fig. 3a and fig. 3b the vibration damping material is provided as a section between the proximal end of the hook 4 and the distal end of said hook 4. The section can be made as a separate part 4b, to which the respective faces of the parts 4a and 4c are subsequently adhered. The part 4b of vibration damping material has a generally

annular shape, as it, like the rest of the hook 4, includes a sound passage 7. The separate part 4b and the other parts 4a, 4c of the hook 4, can be formed in separate moulding processes. Alternatively, the hook 4 could be integrally formed in a multi-component moulding process, such as a two-component injection moulding process. Also, if the damping material is provided as a separate part, it could be formed with mechanical locking means for engaging corresponding locking means formed on the respective parts 4a, 4c.

However, experiments have shown that even a thin segment of vibration damping material between the parts 4a and 4c significantly reduces the feed-back. Thus, by appropriate choice of adhesive, such as silicone glue, the vibration damping material can be provided by the adhesive joining the two parts 4a and 4c of the hook 4 to each other, without the use of a separate vibration damping member as such. That is to say, the adhesive itself serves as the vibration damping means.

It is presently preferred that the vibration damping material is located closer to the proximal end of the hook 4, than to the distal end. Preferably less than half the distance from the proximal end to the distal end, and in particular less than a third of the distance from the proximal end to the distal end.

Also, it should be noted that the embodiment illustrated is only a currently preferred embodiment, and that the vibration damping material need not be located between the two end parts 4a, 4c of the hook 4. Rather, the hook 4 can comprise two parts only,

i.e. a rigid part and a soft part. Preferably, the soft part is located at the proximal end of the hook 4 adjacent the hearing aid housing 2. In particular, the hook could be formed as a single part and the vibration damping material could be located as a spacer between the hook 4 and the hearing aid housing 2.

The thickness of the vibration damping means may depend on the materials or the manufacturing process used. Presently, a thickness of 1 to 3 mm is preferred for a separate element of damping material. However, smaller thicknesses may also be used. In particular if, as indicated above, an adhesive is used as the sole damping material, the thickness thereof may be less than 1 mm, e.g. between 1 mm and 0.1 mm, preferably approximately 0.3 mm.

Moreover, it should be noted that the invention is not limited to the use of a single segment of damping material. Rather, several segments of damping material can be used, possibly with different elastic properties.

Also, it should be noted that even though the illustrated embodiment, presents an annular section of damping material with a constant thickness, the annular section need not have a constant thickness. For instance, the annular segment could be tapered towards the concave side of the hook.

Although the above description of the currently most preferred embodiment relates to the use of the damping means in connection with a separate, replaceable hook, the invention is not restricted to this.

Rather, in a second embodiment of figs. 4a and 4b the damping means is included as an element 4b located between the hook-part 4 and the part of the

hearing aid housing 2 containing the output transducer. The damping means 4b could be a layer of adhesive joining the hook 4 to the remainder of the hearing aid housing 4. Alternatively the hook-part 4, the
5 damping material 4b and at least a part of the housing 2 could be formed integrally, e.g. using a multi-component moulding process, e.g. a two component injection moulding process.

Also, the considerations in respect of materials, dimension, shapes referred to above in connection with the separate hook 4 of the first embodiment would be valid for this second embodiment.

Implicitly, the invention can also be said to utilize a method for reducing feedback in a hearing
15 aid 1, in which the sound is emitted from an output transducer in the hearing aid housing 2 to a hook 4 attached thereto, where the method includes the step of damping vibrations by use of a damping means in connection with the hook 4.

P A T E N T C L A I M S

1. A hook for a hearing aid, said hook comprising a sound passage for transmitting the sound emanating from an output transducer of the hearing aid,
5 c h a r a c t e r i z e d in that said hook comprises first and second materials with different elastic properties.

2. A hook according to claim 1, c h a r a c -
t e r i z e d in that said first and second materi-
10 als are provided as integral parts of the hook.

3. A hook according to claim 2, c h a r a c -
t e r i z e d in that said first material is provided as at least one section between a proximal end of said hook and a distal end of said hook.

15 4. A hook according to claim 2 or 3, c h a r -
a c t e r i z e d in that said first material is a layer of adhesive material joining two parts of the hook.

5. A hook according to any one of claims 2 to
20 4, c h a r a c t e r i z e d in that said first material is a rubber material.

6. A hook according to claims 4 or 5, c h a r -
a c t e r i z e d in that the two parts of the hook are made of a plastic material.

25 7. A hook according to any one of claims 2 to
6, c h a r a c t e r i z e d in that of said first and second materials, the material of which the minor part of the hook is made is softer than the material of which the major part of the hook is made.

30 8. A hearing aid comprising a hook-shaped sound output part having a sound passage for transmitting the sound emanating from an output transducer of the hearing aid, c h a r a c t e r i z e d in that said

hearing aid comprises damping means for damping mechanical vibrations of the hook-shaped sound output part.

9. A hearing aid according to claim 8, 5 c h a r a c t e r i z e d in that the damping means is provided as a separate part between the hook and the part of the hearing aid housing containing the output transducer.

10. A hearing aid according to claim 8, 10 c h a r a c t e r i z e d in that the damping means is provided as an integral part of the hook.

11. A hearing aid according to any one of claims 8, 9 or 10, c h a r a c t e r i z e d in that the damping means is provided between the part 15 of the hearing aid housing in which the output transducer is located and the hook-shaped part.

12. A hearing aid according to any one of claims 8 to 11, c h a r a c t e r i z e d in that the damping means is provided as a damping material, 20 which is softer than the materials of which the major part of the hook-shaped part and the hearing aid housing are made.