

FASTENER ARRANGEMENTS

Embodiments of the present invention relate to fastener arrangements. They relate to fastener
5 arrangements for gas turbine engines.

In many industries, it is desirable to fasten and clamp together a plurality of articles so that they effectively become a unitary body. For example, it is often desirable to clamp together two or more sheets of
10 metal in the manufacture of gas turbine engines.

The fasteners which are currently used comprise a resiliently deformable head with two or more barbed arms which extend from the head. In order to insert such a fastener, it is necessary to insert the fastener into an
15 aperture of the plurality of articles with a large insertion force so that the head may deform and allow the barbed arms to engage the plurality of articles in a clamping manner.

However, the above mentioned fasteners are not
20 suitable for all applications. If the plurality of articles are delicate, the large insertion force needed for the fastener may damage the articles. Additionally, if there is little space around the plurality of articles, it may be difficult to provide a sufficiently large force to
25 deform the head so that the fastener may engage the plurality of articles.

Therefore, it is desirable to provide an alternative fastener arrangement.

According to various embodiments of the present
30 invention, there is provided a fastener arrangement for fastening two or more articles together, the two or more articles having a first length, the fastener arrangement comprising: a fastener including an elongate clamping member for being received in an aperture of the two or more

articles, the elongate clamping member being moveable between a contracted configuration in which the elongate clamping member has a length which is less than the first length and a lengthened configuration in which the elongate clamping member has a length which is greater than the first length, the elongate clamping member being resiliently biased towards the contracted configuration; and an actuator for moving the elongate clamping member, while in the aperture of the two or more articles, from the contracted configuration towards the lengthened configuration to enable the elongate clamping member to protrude through the aperture and to engage the articles in a clamping manner.

The fastener arrangement may further comprise a guide. The guide may include a recess for receiving the elongate clamping member of the fastener. The guide and fastener combination may be moved through the aperture together.

The guide may include the actuator for moving the elongate clamping member. The actuator may be arranged such that when the guide is removed from the fastener when the elongate clamping member is in the aperture, the actuator acts on the elongate clamping member and moves it from the contracted configuration towards the lengthened configuration.

The fastener may comprise a substantially straight elongate holding member for being received in the aperture of the articles. The elongate holding member may have a length which is greater than the first length. The elongate holding member may be arranged to prevent the fastener from being removed from the two or more articles accidentally.

The fastener arrangement may further comprise a locking mechanism arranged to be received in the aperture,

adjacent the elongate clamping member, and to prevent the fastener from being removed from the two or more articles.

When the elongate clamping member is in the contracted configuration, the elongate clamping member may have a concave profile. When the elongate clamping member is in the lengthened configuration, the elongate clamping member may have a substantially straight profile.

According to various embodiments of the present invention, there is provided a gas turbine engine comprising a fastener arrangement as described in the preceding paragraphs.

According to various embodiments of the present invention, there is provided a method of fastening two or more articles together, the two or more articles having a first length, the method comprising: providing a fastener including an elongate clamping member; inserting the elongate clamping member into an aperture of the two or more articles, the elongate clamping member being moveable between a contracted configuration in which the elongate clamping member has a length which is less than the first length and a lengthened configuration in which the elongate clamping member has a length which is greater than the first length, the elongate clamping member being resiliently biased towards the contracted configuration; and moving the elongate clamping member, while in the aperture of the two or more articles, from the contracted configuration towards the lengthened configuration to enable the elongate clamping member to protrude through the aperture and to engage the articles in a clamping manner.

The method may further comprise providing a guide which includes a recess; inserting the elongate clamping member of the fastener into the recess of the guide and moving the combination of the guide and the fastener through the aperture together.

4

The method may further comprise removing the guide from the fastener while the elongate clamping member is in the aperture.

When the guide is removed from the fastener, an
5 actuator portion of the guide may act on the elongate clamping member and may move it from the contracted configuration towards the lengthened configuration.

The fastener may further comprise a substantially straight elongate holding member for being received in the
10 aperture of the articles. The elongate holding member may have a length greater than the first length. The elongate holding member may be arranged to prevent the fastener from being removed from the two or more articles accidentally.

The fastener arrangement may further comprise
15 providing a locking mechanism and inserting the locking mechanism in the aperture, adjacent the elongate clamping member, to prevent the fastener from being removed from the two or more articles.

When the elongate clamping member is in the contracted
20 configuration, the elongate clamping member may have a concave profile. When the elongate clamping member is in the lengthened configuration, the elongate clamping member may have a substantially straight profile.

For a better understanding of the present invention
25 reference will now be made by way of example only to the accompanying drawings in which:

Fig. 1 illustrates a sectional side view of the upper half of a gas turbine engine;

Fig. 2 illustrates a side view of a fastener
30 arrangement according to one embodiment of the present invention;

Figs. 3A, 3B, 3C, 3D and 3E illustrate a series of sequential side view diagrams that show how a fastener and

a guide are used in order to clamp a plurality of articles together according to one embodiment of the invention;

Fig. 4 illustrates a side view of a fastener arrangement according to another embodiment of the invention;

Fig. 5 illustrates a side view of a fastener according to one embodiment of the invention; and

Fig. 6 illustrates a side view of a fastener according to another embodiment of the invention.

Figs. 2 to 6 illustrate a fastener arrangement 22 for fastening two or more articles 62 together, the two or more articles 62 having a first length, the fastener arrangement 22 comprising: a fastener 24 including an elongate clamping member 36 for being received in an aperture 64 of the two or more articles 62, the elongate clamping member 36 being moveable between a contracted configuration in which the elongate clamping member 36 has a length which is less than the first length and a lengthened configuration in which the elongate clamping member 36 has a length which is greater than the first length, the elongate clamping member 36 being resiliently biased towards the contracted configuration; and an actuator 50 for moving the elongate clamping member 36, while in the aperture 64 of the two or more articles 62, from the contracted configuration towards the lengthened configuration to enable the elongate clamping member 36 to protrude through the aperture 64 and to engage the articles 62 in a clamping manner.

Referring to Fig. 1, a gas turbine engine is generally indicated at 10 and comprises, in axial flow series, an air intake 11, a propulsive fan 12, an intermediate pressure compressor 13, a high pressure compressor 14, a combustor 15, a turbine arrangement comprising a high pressure turbine 16, an intermediate pressure turbine 17 and a low pressure turbine 18, and an exhaust nozzle 19.

The gas turbine engine 10 operates in a conventional manner so that air entering the intake 11 is accelerated by the fan 12 which produce two air flows: a first air flow into the intermediate pressure compressor 13 and a second
5 air flow which provides propulsive thrust. The intermediate pressure compressor compresses the air flow directed into it before delivering that air to the high pressure compressor 14 where further compression takes place.

10 The compressed air exhausted from the high pressure compressor 14 is directed into the combustor 15 where it is mixed with fuel and the mixture combusted. The resultant hot combustion products then expand through, and thereby drive, the high, intermediate and low pressure turbines 16,
15 17 and 18 before being exhausted through the nozzle 19 to provide additional propulsive thrust. The high, intermediate and low pressure turbines 16, 17 and 18 respectively drive the high and intermediate pressure compressors 14 and 13 and the fan 12 by suitable
20 interconnecting shafts 20.

Fig. 2 illustrates a side view of a fastener arrangement 22 according to one embodiment of the invention. The fastener arrangement 22 may be used to fasten together two or more articles in the gas turbine
25 engine 10. For example, the fastener arrangement 22 may be used to fasten together two or more casing sections of the gas turbine engine 10.

A Cartesian co-ordination system 28 is also illustrated which includes an X axis 30 and a Y axis 32
30 which are orthogonal to one another. The co-ordinate system shall be used in the following description to describe the structure of the fastener arrangement 22 in detail.

The fastener arrangement 22 includes a fastener 24 for fastening two or more articles together and a guide 26 for guiding the fastener through an aperture of the two or more articles. The fastener 24 comprises a body 34, a first elongate clamping member 36 and a second elongate clamping member 38. In this embodiment, the fastener 24 and the guide 26 comprise a metal such as titanium. However, in other embodiments the fastener 24 and the guide 26 may comprise other materials such as plastics.

10 The first and second elongate clamping members 36, 38 extend from the centre of the body 34 and define abutment surfaces 40 on the body 34 between where the elongate clamping members 36, 38 extend from the body 34 and the periphery of the body 34. The function of the abutment
15 surfaces 40 will be explained in more detail in the following paragraphs with reference to Figs. 3A to 3E.

 The first and second elongate clamping members 36, 38 extend from the body 34 in the +X direction and each end at a barb 42, 44 respectively. The elongate clamping members
20 36, 38 are moveable between a contracted configuration (as illustrated in Fig. 2) and a lengthened configuration (as illustrated in Fig. 3D for example). The elongate clamping members 36, 38 are resiliently biased towards the contracted configuration.

25 In this embodiment, the elongate clamping members 36, 38 have a concave profile when they are in the contracted configuration. For example if the first elongate clamping member 36 is considered, the first elongate clamping member 36 curves in the +X and -Y directions until a mid-point 46
30 and then curves to the barb 42 in the +X and +Y directions. If the second elongate clamping member 38 is considered, the second elongate clamping member 38 curves in the +X and +Y directions until the mid-point 46 and then curves to the barb 44 in the +X and -Y directions.

In this embodiment, the elongate clamping members 36, 38 have a straightened profile when they are in the lengthened configuration. Consequently, in the lengthened configuration the first and second elongate clamping members 36, 38 extend substantially only in the +X direction from the body 34 (it should be appreciated that the first and second elongate clamping members 36, 38 may have some curvature when in the lengthened configuration and have a small +/- Y component of extension).

10 The first and second elongate clamping members 36, 38 and the body 34 define a cavity 47 whose purpose will be described in the following paragraphs.

The guide 26 includes a body 48 and an actuator 50 which extends from a first end 52 of the body 48 in the -Y direction. The second end 54 of the body 48 (opposite to the first end 52) is tapered to a curved end. The first end 52 of the body 48 and the actuator 50 define a first recess 56 and a second recess 58 which are arranged to receive the barbs 42, 44 of the fastener 24.

20 The actuator 50 extends from the first end 52 of the body 48 in the -Y direction to form a cam lobe 60. The cam lobe 60 has a relatively low coefficient of friction and the tangent of its surface forms a relatively small angle with respect to the X axis 30. The cam lobe 60 is arranged so that it may be received in the cavity 47 of the fastener 24. The function of the cam lobe 60 will be explained in detail in the following paragraphs.

The operation of the fastener arrangement 22 will now be described in detail with reference to Figs. 3A to 3E. Since the fastener arrangement 22 illustrated in Figs. 3A to 3E is similar to the fastener arrangement 22 illustrated in Fig. 2, the same reference numerals are used where the features are the same or similar.

The initial step is illustrated in Fig. 3A where the guide 26 has been combined with the fastener 24 so that the barbs 42, 44 of the elongate clamping members 36, 38 are retained by the recesses 56, 58 in the body 48 respectively and so that the cam lobe 60 is retained in the cavity 47.

Prior to this step, the first and second elongate clamping members 36, 38 have been moved together in the Y axis direction and coupled to one another as mentioned in the previous paragraph. It should be appreciated that when both the elongate clamping members 36, 38 are acted on so that they may fit in the recesses 56, 58, the NET force for moving them together is substantially equal to zero.

Also illustrated in Fig. 3A is a plurality of articles 62 which define an aperture 64 and have a first outer surface 66 and a second outer surface 68. In this embodiment, the plurality of articles 62 are a plurality of metal sheets which have a depth of L_1 (measured between the first outer surface 66 and the second outer surface 68). It should be appreciated that in other embodiments, the plurality of articles 62 may be any other articles which require clamping. In this figure, the fastener arrangement 22 is ready to be inserted into the aperture 64.

In Fig. 3B the fastener arrangement 22 is inserted in the aperture 64 so that the second end 54 of the guide 26 is protruding from the aperture 64 beyond the second outer surface 68. Since the cross section of the aperture 64 is greater than the cross section of the body 48, the fastener arrangement 22 may be relatively easily inserted into the aperture 64.

In Fig. 3C the fastener arrangement 22 has been inserted into the aperture 64 so that the abutment surfaces 40 of the fastener 24 abut the first outer surface 66 of the plurality of articles 62. At this step, the length of

10

the fastener 24 is less than the depth L_1 of the plurality of articles 62 and consequently, the barbs 42, 44 do not engage the second outer surface 68 of the plurality of articles 62.

5 In Fig. 3D the guide 26 is being removed from the fastener 24 and the cam lobe 60 has moved from the cavity 47 to the mid-point 46. As the width of the cam lobe 60 is greater than the distance between the first and second elongate members at the mid-point 46, the cam lobe 60 acts
10 on the first and second elongate clamping members 36, 38 and moves them towards the lengthened configuration and thereby makes the length of the fastener greater than the depth L_1 of the plurality of articles 62. Consequently, at this step the barbs 36, 38 extend beyond the aperture 64 so
15 that they abut and engage the second outer surface 68 of the plurality of articles 62.

 In Fig. 3E the guide 26 has been removed from the fastener 24. At this step, the first and second elongate clamping members 36, 38 move toward the contracted
20 configuration due to their resilient bias. Since the length of the fastener 24 when in the contracted state is less than the depth L_1 of the plurality of articles 62, the fastener 24 exerts a clamping force on the plurality of articles 62 and thereby clamps them together between the
25 abutment surfaces 40 and the barbs 42, 44.

 In Fig. 3E, each of the plurality of articles 62 are illustrated as being separated by a space. It should be appreciated however, that each of the plurality of articles 62 abut one another and that this abutment occurs outside
30 of the figure. In other embodiments, each of the plurality of articles 62 abut one another along their surface and there is no space between each of the plurality of articles 62 when clamped by the fastener 24.

Embodiments of present invention provide an advantage in that the fastener arrangement 22 is relatively easy to insert into an aperture of a plurality of articles and therefore doesn't require a large insertion force. Consequently, embodiments of the present invention are less likely to damage the outer surface of a plurality of articles during insertion. Additionally, the provision of an actuator for moving the elongate clamping members 36, 38 from the contracted configuration toward the lengthened configuration enables the fastener to engage and clamp the plurality of articles together with greater force.

The arrangement of the cam lobe 60 provides an advantage in that it moves the elongate clamping members 36, 38 from the contracted configuration towards the lengthened configuration. The cam lobe 60 is also relatively easy to remove from the fastener 24 since it does not require a large removal force (due to its low coefficient of friction and small surface tangent angles). This may result in less or no damage being done to the plurality of articles 62 during removal of the guide 26 from the fastener 24.

Fig. 4 illustrates a fastener arrangement 22 according to another embodiment of the present invention. Where the features illustrated in Fig. 4 are the same or similar to those illustrated in Fig. 2, the same reference numerals are used.

In this figure, a fastener 24 is inserted in an aperture 64 of a plurality of articles 62 and is clamping them together as described in the previous paragraphs. In this embodiment, the fastener arrangement 22 includes a locking mechanism 70 which is arranged to be inserted between the first and second elongate clamping members 36, 38 when the fastener 24 is inserted in the aperture 64 and thereby prevent them from being accidentally knocked from

the contracted configuration to the lengthened configuration.

In more detail, the locking mechanism 70 includes a locking portion 72 which is shaped and sized to fit snugly
5 between the first and second elongate clamping members 36, 38 when they are inserted in the aperture 64. The locking mechanism 70 also includes a neck portion 74 which is arranged to extend into the cavity 47 of the fastener 24. The neck portion 74 includes a larger part at its end which
10 is for location in the cavity 47 and which prevents the locking mechanism 70 from being removed accidentally from the fastener 24.

It should be appreciated that the locking mechanism 70 provides an advantage in that it may improve the safety of
15 a device which includes the fastener arrangement 22 because the locking mechanism 70 may prevent the fastener 24 from being accidentally removed from the plurality of articles 62.

Fig. 5 illustrates a side view of a fastener 24
20 according to one embodiment of the present invention. Where the features illustrated in Fig. 5 are similar to those illustrated in Fig. 2, the same reference numerals are used.

In this embodiment, the fastener 24 is the same as the
25 fastener 24 illustrated in Fig. 2 but only includes a single elongate clamping member 36, i.e. the fastener 24 does not include the second elongate clamping member 38. The operation of the fastener 24 illustrated in Fig. 5 is the same as that illustrated in Figs. 3A to 3E and will not
30 be repeated here.

Fig. 6 illustrates a side view of a fastener 24 according to another embodiment of the present invention. Where the features illustrated in Fig. 6 are similar to

those illustrated in Fig. 2, the same reference numerals are used.

In this embodiment, the fastener 24 is the same as the fastener illustrated in Fig. 2 but includes an elongate holding member 76 instead of the second elongate clamping member 38. The elongate holding member 76 is substantially straight in profile, has only one configuration and includes a barb 78 at the end opposite to the body 34. The length of the elongate holding member 76 is greater than the depth L_1 of the plurality of articles 62 (not illustrated in this figure for clarity purposes). The operation of the fastener 24 is similar to the operation illustrated in Figs. 3A to 3E and will consequently not be described in detail here.

The embodiment illustrated in Fig. 6 provides an advantage in that it may improve the safety of a device which includes the fastener 24. If the first elongate clamping member 36 is accidentally knocked when it is in an aperture of a plurality of articles, the elongate holding member 78 prevents the fastener 24 from being removed from the plurality of articles 62 since it only has a single configuration in which the length of the member 76 is greater than the depth of the plurality of articles. Consequently, the barb 78 of the elongate holding member 76 continues to engage the plurality of articles 62 even if the fastener 24 is accidentally knocked.

It should be appreciated that embodiments of the present invention may be used in various different applications. Since the insertion force of the fastener arrangement into a plurality of articles and the removal force of the guide from the fastener are relatively small, embodiments of the present invention provide an advantage when used in applications where the plurality of articles are delicate. For example, embodiments of the present

14

invention may be particularly advantageous when used in surgery on the human or animal body.

Although embodiments of the present invention have been described in the preceding paragraphs with reference to various examples, it should be appreciated that modifications to the examples given can be made without departing from the scope of the invention as claimed. For example, a fastener 24 may include more than two elongate clamping members and more than one elongate holding member.

10

CLAIMS

1. A fastener arrangement (22) for fastening two or more articles (62) together, the two or more articles having a first length, the fastener arrangement (22) comprising:

a fastener (24) including an elongate clamping member (36) for being received in an aperture (64) of the two or more articles (62), the elongate clamping member (36) being moveable between a contracted configuration in which the elongate clamping member (36) has a length which is less than the first length and a lengthened configuration in which the elongate clamping member (36) has a length which is greater than the first length, the elongate clamping member (36) being resiliently biased towards the contracted configuration; and

an actuator (50) for moving the elongate clamping member, while in the aperture (64) of the two or more articles (62), from the contracted configuration towards the lengthened configuration to enable the elongate clamping member (36) to protrude through the aperture and to engage the articles (62) in a clamping manner.

2. A fastener arrangement as claimed in claim 1, further comprising a guide (26) which includes a recess (56) for receiving the elongate clamping member (36) of the fastener (24), wherein the guide (26) and fastener (24) combination are moved through the aperture (64) together.

3. A fastener arrangement as claimed in claim 2, wherein the guide (26) includes the actuator (50) for moving the elongate clamping member (36).

4. A fastener arrangement as claimed in claim 3, wherein the actuator (50) is arranged such that when the guide (26) is removed from the fastener (24) when the elongate clamping member (36) is in the aperture (64), the actuator (50) acts on the elongate clamping member (36) and moves it

from the contracted configuration towards the lengthened configuration.

5. A fastener arrangement as claimed in any of the preceding claims, wherein the fastener (24) comprises a substantially straight elongate holding member (76) for being received in the aperture (64) of the articles (62), the elongate holding member (76) having a length greater than the first length and being arranged to prevent the fastener (24) from being removed from the two or more articles (62) accidentally.

6. A fastener arrangement as claimed in any of the preceding claims, further comprising a locking mechanism (70) arranged to be received in the aperture (64), adjacent the elongate clamping member (36), and to prevent the fastener (24) from being removed from the two or more articles (62).

7. A fastener arrangement as claimed in any preceding claims, wherein when the elongate clamping member (36) is in the contracted configuration, the elongate clamping member (36) has a concave profile.

8. A fastener arrangement as claimed in any of the preceding claims, wherein when the elongate clamping member (36) is in the lengthened configuration, the elongate clamping member (36) has a substantially straight profile.

10. A gas turbine engine (10) comprising a fastener arrangement (22) as claimed in any of the preceding claims.

11. A method of fastening two or more articles (62) together, the two or more articles having a first length, the method comprising:

providing a fastener (24) including an elongate clamping member (36);

inserting the elongate clamping member (36) into an aperture (64) of the two or more articles (62), the elongate clamping member (36) being moveable between a

contracted configuration in which the elongate clamping member (36) has a length which is less than the first length and a lengthened configuration in which the elongate clamping member (36) has a length which is greater than the first length, the elongate clamping member (36) being resiliently biased towards the contracted configuration; and

moving the elongate clamping member (36), while in the aperture (64) of the two or more articles (62), from the contracted configuration towards the lengthened configuration to enable the elongate clamping member (36) to protrude through the aperture (64) and to engage the articles (62) in a clamping manner.

12. A method as claimed in claim 10, further comprising providing a guide (26) which includes a recess (56); inserting the elongate clamping member (36) of the fastener (24) into the recess (56) of the guide (26) and moving the combination of the guide (26) and the fastener (24) through the aperture (64) together.

13. A method as claim in claim 11, further comprising removing the guide (26) from the fastener (24) while the elongate clamping member (36) is in the aperture (64).

14. A method as claimed in claim 12, wherein when the guide (26) is removed from the fastener (24), an actuator portion (50) of the guide (26) acts on the elongate clamping member (36) and moves it from the contracted configuration towards the lengthened configuration.

15. A method as claimed in any of claims 10 to 13, wherein the fastener (24) further comprises a substantially straight elongate holding member (76) for being received in the aperture (64) of the articles (62), the elongate holding member (72) having a length greater than the first length and being arranged to prevent the fastener (24) from

18

being removed from the two or more articles (62) accidentally.

16. A method as claimed in any of claims 10 to 14, further comprising providing a locking mechanism (70) and inserting
5 the locking mechanism (70) in the aperture (64), adjacent the elongate clamping member (36), to prevent the fastener (24) from being removed from the two or more articles (62).

17. A method as claimed in any of claims 10 to 15, wherein when the elongate clamping member (36) is in the contracted
10 configuration, the elongate clamping member (36) has a concave profile.

18. A method as claimed in any of claims 10 to 16, wherein when the elongate clamping member (36) is in the lengthened configuration, the elongate clamping member (36) has a
15 substantially straight profile.