

TITLE OF THE INVENTION

GENERIC KEY-DECISION MECHANISM FOR GAA

REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority of United States Provisional Patent Application Serial No. 60/669,873, filed April 11, 2005. The subject matter of this earlier filed application is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] This invention is related to a generic mechanism for an application server to determine which key of a Generic Authentication Architecture (GAA) would enable easy integration of additional application servers by extending an existing standard for User Security Settings (USS).

2. Description of the Related Art

[0003] Initial authentication (i.e., bootstrapping) of Third Generation Project Partnership (3GPP) Generic Authentication Architecture (GAA) is based on AKA (Authentication and Key Agreement Protocol). Depending on a mobile terminal, such as a mobile phone, and a Universal Mobile Telecommunications System (UMTS) Integrated Circuit Card (UICC) or subscriber identity module inserted in the mobile terminal, the 3GPP Generic Authentication Architecture (GAA) can have the following keys: Ks_{int_NAF} , Ks_{ext_NAF} , and Ks_NAF . Today, the number of services using GAA is quite small and a definition as to which key to use for the particular smart card or subscriber identity module can be implemented directly into a

server of the Network Application Function (NAF) that offers the service to the user. However, such implementation at the server is not very scalable or easy to administer in case of changes, such as new use cases and changes or updates to existing services, or a user getting a new smart card. The changes or updates to the NAF would require manual configuration, which is especially difficult, if the NAF resides not in the home network of the user or subscriber, but in a third party network.

[0004] The `Ks_int_NAF` key is used for securing Hypertext Transport Protocol (HTTPS) between the smart card or subscriber identity module and the application server NAF. The application would reside in the smart card or subscriber identity module and the mobile terminal would only act as a modem. This mechanism may be used as an alternative to present OTA SMS configuration messages to download new updates or other SAT applications.

[0005] The only use case for the `Ks_int_NAF` key defined today is in Multimedia Broadcast/Multicast Service (MBMS). In MBMS, the NAF is configured according to the definitions in TS33.246 3GPP specification, attached hereto as Appendix A, the contents of which are hereby incorporated by reference. In MBMS, a choice as to which key to use is defined by the description of the specific keys in the specification TS33.246. Therefore for this use case, no key choice mechanism is required because the key is implemented directly into the NAF that is offering the MBMS service to the user.

SUMMARY OF THE INVENTION

[0006] In accordance with a first aspect of the present invention, there is provided a method to provide generic mechanism for a network application server, the method comprising: receiving a request from a user equipment to provide authentication information to a network application function; determining a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings; and providing the authentication information to the network application function.

[0006a] In accordance with a second aspect of the present invention, there is provided an apparatus to provide generic mechanism for a network application server, the apparatus comprising: receiving means for receiving a request from a user equipment to provide authentication information to a network application function; determining means for determining a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings; and first providing means for providing the authentication information to the network application function.

[0006b] In accordance with a third aspect of the present invention, there is provided an apparatus for providing generic mechanism for a network application server, the apparatus comprising: a receiving unit receives a request from a user equipment to provide authentication information to a network application function; a determining unit determines a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings; and a providing unit provides the authentication information to the network application function.

[0006c] In accordance with a fourth aspect of the present invention, there is provided

a computer program embodied within a computer readable medium to provide generic mechanism for a network application server, the computer program being configured to perform a process comprising: receiving a request from a user equipment to provide authentication information to a network application function; determining a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings; and providing the authentication information to the network application function.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention that together with the description serve to explain the principles of the invention, wherein:

[0010] FIG. 1A illustrates an apparatus to provide generic mechanism for a network application server, in accordance with an embodiment of the present invention;

[0011] FIG. 1B, illustrates an exemplary network architecture in which a Network Application Function is in a visited network, in accordance with an embodiment of the present invention;

[0012] FIG. 2 illustrates an apparatus to provide generic mechanism for a network application server, in accordance with an embodiment of the present invention;

[0013] FIG. 3 illustrates a method to provide generic mechanism for a network application server, in accordance with an embodiment of the present invention; and

[0014] FIG. 4 illustrates a method to provide generic mechanism for a network application server, in accordance with an alternative embodiment of the present invention.

TABLE OF ABBREVIATIONS

3GPP -- 3rd Generation Partnership Project

3GPP2--3rd Generation Partnership Project 2

ACM--Address Complete Message

AKA -- Authentication and Key Agreement

Auth--Authentication

AUTHR--Authentication Response

AVP -- Attribute-Value-Pair

BS--Base Station

BSC--Base Station Controller

BSF --Bootstrapping Server Function

BTS—Bas e station Transceiver Subsystem

CK – Confidentiality Key

CM--Cellular Message

GAA – Generic Authentication Architecture

GBA –Generic Bootstrapping Architecture

GBA_U – GBA with UICC-based enhancements

GUSS – GBA User Security Settings

HSS -- Home Subscriber Server

HTTP – Hypertext Transport Protocol

HTTPS – Secured Hypertext Transport Protocol

IK – Integrity Key

IMS--IP Multimedia Subsystem

IMSI--International Mobile Subscriber Identity

IP--Internet Protocol

ISIM-- IMS SIM card

Kc--Ciphering Key

Ki--Individual Subscriber Authentication Key

Ks -- Key Material

Ks_int_NAF -- Derived key in GBA_U which remains on UICC

Ks_ext_NAF -- Derived key in GBA_U

Ks_NAF --Derived Key in GBA_ME

MAP--Mobile Application Part

MBMS – Multimedia Broadcast/Multicast Service

ME -- Mobile Equipment

MIN--Mobile Identification Number

MNO – Home Mobile Network Operator

MO--Mobile Originated

NAF – Network Application Function

NE – Network Element

OTA --Over The Air

PDSN--Packet Data Service Node

PLC--Private Long Code

PLCM--PLC Mask

PSTN--Public Switched Telephone Network

RAN--Radio Access Network

RAND--Random Challenge Data

SAT--SIM Application Toolkit

SIM--Subscriber Identity Module

SMS--Short Message Service

UE – User Equipment

UICC -- UMTS Integrated Circuit Card

UMTS -- Universal Mobile Telecommunications System

USIM--Universal SIM card

USS – User Security Settings

Ub--Bootstrapping air interface (from UE to BSF)

Zh--HSS interface from BSF

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0015] 3GPP is a proposed (3GPP TS 33.220, attached hereto as Appendix B, the contents of which are hereby incorporated by reference) authentication infrastructure. This infrastructure may be utilized to enable application functions in a network side and on a user side to communicate in situations where the network side and the user side would not otherwise be able to communicate. This functionality is referred to as “bootstrapping of application security,” or more generally simply as “bootstrapping.”

[0016] The general principles of bootstrapping are that a generic bootstrapping server function (BSF) allows user equipment (UE) to authenticate therewith, and agree on session keys. Such authentication may be based on authentication and key agreement (AKA). By running AKA, the mobile terminal and the network mutually authenticate each other and agree on keys, specifically a confidentiality key (CK) and an integrity key (IK). After this authentication, the UE and a network application function (NAF), which may also be referred to as a service provider, may run some application specific protocol where the authentication of messages is based on the session keys agreed between the UE and the BSF.

[0017] The bootstrapping function is not intended to be dependent upon any particular network application function. The server implementing the bootstrapping function must be trusted by a home operator to handle authentication vectors. Network application functions may be supported in the operator's home network, a visited network, or in a third network.

[0018] FIG. 1A illustrates an exemplary network architecture, in accordance with an embodiment of the present invention. The network architecture includes a user equipment (UE) 100, at least one network application function (NAF) 102, a bootstrapping server function (BSF) 104, and a home subscriber system (HSS) 106. The BSF 104 and HSS 106 form part of a home mobile network operator (MNO) 108. The UE 100 connects into the MNO 108 in accordance with well-known mobile communication techniques.

[0019] The NAF 102 is hosted in a network element, under the control of the MNO 108, for instance, and the BSF may be also hosted in a network element under the control of the MNO 108. Thus, for practical purposes, each of the NAF 102 and the BSF 104 may be considered to be a network element.

[0020] As illustrated in FIG. 1A, the UE 100 communicates with the NAF 102 through a Ua interface 110. The UE 100 communicates with the BSF 104 through an Ub interface 112. The NAF 102 communicates with the BSF 104 through a Zn interface 114. The BSF 104 communicates with the HSS 106 through a Zh interface 116.

[0021] The NAF 102 may be provided in a further separate network. For instance, as illustrated in FIG. 1B, an exemplary network architecture is provided in which NAF 102 is in the visited network. In the case where UE 100 has contacted a NAF 102 that is operated in another network than the home network, this visited NAF 102 shall use a diameter proxy (D-Proxy) 118 of the NAFs network to communicate with subscriber's BSF (i.e. home BSF) 104. The NAF 102 communicates with the BSF 104 through the Zn interface 114 to the D-Proxy 118 and through a Zn' interface 120 to the BSF 104. D-Proxy 118 functionality may be implemented as a separate network element, or be part of any network element (NE) in the visited network that implements Diameter proxy functionality (examples of such NE's are the BSF of the network that the visited NAF 102 belongs to, or an AAA-server).

[0022] For FIGS. 1A and 1B, the principle of bootstrapping is that the UE 100 and the bootstrapping function mutually authenticate each other, for instance, using the

AKA protocol, and agree on a master shared secret. Afterwards the master shared secret is used to derive one or more network application function specific shared secrets that are applied between the UE 100 and the particular network application functions (NAFs) in question. The NAF specific shared secret key material is generated specifically for each network application function independently. After the bootstrapping operation has been completed, the UE 100 and the network application function may run some specific protocol where the securing of messages will be based on those keys generated during the mutual authentication between the UE 100 and the bootstrapping server function. Thus, the keys may be used for authentication and integrity protection, and for confidentiality. The network application function is then able to acquire the NAF specific shared secret derived from the master shared secret established between the user equipment and the bootstrapping server function.

[0023] The communication Ub interface 112 supports the bootstrapping authentication and key agreement protocol, to provide the mutual authentication and key agreement between the UE 100 and the BSF 104. This protocol may be based on the 3GPP AKA protocol, for instance.

[0024] The Zh interface 116 allows the BSF 104 to fetch any required authentication information and subscriber profile information from the HSS 106. The Ua interface 110 supports any application specific protocol which is secured using the NAF specific shared secret derived from the master shared secret agreed between the UE 100 and the BSF 104, based on the protocol supported by the Ub interface 112. The Zn interface 114 is used by the NAF 102 to fetch the NAF specific shared secret that has derived from the master shared secret agreed in the protocol supported on the Ub interface 112 from the BSF 104. The Zn interface 114 may also be used to fetch subscriber profile information from the BSF 104.

[0025] A message transmitted from BSF 104 to the NAF 102 includes bootstrapping information. The bootstrapping information may include a transaction identifier, a NAF specific shared secret, and optional subscriber profile information ("prof_naf" or "any NAF specific USSs"). The NAF specific shared secret, denoted

Ks_NAF, is established between the UE 100 and the BSF 104, and may be modified for specific use for communications between the UE 100 and the specific NAF. Ks_NAF is derived from Ks by using parameters specified in 3GPP TS 33.220 Annex B (Appendix A). Ks is the master shared secret, and Ks_NAF is a NAF specific shared secret. The bootstrapping information transmitted to each NAF is thus unique to that NAF, in accordance with the specific shared secret Ks_NAF for that NAF.

[0026] A set of all user security settings (GUSS) contains the BSF specific information element and the set of all application-specific USSs. The set of all user security settings (USSs), i.e. GUSS, is stored in the HSS. In the case where the subscriber has multiple subscriptions, i.e., multiple ISIM or USIM applications on the UICC, the HSS shall contain one or more GUSSs that can be mapped to any one or more identities, e.g. (IP Multimedia Private Identity) IMPIs and (International Mobile Subscriber Identity) IMSIs.

[0027] A deployment of new use case for a two NAF specific shared secrets in GBA_U in which one is used on UICC (Ks_int_NAF) and other is used in the mobile equipment (Ks_ext_NAF). This use case needs some “decision logic” which key to take, i.e., Ks_int_NAF, or Ks_ext_NAF. Additions of new services to this ‘logic’ should be possible without new configuration of a smart card in a mobile terminal. In case the NAF support more than one key type, any sort of downplay of security level attack needs to be prevented. This downplay attack can be that the NAF is tricked into using a key of lower level of security instead of requiring the use of the Ks_int_NAF.

[0028] According to an embodiment of the present invention, there is provided a generic mechanism for an application server to obtain knowledge as to which key of a Generic Authentication Architecture (GAA) would enable easy integration of additional application servers by extending an existing standard for User Security Settings (USS). AVP Attribute-Value-Pairs (AVPs) are defined in 3GPP TS 29.109 GAA Zn interface Bootstrapping-Info-Request/Answer messages, attached hereto as Appendix C, the contents of which are hereby incorporated by reference, and

additional new Diameter AVP are defined in 3GPP TS 29.229, attached hereto as Appendix D, the contents of which are hereby incorporated by reference.

[0029] A generic mechanism may be implemented by hard coding or locally configuring of a key usage directly into the software in every NAF during NAF set-up (local in NAF), by hard coding of the key usage in BSF (BSF dictates by only delivering the relevant key to NAF), by providing an additional field(s) in the user security setting (USS) stored in Home Subscriber Server (HSS) that are transferred to the BSF, and/or by using the AVP stored in BSF that indicates key usage. If the BSF would only deliver the relevant keys to the NAF, the NAF would not be aware of the provided quality of security and the key type it is using.

[0030] The 3GPP standardized and existing User Security Settings (USS) could be extended and be used to indicate which key to use. This would provide the user's home-operator with full and flexible control, especially in the case that the service is offered by a third party NAF and the billing of the service is done by the home-operator.

[0031] In accordance with an embodiment of the present invention, there may be at least two embodiments possible. In a first embodiment of the present invention, the USS could indicate what type of smart card or secure environment a user has. Also, the first embodiment would provide whether mobile subscriber's Universal SIM (USIM), IMS SIM card (ISIM) is GBA_U enabled or not. In the first embodiment, there may be a flag field, which indicates whether the card or secure environment is GBA_U enabled.

[0032] In a second embodiment of the present invention, the USS may include one or two authorization flag fields that are transported in an USS of an existing specification 3GPP TS 29.109, attached hereto as Appendix D, the contents of which are hereby incorporated by reference. In the first flag field, if this field is present and indicates the usage of UICC based shared secret (Ks_int_NAF) is mandatory. The second flag field may be an optional field, where if this second flag field is present and indicates the ME based shared secret (Ks_ext_NAF or Ks_NAF) usage.

[0033] If the mobile subscriber is provisioned by a home operator with a new subscriber identity module, then the USS can easily be updated to require that from now on the more secure Ks_int_NAF key is used. Both alternatives prevent security downplay attacks, i.e., Ks_ext_NAF key being used instead of the more secure Ks_int_NAF key.

[0034] FIG. 2 illustrates an apparatus 150 to provide generic mechanism for a network application server, in accordance with an embodiment of the present invention. The apparatus 150 includes a receiving unit 152 for receiving a request from a user equipment to provide authentication information to a network application function. The apparatus 150 further includes a determining unit 154 for determining a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings. The apparatus 150 also includes a first providing unit 156 for providing the authentication information to the network application function.

[0035] FIG. 3 illustrates a method to provide generic mechanism for a network application server, in accordance with an embodiment of the present invention. At operation 200, the method receives a request from a user equipment to provide authentication information to a network application function. At operation 210, the method determines a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings. At operation 220, providing the authentication information to the network application function. In accordance with an embodiment of the present invention, the USS could indicate what type of smart card a user has, or what type (i.e., Ks_ext_NAF or Ks_int_NAF), of shared secret must be used. At operation 230, the method determines whether mobile subscriber's Universal SIM (USIM), IMS SIM card (ISIM) or other secure environment is GBA_U enabled or not. In the first embodiment, there may be a flag field, which indicates whether the card or secure environment is GBA_U enabled.

[0036] FIG. 4 illustrates a method to provide generic mechanism for a network application server, in accordance with an alternative embodiment of the present invention. At operation 300, the method receives a request from a user equipment to provide authentication information to a network application function. At operation 310, the method determines a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings. At operation 320, providing the authentication information to the network application function. In accordance with an embodiment of the present invention, the USS could indicate what type of smart card or secure environment a user has, or what type of shared secret must be used. At operation 330, the method determines whether the USS includes one or two flag fields to be transported in the Authorization header of the existing specification 3GPP TS 29.109, attached hereto as Appendix C. In the first flag field, if this field is present it indicates the usage of UICC based shared secret (Ks_int_NAF) is mandatory. The second flag field may be an optional field, where if this second flag field is present and indicates the ME based shared secret (Ks_ext_NAF or Ks_NAF) usage.

[0037] If a new application server is set-up in the operator network, it does not need to know which key to use for which user or if the user will be provisioned in the near future with a new SIM card. The NAF would obtain the needed key choice information from the BSF.

[0038] In accordance with an embodiment of the present invention, a new AVP could be used to indicate the type of derived key being used. For instance, the new AVP may indicate if the derived key is Ks_int_NAF or some other key type. The new AVP would indicate either if the card or secure environment is GBA_U enabled or, as an alternative, which key to use. Depending on the flag, the NAF may use the UICC based shared secret key (Ks_int_NAF) when indicated. That is, the AVP indicates that a card or secure environment is GBA_U enabled or the AVP indicates explicitly the usage of Ks_int_NAF. The NAF would then require that this key be used and not some other key with lower level of security.

[0039] For a web server in the secure environment, for instance a smart card, a client would reside in a Universal Mobile Telecommunications System (UMTS) Integrated Circuit Card (UICC) and the application would also reside in the secure environment. This would typically be a Java application, an XML application, a C++ application, a Perl application, or a Visual Basic application or other similar types of applications. Then, the UICC may also act as the application server offering a web service towards other entities which where one of them might reside in another trustworthy domain, e.g., a second secure area in the phone and the Ks_int_NAF may be used to secure communications between web service entities. The UICC based NAF would take the role of a WSP (Web Service Provider) as outlined by the Liberty Alliance Web Service Framework Specification (ID-WSF) <http://www.projectliberty.org/resources/specifications.php>. The UICC may act as a Liberty Alliance conformant web service provider providing a requesting entity (i.e., a web service consumer) with sensitive information, which can be authenticated/secured via Ks_int_NAF. The other GAA based keys maybe used further in the web service framework for identification and message security. Furthermore, TS24.109 3GPP specifies bootstrapping interface (Ub) and network application function interface (Ua), attached hereto as Appendix E, the contents of which are hereby incorporated by reference TS29.109 3GPP specifies Zh and Zn interfaces based on a diameter protocol, attached hereto as Appendix F, the contents of which are hereby incorporated by reference.

[0040] The present invention may allow the home-operator of the subscriber to have full control over the used security level. The update of the user security settings in case the user has a new UICC could happen centrally in a Home Service Server (HSS) and it would not be required to update all NAFs individually. Decision logic may reside in the operator controlled HSS or BSF. Further, security downplay attacks would also no longer be possible for new applications.

[0041] The foregoing description has been directed to specific embodiments of this invention. It will be apparent; however, that other variations and modifications may be made to the described embodiments, with the attainment of some or all of their

advantages. Therefore, it is the object of the appended claims to cover all such variations and modifications as come within the true spirit and scope of the invention.

What Is Claimed:

1. A method to provide generic mechanism for a network application server, the method comprising:

receiving a request from a user equipment to provide authentication information to a network application function;

determining a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings; and

providing the authentication information to the network application function.

2. The method as recited in claim 1, further comprising:

providing data relating to a type of smart card or secure environment in the user equipment in the user security settings; and

providing a flag field indicative of whether a generic bootstrapping architecture with integrated circuit based enhancements (GBA_U) enables a universal subscriber identity module, Subscriber identity module, IMS SIM card or another secure environment.

3. The method as recited in claim 1, further comprising:

providing first and second flag fields in the user security settings that are transported in an authorization header of a specification, wherein in the first flag field, the a first derived key (Ks_int_NAF) in integrated circuit based enhancements (GBA_U) is used, and in the second flag field, a second derived key (Ks_ext_NAF) or a third derived key (Ks_NAF) are used.

4. The method as recited in claim 1, wherein the determining step comprises determining at least one of:

- locally configuring a key usage directly into the network application function during a network application function set-up,
- locally configuring the key usage in a bootstrapping server function,
- providing an additional field in the user security setting stored in a home subscriber server that is transferred to the bootstrapping server function, and
- using an attribute-value-pair stored in the bootstrapping server function that indicates key usage.

5. The method as recited in claim 4, further comprising:

- using an attribute-value-pair to indicate a type of derivative key being used or a type of smart card or secure environment enabled, wherein the type of derivative key comprises Ks_int_NAF, Ks_ext_NAF, or Ks_NAF, and the smart card or secure environment comprises a GBA_U.

6. The method as recited in claim 5, wherein when the attribute-value-pair indicates the attribute-value-pair indicates a usage of Ks_int_NAF, further comprising:

- requiring a use of Ks_int_NAF by the network application function instead of a key with a lower level of security.

7. The method as recited in claim 2, wherein, when a web server is in the secure environment, the method further comprises:

allocating a network application in a universal mobile telecommunications system (UMTS) integrated circuit card (UICC), wherein the UICC is the network application function and a derived key (Ks_int_NAF) is used to secure communications between web service entities.

8. The method as recited in claim 7, wherein the allocating step of allocating the network application comprises a Java application, an XML application, a C++ application, a Perl application, or a Visual Basic application.

9. The method as recited in claim 1, further comprising:
locally configuring a key usage in a bootstrapping server function (BSF) by providing an additional field in the user security settings stored in a home subscriber server (HSS).

10. An apparatus to provide generic mechanism for a network application server, the apparatus comprising:

receiving means for receiving a request from a user equipment to provide authentication information to a network application function;

determining means for determining a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings; and

first providing means for providing the authentication information to the network application function.

11. The apparatus as recited in claim 10, further comprising:

second providing means for providing a type of secure environment in the user equipment in the user security settings; and

third providing means for providing a flag field indicative of whether a generic bootstrapping architecture with integrated circuit based enhancements (GBA_U) enables a universal subscriber identity module, Subscriber identity module, secure environment or an IMS SIM card.

12. The apparatus as recited in claim 10, further comprising:

second providing means for providing first and second flag fields in the user security settings that are transported in an authorization header of a specification, wherein in the first flag field, the a first derived key (Ks_int_NAF) in integrated circuit based enhancements (GBA_U) is used, and in the second flag field, a second derived key (Ks_ext_NAF) or a third derived key (Ks_NAF) are used.

13. The apparatus as recited in claim 10, wherein the generic mechanism comprises at least one of:

first hard coding means for locally configuring a key usage directly into the network application function during a network application function set-up,

second hard coding means for locally configuring the key usage in a bootstrapping server function,

second providing means for providing an additional field in the user security setting stored in a home subscriber server that is transferred to the bootstrapping server function, and

first using means for using an attribute-value-pair stored in the bootstrapping server function that indicates key usage.

14. The apparatus as recited in claim 13, further comprising:

second using means for using an attribute-value-pair to indicate a type of derivative key being used or a type of smart card or secure environment enabled, wherein the type of derivative key comprises Ks_int_NAF, Ks_ext_NAF, or Ks_NAF, and the smart card or secure environment comprises a GBA_U.

15. The apparatus as recited in claim 14, wherein when the attribute-value-pair indicates the attribute-value-pair indicates a usage of Ks_int_NAF, the network application function require that Ks_int_NAF be used and not a key with a lower level of security.

16. The apparatus as recited in claim 11, wherein, when a web server is in the smart card or secure environment, further comprising:

allocating means for allocating a network application in a universal mobile telecommunications system (UMTS) integrated circuit card (UICC), wherein the

UICC is the network application function and a derived key (Ks_int_NAF) is used to secure communications between web service entities.

17. The apparatus as recited in claim 10, further comprising:

third hard coding means for locally configuring a key usage in a bootstrapping server function (BSF) by providing an additional field in the user security settings stored in a home subscriber server (HSS).

18. An apparatus for providing generic mechanism for a network application server, the apparatus comprising:

a receiving unit receives a request from a user equipment to provide authentication information to a network application function;

a determining unit determines a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings; and

a providing unit provides the authentication information to the network application function.

19. A computer program embodied within a computer readable medium to provide generic mechanism for a network application server, the computer program being configured to perform a process comprising:

receiving a request from a user equipment to provide authentication information to a network application function;

determining a key of a generic authentication architecture to integrate additional network application servers by extending an existing standard for user security settings; and

providing the authentication information to the network application function.

20. The computer program as recited in claim 19, further comprising:

providing data relating to a type of smart card or secure environment in the user equipment in the user security settings; and

providing a flag field indicative of whether a generic bootstrapping architecture with integrated circuit based enhancements (GBA_U) enables a universal subscriber identity module, Subscriber identity module, secure environment or an IMS SIM card.

21. The computer program as recited in claim 19, further comprising:

providing first and second flag fields in the user security settings that are transported in an authorization header of a specification, wherein in the first flag field, the a first derived key (Ks_int_NAF) in integrated circuit based enhancements (GBA_U) is used, and in the second flag field, a second derived key (Ks_ext_NAF) or a third derived key (Ks_NAF) are used.

22. The computer program as recited in claim 19, wherein the determining step comprises determining at least one of:

locally configuring a key usage directly into the network application function during a network application function set-up,

locally configuring the key usage in a bootstrapping server function,
providing an additional field in the user security setting stored in a home
subscriber server that is transferred to the bootstrapping server function, and
using an attribute-value-pair stored in the bootstrapping server function that
indicates key usage.

23. The computer program as recited in claim 22, further comprising:
using an attribute-value-pair to indicate a type of derivative key being used or a
type of smart card or secure environment enabled, wherein the type of derivative key
comprises Ks_int_NAF, Ks_ext_NAF, or Ks_NAF, and the smart card or secure
environment comprises a GBA_U.

24. The computer program as recited in claim 23, wherein when the
attribute-value-pair indicates the attribute-value-pair indicates a usage of Ks_int_NAF,
further comprising:
requiring a use of Ks_int_NAF by the network application function instead of a
key with a lower level of security.

25. The computer program as recited in claim 20, wherein, when a web
server is in the smart card or secure environment, the computer program further
comprises:
allocating a network application in a universal mobile telecommunications
system (UMTS) integrated circuit card (UICC), wherein the UICC is the network

application function and a derived key (Ks_int_NAF) is used to secure communications between web service entities.

26. The computer program as recited in claim 25, wherein the allocating step of allocating the network application comprises a Java application, an XML application, a C++ application, a Perl application, or a Visual Basic application.

27. The computer program as recited in claim 19, further comprising:
locally configuring a key usage in a bootstrapping server function (BSF) by providing an additional field in the user security settings stored in a home subscriber server (HSS).