

(51) International Patent Classification:
H04W 36/26 (2009.01) *H04W 84/18* (2009.01)(21) International Application Number:
PCT/KR2011/001310(22) International Filing Date:
25 February 2011 (25.02.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/308,081 25 February 2010 (25.02.2010) US
10-2010-0058231 18 June 2010 (18.06.2010) KR(71) Applicant (for all designated States except US): **SAM-SUNG ELECTRONICS CO., LTD.** [KR/KR]; 416, Maetan-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 442-742 (KR).(72) Inventors: **KWON, Hyuk-Choon**; 111-1101 Haengdang Daerim Apt., 347 Haengdang-dong, Seongdong-gu, Seoul 133-070 (KR). **JUN, Hae-Young**; 505-204 Sinnae 5-dan-ji Doosan Apt., Muk 1-dong, Jungnang-gu, Seoul 131-765 (KR). **KIM, Ho-Dong**; 702-201 Jugong Apt., Byeoryang-dong, Gwacheon-si, Gyeonggi-do 427-733(KR). **PARK, Dong-Seek**; 107-1802 SK Apt., Seocheon-dong, Giheung-gu, Yongin-si, Gyeonggi-do 446-959 (KR). **JUNG, Soo-Yeon**; (103) Greenvillage Apt., 212-2 Seongnae-dong, Gangdong-gu, Seoul 134-030 (KR).(74) Agent: **Y.P.LEE, MOCK & PARTNERS**; Koryo Building, 1575-1 Seocho-dong, Seocho-gu, Seoul 137-875 (KR).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR PERFORMING HAND-OVER

[Fig. 1]



(57) Abstract: A method of performing hand-over in a personal basic service set (PBSS) including a plurality of stations and one coordinator is provided. An association request frame comprising PCP capability information, and requesting to associate to the PBSS, is received from each of the stations. The PCP capability information comprises information regarding at least one of whether each of the stations supports a power source capability of continuous power supply, whether each of the stations supports a channel time allocation function, and whether each of the stations supports a network clustering function. An association response frame, indicating whether the association request received from each of the stations is approved, is transmitted to each of the stations, and a priority to be a coordinator of the stations is determined based on the PCP capability information. Hand-over is performed with one of the stations according to the determined priority.



EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, **Published:**

LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,

GW, ML, MR, NE, SN, TD, TG).

— *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*