



(51) International Patent Classification:

C25B 1/02 (2006.01) *C25B 15/02* (2021.01)

B01D 53/32 (2006.01)

(21) International Application Number:

PCT/IB2022/061585

(22) International Filing Date:

30 November 2022 (30.11.2022)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2117327.3

01 December 2021 (01.12.2021) GB

(71) Applicant: **EDWARDS VACUUM LLC** [US/US]; 6416
Inducon Drive West, Sanborn, New York NY 14132 (US).

(72) **Inventor:** DUNBAR, Zachary William; Edwards Vacuum LLC, 6416 Inducon Drive West, Sanborn, New York NY 14132 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CV, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IQ, IR, IS, IT, JM, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, CV,

(54) Title: HYDROGEN RECOVERY SYSTEM AND METHOD




FIG. 1

(57) Abstract: HYDROGEN RECOVERY SYSTEM AND METHOD Aspects of the present invention relate to hydrogen recovery system (1) for extracting hydrogen from process gases. The hydrogen recovery system (1) may include an electrochemical pump (11) for extracting at least some of the hydrogen occurring in the process gases. The electrochemical pump (11) has an anodic compartment (13) having at least one anode (14), a cathodic compartment (15) having at least one cathode (16), and a membrane (17) disposed between the anodic compartment (13) and the cathodic compartment (15). A controller (59) is provided for controlling the electric current supplied to the electrochemical pump (11). The anodic compartment (13) has an anodic compartment inlet (23) for introducing the process gases into the anodic compartment (13); and an anodic compartment outlet (25) for discharging a waste gas from the anodic compartment (13). The cathodic compartment (15) has a cathodic compartment outlet (27) for discharging hydrogen extracted from the process gases.

[Continued on next page]

GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, ME, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*
- *in black and white; the international application as filed contained color or greyscale and is available for download from PATENTSCOPE*

(88) Date of publication of the international search report:

03 August 2023 (03.08.2023)
