ROTATIONAL MOTION-INDUCING VARIABLE FLOW RESISTANCE SYSTEMS HAVING A SIDEWALL FLUID OUTLET AND METHODS FOR USE THEREOF IN A SUBTERRANEAN FORMATION

BACKGROUND

[0001] The present invention generally relates to systems and methods for regulating fluid flow, particularly within a subterranean formation, and, more specifically, to rotational motion-inducing variable flow resistance systems having a sidewall fluid outlet that allows the variable flow resistance systems to be connected in series fluid communication with one another.

[0002] It can often be beneficial to regulate the flow of formation fluids within a wellbore penetrating a subterranean formation. A variety of reasons or purposes can necessitate such regulation including, for example, prevention of water and/or gas coning, minimizing water and/or gas production, minimizing sand production, maximizing oil production, balancing production from various subterranean zones, equalizing pressure among various subterranean zones, and/or the like.

[0003] Likewise, it can also be beneficial to regulate the flow of injection fluids such as, for example, water, steam or gas, within a wellbore penetrating a subterranean formation. Regulation of the flow of injection fluids can be particularly useful, for example, to control the distribution of the injection fluid within various subterranean zones and/or to prevent the introduction of injection fluid into currently producing zones.

[0004] A number of different types of flow resistance systems have been developed in order to meet the foregoing needs. Many of these flow resistance systems are variable flow resistance systems that can restrict the passage of some fluids more than others based upon one or more physical property differences between the fluids. Illustrative physical properties of a fluid that can determine its rate of passage through a variable flow resistance system can include, for example, viscosity, velocity and density. Depending on the type, composition and physical properties of a fluid or fluid mixture whose passage is to be restricted, variable flow resistance systems can be configured such that higher ratios of a desired fluid to an undesired fluid can flow through a flow pathway containing the variable flow resistance system.

[0005] Rotational motion can be particu
restricting fluid flow within a variable flow resistance system. In variable flow resistance systems capable of inducing rotational motion, a fluid composition most often enters a chamber within the variable flow resistance system in such a way that an undesired component of the fluid composition undergoes greater rotational motion than does a desired component of the fluid composition. As a result, the undesired component traverses a longer flow pathway than does the desired component, and the undesired component's residence time within the variable flow resistance system can be increased. Most often, the variable flow resistance system is configured such that fluid exiting the variable flow resistance system is discharged through a hole in the bottom of the chamber. Although such an arrangement of the exit hole can be particularly effective for inducing vortex-like rotational motion within a fluid, it significantly complicates the coupling of multiple chambers to one another in linear series.

[0006] Multiple chambers having a bottom exit hole can be series connected to form an operable variable flow resistance system, but the resulting arrangement of the chambers can be inefficient in terms of space utilization. For example, FIGURES 1A – 1C show side view schematics of several possible arrangements of multiple chambers having a bottom exit hole that are in series connection with one another. As shown in FIGURES 1A and 1B, bottom exit hole **9** of chamber **5** within variable flow resistance systems **1** and **3** can particularly lend itself to vertical (FIGURE 1A) or stepped-vertical (FIGURES 1B) arrangements of the chambers. In confined locales, such as, for example, within a wellbore, such arrangements can prove problematic in terms of available space utilization. As shown in FIGURE 1C, a substantially horizontal arrangement of chambers having a bottom exit hole within variable flow resistance system **4** is possible, at least in principle. However, the substantially horizontal arrangement of chambers shown in FIGURE 1C can also prove problematic by requiring a vertical movement of fluid during transit between adjacent chambers.

SUMMARY OF THE INVENTION

[0007] The present invention generally relates to systems and methods for regulating fluid flow, particularly within a subterranean formation, and, more specifically, to rotational motion-inducing variable flow resistance systems having a sidewall fluid outlet that allows the variable flow resistance systems to be connected in series fluid communication with one another.

[0008] In some embodiments, the present flow resistance system comprising: a chamber configured to induce rotational motion of a fluid flowing therethrough; a fluid inlet coupled to the chamber; and a fluid outlet coupled to the chamber that allows the fluid to exit through at least a sidewall of the chamber.

[0009] In other embodiments, the present invention provides a variable flow resistance system comprising: a plurality of chambers that are connected in series fluid communication with one another, each chamber having a fluid inlet and a fluid outlet coupled thereto; wherein at least some of the chambers are configured to induce rotational motion of a fluid flowing therethrough; and wherein the fluid outlets of at least some of the chambers are configured to allow the fluid to exit through at least a sidewall of the chamber.

[0010] In still other embodiments, the present invention provides a method comprising: installing a wellbore pipe in an uncompleted wellbore; wherein the wellbore pipe comprises at least one variable flow resistance system in fluid communication with the interior of the wellbore pipe, each variable flow resistance system comprising: a plurality of chambers that are connected in series fluid communication with one another, each chamber having a fluid inlet and a fluid outlet coupled thereto; wherein at least some of the chambers are configured to induce rotational motion of a fluid flowing therethrough; and wherein the fluid outlets of at least some of the chambers are configured to allow the fluid to exit through at least a sidewall of the chamber.

[0011] The features and advantages of the present invention will be readily apparent to one having ordinary skill in the art upon a reading of the description of the preferred embodiments that follows.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The following figures are included to illustrate certain aspects of the present invention, and should not be viewed as exclusive or preferred embodiments. The subject matter disclosed is capable of considerable modification, alteration, and equivalents in form and function, as will occur to one having ordinary skill in the art and having the benefit of this disclosure.

[0013] FIGURES 1A – 1C show side view schematics of several possible arrangements of multiple chambers having a bottom exit hole that are in series connection with one another.

[0014] FIGURE 2 shows a partial cross-se
in which the variable flow resistance systems of the present disclosure can be used.

[0015] FIGURE 3A shows a side view schematic of a variable flow resistance system having a single chamber with a channel extending from the bottom interior surface of the chamber though a sidewall of the chamber. FIGURE 3B shows a cutaway top view schematic of a variable flow resistance system having a single chamber with a channel extending from the bottom interior surface of the chamber though a sidewall of the chamber. FIGURES 3C and 3D show cutaway top view schematics of a variable flow resistance system having multiple chambers coupled to one another in series. FIGURE 3E shows a side view schematic of a variable flow resistance system having a single chamber with a cone-shaped fluid exit extending from the bottom interior surface of the chamber though a sidewall of the chamber.

[0016] FIGURES 4A and 4B show side view schematics of a variable flow resistance system having a single chamber that has either a single hole (FIGURE 4A) or multiple holes (FIGURE 4B) within its sidewall.

[0017] FIGURES 5A – 5C show cutaway top view schematics of illustrative variable flow resistance systems having multiple chambers coupled in series via a sidewall fluid outlet.

[0018] FIGURES 6A and 6B show side view schematics of a variable flow resistance system having a chamber with multiple fluid outlets.

[0019] FIGURE 6C shows a cutaway top view schematic of a variable flow resistance system in which the chamber of FIGURE 6A has been used to form a branched arrangement of multiple chambers coupled in series.

[0020] FIGURES 7A and 7B show side view schematics of an illustrative variable flow resistance system in which rotational motion of the fluid occurs at least partially in parallel to the direction of the fluid flow.

[0021] FIGURE 8A shows a cutaway top view schematic of a variable flow resistance system having a chamber with both a main flow pathway and a branch flow pathway within the fluid inlet. FIGURES 8B and 8C show cutaway top view schematics of a variable flow resistance system in which multiple chambers having a fluid inlet with a main flow pathway and a branch flow pathway are series coupled together.

[0022] FIGURE 9 shows a side view sc
resistance system having multiple fluid inlets and fluid outlets interconnecting chambers of the system.

DETAILED DESCRIPTION

[0023] The present invention generally relates to systems and methods for regulating fluid flow, particularly within a subterranean formation, and, more specifically, to rotational motion-inducing variable flow resistance systems having a sidewall fluid outlet that allows the variable flow resistance systems to be connected in series fluid communication with one another.

[0024] As discussed above, variable flow resistance systems that induce rotational motion within a fluid typically can incorporate a fluid exit hole at the bottom of a chamber, where the location of the exit hole both facilitates vortex-like rotational motion and gravity-assisted draining of the fluid. However, this location of the exit hole can make series connections between chambers problematic if a greater degree of fluid flow regulation is needed than can be provided by a single chamber.

[0025] The embodiments presented herein can address the foregoing shortcomings in the art. In particular, the present disclosure describes variable flow resistance systems that have chambers without a fluid exit hole extending through the bottom of the chamber. According to the present embodiments, the chambers instead have a fluid outlet located in a sidewall of the chamber. The primary advantage of such chambers is that they can be efficiently coupled together in series in a variable flow resistance system (*e.g.*, in a substantially horizontal arrangement) without having to conduct excessive vertical movement of the fluid during transport between adjacent chambers. The substantially horizontal arrangement offered by the present chambers can also be particularly efficient in terms of space utilization, such that they can be readily used in confined regions, such as within a wellbore penetrating a subterranean formation. Furthermore, the opportunity to connect multiple chambers in series in a variable flow resistance system can achieve greater fluid flow regulation than is attainable using a single chamber alone.

[0026] The variable flow resistance systems described herein also offer advantages in terms of their manufacturing ease. In general, it is believed that the chambers described herein induce a lower rotational velocity (*e.g.*, less rotational motion) in a fluid than do comparable chambers having a fluid outlet

exiting through the bottom of the chamber. Altho
rotational motion in a fluid would appear to present an operational disadvantage, the opportunity to couple multiple chambers in series can overcome the lower fluid flow restriction provided by a single chamber of the present embodiments. From a manufacturing standpoint, however, the lower rotational velocities of the present chambers can result in lesser mechanical stress on the chamber, thereby allowing variable flow resistance systems to be constructed using materials having lower mechanical strength. For example, in some embodiments, the chambers described herein can be constructed through casting or molding of polymers, polymer composites, ceramics or metals. Materials having lower mechanical strength can oftentimes be considerably reduced in cost relative to higher performance materials needed to fabricate variable flow resistance systems having higher rotational velocities. The opportunity to use lower cost materials in variable flow resistance systems can ultimately lead to lower production costs.

[0027] In some embodiments, variable flow resistance systems described herein can comprise a chamber configured to induce rotational motion of a fluid flowing therethrough, a fluid inlet coupled to the chamber; and a fluid outlet coupled to the chamber that allows the fluid to exit through at least a sidewall of the chamber.

[0028] In some embodiments, multiple chambers can be connected in series with one another in a variable flow resistance system. In some embodiments, variable flow resistance systems described herein can comprise a plurality of chambers that are connected in series fluid communication with one another, where each chamber has a fluid inlet and a fluid outlet coupled thereto, and at least some of the chambers are configured to induce rotational motion of a fluid flowing therethrough, and the fluid outlets of at least some of the chambers are configured to allow the fluid to exit through at least a sidewall of the chamber.

[0029] When multiple chambers are connected in series in a variable flow resistance system, the chambers can all be the same in some embodiments, or at least some of the chambers can be different in other embodiments. In some embodiments, all of the chambers can have a fluid outlet that allows a fluid to exit through a sidewall of the chamber. In other embodiments, chambers having a fluid outlet that allows a fluid to exit through a

sidewall of the chamber can be used in combinatio
fluid outlet exiting through the bottom of the chamber. The choice of a particular combination of chambers may be dictated by operational needs that will be evident to one having ordinary skill in the art.

[0030] As used herein, the term "chamber" refers to an enclosed space having at least one inlet and at least one outlet. As used herein, use of the term "chamber" makes no implication regarding the shape and/or dimensions of the chamber unless otherwise specified.

[0031] As used herein, the term "channel" refers to an elongated passage through which fluids can flow that is open to at least some degree along its length. In various embodiments, the closed portion of the channel can be hemispherical or semi-hemispherical (*i.e.*, tube-like, having only one distinct surface) or trough-shaped (*i.e.*, having two or more distinct surfaces). Furthermore, the channel can have shape or dimensional parameters that are variable along its length.

[0032] As used herein, the term "degree of curvature" refers to at least some deviation from planarity, particularly in regard to the shape of a surface. Unless otherwise specified herein, use of the term "degree of curvature" should not be construed to represent any particular amount or shape of curvature.

[0033] As used herein, the term "sidewall" refers to any surface of chamber extending between the chamber's top exterior surface and the chamber's bottom exterior surface. As used herein, the term "exterior" refers to the outside surface of a chamber that is not in contact with a fluid passing therethrough.

[0034] As used herein, the term "rotational motion" refers to motion that occurs around an axis.

[0035] In various embodiments, the variable flow resistance systems of the present disclosure can be used in a wellbore penetrating a subterranean formation. FIGURE 2 shows a partial cross-sectional schematic of wellbore in which the variable flow resistance systems of the present disclosure can be used. As shown in FIGURE 2, well **10** contains wellbore **12** having generally vertical uncased section **14**, extending from cased section **16**, and generally horizontal uncased section **18** extending through subterranean formation **20**. Wellbore pipe **22** extends through wellbore **12**, where wellbore pipe **22** can be any fluid conduit that allows fluids to be transported to and from wellbore **12**. In some

embodiments, wellbore pipe **22** can be a tubular tubing string.

[0036] Continuing with FIGURE 2, multiple well screens **24**, each in fluid flow communication with variable flow resistance system **25**, can be connected to wellbore pipe **22**. Packers **26** can seal annulus **28** defined by wellbore pipe **22** and the interior surface of horizontal uncased section **18**. Packers **26** can provide zonal isolation of various subterranean zones penetrated by wellbore pipe **22**, thereby allowing fluids **30** to be produced from or introduced into some or all of the zones of subterranean formation **20**. Well screens **24** can filter fluids **30** as they move toward the interior of wellbore pipe **22**. Each variable flow resistance system **25** can regulate access of fluids **30** to the interior of wellbore pipe **22** and/or restrict the flow of certain types of fluids **30** based upon certain characteristics or physical properties thereof.

[0037] It is to be noted that the variable flow resistance systems described herein are not limited to the implementation displayed in FIGURE 2, which has been presented merely for purposes of illustration and not limitation. For example, the type of wellbore in which the present variable flow resistance systems can be used is not particularly limited, and it is not necessary that wellbore **12** contain either vertical uncased section **14** or horizontal uncased section **18**. Furthermore, any section of wellbore **12** can be cased or uncased, and wellbore pipe **22** can be placed in any cased or uncased wellbore section.

[0038] Furthermore, it is not necessarily the case that fluids **30** are solely produced from subterranean formation **20**, since fluids can be injected into subterranean formation **20** and produced therefrom in some embodiments. In addition, the various elements coupled to wellbore pipe **22** that are presented in FIGURE 2 are all optional, and each may not necessarily be used in each subterranean zone, if at all. In some embodiments, however, the various elements coupled to wellbore pipe **22** can be duplicated in each subterranean zone. Still further, zonal isolation using packers **26** need not necessarily be performed, or other types of zonal isolation techniques familiar to one having ordinary skill in the art can be used.

[0039] In various non-limiting embodiments, the present variable flow resistance systems can be used to prevent water coning or gas coning from subterranean formation **20**. In some embodiments, the present variable flow resistance systems can be used to equalize pressure and balance production

between heel **13** and toe **11** of wellbore **12**. In oth
variable flow resistance systems can be used to minimize the production of undesired fluids and to maximize the production of desired fluids. It is also to be recognized that the wellbore flow control devices can be used for injection operations as well to accomplish similar advantages to those noted above.

[0040] Whether a fluid is a desired fluid or an undesired fluid will usually be determined by the nature of the subterranean operation being conducted. For example, if the goal of a subterranean operation is to produce oil but not natural gas or water, the oil can be considered a desired fluid and the natural gas and water can be considered undesired fluids. In other cases, natural gas can be a desired fluid, and water can be an undesired fluid. It should be noted that at downhole temperatures and pressures, natural gas can be at least partially liquefied, and in the disclosure presented herein, the term "natural gas" or more simply "gas" will refer to a hydrocarbon gas (*e.g.*, methane) that is ordinarily in the gas phase at atmospheric pressure and room temperature.

[0041] In general, the variable flow resistance systems described herein can be used in any subterranean operation in which there is a need to regulate the flow of fluids to or from the interior of a wellbore pipe. Reasons why one of ordinary skill in the art might wish to regulate the flow of fluids can include, for example, to prevent or minimize water and/or gas coning, to prevent or minimize water and/or gas production, to prevent or minimize sand production, to maximize oil production, to better balance production from various subterranean zones, to better equalize pressure among various subterranean zones, and/or the like.

[0042] In particular, the variable flow resistance systems described herein can be used during production or injection operations within a subterranean formation in some embodiments. In some embodiments, methods for using the variable flow resistance systems of the present disclosure can comprise: installing a wellbore pipe in an uncompleted wellbore, wherein the wellbore pipe comprises at least one variable flow resistance system that is in fluid communication with the interior of the wellbore pipe. In such embodiments, each variable flow resistance system can comprise a plurality of chambers that are connected in series fluid communication with one another, where each chamber has a fluid inlet and a fluid outlet coupled thereto, and at

least some of the chambers are configured to induc
flowing therethrough and the fluid outlets of at least some of the chambers are configured to allow the fluid to exit through at least a sidewall of the chamber.

[0043] In some embodiments, the methods can further comprise allowing a formation fluid to flow through at least some of the variable flow resistance systems and into the interior of the wellbore pipe. In some embodiments, the methods can further comprise producing the formation fluid from the wellbore pipe.

[0044] In some embodiments, the present variable flow resistance systems can be used in injection operations. For example, the variable flow resistance systems can be used to control the introduction of various types of treatment fluids into a subterranean formation. In injection operations, fluids that can be injected can include, for example, steam, liquefied gases and water. The variable flow resistance systems can be used to compensate for heel-to-toe pressure variations or permeability variations within the subterranean formation.

[0045] In some embodiments, the wellbore can comprise a horizontal wellbore. In other embodiments, the wellbore can comprise a vertical wellbore. In some embodiments, the wellbore can comprise a plurality of intervals, where there is at least one variable flow resistance system located within each interval.

[0046] The present variable flow resistance systems can comprise at least one chamber that has a fluid outlet coupled to a sidewall of the chamber. Otherwise, the design of the variable flow resistance systems and their chambers is not particularly limited. Some illustrative variable flow resistance systems meeting the above requirement are described in more detail hereinbelow with reference to the drawings. It is to be recognized that the drawings presenting variable flow resistance systems with a sidewall fluid outlet coupled to a chamber therein are for purposes of illustration and not limitation. Other implementations, orientations, arrangements and combinations of the features described hereinbelow and presented in the drawings are possible, and given the benefit of the present disclosure, it will be within the capabilities of one having ordinary skill in the art to combine these features.

[0047] Commonly owned United States Patent Application 12/869,836, filed August 27, 2010, which is incorporated herein by reference in its entirety, describes several examples of chambers that are configured to induce rotational motion of a fluid flowing therethrough. The chambers described therein can be

adapted to be compatible with those of the prese
through introduction of a sidewall fluid outlet. Specifically, in some embodiments, the chambers of the present disclosure can contain various flow-inducing structures that induce rotational motion to a fluid flowing therethrough. In some embodiments, the flow-inducing structures can be formed as vanes or recesses on or within the sidewall of the chamber. Any number of flow-inducing structures can be used within the chambers to impart a desired degree of flow resistance to a fluid passing therethrough.

[0048] Furthermore, in some embodiments, the design of the chambers can be such that only fluids having certain physical properties can undergo a desired degree of rotational motion within the chamber. That is, in some embodiments, the design of the chambers can be configured to take advantage of a fluid's physical properties such that at least one physical property dictates the fluid's rate of passage through the chamber. Specifically, fluids having certain physical properties (*e.g.*, viscosity, velocity and/or density) can be induced to undergo greater rotational motion when passing through the chamber, thereby increasing their transit time relative to fluids lacking that physical property. For example, in some embodiments, the chamber can be configured to induce increasing rotational motion of a fluid with decreasing fluid viscosity. Consequently, in such embodiments, a fluid having a greater viscosity (*e.g.*, oil) can undergo less rotational motion when passing through the chamber than does a fluid having a lower viscosity (*e.g.*, gas or water), and the high viscosity fluid can have its transit time through a flow pathway affected to a much lesser degree than does the low viscosity fluid.

[0049] Various types of sidewall fluid outlets are compatible with the variable flow resistance systems described herein. In some embodiments, the fluid outlet can comprise a channel within the chamber that extends from the top or bottom interior surface of the chamber and through at least a sidewall of the chamber. That is, the channel can be defined within the top or bottom interior surface of the chamber, but the channel extends through the sidewall of the chamber, not the top or bottom of the chamber. In some embodiments, the fluid outlet can comprise a cone-shaped fluid outlet that extends through at least a sidewall of the chamber. In some embodiments, the fluid outlet can comprise at least one hole within the sidewall of the chamber. In still other embodiments, the fluid outlet can comprise at least one groove or slit within the sidewall of the

chamber. Other types of fluid outlets can in
pathways, helical pathways, pathways with directional changes, and segmented pathways with diameter variations. Combinations of different fluid outlet types are also possible.

[0050] FIGURE 3A shows a side view schematic of a variable flow resistance system having a single chamber with a channel extending from the bottom interior surface of the chamber though a sidewall of the chamber. FIGURE 3B shows a cutaway top view schematic of a variable flow resistance system having a single chamber with a channel extending from the bottom interior surface of the chamber though a sidewall of the chamber. As shown in FIGURES 3A and 3B, chamber **50** having sidewall **51**, top interior surface **52** and bottom interior surface **53** has fluid inlet **54** and fluid outlet **55** coupled thereto. Chamber **50** has channel **57** defined in bottom interior surface **53** that establishes a fluid flow pathway extending through sidewall **51** to fluid outlet **55**. According to the present embodiments, channel **57** and fluid outlet **55** do not extend through the bottom exterior surface of chamber **50**.

[0051] FIGURES 3C and 3D show cutaway top view schematics of a variable flow resistance system having multiple chambers coupled to one another in series. In FIGURE 3C, fluid inlet **54** and fluid outlet **55** are configured such that multiple chambers **50** are series connected in a substantially linear fashion. In FIGURE 3D, fluid inlet **54** and fluid outlet **55** are configured such that the multiple chambers **50** are connected in a non-linear fashion. According to the present embodiments, fluid outlet **55** of one chamber can couple to fluid inlet **54** of a subsequent chamber to establish the series connection therebetween. Any combination of linear and non-linear arrangements of chambers **50** can be used within the spirit and scope of the present disclosure. Furthermore, fluid outlet **55** is not limited to being coupled to channel **57**, as drawn in FIGURES 3A – 3D. Other routes for a fluid's exit from a chamber via its sidewall are described in more detail hereinbelow and can be used in variable flow resistance system comparable to those presented in FIGURES 3A – 3D.

[0052] In some alternative embodiments, channel **57** of FIGURES 3A – 3D can be replaced with a cone-shaped fluid exit that extends through a sidewall of chamber **50**. FIGURE 3E shows a side view schematic of a variable flow resistance system having a single chamber **50** with a cone-shaped fluid exit **58**

extending from the bottom interior surface of the ch
the chamber.

[0053] FIGURES 4A and 4B show side view schematics of a variable flow resistance system having a single chamber that has either a single hole (FIGURE 4A) or multiple holes (FIGURE 4B) within its sidewall. As shown in FIGURES 4A and 4B, chamber **60** has fluid inlet **61** and fluid outlet **62** coupled thereto. A fluid can exit chamber **60** through sidewall **63** via hole(s) **65** and travel through fluid outlet **62**. As shown in FIGURE 4B, fluid passing through each hole **65** can be rejoined into a single-stream fluid output. In alternative embodiments, fluid passing through each hole **65** can remain as a separated fluid output stream (not shown), each of which can then separately enter a subsequent chamber. Series coupling of the chambers to one another can be accomplished in a manner similar to that shown in FIGURES 3C and 3D above, where the chamber arrangement can again be either substantially linear or non-linear. Furthermore, it is to be recognized that hole(s) **65** can be replaced in any of the various embodiments with openings such as slits or grooves to achieve a like result.

[0054] It is to be recognized that whether a substantially linear or non-linear arrangement of chambers is chosen for a multi-chamber variable flow resistance system will be a matter of operational needs, and one of ordinary skill in the art will be able to implement a preferred orientation of chambers for a particular application. Furthermore, it is to be recognized that the depiction of certain numbers of chambers in the drawings should not be construed as limiting. According to the present embodiments, any number of chambers can be series coupled in a multi-chamber variable flow resistance system, including, for example, 2 chambers to about 20 chambers in some embodiments, or 2 chambers to about 10 chambers in other embodiments, or 2 chambers to about 5 chambers in still other embodiments. Of course, the chambers can be used singularly in a variable flow resistance system, if desired.

[0055] In addition to the illustrative arrangements of multiple chambers that are depicted in FIGURES 3C and 3D, other chamber arrangements are also possible when a fluid outlet extends through the sidewall of the chamber. FIGURES 5A – 5C show cutaway top view schematics of illustrative variable flow resistance systems having multiple chambers **70** coupled in series via sidewall fluid outlet **71**. Some of these alternative chamber arrangements allow a

particularly efficient utilization of space to be realiz
for example). Again, it should be emphasized that the chamber arrangements presented in FIGURES 5A – 5C are for purposes of illustration and not limitation, and any series-connected arrangement of multiple chambers in a variable flow resistance system can be used within the spirit and scope of the present disclosure.

[0056] As illustrated in FIGURES 5A – 5C, the shape of the chambers in the present variable flow resistance systems is not particularly limited. However, it is to be understood the chambers of the present embodiments are not limited to the shapes set forth in those or any other drawing unless otherwise expressly set forth herein. In some embodiments, at least a portion of the sidewall of a given chamber can have at least some degree of curvature. In some embodiments, the degree of curvature can be substantially uniform about the interior of the chamber. That is, the chamber can be approximately circular in such embodiments. In other embodiments, the degree of curvature can vary about the interior of the chamber. For example, the chamber can be approximately elliptical in some embodiments. In embodiments in which the degree of curvature can vary, considerably more complex shapes of the chamber can become possible (for example, see FIGURE 5B). In still other embodiments, a chamber having a portion of its sidewalls with a degree of curvature and a portion of its sidewalls substantially planar can also be used, if desired.

[0057] Although FIGURES 3A – 3E, 4A – 4B and 5A – 5C have shown some particular orientations of the fluid inlet and the fluid outlet relative to one another, the spatial arrangement of these elements should not be considered to be particularly limited in any regard. In some embodiments, the location of the fluid inlet can be such that rotational motion is induced in the fluid as it enters the chamber. For example, the chamber and fluid inlet can be configured such that fluid entering the chamber is introduced along a curved sidewall of the chamber, which can set the fluid into rotational motion within the chamber. Furthermore, there are no limitations regarding the separation of the fluid inlet and the fluid outlet from one another along the sidewalls of the chamber. Generally, at least some degree of separation can be maintained between the fluid inlet and the fluid outlet so that an undesired fluid does not enter the fluid outlet without first undergoing rotational motion, but this is not necessarily the case. Finally, the fluid inlet and the fluid outlet can be located at any height

relative to one another. In some embodiments, th
fluid outlet. In other embodiments, the fluid inlet can be above the fluid outlet. In still other embodiments, the fluid inlet and the fluid outlet can be at approximately the same height above the bottom of the chamber.

[0058] In some embodiments, there can be a single fluid inlet coupled to the chamber(s) of the variable flow resistance systems. In other embodiments, there can be more than one fluid inlet coupled to the chamber(s) of the variable flow resistance systems.

[0059] In some embodiments, there can be a single fluid outlet coupled to the chamber(s) of the variable flow resistance systems. In other embodiments, there can be more than one fluid outlet coupled to the chamber(s) of the variable flow resistance systems. That is, in some embodiments, a fluid can exit the chamber(s) at more than one point. In some embodiments, a channel extending from the top or bottom interior surface of the chamber can extend through a sidewall of the chamber(s) at more than one point. In some or other embodiments, there can be multiple holes or like exit ports within the sidewall of the chamber(s). The presence of multiple fluid outlets within the chamber(s) can allow a variable flow resistance system having a "branched" arrangement of chambers to be constructed.

[0060] FIGURES 6A and 6B show side view schematics of a variable flow resistance system having a chamber with multiple fluid outlets. FIGURE 6A shows chamber **80** in which channel **81** splits into multiple fluid outlets **82** extending through sidewall **83** of the chamber. FIGURE 6B shows chamber **85** in which there are multiple holes **86** extending through sidewall **87** of the chamber. FIGURE 6C shows a cutaway top view schematic of a variable flow resistance system in which the chamber of FIGURE 6A has been used to form a branched arrangement of multiple chambers coupled in series. Although FIGURE 6C has shown only a single branch initiated from chamber **80**, it is to be recognized that further branching can take place if desired by replacing any of chamber(s) **50** with chamber **80** or a like chamber having multiple fluid outlets. Further, it should be recognized that any number of fluid outlets can extend from a sidewall of chamber **80**, and the depiction of three fluid outlets in FIGURES 6A – 6C should be considered to be for purposes of illustration and not limitation.

[0061] The rotational motion induced within a fluid passing through the chambers of the present disclosure can be in any direction relative to the

forward motion of the fluid. In some embodiments,
substantially normal to the direction of the fluid flow. That is, in the chamber of FIGURE 3A or another like chamber described herein, the rotational motion can take place as the fluid passes along the sidewalls of the chamber while it passes to the fluid outlet. In some embodiments, the chamber can be configured such that the rotation motion occurs in the same direction as the fluid flow, that is, substantially parallel to the fluid flow. In some embodiments, the chamber can be configured such that rotational motion of the fluid occurs at least partially in parallel to the direction of the fluid flow. In some embodiments, the rotational motion can occur with a component that is substantially normal and a component that is substantially parallel to the fluid flow.

[0062] FIGURES 7A and 7B show side view schematics of an illustrative variable flow resistance system in which rotational motion of the fluid occurs at least partially in parallel to the direction of the fluid flow. As shown in FIGURES 7A and 7B, a fluid enters chamber **100** through fluid inlet **101** and exits through fluid outlet **102**. In region **103**, the fluid can either rotate substantially normal to the forward direction of fluid motion or not rotate to a significant degree. Once the fluid progresses forward and encounters vane **105**, rotational motion is induced in the fluid in region **104**, where the rotational motion is at least partially in parallel to the forward direction of the fluid motion.

[0063] In some embodiments, the fluid inlets coupled to the chambers of the present disclosure can comprise both a main flow pathway and a branch flow pathway. In some embodiments, the branch flow pathway can be configured such that fluid entering the branch flow pathway does not undergo rotational motion or undergoes less rotational motion than fluid entering the main flow pathway. FIGURE 8A shows a cutaway top view schematic of a variable flow resistance system having a chamber with both a main flow pathway and a branch flow pathway within the fluid inlet. As shown in FIGURE 8A, chamber **90** includes fluid inlet **91** and channel **92** extending through sidewall **93** into fluid outlet **94**. Fluid inlet **91** further comprises main flow pathway **91'** and branch flow pathway **91"**. As one of ordinary skill in the art will recognize, low viscosity fluids, such as water or gas, will tend to enter main flow pathway **91'**, since they have a higher ratio of momentum to viscosity than more viscous fluids (*e.g.*, oil), such that they tend not to make the turn into branch flow pathway **91"**. More viscous fluids, in contrast, by virtue of their lower ratio of

momentum to viscosity can more readily make tl
flow pathway **91**". Outlet **95** of branch flow pathway **91**" can be located within chamber **90** such that high viscosity fluid passing therethrough can undergo less rotational motion via bypassing the portion of chamber **90** that induces rotational motion in the fluid and/or by being located in or near channel **92**, which leads to fluid outlet **94**. In some embodiments, outlet **95** can completely bypass chamber **90** such that a fluid passing therethrough is discharged directly into outlet **94**.

[0064] Similar to the embodiments described above, chambers having fluid inlets with both main and branch flow pathways can likewise be series coupled to one another. FIGURE 8B shows a cutaway top view schematic of a variable flow resistance system in which multiple chambers having a fluid inlet with a main flow pathway and a branch flow pathway are series coupled together. As drawn in FIGURE 8B, outlet **95** of branch flow pathway **91**" discharged near channel **92**. FIGURE 8C shows an alternative embodiment to that presented in FIGURE 8B, in which fluid outlet **95** of branch flow pathway **91**" is discharged directly into fluid outlet **94**, thereby preventing a fluid passing therethrough from undergoing rotational motion. In FIGURE 8C, branch flow pathway **91**" is structurally connected to fluid outlet **95**, thereby allowing chamber **90** to be bypassed altogether. In both cases, main flow pathway **91'** discharges into chamber **90** and fluid therein can undergo rotational motion.

[0065] Another embodiment of a variable flow resistance system having a branch flow pathway is shown in FIGURE 9. FIGURE 9 shows a side view schematic of a variable flow resistance system **110** having multiple fluid inlets **111** and fluid outlets **112** interconnecting chambers **113**, **114**, **115** and **116**. Lower viscosity fluids (solid line) such as, for example, oil and gas can enter main flow pathway **118** and undergo rotational motion within chamber **114**. The lower viscosity fluids can subsequently bypass branch flow pathways in chambers **114** and **115** and undergo additional rotational motion in these chambers. In contrast, a higher viscosity fluid (dashed line) such as oil, for example, can enter branch flow pathway **118'**. As the higher viscosity fluid enters chamber **114**, it has less opportunity to undergo rotational motion and can subsequently enter branch flow pathways in chambers **114** and **115**. Accordingly, the transit rate of the higher viscosity fluid relative to the lower viscosity fluid can be increased.

[0066] Therefore, the present invention i
ends and advantages mentioned as well as those that are inherent therein. The particular embodiments disclosed above are illustrative only, as the present invention may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. Furthermore, no limitations are intended to the details of construction or design herein shown, other than as described in the claims below. It is therefore evident that the particular illustrative embodiments disclosed above may be altered, combined, or modified and all such variations are considered within the scope and spirit of the present invention. The invention illustratively disclosed herein suitably may be practiced in the absence of any element that is not specifically disclosed herein and/or any optional element disclosed herein. While compositions and methods are described in terms of "comprising," "containing," or "including" various components or steps, the compositions and methods can also "consist essentially of" or "consist of" the various components and steps. All numbers and ranges disclosed above may vary by some amount. Whenever a numerical range with a lower limit and an upper limit is disclosed, any number and any included range falling within the range is specifically disclosed. In particular, every range of values (of the form, "from about a to about b," or, equivalently, "from approximately a to b," or, equivalently, "from approximately a-b") disclosed herein is to be understood to set forth every number and range encompassed within the broader range of values. Also, the terms in the claims have their plain, ordinary meaning unless otherwise explicitly and clearly defined by the patentee. Moreover, the indefinite articles "a" or "an," as used in the claims, are defined herein to mean one or more than one of the element that it introduces. If there is any conflict in the usages of a word or term in this specification and one or more patent or other documents that may be incorporated herein by reference, the definitions that are consistent with this specification should be adopted.

CLAIMS

The invention claimed is:

1. A variable flow resistance system comprising:

a chamber configured to induce rotational motion of a fluid flowing therethrough;

a fluid inlet coupled to the chamber; and

a fluid outlet coupled to the chamber that allows the fluid to exit through at least a sidewall of the chamber.

2. The variable flow resistance system of claim 1, wherein the fluid outlet comprises a channel within the chamber that extends from the top or bottom interior surface of the chamber through at least a sidewall of the chamber.

3. The variable flow resistance system of claim 2, wherein the channel exits through the sidewall of the chamber at more than one point.

4. The variable flow resistance system of claim 1, wherein the fluid outlet comprises at least one hole in the sidewall of the chamber.

5. The variable flow resistance system of claim 1, wherein at least a portion of the sidewall of the chamber has at least some degree of curvature.

6. The variable flow resistance system of claim 1, wherein the chamber is configured such that the rotational motion occurs, at least in part, in the same direction as the fluid flow.

7. The variable flow resistance system of claim 1, wherein the fluid inlet comprises a main flow pathway and a branch flow pathway;

wherein the branch flow pathway is configured such that fluid entering the branch flow pathway does not undergo rotational motion or undergoes less rotational motion than fluid entering the main flow pathway.

8. The variable flow resistance system of claim 7, wherein the branch flow pathway is structurally connected to the fluid outlet.

9. The variable flow resistance system of claim 1, wherein the chamber is configured to induce increasing rotational motion of the fluid with decreasing fluid viscosity.

10. A variable flow resistance system comprising:

a plurality of chambers that are connected in series fluid

communication with one another, each chamber having a fluid inlet and a fluid outlet coupled thereto;

wherein at least some of the chambers are configured to induce rotational motion of a fluid flowing therethrough; and

wherein the fluid outlets of at least some of the chambers are configured to allow the fluid to exit through at least a sidewall of the chamber.

11. The variable flow resistance system of claim 10, wherein at least some of the chambers are configured such that the rotational motion occurs, at least in part, in the same direction as the fluid flow.

12. The variable flow resistance system of claim 10, wherein at least some of the chambers are configured to induce increasing rotational motion of the fluid with decreasing fluid viscosity.

13. The variable flow resistance system of claim 10, wherein at least some of the chambers have at least some degree of curvature in at least a portion of the sidewall of the chamber.

14. The variable flow resistance system of claim 10, wherein the fluid outlet of at least some of the chambers comprises a channel within the chamber that extends from the top or bottom interior surface of the chamber through at least a sidewall of the chamber.

15. The variable flow resistance system of claim 10, wherein the fluid outlet of at least some of the chambers comprises at least one hole in the sidewall of the chamber.

16. The variable flow resistance system of claim 10, wherein the fluid inlets of at least some of the chambers comprise a main flow pathway and a branch flow pathway;

wherein the branch flow pathway is configured such that fluid entering the branch flow pathway does not undergo rotational motion or undergoes less rotational motion than fluid entering the main flow pathway.

17. The variable flow resistance system of claim 16, wherein the branch flow pathway is structurally connected to the fluid outlet in at least some of the chambers.

18. A method comprising:

installing a wellbore pipe in an uncompleted wellbore;

wherein the wellbore pipe comprises at least one variable flow resistance system in fluid communication with the interior of the wellbore pipe, each variable flow resistance system comprising:

a plurality of chambers that are connected in series fluid communication with one another, each chamber having a fluid inlet and a fluid outlet coupled thereto;

wherein at least some of the chambers are configured to induce rotational motion of a fluid flowing therethrough; and

wherein the fluid outlets of at least some of the chambers are configured to allow the fluid to exit through at least a sidewall of the chamber.

19. The method of claim 18, further comprising:

allowing a formation fluid to flow through at least some of the variable flow resistance systems and into the interior of the wellbore pipe; and

producing the formation fluid from the wellbore pipe.

20. The method of claim 18, wherein the uncompleted wellbore comprises a horizontal wellbore.

21. The method of claim 18, wherein the uncompleted wellbore penetrates a subterranean formation comprising a plurality of intervals; and

wherein there is at least one variable flow resistance system within each interval.