

Description

FIELD OF THE INVENTION

The present invention relates to an apparatus for the surgical treatment of prostate tissues according to the pre-characterizing part of claim 1. Such an apparatus is known from Medical Tribune 31 march 1988, pages 3, 13 and 14.

BACKGROUND OF THE INVENTION

European Patent 0 248 758 describes a microwave applicator which is inserted in the rectum for treating the prostate by hyperthermia. The microwave applicator is kept in position inside the rectum by a laterally projecting balloon 7, meaning that special protection of the rectum is required. Preferably, for heating the prostate, means 52 are provided for reflecting the emitted microwaves which are then concentrated at the side of the body opening opposite to the balloon 7. Ducts 28 are provided in the microwave emitting rectal applicator for circulating a cooling liquid, as shown in Figures 2 to 4.

The cooling liquid protects the rectal walls in contact with the microwave antenna from damage. Moreover, the presence of the reflecting means 52 is absolutely necessary to prevent the antenna from emitting in all directions, when the radiation is only required to be directed onto the prostate tissues.

European Patent 0 246 176 describes a catheter having an antenna equipped with a temperature sensor which is inserted into the urethra through to the bladder for locating and determining the position of the microwave applicator described in the above-cited European Patent 0 248 558.

From a practical point of view, the design of the microwave applicator described in European Patent 0 248 758 for introduction in the rectum, is not satisfactory in that the application lacks accuracy since the prostate is remotely-irradiated.

It is furthermore essential with this method to prevent the emission of microwaves in all directions, this implying an emitting antenna of very special design equipped with reflecting means for directing the radiated microwaves in only one direction, namely towards the prostate.

Finally, and unquestionably, with such a device, it is quite difficult, if not impossible, to protect the sphincter, and more generally to protect the surrounding tissues. This being especially so in the case of bladder treatment.

European Patent 0 105 677 describes such a microwave antenna device for hyperthermia therapy, designed to be introduced in the tract or the lumen, in which device the antenna assembly is

placed inside a thin supple polymer film, without any means of protecting the sensitive tissues from the heat.

Patent document WO-A-81/03616 to Bircher describes yet again a microwave antenna system for hyperthermia therapy, which is inserted in a body cavity and used in the treatment of cancer and similar. Typical examples of inserting apertures are the mouth and upper throat.

The introductory part of said patent document cites the document J. Microwave Power 14(2) : 167-171 (1969) relative to an applicator introduced through the rectum for irradiation of the prostate. It is specified that said irradiation treatment involves a burning of the tissues which are close to the electrode.

According to said document, the characteristic of this irradiation treatment is that it is carried out at a lower frequency and at a higher wavelength to improve penetration into the tissues to depths of 5 to 6 cm. Such deep penetration permits extensive irradiation of large tumors in the bowels or similar.

The revue "Proceedings of the 13th Annual Northeast Bioengineering Conference, Philadelphia, March 12-13, 1987, pages 390-393, Ryan" describes the pretreating by microwave-induced hyperthermia of patients suffering from biliary obstruction due to cancer, by inserting a catheter into the choledoch to allow drainage in an invasive way.

Tests have been carried out with the same antenna in various media, as reported in Figure 5. In the case of tests B and D, the medium was a saline solution, and it is underlined in the "Discussion" part that when the medium is changed from air to a conductive medium such as a saline or bile medium, the performances decrease dramatically, which rather discourages the specialist from using a saline solution in microwave-induced hyperthermia.

SUMMARY OF THE INVENTION

It is now the object of the present invention to solve this new technical problem by providing a solution permitting a more accurate surgical treatment of tissues by hyperthermia, in particular the prostate, while efficiently protecting the sensitive tissues other than those to be treated by hyperthermia.

The object of the present invention is therefore to solve this new technical problem, particularly in the hyperthermia treatment of the prostate without the need to use special probe means emitting in only one direction.

Another object of the invention is to solve the aforesaid new technical problems in an extremely simple way, using means for readily and reliably locating the position of the emitting probe means.

Yet another object of the invention is to solve the aforesaid new technical problems in a semi-invasive way, namely by using the natural body cavities.

All these technical problems are solved for the first time by the present invention, as claimed in claim 1.

According to a preferred embodiment, the invention provides an apparatus wherein means are provided for protecting from the heat the sensitive tissues other than the tissues to be treated, preferably comprising means forming radioreflecting screen.

According to a particularly advantageous embodiment of the invention, the means which, according to the invention, form radioreflecting screen, contain a radioreflecting liquid medium. Advantageously, said radioreflecting liquid medium is an electrically conductive liquid reflecting the microwaves.

According to a variant embodiment, the radioreflecting screen-forming means according to the invention comprise at least one wire, parallel to the mean electrical field.

According to a currently preferred application to the treatment of the prostate, the apparatus according to the invention is characterized in that the probe means is a urethral probe means inserted in the urethra up to the level of the prostate. Preferably, one part of the means forming radioreflecting screen according to the invention is at the level of an organ to be treated, such as the bladder, the sphincter.

According to another particularly advantageous embodiment of the invention, said means forming radioreflecting screen and protecting the bladder may comprise a balloon provided on the front end of the antenna, means being provided for filling said balloon with a radioreflecting conductive solution.

According to a variant embodiment, the screen-forming means protecting the bladder comprise a conductive solution injected directly into the bladder said solution being preferably hypertonic.

According to another particularly advantageous embodiment of the invention, another part of said screen-forming means is fast with a rectal probe means, for protecting the rectal wall from high temperatures.

Thus, according to a variant embodiment of said means forming protection screen for the rectal wall, said means can comprise a radioreflecting liquid medium, in particular one introduced into a balloon provided around the front end of the rectal probe means.

According to another particularly advantageous embodiment of the invention, the apparatus is characterized in that it further comprises means of

controlling the positioning of the urethral probe means, preferably incorporated in a rectal probe means, said rectal probe means serving thus as a protection for the rectal walls and as a means of controlling the positioning of the microwave-emitting urethral probe means in axial position.

Means of immobilizing the rectal probe means in axial position can be provided, said means preferably permitting a rotation of said probe means around its axis. Said immobilizing means preferably comprise a balloon, for example in latex, which surrounds the rectal probe means, and inside which said probe means can be readily oriented from the outside.

According to another advantageous embodiment of the invention, the apparatus is equipped with means for cooling the surface of the emitting probe means, in order to prevent burns on the walls in contact with the probe means, particularly the urethral walls.

According to another variant embodiment, the apparatus according to the invention is characterized in that it comprises temperature sensing means provided on or in the emitting probe means, and/or on or in the rectal probe means and optionally in said balloon.

According to one particular variant of embodiment, said microwave generating device comprises a metallic cable coaxial to the probe means covered by an insulating sleeve over part of its length, said cable also having a microwave-emitting part which is non-insulated, which part is preferably situated at an intermediate or distal level of the emitting probe means.

According to yet another particularly advantageous variant of embodiment, said temperature sensing means comprise a fiber-optic thermometer, heat-insulated from the cooling circuit, preferably comprising several strands of fibers disposed in radially and/or longitudinally offset fashion in the longitudinal direction of the probe means, in such a way as to detect the temperature in various radial and/or longitudinal directions of the probe means.

It is therefore obvious that with the apparatus according to the invention, the emitting probe means can be positioned with great accuracy since it is inserted directly into the prostate along the natural urethral passage, thus preventing the sphincter from being damaged.

Also, owing to the radioreflecting screen-forming means according to the invention, it becomes possible to protect efficiently the bladder as well as the rectal walls. According to the invention, it is possible to use an emitting probe means emitting in all directions, but naturally, according to the invention, it is possible, and in some cases advisable or advantageous, to use a probe means emitting preferably in one given direction.

Understandably, therefore, all the decisive technical advantages, unexpected by anyone skilled in the art, and listed hereinabove, are obtained according to the invention, and moreover, the proposed apparatus is very versatile and very easy to handle for a practitioner.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more readily understood on reading the following description of several embodiments of an apparatus according to the invention for the surgical treatment of tissues by hyperthermia, in a preferred application to the treatment of the prostate, reference being made to the accompanying drawings, in which:

- Figure 1 is a diagrammatical view of a partial section of the complete apparatus according to the invention for the surgical treatment of tissues to be destroyed by hyperthermia, illustrated in its preferred application to the treatment of the prostate, and comprising a urethral emitting probe means and a rectal echographic detecting probe means, both connected to a central control device;
- Figure 2 is a view showing a partial longitudinal axial section of the main part of the urethral emitting probe means;
- Figure 2a is a cross-section along line IIa-IIa of Figure 2;
- Figure 3 is a perspective side view of the urethral emitting probe means shown in Figures 1 and 2, the balloon being deflated;
- Figure 4 illustrates a variant embodiment of the urethral emitting probe means according to the invention, showing a longitudinal axial section of a second embodiment of the cooling means;
- Figure 5 illustrates another variant embodiment of the structural design of the urethral emitting probe means, showing an axial cross-section of another embodiment of the cooling means;
- Figure 6 illustrates another variant of the cooling means in a view similar to Figure 5.
- Figure 7 illustrates yet another variant embodiment of the cooling means in a view similar to that shown in Figure 5.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Referring in particular to Figure 1, this shows an apparatus according to the invention, bearing the general reference number 10, for the surgical treatment of tissues 12 by hyperthermia, preferably the prostate 14, of the type comprising heating means 16 for inducing hyperthermia, consisting of

a microwave-generating device 18, clearly shown in Figure 2, placed in an emitting probe means of general reference number 20, shown in longitudinal axial section in Figure 2, adapted to be inserted in a cavity of the body.

In the preferred example of application of the apparatus to the destruction of the prostate 14 by hyperthermia, illustrated herein, the emitting probe means 20 is, according to the invention, a urethral probe means.

The apparatus according to the invention is characterized in that it comprises heat protecting means 22, 30 for protecting the sensitive tissues other than the tissues 12 to be destroyed, such as the prostate 14, said means preferably comprising means forming radioreflecting screen 22, 30. According to a variant embodiment of the invention, the means forming radioreflecting screen comprise a radioreflecting liquid medium, preferably an electrically conductive medium able to reflect the microwaves emitted by the emitting probe means 20 equipped with the microwave emitting device 18.

According to a particular variant of embodiment, said radioreflecting conductive solution is injected directly into the patient's bladder 24. In this case, said solution is preferably hypertonic. It can be, for example, a solution with a high ion concentration, such as by using NaCl. In general, suitable conductive solutions are saturated ionic solutions, such as NaCl or nitrate solutions, said solutions are obvious to anyone skilled in the art.

According to another variant of embodiment, one part 22 of the screen forming means is placed level with an organ to be protected, in particular the bladder. According to a preferred embodiment, said means forming protection screen for the bladder comprise a balloon 26 provided on the front end 20a of the probe means 20. Said balloon 26 is equipped with means 28 for filling it, preferably with a radioreflecting conductive solution 23. Said filling means normally comprise an internal duct 29 extending out towards a flexible tube 30. Said radioreflecting conductive solution may be identical to the previous one and based on saturated NaCl solution.

According to one advantageous embodiment of the emitting probe means according to the invention, said probe means comprises cooling means 32 incorporated to the probe means 20 for lowering the temperature of the external wall of said probe means 20, namely, in the illustrated case, the walls of the urethra 34. Said cooling means 32 consists, for example, in at least two conduits, respectively an inlet conduit 36 and an outlet conduit 38, containing the cooling medium and communicating with each other at the front of the probe means 20 via a connection conduit 37 clearly shown in Figure 2. Said conduits 36, 38 communicate with flexible

tubes 40, 42, respectively a supply tube and a discharge tube for the cooling medium, which may be water.

According to another characteristic of the invention, the urethral emitting probe means 20 is equipped with means 44 for sensing the temperature on or inside the urethral probe means 20. According to an advantageous variant, said temperature sensor 44 comprises a fiber-optic thermometer 46, the optical fibers being isolated by heat-insulating means 48 from the rest of the probe means and in particular from the cooling circuit 36, 38, as illustrated in Figures 2a and 3. Said thermometer comprises a plurality of strands of fibers placed in radially and/or longitudinally offset fashion in the longitudinal direction of the probe means 20, in such a way as to detect the temperature in various radial and/or longitudinal positions of the probe means.

Said thermometer 46 and associated insulating means 48 may be disposed in a longitudinal slot 50 provided in the external surface 21 of the probe means 20.

It will be noted that, advantageously, the front end 20a of the probe means 20 should be rounded to facilitate insertion of the probe means 20 through the urethra and up to the level of the bladder 24, as can be seen in Figure 1.

The microwave generating device 16, as illustrated in Figures 2 and 3, comprises a metallic cable 52 coaxial to the probe means 20 and covered with an insulating sleeve 54 over part of its length, said cable 52 comprising at least one microwave-emitting non-insulated part 52a preferably situated at an intermediate or distal level of the emitting probe means, as clearly illustrated in Figures 2 and 3. Preferably, the free end of the cable 52a forming microwave emitting antenna ends up under the balloon 26 forming the means protecting the bladder. Said cable 52 forms an emitting antenna which may be for example 20 to 40 mm long and which radiates in all directions about its axis, i.e. over 360°.

Said emitting antenna 52a constituted by the non-insulated part of the cable 52 is connected to a microwave generator apparatus symbolized by the initials M.W.G., emitting for example at about 915 MHz and of power adjustable up to 50 W or even 100 W.

According to a variant of embodiment, the emitting antenna may be rather more complex and comprise shielding portions along the non-insulated part of cable 52 this with a view to preferentially heating certain parts of the prostate.

Figure 2a shows an axial cross-section of the emitting probe means 20, and illustrates the shape and position of each one of the elements constituting the probe means. This figure shows that the

conduits 36, 38 containing the cooling medium, such as water, are formed by wide openings extending over an arc of circle of the probe means 20 which latter has a substantially circular or slightly ovoidal cross-section for easy passage through the urethra. It is observed that according to the variant embodiment illustrated in Figure 2a, the temperature sensor 44 and the duct 29 supplying the balloon 26 are situated in substantially the same plane passing through the axis of the probe means, hence of the cable 52, whereas the conduits 36,38 containing the cooling medium are also arranged symmetrically with respect to said plane of symmetry.

Other variants of structure of the urethral probe means 20 are shown in Figures 4 to 7 in which the same reference numbers increased by 100, are used to designate identical parts or parts having the same function.

In the embodiment shown in Figure 4, the urethral probe means designated by the general reference 120 comprises an annular duct 136 coaxial to the probe means 120 communicating with a disc-shaped common duct 137 reaching to a central conduit 138 in which is introduced the microwave-emitting device 18.

Referring now to Figure 5, this shows another embodiment of the internal structure of the probe means, of which the general reference number has, in this example, been increased of 200, giving it the reference 220. As shown in this figure, the inlet conduit 236 supplying the cooling medium, occupies an annular sector of the probe means 220, whereas the outlet conduit 238 discharging the heated cooling medium, occupies a complementary annular sector, both annular sectors 236, 238 being separated by longitudinal transversal partitions 239, 241. The emitting device 218 is always placed axially with respect to the probe means 220. Figure 5 also shows the conduit 229 supplying the inflating medium, such as for example an electrically conductive liquid, to the balloon provided on the front end of the probe means 220, as well as the temperature sensor 244.

Figure 6 illustrates another variant of embodiment in which the parts which are identical or have the same function have been given the same reference numbers, further increased by 100. According to said Figure 6, four inlet conduits 336 supplying the cooling medium are provided, said conduits occupying annular sectors of the probe means 320 from the periphery 321 to the central longitudinal orifice 353 in which the microwave-emitting device 318 is inserted. The remaining sectors comprise corresponding annular conduits 338 for discharging the cooling medium, a conduit 329 being also provided for inflating the balloon, as well as a slot 350 for housing the temperature sensor 344.

Referring to Figure 7, this shows yet another variant of the structure of the probe means of which the reference number has been further increased by 100, making it then 420. Four cooling medium inlet sectors 436 are also provided here, said sectors having rounded edges so that the remaining sectors 438 are substantially cross-shaped, which remaining cooling medium outlet sectors may be intercommunicating or not. The emitting device 418 is also placed in the axis of the probe means 428.

It is therefore understood that various forms of embodiment are possible for the structure of the emitting probe means. The probe means structure such as described and illustrated in Figures 1 through 7, forms an integral part of the invention and is incorporated in the description by way of reference.

The apparatus according to the invention further comprises means 80 for controlling the positioning of the urethral probe means 20, said means 80 being preferably incorporated in a rectal probe means 82. Said control means 80 are preferably constituted by an echographic probe 82 of rectal type. Said echographic probe is advantageously connected with a screen-equipped echograph 84. In a variant embodiment, the echographic probe may be connected with a central control device 86 centralizing all the information and capable of automatically controlling the microwave generator device M.W.G. as a function of the recorded temperature data and of any data which may have been programmed by the practitioner, as can be understood from Figure 1.

The central control device 86, such as a computer or the like, receives all the temperature data centralized in a thermometry device as well as the temperature data from the cooling device supplying the cooling means of the emitting probe means 20; it also gives the instructions necessary to the microwave generating device (M.W.G.) as well as to the cooling device. According to a variant embodiment, it can also receive the data issued from the echographic probe 82 relatively to the position of the emitting probe means 20 in relation to the prostate.

An interstitial thermometer 100 may also be provided, inserted in the prostate 14, under echographic control, so that when biopsies have to be carried out, it is possible to detect the temperature at which the prostate 14 has been brought by the microwaves emitted by the probe means 20. Such temperature data is of course important to determine the power instructions given by the control device 86 to the microwave generator M.W.G.

The tissues-protecting means according to the invention may comprise a part 90 fast with the rectal probe means 82, for protecting the rectal wall

from high temperatures. According to a particularly advantageous embodiment, said screen-forming means 90 fast with the rectal probe means comprise an inflatable element 92 forming balloon fixed around the rectal probe 82 on its front end 82a which element is preferably supplied with a radioreflecting liquid medium 94 through a flexible tube 96 preferably identical to that used for inflating the balloon 26 of the urethral probe means. A temperature sensor 98 may be provided inside the balloon 92 for detecting the temperature at the level of the rectal wall 100 facing the prostate 14, the temperature data recorded by said sensor being transmitted to the thermometry device and to the central control device 86, such as a computer or the like.

According to a variant embodiment of the invention, said screen-forming means may comprise at least one wire, parallel to the mean electrical field, which wire is placed preferably in integral fashion with the rectal probe means 82 longitudinally thereto, in the direction of the emitting probe means 20.

Means may also be provided for protecting the sphincter 15 by a balloon system surrounding the probe means 20 similarly to balloon 26, which system can also be supplied by supply means 30.

It is obviously possible, according to the invention, to treat efficiently the prostate 14 by hyperthermia, and in general to destroy tissues by hyperthermia.

It is extremely easy with the echographic probe 82 connected with a screen-equipped echograph 84 to control the exact position of the emitting probe means 20 inside the prostate 14 by monitoring the echographic image of the emitting probe means 20 on the screen 84. When the practitioner sees that the emitting probe means is accurately positioned in the prostate 14, he can then trigger manually the control device 86 into operation, for carrying out the hyperthermia treatment, the temperature being controlled inside the prostate 14 as well as in the surrounding tissues, and in particular in the rectum, by the various temperature sensors such as 98, 100,

It is also possible with the apparatus according to the invention, to protect efficiently the tissues other than the prostate, by various protection means 22, 90. Furthermore, the presence of the cooling means 32 prevents burns from occurring on the walls in contact with the probe means 20, particularly the walls of the urethra 34.

The invention also relates to a method for surgically treating tissues 12 by hyperthermia, preferably the prostate 14, of the type using a microwave generating device 18 provided in an emitting probe means 20 capable of being introduced in a cavity of the body, wherein the sensitive tissues

other than the tissues 12 to be treated are protected from the heat preferably by providing means forming radioreflecting screen 22, 90.

According to a variant embodiment of this surgical treatment method, said emitting probe means 20 is inserted in the urethra, said probe means being then a urethral probe means inserted in the urethra as far as the prostate. It is preferably provided that one part 22 of said screen-forming means is placed at the level of an organ to be protected, such as the bladder 24 and/or the sphincter 15.

According to another advantageous variant of the method of the invention, the positioning of the urethral probe means 20 in relation to the prostate 14 is controlled by inserting a probe means 82 in the rectum, said probe means being of course a rectal probe means. Advantageously, a protection forming radioreflecting means is also provided for protecting the rectal wall 100 from high temperatures.

Other variant embodiments of the treatment method according to the invention follow from the description given hereinabove with reference to the apparatus.

By way of indication, the total duration of a treatment of the prostate by hyperthermia is normally about 1 hour. The emitting probe means can for example emit microwaves at a frequency of about 900 MHz and at a power which can be adjusted up to 50 W or even 100 W. The length of the actual emitting antenna is for example between 20 and 40 mm, these values being given by way of indication only.

Obviously, the invention also extends to any means constituting technical equivalents of the means described herein, as well as to the combination thereof.

Claims

1. Apparatus for the surgical treatment of prostate tissues by hyperthermia, comprising a heating probe constituted by an urethral microwave emitting probe (20) which is adapted to be inserted in the urethra, said emitting probe (20) having a front end (20a) and a rear end, said emitting probe (20) comprising a microwave antenna means (18) placed in said emitting probe (20) and located intermediate said front end and said rear end in the vicinity of said front end (20a), said microwave antenna means (18) emitting microwaves in all directions and being connected to an external microwave generating device (MWG) comprising means for generating microwaves at a frequency and a power effective for hyperthermia treatment,

characterized in that said urethral probe (20) comprises a single microwave antenna means (18) located substantially axially in said urethral emitting probe, cooling means (32) being provided in said urethral probe (20) around said axial microwave antenna means (18) for cooling the surface of the urethral probe (20) facing said single microwave antenna means (18), said cooling means being fed with a cooling fluid, said emission of microwaves being adapted to said cooling fluid to prevent burns from occurring on the prostate urethral wall (34) in contact with the probe (20).

2. The apparatus of claim 1, wherein said cooling means are extending up to the full length of the microwave antenna means (18).
3. The apparatus of claim 1 or 2, comprising an inflatable balloon means (26) to lock in position said emitting probe (20), and inflating means (28, 29, 30) for inflating said balloon means (26), characterized in that said inflatable balloon means (26) is located at said front end (20a) such that it is placed in the bladder (24) when the microwave antenna means (18) is placed inside said prostate (14) to be treated.
4. The apparatus of claim 3, wherein the inflating means comprises a liquid.
5. The apparatus of claims 1, 2, 3 or 4, characterized in that temperature sensing means (44) are provided on or in the urethral probe and optionally in the balloon means (26).
6. The apparatus of any one of claims 1 to 5, characterized in that the microwave emitting antenna means (18) comprise a metallic cable (52) coaxial to the urethral probe (20) covered by an insulating sheath (54), the emitting part (52a) being situated at an intermediate or distal level of the urethral probe means (20).
7. The apparatus as claimed in any one of claims 1 to 6, characterized in that it comprises control means (80) for controlling the positioning of the urethral probe (20).
8. The apparatus of claim 7, wherein the control means (80) are incorporated in a rectal probe means (82).
9. The apparatus of claim 7 or 8, characterized in that immobilizing means (92) are provided for immobilizing the rectal probe means (82) in axial position, but preferably permitting the rotation of said rectal probe means (82) about its

other than the tissues 12 to be treated are protected from the heat preferably by providing means forming radioreflecting screen 22, 90.

According to a variant embodiment of this surgical treatment method, said emitting probe means 20 is inserted in the urethra, said probe means being then a urethral probe means inserted in the urethra as far as the prostate. It is preferably provided that one part 22 of said screen-forming means is placed at the level of an organ to be protected, such as the bladder 24 and/or the sphincter 15.

According to another advantageous variant of the method of the invention, the positioning of the urethral probe means 20 in relation to the prostate 14 is controlled by inserting a probe means 82 in the rectum, said probe means being of course a rectal probe means. Advantageously, a protection forming radioreflecting means is also provided for protecting the rectal wall 100 from high temperatures.

Other variant embodiments of the treatment method according to the invention follow from the description given hereinabove with reference to the apparatus.

By way of indication, the total duration of a treatment of the prostate by hyperthermia is normally about 1 hour. The emitting probe means can for example emit microwaves at a frequency of about 900 MHz and at a power which can be adjusted up to 50 W or even 100 W. The length of the actual emitting antenna is for example between 20 and 40 mm, these values being given by way of indication only.

Obviously, the invention also extends to any means constituting technical equivalents of the means described herein, as well as to the combination thereof.

Claims

1. Apparatus for the surgical treatment of prostate tissues by hyperthermia, comprising a heating probe constituted by an urethral microwave emitting probe (20) which is adapted to be inserted in the urethra, said emitting probe (20) having a front end (20a) and a rear end, said emitting probe (20) comprising a microwave antenna means (18) placed in said emitting probe (20) and located intermediate said front end and said rear end in the vicinity of said front end (20a), said microwave antenna means (18) emitting microwaves in all directions and being connected to an external microwave generating device (MWG) comprising means for generating microwaves at a frequency and a power effective for hyperthermia treatment,

characterized in that said urethral probe (20) comprises a single microwave antenna means (18) located substantially axially in said urethral emitting probe, cooling means (32) being provided in said urethral probe (20) around said axial microwave antenna means (18) for cooling the surface of the urethral probe (20) facing said single microwave antenna means (18), said cooling means being fed with a cooling fluid, said emission of microwaves being adapted to said cooling fluid to prevent burns from occurring on the prostate urethral wall (34) in contact with the probe (20).

2. The apparatus of claim 1, wherein said cooling means are extending up to the full length of the microwave antenna means (18).
3. The apparatus of claim 1 or 2, comprising an inflatable balloon means (26) to lock in position said emitting probe (20), and inflating means (28, 29, 30) for inflating said balloon means (26), characterized in that said inflatable balloon means (26) is located at said front end (20a) such that it is placed in the bladder (24) when the microwave antenna means (18) is placed inside said prostate (14) to be treated.
4. The apparatus of claim 3, wherein the inflating means comprises a liquid.
5. The apparatus of claims 1, 2, 3 or 4, characterized in that temperature sensing means (44) are provided on or in the urethral probe and optionally in the balloon means (26).
6. The apparatus of any one of claims 1 to 5, characterized in that the microwave emitting antenna means (18) comprise a metallic cable (52) coaxial to the urethral probe (20) covered by an insulating sheath (54), the emitting part (52a) being situated at an intermediate or distal level of the urethral probe means (20).
7. The apparatus as claimed in any one of claims 1 to 6, characterized in that it comprises control means (80) for controlling the positioning of the urethral probe (20).
8. The apparatus of claim 7, wherein the control means (80) are incorporated in a rectal probe means (82).
9. The apparatus of claim 7 or 8, characterized in that immobilizing means (92) are provided for immobilizing the rectal probe means (82) in axial position, but preferably permitting the rotation of said rectal probe means (82) about its



axis.

10. The apparatus of claim 9, characterized in that said immobilizing means comprises a balloon (92), for example made of latex, surrounding the rectal probe means (82) and in which said rectal probe means (82) is readily orientable from the outside.
11. The apparatus of any one of claims 7 to 10, characterized in that rectal temperature sensing means (98) are provided on or in the rectal probe means (82).
12. The apparatus of any one of claims 5 to 11, characterized in that said temperature sensing means (44) comprises a fiber optic thermometer which is heat-insulated from the cooling means (32), preferably comprising several strands of fibers disposed in radially and/or longitudinally offset fashion in the longitudinal direction of the urethral probe (20) so as to detect the temperature on various radial and/or longitudinal positions of the urethral probe (20).
13. The apparatus of any one claims 1 to 12, characterized in that heat protecting means (22, 90) are provided for protecting from the heat the sensitive tissues other than the tissues (12) to be treated, comprising means forming radioreflecting screen (22, 90).
14. The apparatus of claim 13, characterized in that said means forming radioreflecting screen comprise a radioreflecting liquid medium (23, 94), preferably comprising an electrically conductive liquid reflecting the microwaves.
15. The apparatus of claim 13, characterized in that said screen forming means comprise at least one wire, which is parallel to the mean electrical field, and preferably incorporated to said rectal probe means (82).
16. The apparatus of any one of claims 11 to 15, characterized in that said external microwave generating device (M.W.G.), which generates microwaves at a frequency of about 900 MHz or 915 MHz, and at a power adjustable up to 100 watts.
17. The apparatus of any one of claims 7 to 16, characterized in that said control means (80) comprises an echographic probe, in particular a rectal echographic probe, connected with a screen equipped echograph (84).

18. The apparatus of any one of claims 5 to 17, characterized in that it comprises a central control device (86) centralizing all the information including all the temperature data centralized in a thermometry device and capable of automatically controlling the microwave generator device (MWG) as a function of the recorded temperature and of any data which may have been programmed by the practitioner.
19. The apparatus of claim 18, characterized in that the central control device (86) receives the data issue from the echographic probe (82) relatively to the position of the urethral probe (20) in relation to the prostate.
20. The apparatus according to any one of claims 1 to 19, characterized in that said cooling means comprise at least an inlet conduit (236 ; 336 ; 436) and at least one outlet conduit (238 ; 338 ; 438), said inlet conduit and outlet conduit being fed with a cooling liquid..
21. The apparatus of claim 20, wherein said inlet conduit occupies an annular sector of the probe and said outlet conduit occupies a complementary annular sector, both annular sectors being separated by longitudinal transversal partitions (239 ; 241).
22. The apparatus of claim 20 or 21, characterized in that said cooling means comprises several inlet conduits and several outlet conduits.
23. The apparatus of anyone of claims 1 to 22, wherein said emission of microwaves is adapted to said cooling fluid to enable to perform a single about one hour heat session and to prevent burns from occurring on the prostate urethral wall (34).
24. The Apparatus of anyone of claims 1 to 23, wherein said apparatus comprises a central control device determining the power instructions to the microwave generating device, adapted to perform a single about one hour heat session and to prevent said burns from occurring on the prostate urethral wall.

Patentansprüche

1. Vorrichtung zur chirurgischen Behandlung von Prostata-Gewebe mittels Hyperthermie, mit einer Heizsonde bestehend aus einer Mikrowellen emittierenden Harnröhrensonde (20), die zur Einführung in die Harnröhre eingerichtet ist, wobei diese emittierende Sonde (20) ein



vorderes Ende (20a) und ein hinteres Ende hat, und wobei diese emittierende Sonde (20) ein Mikrowellenantennenmittel (18) aufweist, das in der emittierenden Sonde (20) placiert ist und sich zwischen dem vorderen Ende und dem hinteren Ende in der Nähe des vorderen Endes (20a) befindet, und wobei das Mikrowellenantennenmittel (18) in allen Richtungen Mikrowellen emittiert und mit einer äußeren, Mikrowellen erzeugenden Einrichtung (MWG) verbunden ist, die Mittel zur Erzeugung von Mikrowellen mit einer Frequenz und einer Leistung, die zur Hyperthermiebehandlung wirksam ist, aufweist,

dadurch gekennzeichnet, daß die Harnröhrensonde (20) ein einziges Mikrowellenantennenmittel (18) aufweist, welches sich im wesentlichen axial in der emittierenden Harnröhrensonde befindet, wobei um das axiale Mikrowellenantennenmittel (18) herum Kühlmittel (32) in der Harnröhrensonde (20) zum Kühlen der Oberfläche der Harnröhrensonde (20) vorgesehen sind, die dem einzigen Mikrowellenantennenmittel (18) zugewandt ist, wobei das Kühlmittel mit einem Kühlfliuid gespeist wird, und wobei die Mikrowellenemission an das Kühlfliuid adaptiert ist, um ein Auftreten von Verbrennungen an der Harnröhrenwand (34) der Prostata, die mit der Sonde (20) in Kontakt ist, zu verhindern.

2. Vorrichtung nach Anspruch 1, worin das Kühlmittel sich bis zur vollständigen Länge des Mikrowellenantennenmittels (18) erstreckt.
3. Vorrichtung nach Anspruch 1 oder 2, mit einem aufblasbaren Ballonmittel (26) zur Verriegelung der emittierenden Sonde (20) in ihrer Position, und Aufblasmitteln (28, 29, 30) zum Aufblasen des Ballonmittels (26), dadurch gekennzeichnet, daß das aufblasbare Ballonmittel (26) am vorderen Ende (20a) so angeordnet ist, daß es in der Blase (24) placiert ist, wenn das Mikrowellenantennenmittel (18) in der zu behandelnden Prostata (14) placiert ist.
4. Vorrichtung nach Anspruch 3, worin das Aufblasmittel eine Flüssigkeit aufweist.
5. Vorrichtung nach den Ansprüchen 1, 2, 3 oder 4, dadurch gekennzeichnet, daß Temperaturfühlmittel (44) auf oder in der Harnröhrensonde und gegebenenfalls im Ballonmittel (26) vorgesehen sind.
6. Vorrichtung nach einem der Ansprüche 1 bis 5, dadurch gekennzeichnet, daß die Mikrowellen emittierenden Antennenmittel (18) ein von

einer Isolierhülle (54) bedecktes Metallkabel (52) koaxial zur Harnröhrensonde (20) aufweisen, wobei sich der emittierende Teil (52a) auf einem Zwischen- oder distalen Niveau der Harnröhrensonde (20) befindet.

7. Vorrichtung nach einem der Ansprüche 1 bis 6, dadurch gekennzeichnet, daß sie Steuermittel (80) zur Steuerung der Positionierung der Harnröhrensonde (20) aufweist.
8. Vorrichtung nach Anspruch 7, wobei die Steuermittel (80) in einem Rektalsondenmittel (82) inkorporiert sind.
9. Vorrichtung nach Anspruch 7 oder 8, dadurch gekennzeichnet, daß Immobilisierungsmittel (92) zur Immobilisierung des Rektalsondenmittels (82) in axialer Position vorgesehen sind, die jedoch vorzugsweise die Drehung des Rektalsondenmittels (82) um seine Achse zulassen.
10. Vorrichtung nach Anspruch 9, dadurch gekennzeichnet, daß das Immobilisierungsmittel einen Ballon (92), beispielsweise aus Latex, aufweist, welcher das Rektalsondenmittel (82) umgibt und in welchem das Rektalsondenmittel (82) von außen leicht ausrichtbar ist.
11. Vorrichtung nach einem der Ansprüche 7 bis 10, dadurch gekennzeichnet, daß Rektaltemperaturfühlmittel (98) auf oder im Rektalsondenmittel (82) vorgesehen sind.
12. Vorrichtung nach einem der Ansprüche 5 bis 11, dadurch gekennzeichnet, daß das Temperaturfühlmittel (44) ein Lichtleiterthermometer aufweist, welches gegenüber dem Kühlmittel (32) wärmeisoliert ist, welches vorzugsweise mehrere Faserstränge aufweist, die in Längsrichtung der Harnröhrensonde (20) radial und/oder in Längsrichtung versetzt angeordnet sind, um die Temperatur an verschiedenen radialen und/oder Längs-Positionen der Harnröhrensonde (20) zu erfassen.
13. Vorrichtung nach einem der Ansprüche 1 bis 12, dadurch gekennzeichnet, daß Hitzeschutzmittel (22, 90) vorgesehen sind, um die empfindlichen Gewebe, die nicht die zu behandelnden Gewebe (12) sind, vor Hitze zu schützen, wobei Mittel vorgesehen sind, die einen strahlenreflektierenden Schirm (22, 90) bilden.
14. Vorrichtung nach Anspruch 13, dadurch gekennzeichnet, daß die einen strahlenreflektierenden Schirm bildenden Mittel ein strahlenre-



flektierendes flüssiges Medium (23, 94), vorzugsweise mit einer elektrisch leitenden, die Mikrowellen reflektierenden Flüssigkeit, aufweisen.

15. Vorrichtung nach Anspruch 13, dadurch gekennzeichnet, daß die den Schirm bildenden Mittel mindestens einen Draht aufweisen, welcher parallel zum mittleren elektrischen Feld verläuft und vorzugsweise im Rektalsondenmittel (82) inkorporiert ist. 5
16. Vorrichtung nach einem der Ansprüche 11 bis 15, dadurch gekennzeichnet, daß die äußere, Mikrowellen erzeugende Einrichtung (MWG) Mikrowellen mit einer Frequenz von etwa 900 MHz oder 915 MHz bei einer bis zu 100 Watt einstellbaren Leistung erzeugt. 10
17. Vorrichtung nach einem der Ansprüche 7 bis 16, dadurch gekennzeichnet, daß das Steuermittel (80) eine Echographsonde, insbesondere eine Rektalechographsonde, aufweist, die mit einem Echograph (84) verbunden ist, der mit einem Bildschirm ausgerüstet ist. 15
18. Vorrichtung nach einem der Ansprüche 5 bis 17, dadurch gekennzeichnet, daß sie eine zentrale Steuereinrichtung (86) aufweist, die alle Informationen, einschließlich aller in einer Temperaturmeßeinrichtung zentralisierten Temperaturdaten zentralisiert und die Mikrowellen erzeugende Einrichtung (MWG) in Abhängigkeit der aufgezeichneten Temperatur und jeglicher Daten, die vom Arzt programmiert worden sein können, automatisch steuern kann. 20
19. Vorrichtung nach Anspruch 18, dadurch gekennzeichnet, daß die zentrale Steuereinrichtung (86) von der Echographsonde (82) abgegebene Daten hinsichtlich der Position der Harnröhrensonde (20) in bezug auf die Prostata empfängt. 25
20. Vorrichtung nach einem der Ansprüche 1 bis 19, dadurch gekennzeichnet, daß die Kühlmittel mindestens eine Einlaßleitung (236; 336; 436) und mindestens eine Auslaßleitung (238; 338; 438) aufweisen, wobei, die Einlaßleitung und die Auslaßleitung mit einer Kühlflüssigkeit gespeist werden. 30
21. Vorrichtung nach Anspruch 20, worin die Einlaßleitung einen ringförmigen Sektor der Sonde und die Auslaßleitung einen komplementären ringförmigen Sektor einnimmt, wobei beide ringförmigen Sektoren durch in Längsrichtung verlaufende Querunterteilungen (239; 241) von- 35

einander getrennt sind.

22. Vorrichtung nach Anspruch 20 oder 21, dadurch gekennzeichnet, daß das Kühlmittel mehrere Einlaßleitungen und mehrere Auslaßleitungen aufweist. 40
23. Vorrichtung nach einem der Ansprüche 1 bis 22, wobei die Emission der Mikrowellen so an das Kühlfluid angepaßt ist, daß die Durchführung einer einzigen, etwa einstündigen Hitzebehandlung ermöglicht und das Auftreten von Verbrennungen an der Harnröhrenwand (34) der Prostata verhindert wird. 45
24. Vorrichtung nach einem der Ansprüche 1 bis 23, wobei die Vorrichtung eine zentrale Steuereinrichtung aufweist, die die Leistungsinstruktionen an die Mikrowellen erzeugende Einrichtung bestimmt, die zur Durchführung einer einzigen, etwa einstündigen Behandlung und zur Verhinderung des Auftretens von Verbrennungen an der Harnröhrenwand der Prostata ausgelegt ist. 50

Revendications

1. Appareil de traitement chirurgical de tissus prostatiques par hyperthermie, comprenant une sonde de chauffage constituée par une sonde urétrale émettrice de micro-ondes (20), conçue pour être insérée dans l'urètre, ladite sonde émettrice (20) ayant une extrémité frontale (20a) et une extrémité terminale, ladite sonde émettrice (20) comprenant un moyen formant antenne de micro-ondes (18) placé dans ladite sonde émettrice (20) et situé entre ladite extrémité frontale et ladite extrémité terminale à proximité de ladite extrémité frontale (20a), ledit moyen formant antenne de micro-ondes (18) émettant des micro-ondes dans toutes les actions et étant relié à un dispositif externe générateur de micro-ondes (MWG) comprenant un moyen de génération de micro-ondes à une fréquence et une puissance efficaces pour le traitement par hyperthermie, caractérisé en ce que ladite sonde urétrale (20) comprend un unique moyen formant antenne de micro-ondes (18) situé sensiblement axialement dans ladite sonde urétrale émettrice, un moyen de refroidissement (32) étant prévu dans ladite sonde urétrale (20) autour dudit moyen axial formant antenne de micro-ondes (18) pour refroidir la surface de la sonde urétrale (20) faisant face audit moyen unique formant antenne de micro-ondes (18), ledit moyen de refroidissement étant alimenté en fluide de refroidissement, ladite émission de 55



micro-ondes étant adaptée audit fluide de refroidissement pour prévenir la survenue de brûlures sur la paroi urétrale (34) de la prostate en contact avec la sonde (20).

2. Appareil selon la revendication 1, dans lequel ledit moyen de refroidissement s'étend sur toute la longueur du moyen formant antenne de micro-ondes (18). 5
3. Appareil selon la revendication 1 ou 2, comprenant un moyen formant ballonnet gonflable (26) pour bloquer ladite sonde émettrice (20) en position et un moyen de gonflage (28, 29, 30) destiné à gonfler ledit moyen formant ballonnet (26), caractérisé en ce que ledit moyen formant ballonnet gonflable (26) est situé à ladite extrémité frontale (20a) de telle sorte qu'il est placé dans la vessie (24) lorsque le moyen formant antenne de micro-ondes (18) est placé à l'intérieur de ladite prostate (14) à traiter. 10 15 20
4. Appareil selon la revendication 3, dans lequel le moyen de gonflage comprend un liquide. 25
5. Appareil selon les revendications 1, 2, 3 ou 4, caractérisé en ce que des moyens capteurs de la température (44) sont prévus sur ou dans la sonde urétrale et facultativement dans le moyen formant ballonnet (26). 30
6. Appareil selon l'une quelconque des revendications 1 à 5, caractérisé en ce que le moyen formant antenne émettrice de micro-ondes (18) comprend un câble métallique (52) coaxial par rapport à la sonde urétrale (20), couvert d'une gaine isolante (54), la partie émettrice (52a) étant située à un niveau intermédiaire ou distal du moyen formant sonde urétrale (20). 35 40
7. Appareil selon l'une quelconque des revendications 1 à 6, caractérisé en ce qu'il comprend des moyens de commande (80) destinés à commander le positionnement de la sonde urétrale (20). 45
8. Appareil selon la revendication 7, dans lequel le moyen de commande (80) est incorporé dans un moyen formant sonde rectale (82). 50
9. Appareil selon la revendication 7 ou 8, caractérisé en ce qu'un moyen d'immobilisation (92) est prévu pour immobiliser le moyen formant sonde rectale (82) en position axiale, mais permettant de préférence la rotation dudit moyen formant sonde rectale (82) autour de son axe. 55

10. Appareil selon la revendication 9, caractérisé en ce que ledit moyen d'immobilisation comprend un ballon (92), par exemple en latex, entourant le moyen formant sonde rectale (82) et en ce que ledit moyen formant sonde rectale (82) est facilement orientable de l'extérieur.

11. Appareil selon l'une quelconque des revendications 7 à 10, caractérisé en ce qu'un moyen capteur de la température rectale (98) est prévu sur ou dans le moyen formant sonde rectale (82).

12. Appareil selon l'une quelconque des revendications 5 à 11, caractérisé en ce que ledit moyen capteur de la température (44) comprend un thermomètre à fibres optiques thermiquement isolé du moyen de refroidissement (32), comprenant de préférence plusieurs brins de fibres disposés en décalage radial et/ou longitudinal dans la direction longitudinale de la sonde urétrale (20) de façon à détecter la température pour diverses positions radiales et/ou longitudinales de la sonde urétrale (20).

13. Appareil selon l'une quelconque des revendications 1 à 12, caractérisé en ce que des moyens de protection thermique (22, 90) sont prévus pour protéger de la chaleur les tissus sensibles autres que les tissus (12) à traiter, comprenant des moyens formant écran radio-réfléchissant (22, 90).

14. Appareil selon la revendication 13, caractérisé en ce que lesdits moyens formant écran radio-réfléchissant comprennent un milieu liquide radio-réfléchissant (23, 94), comprenant de préférence un liquide électriquement conducteur réfléchissant les micro-ondes.

15. Appareil selon la revendication 13, caractérisé en ce que lesdits moyens formant écran comprennent au moins un fil parallèle au champ électrique moyen et de préférence incorporé dans ledit moyen formant sonde rectale (82).

16. Appareil selon l'une quelconque des revendications 11 à 15, caractérisé en ce que ledit dispositif externe de génération de micro-ondes (MWG) génère des micro-ondes à une fréquence d'environ 900 MHz ou 915 MHz et à une puissance ajustable jusqu'à 100 W.

17. Appareil selon l'une quelconque des revendications 7 à 16, caractérisé en ce que ledit moyen de commande (80) comprend une sonde d'échographie, en particulier une sonde d'échographie rectale, reliée à un échographe



(84) équipé d'un écran.

paroi urétrale de la prostate.

18. Appareil selon l'une quelconque des revendications 5 à 17, caractérisé en ce qu'il comprend un dispositif de commande central (86) centralisant toute l'information, y compris toutes les données de température centralisées dans un dispositif de thermométrie, et capable de commander automatiquement le dispositif générateur de micro-ondes (MWG) en fonction de la température enregistrée et de toute donnée susceptible d'avoir été programmée par l'opérateur. 5 10
19. Appareil selon la revendication 18, caractérisé en ce que le dispositif de commande central (86) reçoit les données émises par la sonde d'échographie (82) concernant la position de la sonde urétrale (20) par rapport à la prostate. 15 20
20. Appareil selon l'une quelconque des revendications 1 à 19, caractérisé en ce que ledit moyen de refroidissement comprend au moins un conduit d'admission (236 ; 336 ; 436) et au moins un conduit de sortie (238 ; 338 ; 438), ledit conduit d'admission et ledit conduit de sortie étant alimentés en liquide de refroidissement. 25
21. Appareil selon la revendication 20, dans lequel ledit conduit d'admission occupe un secteur annulaire de la sonde et ledit conduit de sortie occupe un secteur annulaire complémentaire, les deux secteurs annulaires étant séparés par des cloisons transversales longitudinales (239 ; 241). 30 35
22. Appareil selon la revendication 20 ou 21, caractérisé en ce que ledit moyen de refroidissement comprend plusieurs conduits d'admission et plusieurs conduits de sortie. 40
23. Appareil selon l'une quelconque des revendications 1 à 22, dans lequel ladite émission de micro-ondes est adaptée audit fluide de refroidissement pour permettre la réalisation d'une unique séance de chauffage d'environ 1 h et prévenir la survenue de brûlures sur la paroi urétrale (34) de la prostate 45 50
24. Appareil selon l'une quelconque des revendications 1 à 23, dans lequel ledit appareil comprend un dispositif de commande central déterminant les instructions de puissance destinées au dispositif générateur de micro-ondes, adaptées pour la réalisation d'une unique séance de chauffage d'environ 1 h et pour prévenir la survenue desdites brûlures sur la 55

