



(51) International Patent Classification:
H01L 33/62 (2010.01) *H01L 33/64* (2010.01)

(21) International Application Number:
PCT/US2011/023924

(22) International Filing Date:
7 February 2011 (07.02.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/302,474 8 February 2010 (08.02.2010) US
61/364,567 15 July 2010 (15.07.2010) US
13/019,900 2 February 2011 (02.02.2011) US

(72) Inventor; and

(71) Applicant (for all designated States except US): **LOH, Ban, P** [US/US]; 23 Cape Town Place, San Jose, CA 95133 (US).

(74) Agent: **CHUNG, D., James**; SILICON EDGE LAW GROUP LLP, 100 Corson Street, Ste 200, Pasadena, CA 91103 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: LED LIGHT MODULE




FIG. 1

(57) Abstract: A light emitting module is disclosed. The light emitting module includes a lead frame body, lead frame, a heat spreader, an intermediate heat sink, and at least one light emitting element (LED). The lead frame body defines a cavity which accurately registers the heat spreader and includes optical or reflective walls surrounding the light emitting elements soldered on metallized traces of the heat spreader. The lead frame body encases and supports portions of the lead frame. The lead frame extends from outside the body into the cavity to accurately align with solder pads of the heat spreader. All the pre-aligned mechanical, thermal and electrical contacts are then soldered by solder reflow process under tight environmental control to prevent damage to the light emitting element. A robust, healthy 3 -dimensional optical-electro-mechanical assembly having a very low thermal resistance in a thermal path from its light emitting element to its intermediate heatsink is created.