

METHODS, SYSTEMS, AND MEDIA FOR ANTI-SPOOFING USING EYE-TRACKING**CROSS-REFERENCE**

[0001] This application claims the benefit of U.S. Provisional Application No. 62/948,699, filed December 16, 2019, which is hereby incorporated by reference in its entirety herein.

BACKGROUND

[0002] Many physical locations and document databases employ security measures to prevent access to those without authorization. Such locations may include, for example, schools, universities, laboratories, private businesses, government agencies, or military sites. Such documents may include financial documents, medical documents, military documents, or any other sensitive documents. In some cases, identifying those with authorization to access a location or a data comprises identifying an individual based on their appearance.

[0003] Appearance identification may be performed manually by, for example, a security guard recognizing authorized persons and/or by confirming the appearance of authorized persons with their photographic identification. In these cases, the number of authorized individuals may be dependent upon the security guard's memory, and/or the ease of copying and forging such photographic identification.

[0004] Alternatively, although biometric data acquisition methods, such as three-dimensional (3D) scans, may be used to compare the appearance of an individual to a database of authorized users, such technologies may be prohibitively expensive and time consuming for many applications.

[0005] As a middle ground between photographic identification and 3D scanning, liveness detection or anti-spoofing systems may be employed to: photograph an individual requesting access, determine if the photograph of that individual matches a stored photograph of an authorized person, and further, determine if the photograph captured represents a photo of a live human being, or if the individual is attempting to "spoof" the system.

[0006] "Spoofing" a security system is generally defined as a means of masquerading as an authenticated user by submitting false data. In this case, methods of liveness detection may be employed to measure a biometric modality, such as a face structure, to distinguish the physical presence a three-dimensional live user from a two-dimensional photographic image.

SUMMARY

[0007] One aspect provided herein is a computer-implemented method of determining a spoofing attempt by a user during a request to access a resource via a mobile device having a screen and a front facing camera, the method comprising: receiving a user eye gaze profile

comprising a registration eye gaze image of the user, wherein the registration eye gaze image is associated with a registration display location; displaying an authentication eye gaze icon, wherein the authentication eye gaze icon is displayed in an authentication display location on the screen of the mobile phone; determining that the user's gaze is directed towards the authentication display location of the authentication gaze icon during the display of the authentication eye gaze icon; capturing an authentication eye gaze image of the user, wherein the authentication eye gaze image is captured during the display of the authentication gaze icon; and determining that a spoofing attempt has occurred if the authentication eye gaze image has a similarity below an authentication threshold with the registration eye gaze images associated with the registration display location that is equivalent to the authentication display location of the authentication eye gaze image.

[0008] In some embodiments displaying the authentication eye gaze icon comprises displaying a sequence of two or more authentication eye gaze icons. In some embodiments the sequence of the two or more authentication eye gaze icons is a random sequence. In some embodiments the authentication display location of the sequence of the two or more authentication eye gaze icons is a randomized location. In some embodiments the sequence of two or more authentication eye gaze icons is unknown to the user. In some embodiments the user's gaze is determined to be directed towards the authentication display location by a machine learning algorithm. In some embodiments the authentication display location is at a corner of the screen of the mobile device. In some embodiments the method further comprises displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera. In some embodiments the live video feed is overlaid with an image of a face positioning region. In some embodiments the method further comprises determining that the user's face is at least partially displayed within the face positioning region. In some embodiments the user's eye gaze profile is registered by: displaying a registration eye gaze icon, wherein the registration eye gaze icon is displayed in a different registration display location on the screen of the mobile phone; determining that the user's gaze is directed towards the registration display location of each registration gaze icon during the display of each registration eye gaze icon; capturing the registration eye gaze image of the user, wherein the registration eye gaze image is captured during the display of the registration gaze icon; and creating the user's eye gaze profile comprising the captured registration eye gaze images of the user during the display of the registration gaze icon, wherein each captured registration eye gaze image is associated with the registration display location of the registration gaze icon. In some embodiments displaying the registration eye gaze icon comprises displaying a sequence of two or more registration eye gaze icons. In some embodiments the sequence of the two or more

registration eye gaze icons is a random sequence. In some embodiments the registration display location of the sequence of the two or more registration eye gaze icons is a randomized location. In some embodiments the registration display location is a corner of the screen of the mobile device. In some embodiments the method further comprises displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera. In some embodiments the live video feed is overlaid with an image of a face positioning region. In some embodiments the method further comprises determining that the user's face is at least partially displayed within the face positioning region. In some embodiments the number of registration eye gaze images in the registration eye gaze image is greater than the number of authentication eye gaze images in the series of authentication eye gaze images. In some embodiments the authentication eye gaze icon, the registration eye gaze icon, or both is a geometric shape, an irregular shape, or an image. In some embodiments the authentication eye gaze icon, the registration eye gaze icon, or both is displayed for an icon display period. In some embodiments the icon display period is about 0.01 seconds to about 60 seconds. In some embodiments the authentication eye gaze icon, the registration eye gaze icon, or both comprises an indicator associated with the amount of time remaining in the icon display period, or an amount of time lapsed during the icon display period. In some embodiments the indicator comprises a number of seconds, a dynamic pie chart, a dynamic bar chart, a size of the authentication eye gaze icon, a color of the authentication eye gaze icon, or any combination thereof. In some embodiments the authentication eye gaze icon, the registration eye gaze icon, or both comprise a display of a single eye gaze icon. In some embodiments the authentication eye gaze icon, the registration eye gaze icon, or both is static with respect to the mobile phone. In some embodiments the registration display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device. In some embodiments the authentication display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device. In some embodiments the method further comprises displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon, or both. In some embodiments the method further comprises displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon for the notification period, or both. In some embodiments the method

further comprises terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of at least one registration gaze icon during the display of each registration eye gaze icon, or both. In some embodiments the method further comprises terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of at least one registration eye gaze icon for the termination period, or both. In some embodiments the method further comprises requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile. In some embodiments the method further comprises requesting a registration confirmation by the user before creating the user's eye gaze profile. In some embodiments the method further comprises notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region. In some embodiments the method further comprises notifying the user to gaze at the registration eye gaze icon. In some embodiments the method further comprises displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon, or both. In some embodiments the method further comprises displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon for the notification period, or both. In some embodiments the method further comprises denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of at least one authentication gaze icon during the display of each authentication eye gaze icon, or both. In some embodiments the method further comprises denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of at least one authentication eye gaze icon for the termination period, or both. In some embodiments the method further comprises requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile. In some embodiments the method further

comprises requesting an authentication confirmation by the user before granting access for the user to the resource. In some embodiments the method further comprises notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region. In some embodiments the method further comprises notifying the user to gaze at the authentication eye gaze icon. In some embodiments the method further comprises determining if at least a portion of the user's face is occluded by a mask.

[0009] Another aspect provided herein is a computer-implemented system comprising: a digital processing device comprising: at least one processor, an operating system configured to perform executable instructions, a memory, and a computer program including instructions executable by the digital processing device to create an application to determine a spoofing attempt by a user during a request to access a resource via a mobile device having a screen and a front facing camera, the application comprising: a module receiving a user eye gaze profile comprising a registration eye gaze image of the user, wherein each registration eye gaze image is associated with a registration display location; a module displaying an authentication eye gaze icon, wherein the authentication eye gaze icon is displayed in a different authentication display location on the screen of the mobile phone; a module determining that the user's gaze is directed towards the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon; a module capturing an authentication eye gaze image of the user, wherein the authentication eye gaze image is captured during the display of the authentication gaze icon; and a module determining that a spoofing attempt has occurred if the authentication eye gaze image has a similarity below an authentication threshold with one of the registration eye gaze images associated with the registration display location that is equivalent to the authentication display location of the authentication eye gaze image.

[0010] In some embodiments displaying the authentication eye gaze icon comprises displaying a sequence of two or more authentication eye gaze icons. In some embodiments the sequence of the two or more authentication eye gaze icons is a random sequence. In some embodiments the authentication display location of the sequence of the two or more authentication eye gaze icons is a randomized location. In some embodiments the sequence of two or more authentication eye gaze icons is unknown to the user. In some embodiments the user's gaze is determined to be directed towards the authentication display location by a machine learning algorithm. In some embodiments the authentication display location is at a corner of the screen of the mobile device. In some embodiments the system further comprises a module displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera. In some embodiments the live video feed is overlaid with

an image of a face positioning region. In some embodiments the system further comprises a module determining that the user's face is at least partially displayed within the face positioning region. In some embodiments the user's eye gaze profile is registered by: displaying a registration eye gaze icon, wherein the registration eye gaze icon is displayed in a different registration display location on the screen of the mobile phone; determining that the user's gaze is directed towards the registration display location of each registration gaze icon during the display of each registration eye gaze icon; capturing the registration eye gaze image of the user, wherein the registration eye gaze image is captured during the display of the registration gaze icon; and creating the user's eye gaze profile comprising the captured registration eye gaze images of the user during the display of the registration gaze icon, wherein each captured registration eye gaze image is associated with the registration display location of the registration gaze icon. In some embodiments displaying the registration eye gaze icon comprises displaying a sequence of two or more registration eye gaze icons. In some embodiments the sequence of the two or more registration eye gaze icons is a random sequence. In some embodiments the registration display location of the sequence of the two or more registration eye gaze icons is a randomized location. In some embodiments the registration display location is a corner of the screen of the mobile device. In some embodiments the system further comprises a module displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera. In some embodiments the live video feed is overlaid with an image of a face positioning region. In some embodiments the system further comprises a module determining that the user's face is at least partially displayed within the face positioning region. In some embodiments the number of registration eye gaze images in the registration eye gaze image is greater than the number of authentication eye gaze images in the series of authentication eye gaze images. In some embodiments the authentication eye gaze icon, the registration eye gaze icon, or both is a geometric shape, an irregular shape, or an image. In some embodiments the authentication eye gaze icon, the registration eye gaze icon, or both is displayed for an icon display period. In some embodiments the icon display period is about 0.01 seconds to about 60 seconds. In some embodiments the authentication eye gaze icon, the registration eye gaze icon, or both comprises an indicator associated with the amount of time remaining in the icon display period, or an amount of time lapsed during the icon display period. In some embodiments the indicator comprises a number of seconds, a dynamic pie chart, a dynamic bar chart, a size of the authentication eye gaze icon, a color of the authentication eye gaze icon, or any combination thereof. In some embodiments the authentication eye gaze icon, the registration eye gaze icon, or both comprise a display of a single eye gaze icon. In some embodiments the authentication eye gaze icon, the registration eye gaze icon, or both is static

with respect to the mobile phone. In some embodiments the registration display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device. In some embodiments the authentication display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device. In some embodiments the system further comprises a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon, or both. In some embodiments the system further comprises a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon for the notification period, or both. In some embodiments the system further comprises a module terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of at least one registration gaze icon during the display of each registration eye gaze icon, or both. In some embodiments the system further comprises a module terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of at least one registration eye gaze icon for the termination period, or both. In some embodiments the system further comprises a module requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile. In some embodiments the system further comprises a module requesting a registration confirmation by the user before creating the user's eye gaze profile. In some embodiments the system further comprises a module notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region. In some embodiments the system further comprises a module notifying the user to gaze at the registration eye gaze icon. In some embodiments the system further comprises a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon, or both. In some embodiments the system further comprises a module displaying a notification if at least a majority of the

user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon for the notification period, or both. In some embodiments the system further comprises a module denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of at least one authentication gaze icon during the display of each authentication eye gaze icon, or both. In some embodiments the system further comprises a module denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of at least one authentication eye gaze icon for the termination period, or both. In some embodiments the system further comprises a module requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile. In some embodiments the system further comprises a module requesting an authentication confirmation by the user before granting access for the user to the resource. In some embodiments the system further comprises a module notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region. In some embodiments the system further comprises a module notifying the user to gaze at the authentication eye gaze icon. In some embodiments the system further comprises a module determining if at least a portion of the user's face is occluded by a mask.

[0011] Another aspect provided herein is a non-transitory computer-readable storage media encoded with a computer program including instructions executable by a processor to create an application to determine a spoofing attempt by a user during a request to access a resource via a mobile device having a screen and a front facing camera, the application comprising: a module receiving a user eye gaze profile comprising a registration eye gaze image of the user, wherein each registration eye gaze image is associated with a registration display location; a module displaying an authentication eye gaze icon, wherein the authentication eye gaze icon is displayed in a different authentication display location on the screen of the mobile phone; a module determining that the user's gaze is directed towards the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon; a module capturing an authentication eye gaze image of the user, wherein the authentication eye gaze image is captured during the display of the authentication gaze icon; and a module determining that a spoofing attempt has occurred if the authentication eye gaze image has a similarity below

an authentication threshold with one of the registration eye gaze images associated with the registration display location that is equivalent to the authentication display location of the authentication eye gaze image.

[0012] In some embodiments, displaying the authentication eye gaze icon comprises displaying a sequence of two or more authentication eye gaze icons. In some embodiments, the sequence of the two or more authentication eye gaze icons is a random sequence. In some embodiments, the authentication display location of the sequence of the two or more authentication eye gaze icons is a randomized location. In some embodiments, the sequence of two or more authentication eye gaze icons is unknown to the user. In some embodiments, the user's gaze is determined to be directed towards the authentication display location by a machine learning algorithm. In some embodiments, the authentication display location is at a corner of the screen of the mobile device. In some embodiments the media further comprises a module displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera. In some embodiments, the live video feed is overlaid with an image of a face positioning region. In some embodiments the media further comprises a module determining that the user's face is at least partially displayed within the face positioning region. In some embodiments, the user's eye gaze profile is registered by: displaying a registration eye gaze icon, wherein the registration eye gaze icon is displayed in a different registration display location on the screen of the mobile phone; determining that the user's gaze is directed towards the registration display location of each registration gaze icon during the display of each registration eye gaze icon; capturing the registration eye gaze image of the user, wherein the registration eye gaze image is captured during the display of the registration gaze icon; and creating the user's eye gaze profile comprising the captured registration eye gaze images of the user during the display of the registration gaze icon, wherein each captured registration eye gaze image is associated with the registration display location of the registration gaze icon. In some embodiments, displaying the registration eye gaze icon comprises displaying a sequence of two or more registration eye gaze icons. In some embodiments, the sequence of the two or more registration eye gaze icons is a random sequence. In some embodiments, the registration display location of the sequence of the two or more registration eye gaze icons is a randomized location. In some embodiments, the registration display location is a corner of the screen of the mobile device. In some embodiments the media further comprises a module displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera. In some embodiments, the live video feed is overlaid with an image of a face positioning region. In some embodiments the media further comprises a module determining that the user's face is at least partially displayed

within the face positioning region. In some embodiments, the number of registration eye gaze images in the registration eye gaze image is greater than the number of authentication eye gaze images in the series of authentication eye gaze images. In some embodiments, the authentication eye gaze icon, the registration eye gaze icon, or both is a geometric shape, an irregular shape, or an image. In some embodiments, the authentication eye gaze icon, the registration eye gaze icon, or both is displayed for an icon display period. In some embodiments, the icon display period is about 0.01 seconds to about 60 seconds. In some embodiments, the authentication eye gaze icon, the registration eye gaze icon, or both comprises an indicator associated with the amount of time remaining in the icon display period, or an amount of time lapsed during the icon display period. In some embodiments, the indicator comprises a number of seconds, a dynamic pie chart, a dynamic bar chart, a size of the authentication eye gaze icon, a color of the authentication eye gaze icon, or any combination thereof. In some embodiments, the authentication eye gaze icon, the registration eye gaze icon, or both comprise a display of a single eye gaze icon. In some embodiments, the authentication eye gaze icon, the registration eye gaze icon, or both is static with respect to the mobile phone. In some embodiments, the registration display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device. In some embodiments, the authentication display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device. In some embodiments the media further comprises a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon, or both. In some embodiments the media further comprises a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon for the notification period, or both. In some embodiments the media further comprises a module terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of at least one registration gaze icon during the display of each registration eye gaze icon, or both. In some embodiments the media further comprises a module terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the registration display location

of each registration gaze icon during the display of at least one registration eye gaze icon for the termination period, or both. In some embodiments the media further comprises a module requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile. In some embodiments the media further comprises a module requesting a registration confirmation by the user before creating the user's eye gaze profile. In some embodiments the media further comprises a module notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region. In some embodiments the media further comprises a module notifying the user to gaze at the registration eye gaze icon. In some embodiments the media further comprises a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon, or both. In some embodiments the media further comprises a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon for the notification period, or both. In some embodiments the media further comprises a module denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of at least one authentication gaze icon during the display of each authentication eye gaze icon, or both. In some embodiments the media further comprises a module denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of at least one authentication eye gaze icon for the termination period, or both. In some embodiments the media further comprises a module requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile. In some embodiments the media further comprises a module requesting an authentication confirmation by the user before granting access for the user to the resource. In some embodiments the media further comprises a module notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region. In some embodiments the media further comprises a module notifying the user to gaze at the authentication eye gaze icon. In some embodiments the media

further comprises a module determining if at least a portion of the user's face is occluded by a mask.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] The novel features of the disclosure are set forth with particularity in the appended claims. A better understanding of the features and advantages of the present disclosure will be obtained by reference to the following detailed description that sets forth illustrative embodiments, in which the principles of the disclosure are utilized, and the accompanying drawings of which:

[0014] **FIG. 1** shows a non-limiting illustration of a live video feed, per an embodiment herein;

[0015] **FIG. 2** shows a non-limiting illustration of a registration eye gaze icon, per an embodiment herein;

[0016] **FIG. 3** shows a non-limiting illustration of an authentication eye gaze icon, per an embodiment herein;

[0017] **FIG. 4** shows a non-limiting image of a live video feed, per an embodiment herein;

[0018] **FIG. 5** shows a non-limiting image of an eye gaze icon, per an embodiment herein;

[0019] **FIG. 6** shows a non-limiting image of a notification, per an embodiment herein;

[0020] **FIG. 7** shows a non-limiting example of an interface to create a user eye gaze profile, per an embodiment herein;

[0021] **FIG. 8** shows a non-limiting example of an interface to access a user eye gaze profile, per an embodiment herein;

[0022] **FIG. 9** shows a non-limiting example of an interface to access a plurality of user eye gaze profiles, per an embodiment herein;

[0023] **FIG. 10** shows a non-limiting example of an interface to select an anti-spoofing method, per an embodiment herein;

[0024] **FIG. 11** shows a non-limiting example of a computing device; in this case, a device with one or more processors, memory, storage, and a network interface, per an embodiment herein;

[0025] **FIG. 12** shows a non-limiting example of a web/mobile application provision system; in this case, a system providing browser-based and/or native mobile user interfaces, per an embodiment herein;

[0026] **FIG. 13** shows a non-limiting example of a cloud-based web/mobile application provision system; in this case, a system comprising an elastically load balanced, auto-scaling web server and application server resources as well synchronously replicated databases, per an embodiment herein;

[0027] **FIG. 14** shows an exemplary diagram of the parts of a human eye; and

[0028] **FIG. 15A** shows an exemplary diagram of a human eye gazing at a registration gaze icon or authentication eye gaze icon displayed at a top-left position on the user's mobile device, per an embodiment herein;

[0029] **FIG. 15B** shows an exemplary diagram of a human eye gazing at a registration gaze icon or authentication eye gaze icon displayed at a top-right position on the user's mobile device, per an embodiment herein;

[0030] **FIG. 15C** shows an exemplary diagram of a human eye gazing at a registration gaze icon or authentication eye gaze icon displayed at a bottom-left position on the user's mobile device, per an embodiment herein; and

[0031] **FIG. 15D** shows an exemplary diagram of a human eye gazing at a registration gaze icon or authentication eye gaze icon displayed at a bottom-right position on the user's mobile device, per an embodiment herein.

DETAILED DESCRIPTION

Determining a Spoofing Attempt

[0032] Provided herein is a computer-implemented method of determining a spoofing attempt by a user during a request to access a resource via a mobile device having a screen and a front facing camera. Also provided herein is a computer-implemented system comprising: a digital processing device comprising: at least one processor, an operating system configured to perform executable instructions, a memory, and a computer program including instructions executable by the digital processing device to create an application to determine a spoofing attempt by a user during a request to access a resource via a mobile device having a screen and a front facing camera. Additionally, provided herein is a non-transitory computer-readable storage media encoded with a computer program including instructions executable by a processor to create an application to determine a spoofing attempt by a user during a request to access a resource via a mobile device having a screen and a front facing camera.

[0033] In some embodiments, the method comprises: receiving a user eye gaze profile; displaying an authentication eye gaze icon; determining that the user's gaze is directed towards the authentication display location of the authentication gaze icon during the display of the authentication eye gaze icon; capturing an authentication eye gaze image of the user; and determining that a spoofing attempt has occurred if the authentication eye gaze image has a similarity below an authentication threshold with a registration eye gaze image associated with the registration display location that is equivalent to the authentication display location of the authentication eye gaze image. In some embodiments, the method further comprises displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live

video feed captured by the front facing camera. In some embodiments, the live video feed is overlaid with an image of a face positioning region. In some embodiments, the method further comprises determining that the user's face is at least partially displayed within the face positioning region.

[0034] In some embodiments, the application comprises: a module receiving a user eye gaze profile; a module displaying an authentication eye gaze icon; a module determining that the user's gaze is directed towards the authentication display location of the authentication gaze icon during the display of the authentication eye gaze icon; a module capturing an authentication eye gaze image of the user; and a module determining that a spoofing attempt has occurred if the authentication eye gaze image has a similarity below an authentication threshold with the registration eye gaze image associated with the registration display location that is equivalent to the authentication display location of the authentication eye gaze image. In some embodiments, the application further comprises a module displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera. In some embodiments, the live video feed is overlaid with an image of a face positioning region. In some embodiments, the application further comprises a module determining that the user's face is at least partially displayed within the face positioning region.

[0035] In some embodiments, displaying the authentication eye gaze icon comprises displaying a sequence of two or more authentication eye gaze icons. In some embodiments, the sequence of two or more authentication eye gaze icons is a random sequence. In some embodiments, the sequence of two or more authentication eye gaze icons is not a predetermined sequence. In some embodiments, the sequence of two or more authentication eye gaze icons is unknown to the user. In some embodiments, the sequence of two or more authentication eye gaze icons does not represent a password. In some embodiments, the user is not prompted to memorize the sequence of two or more authentication eye gaze icons. In some embodiments, displaying the authentication eye gaze icon comprises displaying a sequence of two or more authentication eye gaze icons.

[0036] In some embodiments, each of the sequence of authentication eye gaze icons is displayed on the screen of the mobile device for a display period. In some embodiments, two or more of the authentication eye gaze icons are displayed on the screen of the mobile device for an equivalent display period. In some embodiments, two or more of the authentication eye gaze icons are displayed on the screen of the mobile device for different display periods. In some embodiments, the different display periods are randomized. In some embodiments, the different display periods are not known to the user. In some embodiments, the display period is about 0.1, 0.5, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more seconds, including increments therein. In some

embodiments, a size, a shape, a rotation or any combination thereof of the sequence of authentication eye gaze icons is random. In some embodiments, a size, a shape, a rotation or any combination thereof of the sequence of authentication eye gaze icons is not known to the user.

[0037] In some embodiments, the authentication eye gaze image is captured during the display of the authentication gaze icon. In some embodiments, each of the sequences of authentication eye gaze images is captured during the display of one of the sequence of authentication gaze icons. In some embodiments, the authentication eye gaze icon comprises a display of a single eye gaze icon. In some embodiments, each of the authentication eye gaze icon in the sequence of authentication eye gaze icons comprises a display of a first single eye gaze icon over a first period of time and a second single eye gaze icon over a period of time subsequent to the first period of time. In some embodiments, each of the sequence of authentication eye gaze icons does not comprise a display of two or more discrete and simultaneous eye gaze icons. In some embodiments, the authentication eye gaze icon is static with respect to the mobile phone. In some embodiments, the authentication eye gaze icon is dynamic with respect to the mobile phone, wherein the authentication display location is the location of the authentication eye gaze icon when a respective authentication eye gaze image is captured. In some embodiments, the authentication eye gaze icon is not dynamic with respect to the mobile phone.

[0038] In some embodiments, the eye gaze image is captured during the display of the authentication gaze icon. In some embodiments, a sequence of authentication eye gaze images are captured during the display of the sequence of authentication gaze icons. In some embodiments, only one of the series of authentication eye gaze images is captured during the display of the authentication gaze icon. In some embodiments, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more of the series of authentication eye gaze images is captured during the display of the authentication gaze icon. In some embodiments, the mobile device captures a video of the user, wherein the video comprises the series of authentication eye gaze images. In some embodiments, the mobile device captures a video of the user, wherein the series of authentication eye gaze images are selected and/or culled from the video. In some embodiments, the series of authentication eye gaze images are individually captured. In some embodiments, the series of authentication eye gaze images comprises 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more images. In some embodiments, each eye gaze image in the series of authentication eye gaze images of the user comprises a single image captured only during the display of one eye gaze icon. In some embodiments, each eye gaze image in the series of authentication eye gaze images of the user comprises two or more image captured only during the display of one eye gaze icon. In some embodiments, the user eye gaze profile comprises a registration eye gaze image of the user. In some embodiments, reducing the number of gaze images in the series of gaze images

reduces a size of the user's eye gaze profile, and the amount of memory required to store the user's eye gaze profile.

[0039] In some embodiments, the method employs a delay period between the capture of an authentication eye gaze image and a subsequent authentication eye gaze image. In some embodiments, the delay period occurs during a transition between the sequential display of authentication icons. In some embodiments, one or more authentication eye gaze images are captured throughout a time period of the display of one the of sequence of authentication gaze icons. In some embodiments, one or more authentication eye gaze images are captured during at most a portion of the time period of the display of one the of sequence of authentication gaze icons. In some embodiments, no authentication eye gaze image is captured during at least a portion time that of one of the of sequence of authentication gaze icons is displayed. In some embodiments, no authentication eye gaze image is captured during at least an initial portion time that of one of the of sequence of authentication gaze icons is displayed. In some embodiments, no authentication eye gaze image is captured during at least a terminal portion time that of one of the of sequence of authentication gaze icons is displayed. In some embodiments, an authentication eye gaze image is not captured during at least a portion time that of one of the of sequence of authentication gaze icons is displayed. In some embodiments, an authentication eye gaze image is not captured during at least an initial portion time that of one of the of sequence of authentication gaze icons is displayed. In some embodiments, an authentication eye gaze image is not captured during at least a terminal portion time that of one of the of sequence of authentication gaze icons is displayed.

[0040] In some embodiments, the authentication eye gaze image is captured with a flash and/or light being emitted from the mobile device. In some embodiments, the authentication eye gaze image is captured without a flash and/or light being emitted from the mobile device. In some embodiments, each of the series of authentication eye gaze images is captured with a flash and/or light being emitted from the mobile device. In some embodiments, at least a portion of the series of authentication eye gaze images is captured with a flash and/or light being emitted from the mobile device. In some embodiments, each of the series of authentication eye gaze images is captured without a flash and/or light being emitted from the mobile device. In some embodiments, at least a portion of the series of authentication eye gaze images is captured without a flash and/or light being emitted from the mobile device. In some embodiments, the capture of at least a portion of the series of authentication eye gaze images is captured without a flash and/or light being emitted from the mobile device improves the user experience by eliminating or reducing sudden and/or shocking effects.

[0041] In some embodiments, the authentication eye gaze icon is displayed in an authentication display location on the screen of the mobile phone. In some embodiments, each of the sequence of authentication eye gaze icons is displayed in a different authentication display location on the screen of the mobile phone. In some embodiments, the authentication eye gaze image is associated with an authentication display location. In some embodiments, the authentication display location of one authentication eye gaze icon is random with respect to the authentication display location of another authentication eye gaze icon. In some embodiments, the sequence of the authentication display locations is not known to the user.

[0042] In some embodiments, the authentication eye gaze icon is located nearest a corner, an edge, or a center of the screen of the mobile device. In some embodiments, a position of the authentication eye gaze icon near a corner of the screen of the mobile device is within about 5%, 10%, 15 %, 20%, or 25% of the width of the screen of the mobile device, or increments therein, from a right or left edge of the screen of the mobile device. In some embodiments, a position of the authentication eye gaze icon near a corner of the screen of the mobile device is within about 5%, 10%, 15 %, 20%, or 25% of the length of the screen of the mobile device, or increments therein, from a top or bottom edge of the screen of the mobile device. In some embodiments, a position of the authentication eye gaze icon near a corner of the screen of the mobile device improves the accuracy, the precision, repeatability or any combination thereof of the determination that the user's gaze is directed towards the authentication display location. In some embodiments, a position of the authentication eye gaze icon near a corner of the screen of the mobile device's screen maximizes the movement distance of the user's eye. In some embodiments, such maximum movement improves accuracy, precision, and repeatability of user gaze determination with difference camera hardware/resolution, screen sizes/resolution, or both.

[0043] In some embodiments, each authentication display location comprises only one distinct location. In some embodiments, each authentication display location comprises two or more distinct locations. In some embodiments, the authentication display location comprises an authentication display path.

[0044] In some embodiments, the determination that the user's gaze is directed towards the authentication display location is based on a position of the user's eye. In some embodiments, the determination that the user's gaze is directed towards the authentication display location is based on a path of the user's eye. In some embodiments, the determination that the user's gaze is directed towards the authentication display location is based only on a position of the user's eye with respect to the mobile device. In some embodiments, the determination that the user's gaze is directed towards the authentication display location is not based on a relative position and/or orientation between the user's head and the mobile device. In some embodiments, the

determination that the user's gaze is directed towards the authentication display location based only on a relative position and/or orientation between the user's eye and the mobile device.

[0045] In some embodiments, the live video feed comprises a live video feed captured by the front facing camera. In some embodiments, the live video feed is overlaid with an image of a face positioning region. In some embodiments, the live video feed is not overlaid with an image of a face positioning region. In some embodiments, the method further comprises determining that the user's face is at least partially displayed within the face positioning region. In some embodiments, the application further comprises a module determining that the user's face is at least partially displayed within the face positioning region. In some embodiments, the methods and/or applications herein do not comprise capturing and/or displaying a live video feed.

[0046] In some embodiments, the method further comprises capturing a biometric authentication parameter of the user. In some embodiments, the method further comprises comparing the biometric authentication parameter with the biometric registration parameter in the user's eye gaze profile. In some embodiments, the method further comprises determining that a spoofing event has occurred if the biometric authentication parameter and the biometric registration parameter differ by a set value. In some embodiments, the application further comprises a module capturing a biometric authentication parameter of the user. In some embodiments, the application further comprises a module comparing the biometric authentication parameter with the biometric registration parameter in the user's eye gaze profile. In some embodiments, the application further comprises a module determining that a spoofing event has occurred if the biometric authentication parameter and the biometric registration parameter differ by a set value. In some embodiments, the biometric authentication parameter of the user is captured during the display authentication gaze icon, the capture authentication eye gaze image, or both. In some embodiments, the specific authentication gaze icon of the sequence of authentication gaze icons in which the biometric authentication parameter is captured is random. In some embodiments, the specific authentication eye gaze image of the sequence of authentication eye gaze images in which the biometric authentication parameter is captured is random. In some embodiments, the method further comprises determining that the user is a human based on the captured the biometric authentication parameter.

[0047] In some embodiments, the biometric authentication parameter comprises a facial landmark, or features, a distance between two or more facial landmarks, a size of a facial landmark, a shape of a facial landmark, a geometric biometric authentication parameter, a photometric biometric authentication parameter, or any combination thereof. In some embodiments, capturing the biometric authentication parameter of the user, comparing the biometric authentication parameter with the biometric registration parameter, or both comprises a holistic

facial recognition mode, a feature-based facial recognition model, or both. In some embodiments, capturing the biometric authentication parameter of the user, comparing the biometric authentication parameter with the biometric registration parameter, or both employs eigenfaces, linear discriminant analysis, an elastic bunch graph, the Fisherface algorithm, the hidden Markov model, a multilinear subspace learning model, or any combination thereof.

[0048] In some embodiments, the methods, systems, and media herein determine if at least a portion of the user's face is occluded by a mask. In some embodiments, such a determination prevents spoofing by a high definition mask formed by an image of the user's face.

Registering a User's Eye Gaze Profile

[0049] In some embodiments, the user's eye gaze profile is registered by: displaying a registration eye gaze icon, wherein the registration eye gaze icon is displayed in a registration display location on the screen of the mobile phone; determining that the user's gaze is directed towards the registration display location of the registration gaze icon during the display of the registration eye gaze icon; capturing the registration eye gaze image of the user, wherein the registration eye gaze image is captured during the display of the registration gaze icon; and creating the user's eye gaze profile comprising the captured registration eye gaze image of the user during the display of the registration gaze icon, wherein the captured registration eye gaze image is associated with the registration display location of the registration gaze icon. In some embodiments, the user eye gaze profile comprises a registration eye gaze image of the user

[0050] In some embodiments, the user's eye gaze profile is registered by an application comprising: a module displaying a registration eye gaze icon, wherein the registration eye gaze icon is displayed in a registration display location on the screen of the mobile phone; a module determining that the user's gaze is directed towards the registration display location of the registration gaze icon during the display of the registration eye gaze icon; a module capturing the registration eye gaze image of the user, wherein the registration eye gaze image is captured during the display of the registration gaze icon; and a module creating the user's eye gaze profile comprising the captured registration eye gaze image of the user during the display of the registration gaze icon, wherein the captured registration eye gaze image is associated with the registration display location of the registration gaze icon. In some embodiments, the user eye gaze profile comprises a registration eye gaze image of the user

[0051] In some embodiments, displaying the registration eye gaze icon comprises displaying a sequence of two or more registration eye gaze icons. In some embodiments, the sequence of two or more registration eye gaze icons is a random sequence. In some embodiments, the sequence of two or more registration eye gaze icons is not a predetermined sequence. In some

embodiments, the sequence of two or more registration eye gaze icons is unknown to the user. In some embodiments, the sequence of two or more registration eye gaze icons does not represent a password. In some embodiments, the user is not prompted to memorize the sequence of two or more registration eye gaze icons. In some embodiments, displaying the registration eye gaze icon comprises displaying a sequence of two or more registration eye gaze icons.

[0052] In some embodiments, each of the sequence of registration eye gaze icons is displayed on the screen of the mobile device for a display period. In some embodiments, two or more of the registration eye gaze icons are displayed on the screen of the mobile device for an equivalent display period. In some embodiments, two or more of the registration eye gaze icons are displayed on the screen of the mobile device for different display periods. In some embodiments, the different display periods are randomized. In some embodiments, the different display periods are not known to the user. In some embodiments, the display period is about 0.1, 0.5, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more seconds, including increments therein. In some embodiments, a size, a shape, a rotation or any combination thereof of the sequence of registration eye gaze icons is random. In some embodiments, a size, a shape, a rotation or any combination thereof of the sequence of registration eye gaze icons is not known to the user.

[0053] In some embodiments, the registration eye gaze image is captured during the display of the registration gaze icon. In some embodiments, each of the sequence of registration eye gaze images is captured during the display of one of the sequence of registration gaze icons. In some embodiments, the registration eye gaze icon comprises a display of a single eye gaze icon. In some embodiments, each of the registration eye gaze icon in the sequence of registration eye gaze icons comprises a display of a first single eye gaze icon over a first period of time and a second single eye gaze icon over a period of time subsequent to the first period of time. In some embodiments, each of the sequence of registration eye gaze icons does not comprise a display of two or more discrete and simultaneous eye gaze icons. In some embodiments, the registration eye gaze icon is static with respect to the mobile phone. In some embodiments, the registration eye gaze icon is dynamic with respect to the mobile phone, wherein the registration display location is the location of the registration eye gaze icon when a respective registration eye gaze image is captured. In some embodiments, the registration eye gaze icon is not dynamic with respect to the mobile phone.

[0054] In some embodiments, the eye gaze image is captured during the display of the registration gaze icon. In some embodiments, a sequence of registration eye gaze images are captured during the display of the sequence of registration gaze icons. In some embodiments, only one of the series of registration eye gaze images is captured during the display of the registration gaze icon. In some embodiments, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more of the series of

registration eye gaze images is captured during the display of the registration gaze icon. In some embodiments, the mobile device captures a video of the user, wherein the video comprises the series of registration eye gaze images. In some embodiments, the mobile device captures a video of the user, wherein the series of registration eye gaze images are selected and/or culled from the video. In some embodiments, the series of registration eye gaze images are individually captured. In some embodiments, the series of registration eye gaze images comprises 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more images. In some embodiments, each eye gaze image in the series of registration eye gaze images of the user comprises a single image captured only during the display of one eye gaze icon. In some embodiments, each eye gaze image in the series of registration eye gaze images of the user comprises two or more image captured only during the display of one eye gaze icon. In some embodiments, reducing the number of gaze images in the series of gaze images reduces a size of the user's eye gaze profile, and the amount of memory required to store the user's eye gaze profile.

[0055] In some embodiments, the method employs a delay period between the capture of a registration eye gaze image and a subsequent registration eye gaze image. In some embodiments, the delay period occurs during a transition between the sequential display of registration icons. In some embodiments, one or more registration eye gaze images are captured throughout a time period of the display of one the of sequence of registration gaze icons. In some embodiments, one or more registration eye gaze images are captured during at most a portion of the time period of the display of one the of sequence of registration gaze icons. In some embodiments, no registration eye gaze image is captured during at least a portion time that of one of the of sequence of registration gaze icons is displayed. In some embodiments, no registration eye gaze image is captured during at least an initial portion time that of one of the of sequence of registration gaze icons is displayed. In some embodiments, no registration eye gaze image is captured during at least a terminal portion time that of one of the of sequence of registration gaze icons is displayed. In some embodiments, a registration eye gaze image is not captured during at least a portion time that of one of the of sequence of registration gaze icons is displayed. In some embodiments, a registration eye gaze image is not captured during at least an initial portion time that of one of the of sequence of registration gaze icons is displayed. In some embodiments, a registration eye gaze image is not captured during at least a terminal portion time that of one of the of sequence of registration gaze icons is displayed.

[0056] In some embodiments, the registration eye gaze image is captured with a flash and/or light being emitted from the mobile device. In some embodiments, the registration eye gaze image is captured without a flash and/or light being emitted from the mobile device. In some embodiments, each of the series of registration eye gaze images is captured with a flash and/or

light being emitted from the mobile device. In some embodiments, at least a portion of the series of registration eye gaze images is captured with a flash and/or light being emitted from the mobile device. In some embodiments, each of the series of registration eye gaze images is captured without a flash and/or light being emitted from the mobile device. In some embodiments, at least a portion of the series of registration eye gaze images is captured without a flash and/or light being emitted from the mobile device. In some embodiments, the capture of at least a portion of the series of registration eye gaze images is captured without a flash and/or light being emitted from the mobile device improves the user experience by eliminating or reducing sudden and/or shocking effects.

[0057] In some embodiments, the registration eye gaze icon is displayed in a registration display location on the screen of the mobile phone. In some embodiments, each of the sequence of registration eye gaze icons is displayed in a different registration display location on the screen of the mobile phone. In some embodiments, the registration eye gaze image is associated with a registration display location. In some embodiments, the registration display location of one registration eye gaze icon is random with respect to the registration display location of another registration eye gaze icon. In some embodiments, the sequence of the registration display locations is not known to the user.

[0058] In some embodiments, the registration eye gaze icon is located nearest a corner, an edge, or a center of the screen of the mobile device. In some embodiments, a position of the registration eye gaze icon near a corner of the screen of the mobile device is within about 5%, 10%, 15 %, 20%, or 25% of the width of the screen of the mobile device, or increments therein, from a right or left edge of the screen of the mobile device. In some embodiments, a position of the registration eye gaze icon near a corner of the screen of the mobile device is within about 5%, 10%, 15 %, 20%, or 25% of the length of the screen of the mobile device, or increments therein, from a top or bottom edge of the screen of the mobile device. In some embodiments, a position of the registration eye gaze icon near a corner of the screen of the mobile device improves the accuracy, the precision, repeatability or any combination thereof of the determination that the user's gaze is directed towards the registration display location. In some embodiments, a position of the registration eye gaze icon near a corner of the screen of the mobile device's screen maximizes the movement distance of the user's eye. In some embodiments, such maximum movement improves accuracy, precision, and repeatability of user gaze determination with difference camera hardware/resolution, screen sizes/resolution, or both.

[0059] In some embodiments, each registration display location comprises only one distinct location. In some embodiments, each registration display location comprises two or more

distinct locations. In some embodiments, the registration display location comprises a registration display path.

[0060] In some embodiments, the determination that the user's gaze is directed towards the registration display location is based on a position of the user's eye. In some embodiments, the determination that the user's gaze is directed towards the registration display location is based on a path of the user's eye. In some embodiments, the determination that the user's gaze is directed towards the registration display location is based only on a position of the user's eye with respect to the mobile device. In some embodiments, the determination that the user's gaze is directed towards the registration display location is not based on a relative position and/or orientation between the user's head and the mobile device. In some embodiments, the determination that the user's gaze is directed towards the registration display location based only on a relative position and/or orientation between the user's eye and the mobile device.

[0061] In some embodiments, the live video feed comprises a live video feed captured by the front facing camera. In some embodiments, the live video feed is overlaid with an image of a face positioning region. In some embodiments, the live video feed is not overlaid with an image of a face positioning region. In some embodiments, the method further comprises determining that the user's face is at least partially displayed within the face positioning region. In some embodiments, the application further comprises a module determining that the user's face is at least partially displayed within the face positioning region. In some embodiments, the methods and/or applications herein do not comprise capturing and/or displaying a live video feed.

[0062] In some embodiments, the method further comprises capturing a biometric registration parameter of the user. In some embodiments, the biometric registration parameter of the user is captured during the display registration gaze icon, the capture registration eye gaze image, or both. In some embodiments, the specific registration gaze icon of the sequence of registration gaze icons in which the biometric registration parameter is captured is random. In some embodiments, the specific registration eye gaze image of the sequence of registration eye gaze images in which the biometric registration parameter is captured is random. In some embodiments, the method further comprises determining that the user is a human based on the captured the biometric registration parameter.

[0063] In some embodiments, the biometric registration parameter comprises a facial landmark, or features, a distance between two or more facial landmarks, a size of a facial landmark, a shape of a facial landmark, a geometric biometric registration parameter, a photo-metric biometric registration parameter, or any combination thereof. In some embodiments, capturing the biometric registration parameter of the user comprises a holistic facial recognition mode, a feature-based facial recognition model, or both. In some embodiments, capturing the biometric

registration parameter of the user employs eigenfaces, linear discriminant analysis, an elastic bunch graph, the Fisherface algorithm, the hidden Markov model, a multilinear subspace learning model, or any combination thereof.

Determination User's Gaze is Directed Towards the Registration or Authentication Display Location

[0064] FIG. 14 shows an exemplary diagram of the parts of a human eye. As shown, the human eye comprises a cornea 1410, a pupil 1420, an iris 1430, a lens 1440, a vitreous 1450, a retina 1460, and a macula 1470. Further, when a light is directed at the human eye, a corneal reflection 1411 appears.

[0065] In some embodiments, determining that the user's gaze is directed towards the registration or authentication display location comprises directing a light at the user's eye, capturing an image of the user's eye, measuring a gaze vector 1510 from the center of the user's pupil 1420 to the center of the corneal reflection 1411 from the image of the user's eye, and determining that the user's gaze is directed towards the registration or authentication display location based on the gaze vector 1510. In some embodiments, determining that the user's gaze is directed towards the registration or authentication display location based on the gaze vector 1510 comprises determining that the registration or authentication display location with respect to the mobile device is in an opposite direction as the gaze vector 1510. In some embodiments, the light is an infrared light.

[0066] FIGS. 15A-15D, show exemplary gaze vectors 1510. Per FIG. 15A a gaze vector 1510 pointing to the bottom right of the user's eye indicates that the user is looking at the top left of the mobile device. If the registration or authentication display location is located at a top left of the mobile device during the capture of the image shown therein, a determination is reached that that the user's gaze is directed towards the registration or authentication display location. If the registration or authentication display location is not located at a top left of the mobile device during the capture of the image shown therein, a determination is reached that that the user's gaze is not directed towards the registration or authentication display location.

[0067] Per FIG. 15B a gaze vector 1510 pointing to the bottom left of the user's eye indicates that the user is looking at the top right of the mobile device. If the registration or authentication display location is located at a top right of the mobile device during the capture of the image shown therein, a determination is reached that that the user's gaze is directed towards the registration or authentication display location. If the registration or authentication display location is not located at a top right of the mobile device during the capture of the image shown

therein, a determination is reached that that the user's gaze is not directed towards the registration or authentication display location.

[0068] Per **FIG. 15C** a gaze vector **1510** pointing to the top right of the user's eye indicates that the user is looking at the bottom left of the mobile device. If the registration or authentication display location is located at a bottom left of the mobile device during the capture of the image shown therein, a determination is reached that that the user's gaze is directed towards the registration or authentication display location. If the registration or authentication display location is not located at a bottom left of the mobile device during the capture of the image shown therein, a determination is reached that that the user's gaze is not directed towards the registration or authentication display location.

[0069] Per **FIG. 15D** a gaze vector **1510** pointing to the top left of the user's eye indicates that the user is looking at the bottom right of the mobile device. If the registration or authentication display location is located at a bottom right of the mobile device during the capture of the image shown therein, a determination is reached that that the user's gaze is directed towards the registration or authentication display location. If the registration or authentication display location is not located at a bottom right of the mobile device during the capture of the image shown therein, a determination is reached that that the user's gaze is not directed towards the registration or authentication display location.

[0070] In some embodiments, the user's gaze is determined to be directed towards the registration or authentication display location independently of a position of the user's head with respect to the mobile device. In some embodiments, the user's gaze is determined to be directed towards the registration or authentication display location independently of a movement of the user's head with respect to the mobile device.

[0071] In some embodiments, the user's gaze is determined to be directed towards the registration or authentication display location by a machine learning algorithm. In some embodiments, the machine learning algorithm is applied to the authentication eye gaze image to determine the user's gaze. In some embodiments, the authentication eye gaze image is a single image. In some embodiments, the authentication eye gaze image comprises a plurality of images. In some embodiments, the plurality of images is a video. In some embodiments, the video is captured of the user in a static pose. In some embodiments, the video is captured of the user in a dynamic pose. In some embodiments, the user's gaze is determined by the machine learning algorithm based on a sequential order of the plurality of images. In some embodiments, the user's gaze is determined by the machine learning algorithm based on a random order of the plurality of images.

[0072] In some embodiments, the machine learning algorithm employs one or more forms of labels including but not limited to human annotated labels and semi-supervised labels. The human annotated labels can be provided by a hand-crafted heuristic. For example, the hand-crafted heuristic can comprise predetermined gaze locations. The semi-supervised labels can be determined using a clustering technique to find properties similar to those flagged by previous human annotated labels and previous semi-supervised labels. The semi-supervised labels can employ a XGBoost, a neural network, or both.

[0073] In some embodiments, machine learning algorithms determine a probability that the user's gaze is determined to be directed towards the registration or authentication display location. In some embodiments, the machine learning algorithms herein employ a distant supervision method. The distant supervision method can create a large training set seeded by a small hand-annotated training set. The distant supervision method can comprise positive-unlabeled learning with the training set as the 'positive' class. The distant supervision method can employ a logistic regression model, a recurrent neural network, or both. The recurrent neural network can be advantageous for Natural Language Processing (NLP) machine learning. Examples of machine learning algorithms can include a support vector machine (SVM), a naïve Bayes classification, a random forest, a neural network, deep learning, or other supervised learning algorithm or unsupervised learning algorithm for classification and regression.

[0074] The machine learning algorithms can be trained using one or more training datasets. In some embodiments, the machine learning algorithm is trained with a single training eye gaze image per user. In some embodiments, the machine learning algorithm is trained with a plurality of images per user. In some embodiments, the plurality of images is a video. In some embodiments, the video is captured of the user in a static pose. In some embodiments, the video is captured of the user in a dynamic pose. In some embodiments, the video is captured of the user in a specific pose. In some embodiments, two or more of the training eye gaze images are captured of users having different facial features (i.e. facial hair, hair style). In some embodiments, two or more of the training eye gaze images are captured of users having different genders, ethnicities, ages, or any combination thereof. In some embodiments, two or more of the training eye gaze images are captured of users by different camera hardware. In some embodiments, at least one of the training eye gaze images is augmented from another training eye gaze image by translation, rotation, skewing, or any combination thereof. In some embodiments, the machine learning algorithm is trained with the plurality of training images in a sequential order. In some embodiments, the machine learning algorithm is trained with the plurality of training images in a random order.

[0075] In some embodiments, the machine learning algorithm utilizes regression modeling, wherein relationships between predictor variables and dependent variables are determined and weighted. In one embodiment, for example, the eye gaze vector can be a dependent variable and is derived from the brightness of the pixels in the image of the user's eye. In some embodiments, a machine learning algorithm is used to select catalogue images and recommend project scope. A non-limiting example of a multi-variate linear regression model algorithm is seen below:

$$\text{probability} = A_0 + A_1(X_1) + A_2(X_2) + A_3(X_3) + A_4(X_4) + A_5(X_5) + A_6(X_6) + A_7(X_7) \dots$$
 wherein A_i ($A_1, A_2, A_3, A_4, A_5, A_6, A_7, \dots$) are "weights" or coefficients found during the regression modeling; and X_i ($X_1, X_2, X_3, X_4, X_5, X_6, X_7, \dots$) are data collected from the User. Any number of A_i and X_i variable can be included in the model. In some embodiments, the programming language "R" is used to run the model.

[0076] In some embodiments, training comprises multiple steps. In a first step, an initial model is constructed by assigning probability weights to predictor variables. In a second step, the initial model is used to "recommend" a probability that the user's gaze is determined to be directed towards the registration or authentication display location. In a third step, the validation module accepts verified data regarding the user's gaze location and feeds back the verified data. At least one of the first step, the second step, and the third step can repeat one or more times continuously or at set intervals.

[0077] In some embodiments, the machine learning algorithms herein are further configured to determine a type of spoofing attempt. In some embodiments, the spoofing attempt is a spoofing attempt by printout, a digital spoofing attempt, or both. In some embodiments, the machine learning algorithms are taught by a model training process for improved robustness. In some embodiments, the machine learning algorithms herein extract image features at multiple levels directly from data to capture essential characteristics of gaze more accurately and thoroughly.

[0078] User Eye Gaze Profile

[0079] In some embodiments, a user registers an eye gaze profile and authenticates that they are a registered user during the authentication and/or determination of the spoofing event. In some embodiments, the user's eye gaze profile grants them access to one or more resources and/or one or more locations. In some embodiments, the user's eye gaze profile grants them access to one or more resources and/or one or more locations while preventing access to one or more other resources and/or one or more locations.

[0080] In some embodiments, registration comprises requesting and associating a user name, an identification parameter, or both with the user's eye gaze profile. In some embodiments, the user confirms their registration before an eye gaze profile is created.

[0081] FIG. 7 shows a non-limiting example of an interface to create the user eye gaze profile. In some embodiments, a user can access their user eye gaze profile, edit their user eye gaze profile, reprogram their user eye gaze profile, or any combination thereof. FIG. 8 shows a non-limiting example of an interface to access a user eye gaze profile. FIG. 9 shows a non-limiting example of an interface to access a plurality of user eye gaze profiles. In some embodiments, a user can edit their eye gaze profile by selecting an anti-spoofing method. FIG. 10 shows a non-limiting example of an interface to select an anti-spoofing method.

Authentication Threshold

[0082] In some embodiments, a spoofing attempt is detected if the authentication eye gaze image has a similarity below an authentication threshold with one of the registration eye gaze images associated with the registration display location that is equivalent to the authentication display location of the authentication eye gaze image. In some embodiments, a spoofing attempt is detected if the biometric registration parameter stored in the user's eye gaze profile differs from the biometric authentication parameter by a biometric authentication threshold.

[0083] In some embodiments, the similarity is determined by: applying a facial recognition algorithm to each authentication eye gaze image; determining a recognized gaze location for each authentication eye gaze image based on the output of the facial recognition algorithm; and comparing the recognized gaze location to the authentication display location of the authentication eye gaze image. In some embodiments, similarity corresponds to a distance between the recognized gaze location to the authentication display location of the authentication eye gaze image. In some embodiments, a greater distance between the recognized gaze location to the authentication display location of the authentication eye gaze image correlates with a lower similarity.

[0084] In some embodiments, the similarity is determined by comparing the registration eye gaze image of the user gazing at a user registration gaze icon in a first registration display location with the authentication eye gaze image of the user gazing at a user authentication gaze icon in the same first registration display location. In some embodiments, a greater difference between the registration eye gaze image of the user gazing at a user registration gaze icon in a first registration display location with the authentication eye gaze image of the user gazing at a user authentication gaze icon in the same first registration display location correlates to a lower similarity.

[0085] In some embodiments, the facial recognition algorithm determines a facial landmark, or feature, a distance between two or more facial landmarks, a size of a facial landmark, a shape of a facial landmark, a geometric biometric authentication parameter, a photo-metric biometric

authentication parameter, or any combination thereof. In some embodiments, the facial recognition algorithm comprises a holistic facial recognition mode, a feature-based facial recognition model, or both. In some embodiments, the facial recognition algorithm employs eigenfaces, linear discriminant analysis, an elastic bunch graph, the Fisherface algorithm, the hidden Markov model, a multilinear subspace learning model, or any combination thereof.

Live Video Feed

[0086] FIG. 1 shows a non-limiting illustration of a live video feed. In some embodiments, the live video feed **100** is displayed on a screen **120** of a mobile device. In some embodiments, live video feed **100** comprises an image captured by a front facing camera of a mobile device. In some embodiments, the live video feed **100** comprises the live video feed captured by the front facing camera of the mobile device. In some embodiments, the live video feed **100** comprises the live video feed captured by the front facing camera of the mobile device that is overlaid with an image of a face positioning region **110**. In some embodiments, the live video feed **100** enables the user to maintain a set position of their face with respect to the mobile device. In some embodiments, the live video feed **100** enables the user to maintain a set position of their face with respect to the mobile device such that the registration and/or authentication eye gaze images capture at least a majority of the face of the user. In some embodiments, the live video feed **100** enables the user to maintain a set position of their face with respect to the mobile device such that the series of registration eye gaze images are captured with the same orientation of the user's face with respect to the front facing camera of the mobile device. In some embodiments, the live video feed **100** does not obscure the face of the user. In some embodiments, the live video feed **100** does not obscure a majority of the face of the user. In some embodiments, the live video feed **100** is shown concurrently with the registration and/or authentication gaze icons. In some embodiments, the live video feed **100** is not shown concurrently with the registration and/or authentication gaze icons. In some embodiments, the face positioning region **110** is located in the live video feed **100** such that entire face of the user is captured by the front facing camera and displayed in the live video feed **110**. In some embodiments, the face positioning region **110** is located in the center of the screen of the mobile phone.

[0087] FIG. 3 shows a non-limiting live video feed. As shown, in some embodiments, the user positions their face within the face positioning region of the live video feed. Further as shown, in some embodiments, a notification is displayed to the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region.

Registration and Authentication Eye Gaze Icons

[0088] FIGS. 2-3 shows a non-limiting illustration of eye gaze icons **210** **310**. In some embodiments, registration of the user's eye gaze profile employs a registration eye gaze icon **210**. In some embodiments, authentication and/or determination of a spoofing attempt employs an authentication eye gaze icon **310**. In some embodiments, the registration eye gaze icon **210** and the authentication eye gaze icon **310** have the same shape. In some embodiments, the registration eye gaze icon **210** and the authentication eye gaze icon **310** have different shapes. In some embodiments, the registration eye gaze icon **210** and the authentication eye gaze icon **310** are shown in the same location with respect to the screen **120** of the mobile phone. In some embodiments, the registration eye gaze icon **210** and the authentication eye gaze icon **310** are shown in different locations with respect to the screen **120** of the mobile phone. In some embodiments, only one registration eye gaze icon **210** is shown at a time. In some embodiments, only one authentication eye gaze icon **310** is shown at a time.

[0089] As shown, the registration eye gaze icon **210** and the authentication eye gaze icon **310** comprise a circle. In some embodiments, at least one of the registration eye gaze icon **210** and the authentication eye gaze icon **310** is a geometric shape, an irregular shape, or an image.

[0090] In some embodiments, at least one the registration eye gaze icon **210** and the authentication eye gaze icon **310** comprises an indicator associated with the amount of time remaining in the icon display period, or an amount of time lapsed during the icon display period. In some embodiments, the indicator comprises a number of seconds, a dynamic pie chart, a dynamic bar chart, a size of the registration eye gaze icon **210** or the authentication eye gaze icon **310**, a color of the registration eye gaze icon **210** or the authentication eye gaze icon **310**, a pulse rate of the registration eye gaze icon **210** or the authentication eye gaze icon **310** or any combination thereof.

[0091] In some embodiments, a notification is displayed to the user to gaze at the registration eye gaze icon **210**. In some embodiments, a notification is displayed to the user to gaze at the authentication eye gaze icon **310**. In some embodiments, a notification is displayed to the user to gaze at the registration eye gaze icon **210** at two or more speeds, paths, distances, or any combination thereof. In some embodiments, a notification is displayed to the user to gaze at the authentication eye gaze icon **310** at two or more speeds, paths, distances, or any combination thereof.

[0092] In some embodiments, the number of registration icons **210** in the sequence of registration icons **210** is greater than the number of authentication icons **310** in the series of authentication icons **310**. In some embodiments, the number of registration icons **210** in the

sequence of registration icons **210** is greater than the number of authentication icons **310** in the series of authentication icons **310** by 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more.

[0093] As shown in **FIG. 3** the current registration display location of the registration icon **210** is at the top-left corner of the top-right corner, whereas a previous or subsequent registration display locations of the registration icon **210** (shown in dotted lines) are located at the top-right corner, bottom-right corner, or bottom-left corner of the screen. As shown in **FIG. 3** the current authentication display location of the authentication icon **310** is at the top-left corner of the top-right corner, whereas a previous or subsequent registration display location of the authentication icon **310** (shown in dotted lines) is located at the bottom-right corner of the screen of the mobile device.

[0094] In some embodiments, a number of registration display locations of the registration icon **210** is equal to a number of authentication display locations of the authentication icon **310**. In some embodiments, a number of registration display locations of the registration icon **210** is greater or less than the number of authentication display locations of the authentication icon **310**. In some embodiments, a number of registration display locations of the registration icon **210** is greater or less than the number of authentication display locations of the authentication icon **310** by 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more.

[0095] In some embodiments, the number of authentication icons **310** in the sequence of authentication icons **310** is equal to the number of authentication display locations of the authentication icon **310**. In some embodiments, the number of authentication icons **310** in the sequence of authentication icons **310** is greater or less than the number of authentication display locations of the authentication icon **310**. In some embodiments, the number of authentication icons **310** in the sequence of authentication icons **310** is greater or less than the number of authentication display locations of the authentication icon **310** by 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more.

[0096] In some embodiments, the number of registration icon **210** locations is greater than the number of authentication icon **310** locations. In some embodiments, the number of registration icon **210** locations is greater than the number of authentication icon **310** locations by 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more.

[0097] In some embodiments, the sequence of the two or more registration eye gaze icons **210** is a random sequence. In some embodiments, the registration display location of the sequence of the two or more registration eye gaze icons **210** is a randomized location. In some embodiments, the sequence of the two or more authentication eye gaze icons **310** is a random sequence. In some embodiments, the authentication display location of the sequence of the two or more authentication eye gaze icons **310** is a randomized location.

[0098] In some embodiments, each registration eye gaze icon **210** in the sequence of the two or more registration eye gaze icons **210** is the same registration eye gaze icon **210**, having the same size, shape, color, appearance, or any combination thereof. In some embodiments, each registration eye gaze icon **210** in the sequence of the two or more registration eye gaze icons **210** is a same registration eye gaze icon **210**, having a different size, shape, color, appearance, or any combination thereof. In some embodiments, each authentication eye gaze icon **310** in the sequence of the two or more authentication eye gaze icons **310** is the same authentication eye gaze icon **310**, having the same size, shape, color, appearance, or any combination thereof. In some embodiments, each authentication eye gaze icon **310** in the sequence of the two or more authentication eye gaze icons **310** is a same authentication eye gaze icon **310**, having a different size, shape, color, appearance, or any combination thereof.

[0099] In some embodiments, at least one of the registration eye gaze icon **210A** and the authentication eye gaze icon **210B** is displayed for an icon display period. In some embodiments, each registration eye gaze icon **210A** in the sequence of two or more registration eye gaze icons is displayed for an icon display period. In some embodiments, at least one registration eye gaze icon **210A** is displayed for a first registration icon display period, wherein at least one other registration eye gaze icon **210A** is displayed for a second registration icon display period. In some embodiments, the first registration icon display period is equal to or greater than the second registration icon display period. In some embodiments, the first registration icon display period is equal to or less than the second registration icon display period. In some embodiments, the first registration icon display period is greater than the second registration icon display period by 0.1 seconds, 0.5 seconds, 1 second, .3 seconds, 4 seconds, 5 seconds, or more, including increments therein. In some embodiments, the first registration icon display period is less than the second registration icon display period by 0.1 seconds, 0.5 seconds, 1 second, .3 seconds, 4 seconds, 5 seconds, or more, including increments therein. In some embodiments, at least one authentication eye gaze icon **210B** is displayed for a first authentication icon display period, wherein at least one other authentication eye gaze icon **210B** is displayed for a second authentication icon display period. In some embodiments, the first authentication icon display period is equal to or greater than the second authentication icon display period. In some embodiments, the first authentication icon display period is equal to or less than the second authentication icon display period. In some embodiments, the first authentication icon display period is greater than the second authentication icon display period by 0.1 seconds, 0.5 seconds, 1 second, .3 seconds, 4 seconds, 5 seconds, or more, including increments therein. In some embodiments, the first authentication icon display period is less than

the second authentication icon display period by 0.1 seconds, 0.5 seconds, 1 second, 3 seconds, 4 seconds, 5 seconds, or more, including increments therein.

[0100] In some embodiments, the icon display period is about 0.01 seconds to about 60 seconds. In some embodiments, at least one of the registration eye gaze icon **210A** and the authentication eye gaze icon **210B** is displayed for an icon display period. In some embodiments, the icon display period is about 0.01 seconds to about 0.05 seconds, about 0.01 seconds to about 0.1 seconds, about 0.01 seconds to about 0.5 seconds, about 0.01 seconds to about 1 second, about 0.01 seconds to about 5 seconds, about 0.01 seconds to about 10 seconds, about 0.01 seconds to about 20 seconds, about 0.01 seconds to about 30 seconds, about 0.01 seconds to about 40 seconds, about 0.01 seconds to about 50 seconds, about 0.01 seconds to about 60 seconds, about 0.05 seconds to about 0.1 seconds, about 0.05 seconds to about 0.5 seconds, about 0.05 seconds to about 1 second, about 0.05 seconds to about 5 seconds, about 0.05 seconds to about 10 seconds, about 0.05 seconds to about 20 seconds, about 0.05 seconds to about 30 seconds, about 0.05 seconds to about 40 seconds, about 0.05 seconds to about 50 seconds, about 0.05 seconds to about 60 seconds, about 0.1 seconds to about 0.5 seconds, about 0.1 seconds to about 1 second, about 0.1 seconds to about 5 seconds, about 0.1 seconds to about 10 seconds, about 0.1 seconds to about 20 seconds, about 0.1 seconds to about 30 seconds, about 0.1 seconds to about 40 seconds, about 0.1 seconds to about 50 seconds, about 0.1 seconds to about 60 seconds, about 0.5 seconds to about 1 second, about 0.5 seconds to about 5 seconds, about 0.5 seconds to about 10 seconds, about 0.5 seconds to about 20 seconds, about 0.5 seconds to about 30 seconds, about 0.5 seconds to about 40 seconds, about 0.5 seconds to about 50 seconds, about 0.5 seconds to about 60 seconds, about 1 second to about 5 seconds, about 1 second to about 10 seconds, about 1 second to about 20 seconds, about 1 second to about 30 seconds, about 1 second to about 40 seconds, about 1 second to about 50 seconds, about 1 second to about 60 seconds, about 5 seconds to about 10 seconds, about 5 seconds to about 20 seconds, about 5 seconds to about 30 seconds, about 5 seconds to about 40 seconds, about 5 seconds to about 50 seconds, about 5 seconds to about 60 seconds, about 10 seconds to about 20 seconds, about 10 seconds to about 30 seconds, about 10 seconds to about 40 seconds, about 10 seconds to about 50 seconds, about 10 seconds to about 60 seconds, about 20 seconds to about 30 seconds, about 20 seconds to about 40 seconds, about 20 seconds to about 50 seconds, about 20 seconds to about 60 seconds, about 30 seconds to about 40 seconds, about 30 seconds to about 50 seconds, about 30 seconds to about 60 seconds, about 40 seconds to about 50 seconds, about 40 seconds to about 60 seconds, or about 50 seconds to about 60 seconds. In some embodiments, at least one of the registration eye gaze icon **210A** and the authentication eye gaze icon **210B** is displayed for an icon display period. In some embodiments, the icon display period is about 0.01 seconds, about

0.05 seconds, about 0.1 seconds, about 0.5 seconds, about 1 second, about 5 seconds, about 10 seconds, about 20 seconds, about 30 seconds, about 40 seconds, about 50 seconds, or about 60 seconds, including increments therein. In some embodiments, at least one of the registration eye gaze icon **210A** and the authentication eye gaze icon **210B** is displayed for an icon display period. In some embodiments, the icon display period is at least about 0.01 seconds, about 0.05 seconds, about 0.1 seconds, about 0.5 seconds, about 1 second, about 5 seconds, about 10 seconds, about 20 seconds, about 30 seconds, about 40 seconds, or about 50 seconds. In some embodiments, at least one of the registration eye gaze icon **210A** and the authentication eye gaze icon **210B** is displayed for an icon display period. In some embodiments, the icon display period is at most about 0.05 seconds, about 0.1 seconds, about 0.5 seconds, about 1 second, about 5 seconds, about 10 seconds, about 20 seconds, about 30 seconds, about 40 seconds, about 50 seconds, or about 60 seconds. **FIG. 4** shows a non-limiting image of an eye gaze icon.

Registration and Authentication Notifications

[0101] In some embodiments, the methods and applications herein further initiate a notification if at least a majority of the user's face is displayed outside the face positioning region. In some embodiments, the methods and applications herein further initiate a notification if at least a portion of the user's face is displayed outside the face positioning region. In some embodiments, the methods and applications herein further initiate a notification if 1%, 2%, 3%, 4%, 5%, 6%, 7%, 8%, 9%, 10%, 15%, 20%, 25%, or more of the user's face is displayed outside the face positioning region, including increments therein. In some embodiments, the notification is a visual notification, an auditory notification, a vibration notification, or any combination thereof.

[0102] Such a notification ensures that the user maintains a set position of their face with respect to the mobile device so that the series of registration eye gaze images are captured with the same orientation of the user's face with respect to the front facing camera of the mobile device. In some embodiments, ensuring that the user maintains a set position of their face with respect to the mobile device prevents misuse of the user registration such that user authentication can be spoofed.

[0103] In some embodiments, the methods and applications herein further initiate a notification if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon.

[0104] In some embodiments, determining the user's gaze location comprises applying a facial recognition algorithm to each registration eye gaze image; determining a recognized gaze location for each registration eye gaze image based on the output of the facial recognition algorithm; and determining if a distance between the recognized gaze location and the display

location of the registration eye gaze icon is greater than a threshold distance. In some embodiments, the threshold distance is equal to 5%, 10%, 15%, 20%, or more of the width, height, or both of the registration eye gaze icon, including increments therein. In some embodiments, the threshold distance is equal to 5%, 10%, 15%, 20%, or more of the width, height, or both of the screen of the mobile phone, including increments therein.

[0105] In some embodiments, the methods and applications herein further initiate a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period. In some embodiments, the methods and applications herein further initiate a notification if at least a portion of the user's face is displayed outside the face positioning region for the notification period. In some embodiments, the methods and applications herein further initiate a notification if 1%, 2%, 3%, 4%, 5%, 6%, 7%, 8%, 9%, 10%, 15%, 20%, 25%, or more of the user's face is displayed outside the face positioning region, including increments therein, for the notification period.

[0106] In some embodiments, the notification period is about 0.01 seconds to about 60 seconds. In some embodiments, the notification period is about 0.01 seconds to about 0.05 seconds, about 0.01 seconds to about 0.1 seconds, about 0.01 seconds to about 0.5 seconds, about 0.01 seconds to about 1 second, about 0.01 seconds to about 5 seconds, about 0.01 seconds to about 10 seconds, about 0.01 seconds to about 20 seconds, about 0.01 seconds to about 30 seconds, about 0.01 seconds to about 40 seconds, about 0.01 seconds to about 50 seconds, about 0.01 seconds to about 60 seconds, about 0.05 seconds to about 0.1 seconds, about 0.05 seconds to about 0.5 seconds, about 0.05 seconds to about 1 second, about 0.05 seconds to about 5 seconds, about 0.05 seconds to about 10 seconds, about 0.05 seconds to about 20 seconds, about 0.05 seconds to about 30 seconds, about 0.05 seconds to about 40 seconds, about 0.05 seconds to about 50 seconds, about 0.05 seconds to about 60 seconds, about 0.1 seconds to about 0.5 seconds, about 0.1 seconds to about 1 second, about 0.1 seconds to about 5 seconds, about 0.1 seconds to about 10 seconds, about 0.1 seconds to about 20 seconds, about 0.1 seconds to about 30 seconds, about 0.1 seconds to about 40 seconds, about 0.1 seconds to about 50 seconds, about 0.1 seconds to about 60 seconds, about 0.5 seconds to about 1 second, about 0.5 seconds to about 5 seconds, about 0.5 seconds to about 10 seconds, about 0.5 seconds to about 20 seconds, about 0.5 seconds to about 30 seconds, about 0.5 seconds to about 40 seconds, about 0.5 seconds to about 50 seconds, about 0.5 seconds to about 60 seconds, about 1 second to about 5 seconds, about 1 second to about 10 seconds, about 1 second to about 20 seconds, about 1 second to about 30 seconds, about 1 second to about 40 seconds, about 1 second to about 50 seconds, about 1 second to about 60 seconds, about 5 seconds to about 10 seconds, about 5 seconds to about 20 seconds, about 5 seconds to about 30 seconds, about 5 seconds to about 40 seconds, about 5

seconds to about 50 seconds, about 5 seconds to about 60 seconds, about 10 seconds to about 20 seconds, about 10 seconds to about 30 seconds, about 10 seconds to about 40 seconds, about 10 seconds to about 50 seconds, about 10 seconds to about 60 seconds, about 20 seconds to about 30 seconds, about 20 seconds to about 40 seconds, about 20 seconds to about 50 seconds, about 20 seconds to about 60 seconds, about 30 seconds to about 40 seconds, about 30 seconds to about 50 seconds, about 30 seconds to about 60 seconds, about 40 seconds to about 50 seconds, about 40 seconds to about 60 seconds, or about 50 seconds to about 60 seconds. In some embodiments, the notification period is about 0.01 seconds, about 0.05 seconds, about 0.1 seconds, about 0.5 seconds, about 1 second, about 5 seconds, about 10 seconds, about 20 seconds, about 30 seconds, about 40 seconds, about 50 seconds, or about 60 seconds, including increments therein. In some embodiments, the notification period is at least about 0.01 seconds, about 0.05 seconds, about 0.1 seconds, about 0.5 seconds, about 1 second, about 5 seconds, about 10 seconds, about 20 seconds, about 30 seconds, about 40 seconds, or about 50 seconds, including increments therein. In some embodiments, the notification period is at most about 0.05 seconds, about 0.1 seconds, about 0.5 seconds, about 1 second, about 5 seconds, about 10 seconds, about 20 seconds, about 30 seconds, about 40 seconds, about 50 seconds, or about 60 seconds, including increments therein. **FIG. 6** shows a non-limiting image of a notification. In some embodiments, the methods and applications herein further request a registration confirmation by the user before creating the user's eye gaze profile. In some embodiments, the methods and applications herein further request an authentication confirmation by the user before granting access for the user to the resource. In some embodiments, the methods and applications herein further initiate a notification if the registration is not accepted or terminated. In some embodiments, the methods and applications herein further initiate a notification if the authentication attempt is not accepted or terminated.

Registration and Authentication Termination

[0107] In some embodiments, the methods and applications herein further terminate the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region. In some embodiments, the methods and applications herein further terminate the registration of the user's eye gaze profile if at least a portion of the user's face is displayed outside the face positioning region. In some embodiments, the methods and applications herein further terminate the registration of the user's eye gaze profile if 1%, 2%, 3%, 4%, 5%, 6%, 7%, 8%, 9%, 10%, 15%, 20%, 25%, or more of the user's face is displayed outside the face positioning region, including increments therein.

[0108] Such a termination ensures that the user maintains a set position of their face with respect to the mobile device so that the series of registration eye gaze images are captured with the same orientation of the user's face with respect to the front facing camera of the mobile device. In some embodiments, ensuring that the user maintains a set position of their face with respect to the mobile device prevents misuse of the user registration such that user authentication can be spoofed.

[0109] In some embodiments, the methods and applications herein further terminate the registration of the user's eye gaze profile if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon.

[0110] In some embodiments, determining the user's gaze location comprises applying a facial recognition algorithm to each registration eye gaze image; determining a recognized gaze location for each registration eye gaze image based on the output of the facial recognition algorithm; and determining if a distance between the recognized gaze location and the display location of the registration eye gaze icon is greater than a threshold distance. In some embodiments, the threshold distance is equal to 5%, 10%, 15%, 20%, or more of the width, height, or both of the registration eye gaze icon, including increments therein. In some embodiments, the threshold distance is equal to 5%, 10%, 15%, 20%, or more of the width, height, or both of the screen of the mobile phone, including increments therein.

[0111] In some embodiments, the methods and applications herein further terminate the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region for a termination period. In some embodiments, the methods and applications herein further terminate the registration of the user's eye gaze profile if at least a portion of the user's face is displayed outside the face positioning region for the termination period. In some embodiments, the methods and applications herein further terminate the registration of the user's eye gaze profile if 1%, 2%, 3%, 4%, 5%, 6%, 7%, 8%, 9%, 10%, 15%, 20%, 25%, or more of the user's face is displayed outside the face positioning region, including increments therein, for the termination period.

[0112] In some embodiments, the methods and applications herein further deny the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region. In some embodiments, the methods and applications herein further deny the request to access the resource if at least a portion of the user's face is displayed outside the face positioning region. In some embodiments, the methods and applications herein further deny the request to access the resource if 1%, 2%, 3%, 4%, 5%, 6%, 7%, 8%, 9%, 10%, 15%, 20%, 25%,

or more of the user's face is displayed outside the face positioning region, including increments therein.

[0113] Such a termination ensures that the user maintains a set position of their face with respect to the mobile device so that the series of authentication eye gaze images are captured with the same orientation of the user's face with respect to the front facing camera of the mobile device. In some embodiments, ensuring that the user maintains a set position of their face with respect to the mobile device prevents misuse or spoofing of the user authentication.

[0114] In some embodiments, the methods and applications herein further deny the request to access the resource if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon.

[0115] In some embodiments, determining the user's gaze location comprises applying a facial recognition algorithm to each authentication eye gaze image; determining a recognized gaze location for each authentication eye gaze image based on the output of the facial recognition algorithm; and determining if a distance between the recognized gaze location and the display location of the authentication eye gaze icon is greater than a threshold distance. In some embodiments, the threshold distance is equal to 5%, 10%, 15%, 20%, or more of the width, height, or both of the authentication eye gaze icon, including increments therein. In some embodiments, the threshold distance is equal to 5%, 10%, 15%, 20%, or more of the width, height, or both of the screen of the mobile phone, including increments therein.

[0116] In some embodiments, the methods and applications herein further deny the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region for a termination period. In some embodiments, the methods and applications herein further deny the request to access the resource if at least a portion of the user's face is displayed outside the face positioning region for the termination period. In some embodiments, the methods and applications herein further deny the request to access the resource if 1%, 2%, 3%, 4%, 5%, 6%, 7%, 8%, 9%, 10%, 15%, 20%, 25%, or more of the user's face is displayed outside the face positioning region, including increments therein, for the termination period.

[0117] In some embodiments, the termination period is about 0.01 seconds to about 60 seconds. In some embodiments, the termination period is about 0.01 seconds to about 0.05 seconds, about 0.01 seconds to about 0.1 seconds, about 0.01 seconds to about 0.5 seconds, about 0.01 seconds to about 1 second, about 0.01 seconds to about 5 seconds, about 0.01 seconds to about 10 seconds, about 0.01 seconds to about 20 seconds, about 0.01 seconds to about 30 seconds, about 0.01 seconds to about 40 seconds, about 0.01 seconds to about 50 seconds, about 0.01 seconds to about 60 seconds, about 0.05 seconds to about 0.1 seconds, about 0.05 seconds to about 0.5

seconds, about 0.05 seconds to about 1 second, about 0.05 seconds to about 5 seconds, about 0.05 seconds to about 10 seconds, about 0.05 seconds to about 20 seconds, about 0.05 seconds to about 30 seconds, about 0.05 seconds to about 40 seconds, about 0.05 seconds to about 50 seconds, about 0.05 seconds to about 60 seconds, about 0.1 seconds to about 0.5 seconds, about 0.1 seconds to about 1 second, about 0.1 seconds to about 5 seconds, about 0.1 seconds to about 10 seconds, about 0.1 seconds to about 20 seconds, about 0.1 seconds to about 30 seconds, about 0.1 seconds to about 40 seconds, about 0.1 seconds to about 50 seconds, about 0.1 seconds to about 60 seconds, about 0.5 seconds to about 1 second, about 0.5 seconds to about 5 seconds, about 0.5 seconds to about 10 seconds, about 0.5 seconds to about 20 seconds, about 0.5 seconds to about 30 seconds, about 0.5 seconds to about 40 seconds, about 0.5 seconds to about 50 seconds, about 0.5 seconds to about 60 seconds, about 1 second to about 5 seconds, about 1 second to about 10 seconds, about 1 second to about 20 seconds, about 1 second to about 30 seconds, about 1 second to about 40 seconds, about 1 second to about 50 seconds, about 1 second to about 60 seconds, about 5 seconds to about 10 seconds, about 5 seconds to about 20 seconds, about 5 seconds to about 30 seconds, about 5 seconds to about 40 seconds, about 5 seconds to about 50 seconds, about 5 seconds to about 60 seconds, about 10 seconds to about 20 seconds, about 10 seconds to about 30 seconds, about 10 seconds to about 40 seconds, about 10 seconds to about 50 seconds, about 10 seconds to about 60 seconds, about 20 seconds to about 30 seconds, about 20 seconds to about 40 seconds, about 20 seconds to about 50 seconds, about 20 seconds to about 60 seconds, about 30 seconds to about 40 seconds, about 30 seconds to about 50 seconds, about 30 seconds to about 60 seconds, about 40 seconds to about 50 seconds, about 40 seconds to about 60 seconds, or about 50 seconds to about 60 seconds. In some embodiments, the termination period is about 0.01 seconds, about 0.05 seconds, about 0.1 seconds, about 0.5 seconds, about 1 second, about 5 seconds, about 10 seconds, about 20 seconds, about 30 seconds, about 40 seconds, about 50 seconds, or about 60 seconds, including increments therein. In some embodiments, the termination period is at least about 0.01 seconds, about 0.05 seconds, about 0.1 seconds, about 0.5 seconds, about 1 second, about 5 seconds, about 10 seconds, about 20 seconds, about 30 seconds, about 40 seconds, or about 50 seconds, including increments therein. In some embodiments, the termination period is at most about 0.05 seconds, about 0.1 seconds, about 0.5 seconds, about 1 second, about 5 seconds, about 10 seconds, about 20 seconds, about 30 seconds, about 40 seconds, about 50 seconds, or about 60 seconds, including increments therein.

Terms and Definitions

[0118] Unless otherwise defined, all technical terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs.

[0119] As used herein, the singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise. Any reference to “or” herein is intended to encompass “and/or” unless otherwise stated.

[0120] As used herein, the term “about” in some cases refers to an amount that is approximately the stated amount.

[0121] As used herein, the term “about” refers to an amount that is near the stated amount by 10%, 5%, or 1%, including increments therein.

[0122] As used herein, the term “about” in reference to a percentage refers to an amount that is greater or less the stated percentage by 10%, 5%, or 1%, including increments therein.

[0123] As used herein, the phrases “at least one”, “one or more”, and “and/or” are open-ended expressions that are both conjunctive and disjunctive in operation. For example, each of the expressions “at least one of A, B and C”, “at least one of A, B, or C”, “one or more of A, B, and C”, “one or more of A, B, or C” and “A, B, and/or C” means A alone, B alone, C alone, A and B together, A and C together, B and C together, or A, B and C together.

[0124] Computing system

[0125] Referring to **FIG. 11**, a block diagram is shown depicting an exemplary machine that includes a computer system **1100** (e.g., a processing or computing system) within which a set of instructions can execute for causing a device to perform or execute any one or more of the aspects and/or methodologies for static code scheduling of the present disclosure. The components in **FIG. 11** are examples only and do not limit the scope of use or functionality of any hardware, software, embedded logic component, or a combination of two or more such components implementing particular embodiments.

[0126] Computer system **1100** may include one or more processors **1101**, a memory **1103**, and a storage **1108** that communicate with each other, and with other components, via a bus **1140**. The bus **1140** may also link a display **1132**, one or more input devices **1133** (which may, for example, include a keypad, a keyboard, a mouse, a stylus, etc.), one or more output devices **1134**, one or more storage devices **1135**, and various tangible storage media **1136**. All of these elements may interface directly or via one or more interfaces or adaptors to the bus **1140**. For instance, the various tangible storage media **1136** can interface with the bus **1140** via storage medium interface **1126**. Computer system **1100** may have any suitable physical form, including but not limited to one or more integrated circuits (ICs), printed circuit boards (PCBs), mobile

handheld devices (such as mobile telephones or PDAs), laptop or notebook computers, distributed computer systems, computing grids, or servers.

[0127] Computer system **1100** includes one or more processor(s) **1101** (e.g., central processing units (CPUs) or general purpose graphics processing units (GPGPUs)) that carry out functions. Processor(s) **1101** optionally contains a cache memory unit **1102** for temporary local storage of instructions, data, or computer addresses. Processor(s) **1101** are configured to assist in execution of computer readable instructions. Computer system **1100** may provide functionality for the components depicted in **FIG. 11** as a result of the processor(s) **1101** executing non-transitory, processor-executable instructions embodied in one or more tangible computer-readable storage media, such as memory **1103**, storage **1108**, storage devices **1135**, and/or storage medium **1136**. The computer-readable media may store software that implements particular embodiments, and processor(s) **1101** may execute the software. Memory **1103** may read the software from one or more other computer-readable media (such as mass storage device(s) **1135**, **1136**) or from one or more other sources through a suitable interface, such as network interface **1120**. The software may cause processor(s) **1101** to carry out one or more processes or one or more steps of one or more processes described or illustrated herein. Carrying out such processes or steps may include defining data structures stored in memory **1103** and modifying the data structures as directed by the software.

[0128] The memory **1103** may include various components (e.g., machine readable media) including, but not limited to, a random access memory component (e.g., RAM **1104**) (e.g., static RAM (SRAM), dynamic RAM (DRAM), ferroelectric random access memory (FRAM), phase-change random access memory (PRAM), etc.), a read-only memory component (e.g., ROM **1105**), and any combinations thereof. ROM **1105** may act to communicate data and instructions unidirectionally to processor(s) **1101**, and RAM **1104** may act to communicate data and instructions bidirectionally with processor(s) **1101**. ROM **1105** and RAM **1104** may include any suitable tangible computer-readable media described below. In one example, a basic input/output system **1106** (BIOS), including basic routines that help to transfer information between elements within computer system **1100**, such as during start-up, may be stored in the memory **1103**.

[0129] Fixed storage **1108** is connected bidirectionally to processor(s) **1101**, optionally through storage control unit **1107**. Fixed storage **1108** provides additional data storage capacity and may also include any suitable tangible computer-readable media described herein. Storage **1108** may be used to store operating system **1109**, executable(s) **1110**, data **1111**, applications **1112** (application programs), and the like. Storage **1108** can also include an optical disk drive, a solid-state memory device (e.g., flash-based systems), or a combination of any of the above.

Information in storage **1108** may, in appropriate cases, be incorporated as virtual memory in memory **1103**.

[0130] In one example, storage device(s) **1135** may be removably interfaced with computer system **1100** (e.g., via an external port connector (not shown)) via a storage device interface **1125**. Particularly, storage device(s) **1135** and an associated machine-readable medium may provide non-volatile and/or volatile storage of machine-readable instructions, data structures, program modules, and/or other data for the computer system **1100**. In one example, software may reside, completely or partially, within a machine-readable medium on storage device(s) **1135**. In another example, software may reside, completely or partially, within processor(s) **1101**.

[0131] Bus **1140** connects a wide variety of subsystems. Herein, reference to a bus may encompass one or more digital signal lines serving a common function, where appropriate. Bus **1140** may be any of several types of bus structures including, but not limited to, a memory bus, a memory controller, a peripheral bus, a local bus, and any combinations thereof, using any of a variety of bus architectures. As an example and not by way of limitation, such architectures include an Industry Standard Architecture (ISA) bus, an Enhanced ISA (EISA) bus, a Micro Channel Architecture (MCA) bus, a Video Electronics Standards Association local bus (VLB), a Peripheral Component Interconnect (PCI) bus, a PCI-Express (PCI-X) bus, an Accelerated Graphics Port (AGP) bus, HyperTransport (HTX) bus, serial advanced technology attachment (SATA) bus, and any combinations thereof.

[0132] Computer system **1100** may also include an input device **1133**. In one example, a user of computer system **1100** may enter commands and/or other information into computer system **1100** via input device(s) **1133**. Examples of an input device(s) **1133** include, but are not limited to, an alpha-numeric input device (e.g., a keyboard), a pointing device (e.g., a mouse or touchpad), a touchpad, a touch screen, a multi-touch screen, a joystick, a stylus, a gamepad, an audio input device (e.g., a microphone, a voice response system, etc.), an optical scanner, a video or still image capture device (e.g., a camera), and any combinations thereof. In some embodiments, the input device is a Kinect, Leap Motion, or the like. Input device(s) **1133** may be interfaced to bus **1140** via any of a variety of input interfaces **1123** (e.g., input interface **1123**) including, but not limited to, serial, parallel, game port, USB, FIREWIRE, THUNDERBOLT, or any combination of the above.

[0133] In particular embodiments, when computer system **1100** is connected to network **1130**, computer system **1100** may communicate with other devices, specifically mobile devices and enterprise systems, distributed computing systems, cloud storage systems, cloud computing systems, and the like, connected to network **1130**. Communications to and from computer

system **1100** may be sent through network interface **1120**. For example, network interface **1120** may receive incoming communications (such as requests or responses from other devices) in the form of one or more packets (such as Internet Protocol (IP) packets) from network **1130**, and computer system **1100** may store the incoming communications in memory **1103** for processing. Computer system **1100** may similarly store outgoing communications (such as requests or responses to other devices) in the form of one or more packets in memory **1103** and communicated to network **1130** from network interface **1120**. Processor(s) **1101** may access these communication packets stored in memory **1103** for processing.

[0134] Examples of the network interface **1120** include, but are not limited to, a network interface card, a modem, and any combination thereof. Examples of a network **1130** or network segment **1130** include, but are not limited to, a distributed computing system, a cloud computing system, a wide area network (WAN) (e.g., the Internet, an enterprise network), a local area network (LAN) (e.g., a network associated with an office, a building, a campus or other relatively small geographic space), a telephone network, a direct connection between two computing devices, a peer-to-peer network, and any combinations thereof. A network, such as network **1130**, may employ a wired and/or a wireless mode of communication. In general, any network topology may be used.

[0135] Information and data can be displayed through a display **1132**. Examples of a display **1132** include, but are not limited to, a cathode ray tube (CRT), a liquid crystal display (LCD), a thin film transistor liquid crystal display (TFT-LCD), an organic liquid crystal display (OLED) such as a passive-matrix OLED (PMOLED) or active-matrix OLED (AMOLED) display, a plasma display, and any combinations thereof. The display **1132** can interface to the processor(s) **1101**, memory **1103**, and fixed storage **1108**, as well as other devices, such as input device(s) **1133**, via the bus **1140**. The display **1132** is linked to the bus **1140** via a video interface **1122**, and transport of data between the display **1132** and the bus **1140** can be controlled via the graphics control **1121**. In some embodiments, the display is a video projector. In some embodiments, the display is a head-mounted display (HMD) such as a VR headset. In further embodiments, suitable VR headsets include, by way of non-limiting examples, HTC Vive, Oculus Rift, Samsung Gear VR, Microsoft HoloLens, Razer OSVR, FOVE VR, Zeiss VR One, Avegant Glyph, Freefly VR headset, and the like. In still further embodiments, the display is a combination of devices such as those disclosed herein.

[0136] In addition to a display **1132**, computer system **1100** may include one or more other peripheral output devices **1134** including, but not limited to, an audio speaker, a printer, a storage device, and any combinations thereof. Such peripheral output devices may be connected to the bus **1140** via an output interface **1124**. Examples of an output interface **1124** include, but

are not limited to, a serial port, a parallel connection, a USB port, a FIREWIRE port, a THUNDERBOLT port, and any combinations thereof.

[0137] In addition or as an alternative, computer system **1100** may provide functionality as a result of logic hardwired or otherwise embodied in a circuit, which may operate in place of or together with software to execute one or more processes or one or more steps of one or more processes described or illustrated herein. Reference to software in this disclosure may encompass logic, and reference to logic may encompass software. Moreover, reference to a computer-readable medium may encompass a circuit (such as an IC) storing software for execution, a circuit embodying logic for execution, or both, where appropriate. The present disclosure encompasses any suitable combination of hardware, software, or both.

[0138] Those of skill in the art will appreciate that the various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed herein may be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality.

[0139] The various illustrative logical blocks, modules, and circuits described in connection with the embodiments disclosed herein may be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

[0140] The steps of a method or algorithm described in connection with the embodiments disclosed herein may be embodied directly in hardware, in a software module executed by one or more processor(s), or in a combination of the two. A software module may reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. An exemplary storage medium is coupled to the processor such the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor. The processor and the storage medium may reside in an ASIC. The

ASIC may reside in a user terminal. In the alternative, the processor and the storage medium may reside as discrete components in a user terminal.

[0141] In accordance with the description herein, suitable computing devices include, by way of non-limiting examples, server computers, desktop computers, laptop computers, notebook computers, sub-notebook computers, netbook computers, netpad computers, set-top computers, media streaming devices, handheld computers, Internet appliances, mobile smartphones, tablet computers, personal digital assistants, video game consoles, and vehicles. Those of skill in the art will also recognize that select televisions, video players, and digital music players with optional computer network connectivity are suitable for use in the system described herein. Suitable tablet computers, in various embodiments, include those with booklet, slate, and convertible configurations, known to those of skill in the art.

[0142] In some embodiments, the computing device includes an operating system configured to perform executable instructions. The operating system is, for example, software, including programs and data, which manages the device's hardware and provides services for execution of applications. Those of skill in the art will recognize that suitable server operating systems include, by way of non-limiting examples, FreeBSD, OpenBSD, NetBSD[®], Linux, Apple[®] Mac OS X Server[®], Oracle[®] Solaris[®], Windows Server[®], and Novell[®] NetWare[®]. Those of skill in the art will recognize that suitable personal computer operating systems include, by way of non-limiting examples, Microsoft[®] Windows[®], Apple[®] Mac OS X[®], UNIX[®], and UNIX-like operating systems such as GNU/Linux[®]. In some embodiments, the operating system is provided by cloud computing. Those of skill in the art will also recognize that suitable mobile smartphone operating systems include, by way of non-limiting examples, Nokia[®] Symbian[®] OS, Apple[®] iOS[®], Research in Motion[®] BlackBerry OS[®], Google[®] Android[®], Microsoft[®] Windows Phone[®] OS, Microsoft[®] Windows Mobile[®] OS, Linux[®], and Palm[®] WebOS[®]. Those of skill in the art will also recognize that suitable media streaming device operating systems include, by way of non-limiting examples, Apple TV[®], Roku[®], Boxee[®], Google TV[®], Google Chromecast[®], Amazon Fire[®], and Samsung[®] HomeSync[®]. Those of skill in the art will also recognize that suitable video game console operating systems include, by way of non-limiting examples, Sony[®] PS3[®], Sony[®] PS4[®], Microsoft[®] Xbox 360[®], Microsoft Xbox One, Nintendo[®] Wii[®], Nintendo[®] Wii U[®], and Ouya[®].

Non-transitory computer readable storage medium

[0143] In some embodiments, the platforms, systems, media, and methods disclosed herein include one or more non-transitory computer readable storage media encoded with a program including instructions executable by the operating system of an optionally networked computing device. In further embodiments, a computer readable storage medium is a tangible component of

a computing device. In still further embodiments, a computer readable storage medium is optionally removable from a computing device. In some embodiments, a computer readable storage medium includes, by way of non-limiting examples, CD-ROMs, DVDs, flash memory devices, solid state memory, magnetic disk drives, magnetic tape drives, optical disk drives, distributed computing systems including cloud computing systems and services, and the like. In some cases, the program and instructions are permanently, substantially permanently, semi-permanently, or non-transitorily encoded on the media.

Computer program

[0144] In some embodiments, the platforms, systems, media, and methods disclosed herein include at least one computer program, or use of the same. A computer program includes a sequence of instructions, executable by one or more processor(s) of the computing device's CPU, written to perform a specified task. Computer readable instructions may be implemented as program modules, such as functions, objects, Application Programming Interfaces (APIs), computing data structures, and the like, that perform particular tasks or implement particular abstract data types. In light of the disclosure provided herein, those of skill in the art will recognize that a computer program may be written in various versions of various languages.

[0145] The functionality of the computer readable instructions may be combined or distributed as desired in various environments. In some embodiments, a computer program comprises one sequence of instructions. In some embodiments, a computer program comprises a plurality of sequences of instructions. In some embodiments, a computer program is provided from one location. In other embodiments, a computer program is provided from a plurality of locations. In various embodiments, a computer program includes one or more software modules. In various embodiments, a computer program includes, in part or in whole, one or more web applications, one or more mobile applications, one or more standalone applications, one or more web browser plug-ins, extensions, add-ins, or add-ons, or combinations thereof.

Web application

[0146] In some embodiments, a computer program includes a web application. In light of the disclosure provided herein, those of skill in the art will recognize that a web application, in various embodiments, utilizes one or more software frameworks and one or more database systems. In some embodiments, a web application is created upon a software framework such as Microsoft®.NET or Ruby on Rails (RoR). In some embodiments, a web application utilizes one or more database systems including, by way of non-limiting examples, relational, non-relational, object oriented, associative, and XML database systems. In further embodiments, suitable relational database systems include, by way of non-limiting examples, Microsoft® SQL Server,

mySQL™, and Oracle®. Those of skill in the art will also recognize that a web application, in various embodiments, is written in one or more versions of one or more languages. A web application may be written in one or more markup languages, presentation definition languages, client-side scripting languages, server-side coding languages, database query languages, or combinations thereof. In some embodiments, a web application is written to some extent in a markup language such as Hypertext Markup Language (HTML), Extensible Hypertext Markup Language (XHTML), or eXtensible Markup Language (XML). In some embodiments, a web application is written to some extent in a presentation definition language such as Cascading Style Sheets (CSS). In some embodiments, a web application is written to some extent in a client-side scripting language such as Asynchronous Javascript and XML (AJAX), Flash® ActionScript, JavaScript, or Silverlight®. In some embodiments, a web application is written to some extent in a server-side coding language such as Active Server Pages (ASP), ColdFusion®, Perl, Java™, JavaServer Pages (JSP), Hypertext Preprocessor (PHP), Python™, Ruby, Tcl, Smalltalk, WebDNA®, or Groovy. In some embodiments, a web application is written to some extent in a database query language such as Structured Query Language (SQL). In some embodiments, a web application integrates enterprise server products such as IBM® Lotus Domino®. In some embodiments, a web application includes a media player element. In various further embodiments, a media player element utilizes one or more of many suitable multimedia technologies including, by way of non-limiting examples, Adobe® Flash®, HTML 5, Apple® QuickTime®, Microsoft® Silverlight®, Java™, and Unity®.

[0147] Referring to **FIG. 12**, in a particular embodiment, an application provision system comprises one or more databases **1200** accessed by a relational database management system (RDBMS) **1210**. Suitable RDBMSs include Firebird, MySQL, PostgreSQL, SQLite, Oracle Database, Microsoft SQL Server, IBM DB2, IBM Informix, SAP Sybase, SAP Sybase, Teradata, and the like. In this embodiment, the application provision system further comprises one or more application servers **1220** (such as Java servers, .NET servers, PHP servers, and the like) and one or more web servers **1230** (such as Apache, IIS, GWS and the like). The web server(s) optionally expose one or more web services via application programming interfaces (APIs) **1240**. Via a network, such as the Internet, the system provides browser-based and/or mobile native user interfaces.

[0148] Referring to **FIG. 13**, in a particular embodiment, an application provision system alternatively has a distributed, cloud-based architecture **1300** and comprises elastically load balanced, auto-scaling web server resources **1310** and application server resources **1320** as well as synchronously replicated databases **1330**.

Mobile Application

[0149] In some embodiments, a computer program includes a mobile application provided to a mobile computing device. In some embodiments, the mobile application is provided to a mobile computing device at the time it is manufactured. In other embodiments, the mobile application is provided to a mobile computing device via the computer network described herein.

[0150] In view of the disclosure provided herein, a mobile application is created by techniques known to those of skill in the art using hardware, languages, and development environments known to the art. Those of skill in the art will recognize that mobile applications are written in several languages. Suitable programming languages include, by way of non-limiting examples, C, C++, C#, Objective-C, Java™, Javascript, Pascal, Object Pascal, Python™, Ruby, VB.NET, WML, and XHTML/HTML with or without CSS, or combinations thereof.

[0151] Suitable mobile application development environments are available from several sources. Commercially available development environments include, by way of non-limiting examples, AirplaySDK, alcheMo, Appcelerator®, Celsius, Bedrock, Flash Lite, .NET Compact Framework, Rhomobile, and WorkLight Mobile Platform. Other development environments are available without cost including, by way of non-limiting examples, Lazarus, MobiFlex, MoSync, and Phonegap. Also, mobile device manufacturers distribute software developer kits including, by way of non-limiting examples, iPhone and iPad (iOS) SDK, Android™ SDK, BlackBerry® SDK, BREW SDK, Palm® OS SDK, Symbian SDK, webOS SDK, and Windows® Mobile SDK.

[0152] Those of skill in the art will recognize that several commercial forums are available for distribution of mobile applications including, by way of non-limiting examples, Apple® App Store, Google® Play, Chrome WebStore, BlackBerry® App World, App Store for Palm devices, App Catalog for webOS, Windows® Marketplace for Mobile, Ovi Store for Nokia® devices, Samsung® Apps, and Nintendo® DSi Shop.

Standalone Application

[0153] In some embodiments, a computer program includes a standalone application, which is a program that is run as an independent computer process, not an add-on to an existing process, e.g., not a plug-in. Those of skill in the art will recognize that standalone applications are often compiled. A compiler is a computer program(s) that transforms source code written in a programming language into binary object code such as assembly language or machine code. Suitable compiled programming languages include, by way of non-limiting examples, C, C++, Objective-C, COBOL, Delphi, Eiffel, Java™, Lisp, Python™, Visual Basic, and VB.NET, or combinations thereof. Compilation is often performed, at least in part, to create an executable

program. In some embodiments, a computer program includes one or more executable compiled applications.

Web Browser Plug-in

[0154] In some embodiments, the computer program includes a web browser plug-in (e.g., extension, etc.). In computing, a plug-in is one or more software components that add specific functionality to a larger software application. Makers of software applications support plug-ins to enable third-party developers to create abilities which extend an application, to support easily adding new features, and to reduce the size of an application. When supported, plug-ins enable customizing the functionality of a software application. For example, plug-ins are commonly used in web browsers to play video, generate interactivity, scan for viruses, and display particular file types. Those of skill in the art will be familiar with several web browser plug-ins including, Adobe® Flash® Player, Microsoft® Silverlight®, and Apple® QuickTime®. In some embodiments, the toolbar comprises one or more web browser extensions, add-ins, or add-ons. In some embodiments, the toolbar comprises one or more explorer bars, tool bands, or desk bands.

[0155] In view of the disclosure provided herein, those of skill in the art will recognize that several plug-in frameworks are available that enable development of plug-ins in various programming languages, including, by way of non-limiting examples, C++, Delphi, Java™, PHP, Python™, and VB.NET, or combinations thereof.

[0156] Web browsers (also called Internet browsers) are software applications, designed for use with network-connected computing devices, for retrieving, presenting, and traversing information resources on the World Wide Web. Suitable web browsers include, by way of non-limiting examples, Microsoft® Internet Explorer®, Mozilla® Firefox®, Google® Chrome, Apple® Safari®, Opera Software® Opera®, and KDE Konqueror. In some embodiments, the web browser is a mobile web browser. Mobile web browsers (also called microbrowsers, mini-browsers, and wireless browsers) are designed for use on mobile computing devices including, by way of non-limiting examples, handheld computers, tablet computers, netbook computers, subnotebook computers, smartphones, music players, personal digital assistants (PDAs), and handheld video game systems. Suitable mobile web browsers include, by way of non-limiting examples, Google® Android® browser, RIM BlackBerry® Browser, Apple® Safari®, Palm® Blazer, Palm® WebOS® Browser, Mozilla® Firefox® for mobile, Microsoft® Internet Explorer® Mobile, Amazon® Kindle® Basic Web, Nokia® Browser, Opera Software® Opera® Mobile, and Sony® PSP™ browser.

Software Modules

[0157] In some embodiments, the platforms, systems, media, and methods disclosed herein include software, server, and/or database modules, or use of the same. In view of the disclosure provided herein, software modules are created by techniques known to those of skill in the art using machines, software, and languages known to the art. The software modules disclosed herein are implemented in a multitude of ways. In various embodiments, a software module comprises a file, a section of code, a programming object, a programming structure, or combinations thereof. In further various embodiments, a software module comprises a plurality of files, a plurality of sections of code, a plurality of programming objects, a plurality of programming structures, or combinations thereof. In various embodiments, the one or more software modules comprise, by way of non-limiting examples, a web application, a mobile application, and a standalone application. In some embodiments, software modules are in one computer program or application. In other embodiments, software modules are in more than one computer program or application. In some embodiments, software modules are hosted on one machine. In other embodiments, software modules are hosted on more than one machine. In further embodiments, software modules are hosted on a distributed computing platform such as a cloud computing platform. In some embodiments, software modules are hosted on one or more machines in one location. In other embodiments, software modules are hosted on one or more machines in more than one location.

Databases

[0158] In some embodiments, the platforms, systems, media, and methods disclosed herein include one or more databases, or use of the same. In view of the disclosure provided herein, those of skill in the art will recognize that many databases are suitable for storage and retrieval of user, biometric, eye-tracking, and spoofing attempt information. In various embodiments, suitable databases include, by way of non-limiting examples, relational databases, non-relational databases, object oriented databases, object databases, entity-relationship model databases, associative databases, and XML databases. Further non-limiting examples include SQL, PostgreSQL, MySQL, Oracle, DB2, and Sybase. In some embodiments, a database is internet-based. In further embodiments, a database is web-based. In still further embodiments, a database is cloud computing-based. In a particular embodiment, a database is a distributed database. In other embodiments, a database is based on one or more local computer storage devices.

EXAMPLES

[0159] The following illustrative examples are representative of embodiments of the software applications, systems, and methods described herein and are not meant to be limiting in any way.

Example 1 – Registering a User’s Eye Gaze Profile

[0160] In some embodiments, registering a user’s eye gaze profile is performed by displaying a live video feed on the screen of the mobile device comprising a live video feed captured by the front facing camera overlaid with an image of a face positioning region. Once it is determined that the user’s face is at least partially displayed within the face positioning region, the user is notified to gaze at the sequence of two or more registration eye gaze icons. While the user’s face is maintained at least partially displayed within the face positioning region the sequence of four registration eye gaze icons are displayed. In this example, the sequence of four registration eye gaze icons are displayed in the four registration display locations on the screen of the mobile phone, comprising in order, a top-left location, a top-right location, a bottom-left location, and a top-right location. If the user gazes at a point a distance 10% or more than the width of the four registration eye gaze icons from the center of one or more of the four registration eye gaze icons during their display, the user is notified of the error and/or the user’s eye gaze profile registration is terminated.

[0161] While the user is gazing at the sequence of four registration eye gaze icons with their face at least partially displayed within the face positioning region, the front facing camera of the mobile device captures a registration eye gaze image of the user.

[0162] Thereafter the user’s eye gaze profile is registered comprising the captured registration eye gaze images of the user during the display of the registration gaze icon, wherein each captured registration eye gaze image is associated with the registration display location of the registration gaze icon. In this example, the user’s eye gaze profile further comprises the user’s name and a list of assets to which the user is granted access.

Example 2 – Registering a User’s Eye Gaze Profile

[0163] In some embodiments, registering a user’s eye gaze profile is performed by displaying a live video feed on the screen of the mobile device comprising a live video feed captured by the front facing camera. The user is then notified to gaze at the sequence of two or more registration eye gaze icons. Four registration eye gaze icons are each displayed in their respective registration display locations for a registration display period in the following order: a top-left location for 0.1 seconds, a top-right location for 0.5 seconds, a bottom-left location for 1 second,

and a top-right location for 2 seconds. If the user gazes at a point a distance 10% or more than the width of the four registration eye gaze icons from the center of one or more of the four registration eye gaze icons during their display, the user is notified of the error and/or the user's eye gaze profile registration is terminated.

[0164] While the user is gazing at the sequence of four registration eye gaze icons the front facing camera of the mobile device captures a registration eye gaze image of the user. Thereafter the user's eye gaze profile is registered comprising the captured registration eye gaze images of the user during the display of the registration gaze icon, wherein each captured registration eye gaze image is associated with the registration display location of the registration gaze icon. In this example, the user's eye gaze profile further comprises the user's name and a list of assets to which the user is granted access.

Example 3 – Authenticating a User and/or Determining a Spoofing Attempt

[0165] In some embodiments, determining a spoofing attempt by a user during a request to access a resource is performed by displaying a live video feed on the screen of the mobile device comprising a live video feed captured by the front facing camera overlaid with an image of a face positioning region. Once it is determining that the user's face is at least partially displayed within the face positioning region, the user is notified to gaze at the sequence of two or more authentication eye gaze icons. While the user's face is maintained at least partially displayed within the face positioning region the sequence of two authentication eye gaze icons are displayed. In this example, the sequence of two authentication eye gaze icons are displayed in the four authentication display locations on the screen of the mobile phone, comprising in order, a top-left location, a top-right location and a bottom-right location.

[0166] If the user gazes at a point a distance 10% or more than the width of the two authentication eye gaze icons from the center of one or more of the two authentication eye gaze icons during their display, the user is notified of the error and/or the user's request to access a resource is terminated.

[0167] While the user is gazing at the sequence of two authentication eye gaze icons with their face at least partially displayed within the face positioning region, the front facing camera of the mobile device captures an authentication eye gaze image of the user.

[0168] Thereafter a spoofing attempt is determined to have occurred by as a similarity between the registration eye gaze image of the user gazing at a user registration gaze icon in a first registration display location and the authentication eye gaze image of the user gazing at a user authentication gaze icon in the same first registration display location is greater than the authentication threshold.

Example 4 – Authenticating a User and/or Determining a Spoofing Attempt

[0169] In some embodiments, determining a spoofing attempt by a user during a request to access a resource is performed by displaying a live video feed on the screen of the mobile device comprising a live video feed captured by the front facing camera. The user is then notified to gaze at the sequence of two or more authentication eye gaze icons. Four authentication eye gaze icons are each displayed in their respective authentication display locations for an authentication display period in the following order: a top-left location for 0.1 seconds, a top-right location for 0.5 seconds, a bottom-left location for 1 second, and a top-right location for 2 seconds. If the user gazes at a point a distance 10% or more than the width of the two authentication eye gaze icons from the center of one or more of the two authentication eye gaze icons during their display, the user is notified of the error and/or the user's request to access a resource is terminated.

[0170] While the user is gazing at the sequence of two authentication eye gaze icons with their face at least partially displayed within the face positioning region, the front facing camera of the mobile device captures an authentication eye gaze image of the user.

[0171] Thereafter a spoofing attempt is determined to have occurred by as a similarity between the registration eye gaze image of the user gazing at a user registration gaze icon in a first registration display location and the authentication eye gaze image of the user gazing at a user authentication gaze icon in the same first registration display location is greater than the authentication threshold.

[0172] While preferred embodiments of the present disclosure have been shown and described herein, it will be obvious to those skilled in the art that such embodiments are provided by way of example only. Numerous variations, changes, and substitutions will now occur to those skilled in the art without departing from the disclosure. It should be understood that various alternatives to the embodiments of the disclosure described herein may be employed in practicing the disclosure.

CLAIMS**WHAT IS CLAIMED IS:**

1. A computer-implemented method of determining a spoofing attempt by a user during a request to access a resource via a mobile device having a screen and a front facing camera, the method comprising:
 - (a) receiving a user eye gaze profile comprising a registration eye gaze image of the user, wherein the registration eye gaze image is associated with a registration display location;
 - (b) displaying an authentication eye gaze icon, wherein the authentication eye gaze icon is displayed in an authentication display location on the screen of the mobile phone;
 - (c) determining that the user's gaze is directed towards the authentication display location of the authentication gaze icon during the display of the authentication eye gaze icon;
 - (d) capturing an authentication eye gaze image of the user, wherein the authentication eye gaze image is captured during the display of the authentication gaze icon; and
 - (e) determining that a spoofing attempt has occurred if the authentication eye gaze image has a similarity below an authentication threshold with the registration eye gaze images associated with the registration display location that is equivalent to the authentication display location of the authentication eye gaze image.
2. The method of any claim, wherein displaying the authentication eye gaze icon comprises displaying a sequence of two or more authentication eye gaze icons.
3. The method of any claim, wherein the sequence of the two or more authentication eye gaze icons is a random sequence.
4. The method of any claim, wherein the authentication display location of the sequence of the two or more authentication eye gaze icons is a randomized location.
5. The method of any claim, wherein the sequence of two or more authentication eye gaze icons is unknown to the user.
6. The method of any claim, wherein the user's gaze is determined to be directed towards the authentication display location by a machine learning algorithm.

7. The method of any claim, wherein the authentication display location is at a corner of the screen of the mobile device.
8. The method of any claim, further comprising displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera.
9. The method of any claim, wherein the live video feed is overlaid with an image of a face positioning region.
10. The method of any claim, further comprising determining that the user's face is at least partially displayed within the face positioning region.
11. The method of any claim, wherein the user's eye gaze profile is registered by:
 - (a) displaying a registration eye gaze icon, wherein the registration eye gaze icon is displayed in a different registration display location on the screen of the mobile phone;
 - (b) determining that the user's gaze is directed towards the registration display location of each registration gaze icon during the display of each registration eye gaze icon;
 - (c) capturing the registration eye gaze image of the user, wherein the registration eye gaze image is captured during the display of the registration gaze icon; and
 - (d) creating the user's eye gaze profile comprising the captured registration eye gaze images of the user during the display of the registration gaze icon, wherein each captured registration eye gaze image is associated with the registration display location of the registration gaze icon.
12. The method of any claim, wherein displaying the registration eye gaze icon comprises displaying a sequence of two or more registration eye gaze icons.
13. The method of any claim, wherein the sequence of the two or more registration eye gaze icons is a random sequence.
14. The method of any claim, wherein the registration display location of the sequence of the two or more registration eye gaze icons is a randomized location.
15. The method of any claim, wherein the registration display location is a corner of the screen of the mobile device.

16. The method of any claim, further comprising displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera.
17. The method of any claim, wherein the live video feed is overlaid with an image of a face positioning region.
18. The method of any claim, further comprising determining that the user's face is at least partially displayed within the face positioning region.
19. The method of any claim, wherein the number of registration eye gaze images in the registration eye gaze image is greater than the number of authentication eye gaze images in the series of authentication eye gaze images.
20. The method of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both is a geometric shape, an irregular shape, or an image.
21. The method of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both is displayed for an icon display period.
22. The method of any claim, wherein the icon display period is about 0.01 seconds to about 60 seconds.
23. The method of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both comprises an indicator associated with the amount of time remaining in the icon display period, or an amount of time lapsed during the icon display period.
24. The method of any claim, wherein the indicator comprises a number of seconds, a dynamic pie chart, a dynamic bar chart, a size of the authentication eye gaze icon, a color of the authentication eye gaze icon, or any combination thereof.
25. The method of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both comprise a display of a single eye gaze icon.
26. The method of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both is static with respect to the mobile phone.
27. The method of any claim, wherein the registration display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device.

28. The method of any claim, wherein the authentication display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device.
29. The method of any claim, further comprising displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon, or both.
30. The method of any claim, further comprising displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon for the notification period, or both.
31. The method of any claim, further comprising terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of at least one registration gaze icon during the display of each registration eye gaze icon, or both.
32. The method of any claim, further comprising terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of at least one registration eye gaze icon for the termination period, or both.
33. The method of any claim, further comprising requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile.
34. The method of any claim, further comprising requesting a registration confirmation by the user before creating the user's eye gaze profile.
35. The method of any claim, further comprising notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region.
36. The method of any claim, further comprising notifying the user to gaze at the registration eye gaze icon.

37. The method of any claim, further comprising displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon, or both.
38. The method of any claim, further comprising displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon for the notification period, or both.
39. The method of any claim, further comprising denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of at least one authentication gaze icon during the display of each authentication eye gaze icon, or both.
40. The method of any claim, further comprising denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of at least one authentication eye gaze icon for the termination period, or both.
41. The method of any claim, further comprising requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile.
42. The method of any claim, further comprising requesting an authentication confirmation by the user before granting access for the user to the resource.
43. The method of any claim, further comprising notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region.
44. The method of any claim, further comprising notifying the user to gaze at the authentication eye gaze icon.
45. The method of any claim, further comprising determining if at least a portion of the user's face is occluded by a mask.

46. A computer-implemented system comprising: a digital processing device comprising: at least one processor, an operating system configured to perform executable instructions, a memory, and a computer program including instructions executable by the digital processing device to create an application to determine a spoofing attempt by a user during a request to access a resource via a mobile device having a screen and a front facing camera, the application comprising:
- (a) a module receiving a user eye gaze profile comprising a registration eye gaze image of the user, wherein each registration eye gaze image is associated with a registration display location;
 - (b) a module displaying an authentication eye gaze icon, wherein the authentication eye gaze icon is displayed in a different authentication display location on the screen of the mobile phone;
 - (c) a module determining that the user's gaze is directed towards the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon;
 - (d) a module capturing an authentication eye gaze image of the user, wherein the authentication eye gaze image is captured during the display of the authentication gaze icon; and
 - (e) a module determining that a spoofing attempt has occurred if the authentication eye gaze image has a similarity below an authentication threshold with one of the registration eye gaze images associated with the registration display location that is equivalent to the authentication display location of the authentication eye gaze image.
47. The system of any claim, wherein displaying the authentication eye gaze icon comprises displaying a sequence of two or more authentication eye gaze icons.
48. The system of any claim, wherein the sequence of the two or more authentication eye gaze icons is a random sequence.
49. The system of any claim, wherein the authentication display location of the sequence of the two or more authentication eye gaze icons is a randomized location.
50. The system of any claim, wherein the sequence of two or more authentication eye gaze icons is unknown to the user.

51. The system of any claim, wherein the user's gaze is determined to be directed towards the authentication display location by a machine learning algorithm.
52. The system of any claim, wherein the authentication display location is at a corner of the screen of the mobile device.
53. The system of any claim, further comprising a module displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera.
54. The system of any claim, wherein the live video feed is overlaid with an image of a face positioning region.
55. The system of any claim, further comprising a module determining that the user's face is at least partially displayed within the face positioning region.
56. The system of any claim, wherein the user's eye gaze profile is registered by:
 - (a) displaying a registration eye gaze icon, wherein the registration eye gaze icon is displayed in a different registration display location on the screen of the mobile phone;
 - (b) determining that the user's gaze is directed towards the registration display location of each registration gaze icon during the display of each registration eye gaze icon;
 - (c) capturing the registration eye gaze image of the user, wherein the registration eye gaze image is captured during the display of the registration gaze icon; and
 - (d) creating the user's eye gaze profile comprising the captured registration eye gaze images of the user during the display of the registration gaze icon, wherein each captured registration eye gaze image is associated with the registration display location of the registration gaze icon.
57. The system of any claim, wherein displaying the registration eye gaze icon comprises displaying a sequence of two or more registration eye gaze icons.
58. The system of any claim, wherein the sequence of the two or more registration eye gaze icons is a random sequence.
59. The system of any claim, wherein the registration display location of the sequence of the two or more registration eye gaze icons is a randomized location.

60. The system of any claim, wherein the registration display location is a corner of the screen of the mobile device.
61. The system of any claim, further comprising a module displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera.
62. The system of any claim, wherein the live video feed is overlaid with an image of a face positioning region.
63. The system of any claim, further comprising a module determining that the user's face is at least partially displayed within the face positioning region.
64. The system of any claim, wherein the number of registration eye gaze images in the registration eye gaze image is greater than the number of authentication eye gaze images in the series of authentication eye gaze images.
65. The system of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both is a geometric shape, an irregular shape, or an image.
66. The system of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both is displayed for an icon display period.
67. The system of any claim, wherein the icon display period is about 0.01 seconds to about 60 seconds.
68. The system of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both comprises an indicator associated with the amount of time remaining in the icon display period, or an amount of time lapsed during the icon display period.
69. The system of any claim, wherein the indicator comprises a number of seconds, a dynamic pie chart, a dynamic bar chart, a size of the authentication eye gaze icon, a color of the authentication eye gaze icon, or any combination thereof.
70. The system of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both comprise a display of a single eye gaze icon.
71. The system of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both is static with respect to the mobile phone.
72. The system of any claim, wherein the registration display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device.

73. The system of any claim, wherein the authentication display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device.
74. The system of any claim, further comprising a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon, or both.
75. The system of any claim, further comprising a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon for the notification period, or both.
76. The system of any claim, further comprising a module terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of at least one registration gaze icon during the display of each registration eye gaze icon, or both.
77. The system of any claim, further comprising a module terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of at least one registration eye gaze icon for the termination period, or both.
78. The system of any claim, further comprising a module requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile.
79. The system of any claim, further comprising a module requesting a registration confirmation by the user before creating the user's eye gaze profile.
80. The system of any claim, further comprising a module notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region.
81. The system of any claim, further comprising a module notifying the user to gaze at the registration eye gaze icon.

82. The system of any claim, further comprising a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon, or both.
83. The system of any claim, further comprising a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon for the notification period, or both.
84. The system of any claim, further comprising a module denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of at least one authentication gaze icon during the display of each authentication eye gaze icon, or both.
85. The system of any claim, further comprising a module denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of at least one authentication eye gaze icon for the termination period, or both.
86. The system of any claim, further comprising a module requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile.
87. The system of any claim, further comprising a module requesting an authentication confirmation by the user before granting access for the user to the resource.
88. The system of any claim, further comprising a module notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region.
89. The system of any claim, further comprising a module notifying the user to gaze at the authentication eye gaze icon.
90. The system of any claim, further comprising a module determining if at least a portion of the user's face is occluded by a mask.

91. A non-transitory computer-readable storage media encoded with a computer program including instructions executable by a processor to create an application to determine a spoofing attempt by a user during a request to access a resource via a mobile device having a screen and a front facing camera, the application comprising:
- (a) a module receiving a user eye gaze profile comprising a registration eye gaze image of the user, wherein each registration eye gaze image is associated with a registration display location;
 - (b) a module displaying an authentication eye gaze icon, wherein the authentication eye gaze icon is displayed in a different authentication display location on the screen of the mobile phone;
 - (c) a module determining that the user's gaze is directed towards the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon;
 - (d) a module capturing an authentication eye gaze image of the user, wherein the authentication eye gaze image is captured during the display of the authentication gaze icon; and
 - (e) a module determining that a spoofing attempt has occurred if the authentication eye gaze image has a similarity below an authentication threshold with one of the registration eye gaze images associated with the registration display location that is equivalent to the authentication display location of the authentication eye gaze image.
92. The media of any claim, wherein displaying the authentication eye gaze icon comprises displaying a sequence of two or more authentication eye gaze icons.
93. The media of any claim, wherein the sequence of the two or more authentication eye gaze icons is a random sequence.
94. The media of any claim, wherein the authentication display location of the sequence of the two or more authentication eye gaze icons is a randomized location.
95. The media of any claim, wherein the sequence of two or more authentication eye gaze icons is unknown to the user.
96. The media of any claim, wherein the user's gaze is determined to be directed towards the authentication display location by a machine learning algorithm.

97. The media of any claim, wherein the authentication display location is at a corner of the screen of the mobile device.
98. The media of any claim, further comprising a module displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera.
99. The media of any claim, wherein the live video feed is overlaid with an image of a face positioning region.
100. The media of any claim, further comprising a module determining that the user's face is at least partially displayed within the face positioning region.
101. The media of any claim, wherein the user's eye gaze profile is registered by:
 - (a) displaying a registration eye gaze icon, wherein the registration eye gaze icon is displayed in a different registration display location on the screen of the mobile phone;
 - (b) determining that the user's gaze is directed towards the registration display location of each registration gaze icon during the display of each registration eye gaze icon;
 - (c) capturing the registration eye gaze image of the user, wherein the registration eye gaze image is captured during the display of the registration gaze icon; and
 - (d) creating the user's eye gaze profile comprising the captured registration eye gaze images of the user during the display of the registration gaze icon, wherein each captured registration eye gaze image is associated with the registration display location of the registration gaze icon.
102. The media of any claim, wherein displaying the registration eye gaze icon comprises displaying a sequence of two or more registration eye gaze icons.
103. The media of any claim, wherein the sequence of the two or more registration eye gaze icons is a random sequence.
104. The media of any claim, wherein the registration display location of the sequence of the two or more registration eye gaze icons is a randomized location.
105. The media of any claim, wherein the registration display location is a corner of the screen of the mobile device.

106. The media of any claim, further comprising a module displaying a live video feed on the screen of the mobile device, wherein the live video feed comprises a live video feed captured by the front facing camera.
107. The media of any claim, wherein the live video feed is overlaid with an image of a face positioning region.
108. The media of any claim, further comprising a module determining that the user's face is at least partially displayed within the face positioning region.
109. The media of any claim, wherein the number of registration eye gaze images in the registration eye gaze image is greater than the number of authentication eye gaze images in the series of authentication eye gaze images.
110. The media of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both is a geometric shape, an irregular shape, or an image.
111. The media of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both is displayed for an icon display period.
112. The media of any claim, wherein the icon display period is about 0.01 seconds to about 60 seconds.
113. The media of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both comprises an indicator associated with the amount of time remaining in the icon display period, or an amount of time lapsed during the icon display period.
114. The media of any claim, wherein the indicator comprises a number of seconds, a dynamic pie chart, a dynamic bar chart, a size of the authentication eye gaze icon, a color of the authentication eye gaze icon, or any combination thereof.
115. The media of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both comprise a display of a single eye gaze icon.
116. The media of any claim, wherein the authentication eye gaze icon, the registration eye gaze icon, or both is static with respect to the mobile phone.
117. The media of any claim, wherein the registration display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device.

118. The media of any claim, wherein the authentication display location is a top-right corner, a top-left corner, a bottom-right corner, a bottom-left corner, a top side, a bottom side, a right side, or a left side of the screen of the mobile device.
119. The media of any claim, further comprising a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon, or both.
120. The media of any claim, further comprising a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of each registration eye gaze icon for the notification period, or both.
121. The media of any claim, further comprising a module terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the registration display location of at least one registration gaze icon during the display of each registration eye gaze icon, or both.
122. The media of any claim, further comprising a module terminating the registration of the user's eye gaze profile if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the registration display location of each registration gaze icon during the display of at least one registration eye gaze icon for the termination period, or both.
123. The media of any claim, further comprising a module requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile.
124. The media of any claim, further comprising a module requesting a registration confirmation by the user before creating the user's eye gaze profile.
125. The media of any claim, further comprising a module notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region.
126. The media of any claim, further comprising a module notifying the user to gaze at the registration eye gaze icon.

127. The media of any claim, further comprising a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon, or both.
128. The media of any claim, further comprising a module displaying a notification if at least a majority of the user's face is displayed outside the face positioning region for a notification period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of each authentication eye gaze icon for the notification period, or both.
129. The media of any claim, further comprising a module denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region, if the user's gaze is determined to be directed away from the authentication display location of at least one authentication gaze icon during the display of each authentication eye gaze icon, or both.
130. The media of any claim, further comprising a module denying the request to access the resource if at least a majority of the user's face is displayed outside the face positioning region for a termination period, if the user's gaze is determined to be directed away from the authentication display location of each authentication gaze icon during the display of at least one authentication eye gaze icon for the termination period, or both.
131. The media of any claim, further comprising a module requesting a user name, an identification parameter, or both and associating the user name, the identification parameter, or both with the user's eye gaze profile.
132. The media of any claim, further comprising a module requesting an authentication confirmation by the user before granting access for the user to the resource.
133. The media of any claim, further comprising a module notifying the user to position their face with respect to the mobile devices such that their face is at least partially displayed within the face positioning region.
134. The media of any claim, further comprising a module notifying the user to gaze at the authentication eye gaze icon.
135. The media of any claim, further comprising a module determining if at least a portion of the user's face is occluded by a mask.