

Process for managing objects in a communication network and device for the implementation thereof

5 The invention relates to a process for managing objects, in particular software modules, in a communication network which may be of the home-automation type. It also relates to devices able to be linked to such a network and comprising means for implementing the process.

10 The invention applies in particular in a home network adapted to the interconnecting of audio and video appliances.

15 In a network of mass-market electronic appliances such as televisions, cable or satellite decoders or video recorders, it is necessary to provide means of communication between the appliances, whilst taking account of the complexity and price constraints inherent in mass-produced appliances.

20 Depending upon the type of network envisaged, it may be necessary for an appliance (also referred to as a node in what follows) of the network to ascertain the access path or the address of another appliance. This is also the case if the concept of appliance is replaced with the concept of object, or of software module, it being possible for an appliance to contain a large number of objects. This may relate to downloaded or resident applications, particular user interfaces or lower level modules. Each object or module of an appliance may seek to communicate with another object or module of the same appliance or of another appliance of the network. Each object is regarded as a resource
25 available to other objects.

 In this case, the problem arises of obtaining one or the dynamic list of resources available in the network.

30 In this context, the subject of the invention is a process for the distributed management of a catalogue of objects in a communication network comprising appliances, the said process comprising the step of registering local objects present in an appliance in a local registry managed at the level of this appliance, the said process being characterized in that it furthermore comprises
35 the steps:

- of formulating, by a local object, a request for a list of objects, the said request being transmitted to the single local registry of the appliance hosting the said local object;

- of propagating the said request through the said local registry to
5 distant registries;

- of collecting the responses to the said request by the distant registries and the response of the local registry;

- of transmitting the responses collected to the local object having
10 formulated the initial request.

Each node (or appliance) stores only the information local to this node or appliance: the information is not duplicated in other nodes, an object registering itself only at the local registry. Thus, the memory requirements in each appliance are restricted.

15 The search for objects (software modules) is distributed amongst several appliances, each database being interrogated at local level. Thus, the requirements for resources for processing the information at local level are themselves also restricted. Moreover, only the relevant information, that is to say that which meets the search criteria, travels over the network: the passband
20 is therefore used wisely.

The consistency of the data is maintained in a simple manner: it is not necessary to update, by virtue of complex processing, distant databases when a change is made in a local database.

If a node disappears, only the information related to this node is lost.

25 Also, the requests are propagated in the network only to the other registries. There is no transmission to ALL the elements in the network, only to a well-identified subset, namely the registries. This also limits the passband required.

30 According to a particular embodiment, a local registry comprises for each object registered therein an identifier of this object in the network, this identifier being unique for the network, as well as attributes of the said object.

35 According to a particular embodiment, the said identifier (SEID) comprises an identifier of the appliance in which the object is present, this appliance identifier being unique in the network, as well as of a local identifier unique to this object at the level of the said appliance.

According to a particular embodiment, a type of request formulated by an object is a request comprising at least one selection criterion pertaining to an object attribute.

5

According to a particular embodiment, the function of an object is an attribute stored by a local registry in respect of the said object.

According to a particular embodiment, the step of propagating a request comprises the step of determining the appliances connected to the network which themselves comprise a registry.

10

An object may thus initiate a request to obtain a list of other objects without concerning itself with knowing whether these objects are or are not located in the same node.

15

According to a particular embodiment, the step of determining the appliances comprises the determination of the types (FAV, IAV, BAV, LAV) of the appliances present in the network, the type of an appliance indicating whether it hosts a registry or whether it does not host one.

20

In a HAVi type network, the FAV and IAV type appliances are obliged to comprise a registry, whilst the BAV and LAV type appliances do not possess one.

25

According to a variant embodiment, a request is propagated only to a specified group of distant registries.

When it is known for example in advance that software modules comprising certain attributes are present only in a given type of appliance, then it is possible to limit the propagation of requests to this type of appliance so as to limit the number of messages flowing around the network.

30

According to a variant embodiment, one of the types of request which can be formulated by an object is a request comprising selection criteria for at least two lists of objects, as well as at least one operator for processing the said lists.

35

The subject of the invention is also an appliance in a communication network comprising means for storing local objects, means for storing a local registry for containing a catalogue of objects local to the appliance, means for
 5 connecting the said appliance to the network, the said appliance being characterized in that furthermore comprises:

- means for propagating a request for a list of objects formulated by a local object to the local registries of other appliances;
- means for collecting the responses of the registries of the other
 10 appliances and the response of the local registry and for transmitting the said responses to the object having formulated the said request.

According to a particular embodiment, the appliance furthermore comprises means for determining the addresses of appliances of the network
 15 comprising so-called distant registries.

Other characteristics and advantages of the invention will become apparent through the description of a particular non-limiting embodiment illustrated by the appended figures, among which:

- Figure 1a schematically represents a home network comprising
 20 four appliances of different types
- Figure 1b is a block diagram of one of the appliances of Figure 1;
- Figure 2 is a schematic illustrating the software organization of the appliance of Figure 1b;
- Figure 3 represents the states of a registry module of an appliance
 25 of the network;
- Figure 4 represents the sequencing of the messages upon a request requiring propagation to a distant registry module.

30 According to the present exemplary embodiment, the home network comprises four types of appliances: audio-video appliances possessing full functionalities (FAV), audio-video appliances with an intermediate function (IAV), base audio-video appliances (BAV) and legacy audio-video appliances (LAV). The communication bus is of the IEEE1394 type, but may be of some
 35 other type. The network admits a common control language, referred to as the HAVI language.

The FAV type appliances possess the most complete functionalities of all the appliances of the network: a communication manager, a registry module, an appliance control module manager and appliance control modules (referred to as "DCMs" in what follows), it being possible for the latter to be downloaded. According to a variant, the appliance also comprises a user interface manager. The FAV appliances can take control of less sophisticated appliances, such as BAV and LAV type appliances by way of appliance control modules. An FAV appliance can access other FAV or IAV type appliances in order to access resources which it lacks (for example a user interface manager).

The IAV type appliances possess the same functionalities as an FAV except for the possibility of downloading the appliance control modules.

The BAV type appliances possess a private control language specific to them, and which is not necessarily the one used by the remainder of the appliances. This type of appliance is controlled by an FAV appliance by way of a control module (DCM) downloaded from the BAV type appliance itself and adapted for the control thereof, for example the BAV type appliance can be a printer, whose print manager is downloaded.

The LAV type appliances are appliances connected to the bus or to IAV or FAV type appliances by way of specific connections. The LAV type appliances are controlled by specific control modules (DCM) which do not originate from the appliance itself and possess their own private language.

Figure 1a represents an exemplary network in the form of four appliances FAV, IAV, BAV and LAV. The FAV, IAV and BAV appliances are connected to the same bus whilst the LAV appliance is connected directly to the FAV appliance and controlled by a control module present in the latter. The BAV appliance is controlled, for example, by way of the IAV appliance.

Figure 1b schematically represents the FAV appliance 1. It comprises a microprocessor 2 linked to a random access memory 3 and an at least partially reprogrammable read-only memory 4, as well as an IEEE 1394 bus interface (reference 5) consisting of a link circuit and of a physical circuit

('PHY' according to the IEEE 1394 terminology). The appliance 1 also comprises a specific interface 6 for plugging in the LAV video recorder.

5 In particular four types of software modules may be present in the memory of the appliances of the present network. These are DCM appliance control modules, applications, service modules and a message transmission manager.

10 The DCM appliance control modules allow the control of an appliance or of a subset of this appliance. The control module can be located in the appliance to be controlled itself (if it is an IAV or FAV type appliance) or in an appliance other than the appliance to be controlled (if the appliance to be controlled is of LAV or BAV type, the control manager will be located in an IAV or FAV type appliance, the latter serving as execution platform). A control
15 manager is either present right from the outset, or can be downloaded. In the latter case, the downloading is carried out for example at the moment of initialization of the appliance, or when requested by an application.

20 The function control modules (referred to as FCMs) are software modules allowing control of a function of an appliance and are included in the DCM appliance control modules. An appliance can in this regard possess several functions: recording, tuner, camera, display, mass memory, etc.

25 The service modules offer system services or functions. They can be accessed either by local software modules, or through the system for transmitting messages to modules of other appliances. These system services or functions comprise in particular the graphical management of user interfaces, the management (for example the downloading) of the DCM modules, the procedures for connecting an appliance to the network, the initializing of the
30 network, (listing of the network resources), as well as the registry module, which will be seen in greater detail hereinbelow.

Each software module (DCM or application or system services
35 modules) must register itself at the local registry module (that is to say the registry module in which it resides or into which it has been loaded) if it wishes to grant access through the message layer to other software modules of the

network. The FCM function modules related to a DCM control module also register themselves at the local registry module.

5 The message transmission managers are responsible for communicating messages from one software module to another, regardless of the appliances in which these modules are located. When a software module wants to send a message to another module, it does not know the physical appliance which hosts the destination module.

10 Figure 2 illustrates an example of a software organisation of an FAV type appliance.

This appliance comprises a downloaded application 21 (for example a game), two DCM control modules A and B 22 and 23, a private application 24 (for example an electronic program guide), an IEEE 1883/1394 type communication bus manager 25, a registry module 26, a high-level user interface 27, a DCM manager 28 and a message transmission system 29. The modules communicate with one another by way of the message transmission system accessible through an application programming interface 30 (referred to as the 'API' in what follows). The appliance also comprises an interface 31 with the 1394 bus.

20 Upon its installation into the network, the FAV appliance will seek to load the DCM control modules of BAV type appliances with the aim of making them available to the applications. With this in mind, the BAV appliances place the code of the corresponding DCM module into a known area of their memory and in a self-descriptive data structure referred to as the SDD (SDD standing for "Self Describing Device") The FAV type appliance can thus read this memory space and load the DCM module of the BAV type of appliance. An example is that where the BAV appliance is a printer. The DCM control modules thus loaded are registered in the module of the registry of the FAV appliance and thus accessible by the remainder of the network.

30 An SDD type data structure is obligatory in FAV, IAV or BAV type appliances, and is situated at a fixed address in each appliance. On initialization thereof, it thus becomes possible for an FAV type appliance to explore the network so as to load the DCM modules of all the BAV type appliances. It is the manager of DCM modules of the FAV appliance which executes this task.

An SDD data structure also comprises the appliance type (FAV, IAV, BAV, LAV).

- 5 The message transmission system of an appliance comprises:
- the module 26 of the registry (declaration and search for software modules),
 - a message layer, comprising the message dispatcher 29 (sending and receiving of messages), the application programming interface (API) 30 for
- 10 allowing access to the transmission system and an IEEE 1394 bus adaptation sub-layer.

 The IEEE 1394 bus adaptation sub-layer has in particular the role of adapting the transmission of data to the IEEE 1394 protocol, by encapsulating

15 the messages to be transmitted into packets adapted to the IEEE 1394 standard.

 A message comprises three components: the address of the destination software module, the address of the source software module and

20 useful data.

 An address of a software module is composed of an identifier of the node on which it is executed, this identifier being unique to the network, followed by a software module identifier unique to the node in which it is executed. The identifiers of the software modules are allocated by the message

25 transmission system local to a node. The addresses are used by the message dispatcher for forwarding messages to the appropriate software module. According to the present exemplary embodiment, a software module address or identifier (referenced "SEID" in what follows) is an 80-bit binary word. It comprises:

- 30 • a 64-bit appliance identifier stored in the ROM of the appliance in which the software module is executed. In the case of a downloaded module, it is the identifier of the host which is used. The appliance identifier is allocated at the time of manufacture and corresponds to the EUI64 field defined in the IEEE 1394 - 1995 standard. A part of this
- 35 appliance identifier is administered by the IEEE organization and is specific to each manufacturer, the other is chosen by the manufacturer of the

appliance himself, in such a way that each appliance manufactured is provided with a different identifier;

- a local identifier consisting of a serial number allocated directly by the message transmission system of a node, this number being coded on 16 bits and concatenated with the appliance identifier to form the SEID identifier. The message transmission system maintains a counter in this regard. A few serial numbers are reserved (for example from 0x0000 to 0x0005) and used to define particular service modules. For example, the serial number 0x0001 corresponds routinely to the module of the registry of an appliance.

Thus, each software module of the network comprises a distinct and unique SEID identifier. It is however possible to define unique identifiers by means other than those indicated hereinabove.

The module of the registry maintains a database comprising a directory of the software modules available locally at the appliance level. It makes available a programming interface which provides access to the functions of software module registration and module searching according to a list of criteria.

There is a module of the registry in each FAV or IAV type appliance. Inside such an appliance, all the software modules are registered by the module of the local registry. If a software module wishes to be able to be concatenated, it must register itself at the module of the registry. For each software module registered therein, the module of the registry maintains the address thereof in the network and the attributes of this module.

According to a variant embodiment, the module of the registry comprises not the address of the software module, but its serial number.

The attributes of a software module enable it to be characterized. For each software module, these attributes are stored in a table, comprising for each attribute the reference of the latter on 32 bits, its size in bytes, as well as its value.

Table 1 gives a list of predetermined attributes:

<u>Attribute reference</u>	<u>Format of the type</u>	<u>Size</u>	<u>Presence</u>
Type of software module	integer	32 bits	M
HUID identifier	string of bytes	80 bits	M*
Type of appliance	integer	32 bits	M*
Graphical interface	integer	32 bits	Y
Support format	bit field	32 bits	Y
Data format	bit field	32 bits	Y
Appliance manufacturer	character string	15 bytes	M*
Software module manufacturer	character string	15 bytes	Y
Software module version	character string	15 bytes	Y
Audio/video control language	bit field	32 bits	Y

Table 1

5 The software module type represents the prime function of the module. If the software module is a system service module, then the type of the attribute designates the system service itself. The module of the registry is such a service module. If the software module is an FCM, function control manager, the type defines the function: recorder, display, tuner, etc. If the software module is a DCM appliance control manager, the type is "DCM". If the software module possesses an application programming interface ("API") which is incompatible with the remainder of the network, then the type is "Private".

10 The "HUID" identifier is an identifier of the appliance with which a DCM manager is associated or of a function with which an FCM manager is associated.

15 The appliance type associated with the software module is FAV, IAV, BAV or LAV, as already explained.

20 A DCM manager can be associated with a graphical user interface. The attribute "graphical interface" indicates that this is the case, and what as appropriate is the degree of compatibility of the interface of the DCM manager with the various interface levels provided in the network.

The attribute "support format" indicates the type of data storage support which is supported by an appliance. These are for example DVD, DAT, DVHS, DVC supports.

5 The attribute "data format" indicates the format of data which can be manipulated by an appliance. These are for example MPEG2, JPEG, MIDI, ASCII formats.

10 The attributes "appliance manufacturer" and "software module manufacturer" indicate a reference respectively of the manufacturer of the appliance or of the software module whilst the attribute "software module version" indicates the version number of a module.

15 Lastly, the attribute "audio/video command language" indicates the type of languages specific to the software module, in addition to the common HAVI command language already mentioned. The value of the attribute is a 32-bit field, the value of each bit indicating compatibility with a specific command language, for example CAL or AV/C.

The database of a registry module can, according to a variant embodiment, also comprise specific or "private" attributes.

20 It should be noted that the modules of the registries of various appliances are distinct. There is no centralized registry, in which all the software modules would be catalogued. The software modules are registered only at the level of a single registry: their local registry. There is therefore no double registration at several registries.

25

According to the present exemplary embodiment, the application programming interface of a module of the registry comprises five commands, which will be detailed hereinbelow:

30

(a) Software module registration

35 This command is used to add a software module to the database of the local registry or to modify the attributes of a software module already registered. It is used in particular by a software module to register itself when the appliance comprising this element is plugged in.

The software module transmits its SEID identifier and the attributes to the module of the registry. If this identifier is already present, the new attributes replace the old ones. Otherwise, a new entry is created in the local database (local registry). The module of the registry transmits a status message to the software module, depending on the result of the recording: confirmation of recording or error message.

(b) Software module extraction

10 This command is used to read the attributes of a software module, knowing its SEID identifier. A pointer to an area of the random access memory of the appliance, to which area the data must be copied, is transmitted with the extraction request. If the software module is not present in the local database, then the pointer is set to zero and returned by the module of the registry.

15 The module of the registry also returns a status message, which confirms the copying of the attributes, or indicates that the sought-after identifier is not present.

(c) Erase a software module from the registry

20

This command is used to eliminate a software module from the local database. Its SEID identifier is supplied as command parameter. The module of the registry returns a status message confirming the deletion or indicating that the corresponding software module has not been found.

25

(d) Request the list of software modules ('Simple request')

This command makes it possible to determine the identifiers of software modules registered in the set of local registers and meeting certain criteria. According to the present exemplary embodiment, these criteria are the reference of an attribute and the value of an attribute. A parameter of the command is also an operator indicating the way in which the comparison between the value of the attribute specified in the command and the values of the base is to be made (equal, larger, larger or equal, smaller, smaller or equal, different, bitwise logical "AND", bitwise logical "OR", etc.).

30
35

The module of the registry returns as appropriate the list of SEID identifiers of the corresponding software modules. It also returns a status

message indicating the success of the operation (whether or not identifiers have been found), or its failure.

- 5 (e) Perform a boolean operation between two lists of software modules ("multiple request")

This command is used to perform a boolean operation on two lists of identifiers. The command comprises as parameters the requests corresponding to each list. A request can consist of the criteria already mentioned in
10 paragraph (d) (simple request), or of another multiple request.

A parameter of this command is also the relevant boolean operator ("AND" or "OR" within the context of the present exemplary embodiment).

The module of the registry returns as appropriate the list of SEID identifiers as well as a status message informing of the success of the
15 operation or its failure, for any reason whatsoever, such as for example a shortage of resources.

To access other software modules, a software module must know the SEID identifier of its corresponding modules. As regards software modules
20 registered in the same module of the registry, this is not a problem, the requests set out above enabling each software module to extract lists of identifiers from the local database.

A software module accesses the module of the local registry through
25 the local message transmission system. It can also access a distant registry module, and thus send back identifiers of modules registered at other registry modules. To do this, each registry module propagates a request which has been transmitted to it locally to the modules of the registries of all the other appliances. According to the present exemplary embodiment, a distant registry
30 module from which no response is received in a given time interval is ignored.

Each module of the registry receiving the request of the module of the initial registry performs its own search in its local database and returns as appropriate separately the lists of identifiers corresponding to the criteria of the request to the module of the initial registry. The latter then transmits the
35 concatenated list of all the identifiers received to the software module which initiated the request. The software module which initiated the request can then

communicate with the software modules of other appliances and use the resources corresponding to them.

5 Figure 3 is a state diagram of a module of the registry of an appliance. This diagram comprises two states, A and B. State A is a state awaiting a request of a software module. State B is the state awaiting a response to a request made of the modules of distant registries by the module of the local registry.

10 Table 2 gives the events triggering actions undertaken by the module of the local registry and the corresponding starting and finishing states. The references of the events are the same as in Figure 4.

<u>Event</u>	<u>Meaning</u>	<u>Action</u>	<u>Starting state</u>	<u>Finishing state</u>
41	Registration or extraction or erasure of a software module of the base	Determine and transmit response	A	A
42	Request for a 'simple' or 'multiple' list received from a distant registry module.	Determine and transmit response	A	A
43	Request for a 'simple' or 'multiple' list received from a local software module.	Determine response for local base and transmit request to the modules of distant registries	A	B
44	All the responses have been received	Determine and transmit final response to the local software module	B	A

The requests are propagated by the registry module. It should be recalled that the identifier of a registry module is composed of a manufacturer identifier (fixed by IEEE), an appliance identifier (fixed by the manufacturer) and of a registry module identifier, the latter being identical for all the registry modules.

To be able to propagate a request, the registry module of an appliance enrolls all the appliances of the network, whose identifiers it obtains. It then determines those among these appliances which also comprise a registry. In the present exemplary embodiment, these are only FAV or IAV type appliances. Knowing the identifiers of the appliances which can be accessed by the network, the module of the registry reads the type of each appliance in the SDD data structure mentioned above. It thus eliminates the BAV type appliances. The concatenation of each appliance identifier with the local identifier (serial number) fixes common to all the registry modules to obtain the list of complete SEID addresses of all the registry modules. A registry module obtains the list of appliance identifiers by way of the local bus management module (the so-called "CMM"), which monitors the connecting and disconnecting of network appliances. This module reads the list of all the nodes connected to the network from a registry referred to as "TOPOLOGY_MAP" defined by the IEEE 1394-1995 document, paragraph 8.3.2.4.1 This registry is situated in a bus manager appliance (referred to as the "Bus Manager" in the abovesited IEEE document) which updates the registry relating to the topology of the network. The address of this appliance is known by the other appliances by means also described in the IEEE document.

Figure 4 is a diagram indicating the sequencing of the messages when a request issued by a software module A of a first appliance is to be propagated to the registry module of a second appliance, a software module B being registered in the registry of this second appliance.

According to the embodiment presented hereinabove, a request issued by a software module with a view to determining the set of non-local software modules is propagated to all the distant registry modules. According to a variant embodiment, this type of request can also be limited to a group of distant registry modules, for example those of a particular appliance type.

Claims

1. Process for the distributed management of a catalogue of objects
5 in a communication network comprising appliances, the said process comprising the step of registering local objects present in an appliance in a local registry managed at the level of this appliance, the said process being characterized in that it furthermore comprises the steps:
- of formulating, by a local object, a request for a list of objects, the
10 said request being transmitted to the single local registry of the appliance hosting the said local object;
 - of propagating the said request through the said local registry to distant registries;
 - of collecting the responses to the said request by the distant
15 registries and the response of the local registry;
 - of transmitting the responses collected to the local object having formulated the initial request.
2. Process according to Claim 1, characterized in that a local registry
20 comprises for each object registered therein an identifier of this object in the network, this identifier being unique for the network, as well as attributes of the said object.
3. Process according to Claim 2, characterized in that the said
25 identifier (SEID) comprises an identifier of the appliance in which the object is present, this appliance identifier being unique in the network, as well as of a local identifier unique to this object at the level of the said appliance.
4. Process according to Claim 2 or 3, characterized in that a type of
30 request formulated by an object is a request comprising at least one selection criterion pertaining to an object attribute.
5. Process according to Claim 4, characterized in that the function of an object is an attribute stored by a local registry in respect of the said object.



6. Process according to one of the preceding claims, characterized in that the step of propagating a request comprises the step of determining the appliances connected to the network which themselves comprise a registry.

5 7. Process according to Claim 6, characterized in that the step of determining the appliances comprises the determination of the types (FAV, IAV, BAV, LAV) of the appliances present in the network, the type of an appliance indicating whether it hosts a registry or whether it does not host one.

10 8. Process according to one of the preceding claims, characterized in that a type of request formulated by an object is a request comprising selection criteria for at least two lists of objects, as well as at least one operator for processing the said lists.

15 9. Appliance in a communication network comprising means (3, 4) for storing local objects (21 to 28), means (3) for storing a local registry (26) for containing a catalogue of objects local to the appliance, means (5, 31) for connecting the said appliance to the network, the said appliance being characterized in that furthermore comprises:

20 - means (26, 29, 31) for propagating a request for a list of objects formulated by a local object to the local registries of other appliances;
 - means (26) for collecting the responses of the registries of the other appliances and the response of the local registry and for transmitting the said responses to the object having formulated the said request.

25 10. Appliance according to Claim 9, characterized in that it furthermore comprises means for determining the addresses of appliances of the network comprising so-called distant registries.



Abstract

5 The subject of the invention is a process for the distributed management of a catalogue of objects in a communication network comprising appliances, the said process comprising the step of registering local objects present in an appliance in a local registry managed at the level of this appliance.

10 The process in accordance with the invention comprises the steps:
- of formulating, by a local object, a request for a list of objects, the said request being transmitted to the single local registry of the appliance hosting the said local object;
- of propagating the said request through the said local registry to distant registries;
15 - of collecting the responses to the said request by the distant registries and the response of the local registry;
- of transmitting the responses collected to the local object having formulated the initial request.

20 The subject of the invention is also appliances able to be connected to a network in which the above process is implemented.

 The invention applies in particular within the context of home communication networks.

25

Fig. 4.




Fig. 1a




Fig. 1b




Fig. 2




Fig. 3




Fig. 4