

## Description

The invention relates to a process for the simultaneous separation into aromatics and non-aromatics of a heavy hydrocarbon stream and a light hydrocarbon stream, in which process

a) aromatics are extracted in a first extractor from the heavy hydrocarbon stream with the aid of a selective solvent,

b) the selective solvent phase is removed from the raffinate obtained from said first extractor, to yield non-aromatics ex-heavy hydrocarbon stream,

c) aromatics are extracted from the light hydrocarbon stream in a second extractor with the aid of the extract phase obtained from the first extractor,

d) the selective solvent phase is removed from the raffinate obtained from said second extractor to yield aromatics ex-heavy hydrocarbon stream and non-aromatics ex-light hydrocarbon stream.

It has been known for a long time to separate aromatics and non-aromatics present in a hydrocarbon stream by extraction of the aromatics with the aid of a selective solvent, followed by distillative separation of the extract phase obtained in aromatics and solvent. Such a process is very convenient for hydrocarbon streams which have a boiling range below that of the selective solvent, because the difference in boiling points between the aromatics extracted and the selective solvent enables good separation by distillation.

A process of the type to which the invention relates is described in French patent specification No. 792,281. In this known process the selective solvent is never regenerated, in other words, not separated from the extract phase from the second extractor in a pure or almost pure state. The extract phase from the second extractor is conducted to a third extractor and the extract phase of the third extractor is conducted to the first extractor. The heavy non-aromatics are isolated by distillation of the raffinate from the first extractor, the light non-aromatics and the heavy aromatics by distillation of the raffinate of the second extractor and the light aromatics by distillation of the raffinate of the third extractor (see Figure 2 of the French patent specification). Alternatively, the extract phase from the second extractor is conducted to the first extractor. The heavy non-aromatics and light aromatics are isolated by distillation of the raffinate from the first extractor and the heavy aromatics and light non-aromatics by distillation of the raffinate from the second extractor (see Figure 3 of the French patent specification).

The separation of hydrocarbon streams having a boiling range which is close to or comprising the boiling point of the selective solvent is a difficult problem, because distillative separation of aromatics extracted from

such a hydrocarbon stream and selective solvent is impossible, and more complicated methods for separation are needed.

The invention avoids this difficult problem.

According to the invention the process for the simultaneous separation into aromatics and non-aromatics of a heavy hydrocarbon stream and a light hydrocarbon stream is characterized in that the selective solvent being used has a boiling point higher than that of the said light hydrocarbon stream and within the boiling range of the heavy hydrocarbon stream and in that the following steps are applied:-

e) subjecting the extract phase from the second extractor to extractive distillation,

f) separating the bottom fraction of the extractive distillation by distillation in aromatics ex-light hydrocarbon stream and selective solvent and

g) recycling the selective solvent obtained in step f at least partially to the first extractor.

A light hydrocarbon stream in the context of this specification and claims is a hydrocarbon stream which has a boiling range which is lower than the boiling point (or if appropriate boiling range) of the selective solvent used.

A heavy hydrocarbon stream in the context of this specification and claims is a hydrocarbon stream which has a boiling range which is higher than that of the light hydrocarbon stream. Although there may be some overlap of the boiling range of the light and the heavy hydrocarbon streams, it is preferred that no such overlap exists. The boiling range of the heavy hydrocarbon stream comprises the boiling point (or if appropriate boiling range) of the selective solvent used.

Light hydrocarbon streams which boil in the range from 50—170°C, such as gasoline fractions, which may be straight run or have been obtained from a conversion process, in particular from catalytic reforming or from a pyrolysis process, are preferred.

Very suitable heavy hydrocarbon streams are boiling in the range from 150 to 350°C, such as kerosines, gas oils, which may have been obtained as straight run fractions or from a catalytic or non-catalytic process e.g. thermal cracking, catalytic cracking and/or hydrocracking.

In the process according to the invention use may in principle be made of a variety of selective solvents, for example furfural, phenol, sulfoxides, fatty acid alkyl amides. Preferred is the use of solvents which at least in part are of the sulfolane, the glycol, the morpholine and/or the pyrrolidone/piperidone type; i.e. sulfolane (tetrahydrothiophene 1,1-dioxide), the unsaturated analogues thereof and the derivatives of both, as described, for example, in U.K. Patent Specification No. 625,505; lower polyalkylene glycols (such as diethylene, triethylene, tetraethylene and dipropylene glycol); morpholine as well as substituted morpholines such as formyl-morpholine; pyrrolidone and piperidone, as well

as their derivatives (such as N-alkyl-, in particular N-methylpyrrolidone and -piperidone). If desired, the selective solvent may contain a quantity of a substance, such as water, which has a favourable effect on the selectivity and/or the solvent power thereof. The use of a selective solvent which totally or substantially consists of sulfolane is in particular preferred.

The extractions in the first and second extractor are preferably carried out in multi-stage; use may be made of any suitable equipment. The extractions may e.g. be carried out with the aid of a number of mixing and settling steps. It is preferred to carry out the extractions by means of an extraction column, in particular a rotating disc contactor such as described e.g. in U.K. patent specification 659,241.

The raffinates from the first and second extractor contain a small amount of the selective solvent phase which is to be removed. It is preferred to wash these raffinates with water in order to remove the selective solvent phase therefrom.

The extract phase from the first extractor which contains aromatics ex-heavy hydrocarbon stream (also indicated as heavy aromatics) is used as the extracting solvent for the light hydrocarbon stream in the second extractor. As a result of this extraction a raffinate is obtained which comprises all or the greater part of the heavy aromatics and the non-aromatics ex-light hydrocarbon stream (also indicated as light non-aromatics) together with a small amount of selective solvent, the extract phase containing all or the greater part of the aromatics ex-light hydrocarbon stream (also indicated as light aromatics). The raffinate can (after having been washed with water) if desired be easily separated in light non-aromatics and heavy aromatics by distillation because of the difference in boiling ranges between these fractions.

The extract phase from the second extractor which contains light aromatics and part of the light non-aromatics is subjected to extractive distillation in order to remove the light non-aromatics therefrom. In an extractive distillation hydrocarbons at least partially in the vapour phase are contacted with liquid selective solvent, as a result of which aromatics are separated from non-aromatics, the latter being removed in the vapour form.

The overhead fraction of the extractive distillation, which contains light non-aromatics and a small amount of light aromatics, is very suitably condensed, the water layer (if any) is removed, and the hydrocarbon layer is recirculated to the second extractor.

The greater part of the light aromatics remains in the bottom fraction of the extractive distillation. According to the invention these light aromatics are separated from the selective solvent by distillation of the bottom fraction of the extractive distillation.

This distillation is very conveniently carried

out in a separate column, very suitably under reduced pressure. Preferably steam is introduced to improve the separation. The overhead product which contains steam and light aromatics is cooled, the water layer is separated and the light aromatics (which may be partially recycled to the distillation column) are removed.

As a matter of course the amount of fresh water to be introduced into the system can be kept limited by reintroduction into the system of at least part of the aqueous liquids becoming available from the water-washes of the raffinates of the extractors, from the top product of the extractive distillation and from the top product of the distillation in which the selective solvent is separated from the light aromatics. It is in particular attractive to use at least part of the water phase obtained as top product of the distillation in which the selective solvent is separated from the light aromatics as washing medium for the raffinates.

The selective solvent obtained after removal of the light aromatics is at least partially recycled to the first extractor. If desired part thereof may be recycled to the second extractor, and may be introduced therein together with the extract phase from the first extractor and/or at a point nearer to the entrance of the light hydrocarbon stream into the second extractor. If desired part of the selective solvent may also be introduced into the extractive distillation column.

The invention will be illustrated with reference to the accompanying drawing, in which an embodiment of the invention is depicted.

A heavy hydrocarbon stream is introduced via line 1 into the first extractor 2, into which first extractor selective solvent is introduced via line 3. Raffinate is leaving extractor 2 via line 4, and is water-washed (not shown). The extract phase is removed via line 5 and introduced into the second extractor 6. A light hydrocarbon stream is introduced into extractor 6 via line 7. In the embodiment of the invention depicted selective solvent is introduced into extractor 6 via line 8. The raffinate which leaves extractor 6 via line 9, is water-washed (not shown) and is distilled (not shown) to yield heavy aromatics and light non-aromatics. The extract phase is leaving extractor 6 via line 10 and is led via heat-exchanger 11 to extractive distillation column 12.

The top product thereof is forwarded to a separation vessel 26 via line 13. From this vessel the water layer is removed via 15, and the hydrocarbon layer is recycled to extractor 6 via line 14. The bottom product from the extractive distillation column 12 is forwarded via line 16 to distillation column 17. Steam is introduced into this column via line 18. The top product is led to separation vessel 20 via line 19. From this vessel the water layer is removed via line 23 and the hydrocarbon layer (light aromatics) is partly recycled to the distillation

column 17 via line 21 and partly removed via line 22. The regenerated selective solvent obtained as bottom product from distillation column 17 is removed therefrom via line 24, and led via heat exchangers 25 and 11 partly to extractor 2 and partly to extractor 6.

#### Example

61 t/d of a kerosine fraction with a boiling range of 190—240°C, which contains 20% w aromatics, is fed to extractor 2 via line 1. The extractor is a rotating disc contactor of the type described in British patent specification 659,241. The extraction is carried out at a temperature of 125°C with sulfolane forwarded via line 3 in an amount of 555 t/d. The raffinate leaving the extractor via line 4 is washed with water yielding 37 t/d of heavy non-aromatics (the aromatics content is below 1% w). To extractor 6 (which is also rotating disc contactor) there are fed via line 7 122 t/d of a light straight run hydrocarbon fraction with a boiling range of 55—85°C which contains 5% w benzene. The extract phase from extractor 2 (579 t/d) is introduced into extractor 6 via line 5. The temperature in extractor 6 is 90°C. Via line 8 430 t/d sulfolane is also introduced into extractor 6. The raffinate phase leaving the extractor via line 9 is washed with water yielding 134 t/d raffinate. The extract phase of extractor 6 (1025 t/d) is fed (after being heat-exchanged in heat exchanger 11) to extractive distillation column 12 via line 10. The extractive distillation in column 12 is carried out at a pressure of 0.2 bar and a bottom temperature of 175°C. The overhead product is forwarded via line 13 to separator 26 and separated in a water phase and a hydrocarbon phase; the hydrocarbon phase is recycled to extractor 6 via line 14. The bottom product of column 12 is fed via line 16 to distillation column 17 which is heated with steam from line 18. The top product is led via line 19 to separator 20, the hydrocarbon phase (light aromatics) obtained therein is partly recycled to the distillation column via line 21, and partly removed via line 22 in an amount of 12 t/d. The raffinate emerging via line 9 from extractor 6 (which contains less than 100 ppm benzene) is water washed and distilled yielding 24 t/d heavy aromatics and 110 t/d food-grade hexane.

#### Claims

1. A process for the simultaneous separation into aromatics and non-aromatics of a heavy hydrocarbon stream and a light hydrocarbon stream in which process

a) aromatics are extracted in a first extractor from the heavy hydrocarbon stream with the aid of a selective solvent,

b) the selective solvent phase is removed from the raffinate obtained from said first extractor, to yield non-aromatics ex-heavy hydrocarbon stream,

c) aromatics are extracted from the light hydrocarbon stream in a second extractor with the aid of the extract phase obtained from the first extractor,

d) the selective solvent phase is removed from the raffinate obtained from said second extractor to yield aromatics ex-heavy hydrocarbon stream and non-aromatics ex-light hydrocarbon stream, characterized in that the selective solvent being used has a boiling point higher than that of the said light hydrocarbon stream and within the boiling range of the heavy hydrocarbon stream and in that the following steps are applied:-

e) subjecting the extract phase from the second extractor to extractive distillation,

f) separating the bottom fraction of the extractive distillation by distillation in aromatics ex-light hydrocarbon stream and selective solvent and

g) recycling the selective solvent obtained in step f at least partially to the first extractor.

2. A process according to claim 1, characterized in that the selective solvent which has a higher boiling point than that of said light hydrocarbon stream consists totally or substantially of sulfolane.

3. A process according to claim 1 or 2, characterized in that the light hydrocarbon stream boils in the range from 50—170°C.

4. A process according to any one of the preceding claims, characterized in that the heavy hydrocarbon stream boils in the range from 150—350°C.

5. A process according to any one of the preceding claims characterized in that the selective solvent phase is removed from the raffinates from the first and/or second extractor by washing with water.

6. A process according to any one of the preceding claims, characterized in that the aromatics ex-heavy hydrocarbon stream and the non-aromatics ex-light hydrocarbon stream obtained in step d) are separated by distillation.

7. A process according to any one of the preceding claims in which the overhead product of the extractive distillation is at least partially recycled to the second extractor.

8. A process according to any one of the preceding claims, characterized in that part of the selective solvent obtained in step f) is recycled to the second extractor.

#### Revendications

1. Un procédé pour la séparation simultanée en aromatiques et non-aromatiques d'un courant lourd d'hydrocarbures et d'un courant léger d'hydrocarbures, dans lequel

a) les composés aromatiques sont extraits dans un premier extracteur du courant lourd d'hydrocarbures à l'aide d'un solvant sélectif,

b) la phase de solvant sélectif est séparée du raffinat obtenu à partir du premier extracteur, pour donner des composés non-aromatiques

column 17 via line 21 and partly removed via line 22. The regenerated selective solvent obtained as bottom product from distillation column 17 is removed therefrom via line 24, and led via heat exchangers 25 and 11 partly to extractor 2 and partly to extractor 6.

#### Example

61 t/d of a kerosine fraction with a boiling range of 190—240°C, which contains 20% w aromatics, is fed to extractor 2 via line 1. The extractor is a rotating disc contactor of the type described in British patent specification 659,241. The extraction is carried out at a temperature of 125°C with sulfolane forwarded via line 3 in an amount of 555 t/d. The raffinate leaving the extractor via line 4 is washed with water yielding 37 t/d of heavy non-aromatics (the aromatics content is below 1% w). To extractor 6 (which is also rotating disc contactor) there are fed via line 7 122 t/d of a light straight run hydrocarbon fraction with a boiling range of 55—85°C which contains 5% w benzene. The extract phase from extractor 2 (579 t/d) is introduced into extractor 6 via line 5. The temperature in extractor 6 is 90°C. Via line 8 430 t/d sulfolane is also introduced into extractor 6. The raffinate phase leaving the extractor via line 9 is washed with water yielding 134 t/d raffinate. The extract phase of extractor 6 (1025 t/d) is fed (after being heat-exchanged in heat exchanger 11) to extractive distillation column 12 via line 10. The extractive distillation in column 12 is carried out at a pressure of 0.2 bar and a bottom temperature of 175°C. The overhead product is forwarded via line 13 to separator 26 and separated in a water phase and a hydrocarbon phase; the hydrocarbon phase is recycled to extractor 6 via line 14. The bottom product of column 12 is fed via line 16 to distillation column 17 which is heated with steam from line 18. The top product is led via line 19 to separator 20, the hydrocarbon phase (light aromatics) obtained therein is partly recycled to the distillation column via line 21, and partly removed via line 22 in an amount of 12 t/d. The raffinate emerging via line 9 from extractor 6 (which contains less than 100 ppm benzene) is water washed and distilled yielding 24 t/d heavy aromatics and 110 t/d food-grade hexane.

#### Claims

1. A process for the simultaneous separation into aromatics and non-aromatics of a heavy hydrocarbon stream and a light hydrocarbon stream in which process

a) aromatics are extracted in a first extractor from the heavy hydrocarbon stream with the aid of a selective solvent,

b) the selective solvent phase is removed from the raffinate obtained from said first extractor, to yield non-aromatics ex-heavy hydrocarbon stream,

c) aromatics are extracted from the light hydrocarbon stream in a second extractor with the aid of the extract phase obtained from the first extractor,

d) the selective solvent phase is removed from the raffinate obtained from said second extractor to yield aromatics ex-heavy hydrocarbon stream and non-aromatics ex-light hydrocarbon stream,

characterized in that the selective solvent being used has a boiling point higher than that of the said light hydrocarbon stream and within the boiling range of the heavy hydrocarbon stream and in that the following steps are applied:-

e) subjecting the extract phase from the second extractor to extractive distillation,

f) separating the bottom fraction of the extractive distillation by distillation in aromatics ex-light hydrocarbon stream and selective solvent and

g) recycling the selective solvent obtained in step f at least partially to the first extractor.

2. A process according to claim 1, characterized in that the selective solvent which has a higher boiling point than that of said light hydrocarbon stream consists totally or substantially of sulfolane.

3. A process according to claim 1 or 2, characterized in that the light hydrocarbon stream boils in the range from 50—170°C.

4. A process according to any one of the preceding claims, characterized in that the heavy hydrocarbon stream boils in the range from 150—350°C.

5. A process according to any one of the preceding claims characterized in that the selective solvent phase is removed from the raffinate from the first and/or second extractor by washing with water.

6. A process according to any one of the preceding claims, characterized in that the aromatics ex-heavy hydrocarbon stream and the non-aromatics ex-light hydrocarbon stream obtained in step d) are separated by distillation.

7. A process according to any one of the preceding claims in which the overhead product of the extractive distillation is at least partially recycled to the second extractor.

8. A process according to any one of the preceding claims, characterized in that part of the selective solvent obtained in step f) is recycled to the second extractor.

#### Revendications

1. Un procédé pour la séparation simultanée en aromatiques et non-aromatiques d'un courant lourd d'hydrocarbures et d'un courant léger d'hydrocarbures, dans lequel

a) les composés aromatiques sont extraits dans un premier extracteur du courant lourd d'hydrocarbures à l'aide d'un solvant sélectif,

b) la phase de solvant sélectif est séparée du raffinat obtenu à partir du premier extracteur, pour donner des composés non-aromatiques



provenant du courant lourd d'hydrocarbures,

c) les composés aromatiques sont extraits du courant léger d'hydrocarbures dans un second extracteur à l'aide de la phase d'extrait obtenue dans le premier extracteur,

d) la phase de solvant sélectif est séparée du raffinat obtenu à partir du second extracteur pour donner des composés aromatiques provenant du courant lourd d'hydrocarbures et des composés non-aromatiques provenant du courant léger d'hydrocarbures, caractérisé en ce que le solvant sélectif utilisé a un point d'ébullition plus élevé que celui du courant léger d'hydrocarbures et compris dans l'intervalle d'ébullition du courant lourd d'hydrocarbures et que l'on utilise les étapes suivantes:

e) on soumet la phase d'extrait du second extracteur à une distillation extractive,

f) on sépare la fraction résiduelle de la distillation extractive par distillation en composés aromatiques provenant du courant léger d'hydrocarbures et en solvant sélectif et

g) on recycle le solvant sélectif obtenu dans l'étape f au moins partiellement au premier extracteur.

2. Un procédé selon la revendication 1, caractérisé en ce que le solvant sélectif qui a un point d'ébullition plus élevé que celui du courant léger d'hydrocarbures est constitué totalement ou essentiellement de sulfolane.

3. Un procédé selon la revendication 1 ou 2, caractérisé en ce que le courant léger d'hydrocarbures bout dans l'intervalle de 50—170°C.

4. Un procédé selon l'une quelconque des revendications précédentes, caractérisé en ce que le courant lourd d'hydrocarbures bout dans l'intervalle de 150—350°C.

5. Un procédé selon l'une quelconque des revendications précédentes, caractérisé en ce que la phase de solvant sélectif est séparée des raffinats du premier extracteur et/ou du second par lavage à l'eau.

6. Un procédé selon l'une quelconque des revendications précédentes, caractérisé en ce que les composés aromatiques provenant du courant lourd d'hydrocarbures et les composés non-aromatiques provenant du courant léger d'hydrocarbures obtenus dans l'étape d) sont séparés par distillation.

7. Un procédé selon l'une quelconque des revendications précédentes, dans lequel le produit de tête de la distillation extractive est au moins partiellement recyclé au second extracteur.

8. Un procédé selon l'une quelconque des revendications précédentes, caractérisé en ce qu'une partie du solvant sélectif obtenu dans l'étape f) est recyclée au second extracteur.

#### Patentansprüche

1. Ein Verfahren zur gleichzeitigen Auftrennung eines schweren Kohlenwasserstoffstroms und eines leichten Kohlenwasserstoffstroms in

Aromaten und Nicht-Aromaten, in welchem Verfahren

a) Aromaten in einer ersten Extraktionsvorrichtung mittels eines selektiven Lösungsmittels aus dem schweren Kohlenwasserstoffstrom extrahiert werden,

b) die Phase des selektiven Lösungsmittels aus dem Raffinat entfernt wird, welches aus der besagten ersten Extraktionsvorrichtung erhalten wird, um aus diesem Raffinat Nicht-Aromaten aus dem schweren Kohlenwasserstoffstrom zu gewinnen,

c) aus dem leichten Kohlenwasserstoffstrom in einer zweiten Extraktionsvorrichtung Aromaten mit der Extraktphase extrahiert werden, welche in der ersten Extraktionsvorrichtung erhalten worden ist,

d) die Phase des selektiven Lösungsmittels aus dem Raffinat entfernt wird, welches aus der zweiten Extraktionsvorrichtung erhalten wird, um aus dem Raffinat Aromaten des schweren Kohlenwasserstoffstroms und Nicht-Aromaten des leichten Kohlenwasserstoffstroms zu gewinnen,

dadurch gekennzeichnet, daß das verwendete selektive Lösungsmittel einen Siedepunkt aufweist, welcher höher liegt als derjenige des leichten Kohlenwasserstoffstroms und innerhalb des Siedebereiches des schweren Kohlenwasserstoffstroms liegt, und daß die nachstehenden Verfahrensschritte angewendet werden:

e) die aus der zweiten Extraktionsvorrichtung abgezogene Extraktphase wird einer extraktiven Destillation unterworfen,

f) die aus der Stufe der extraktiven Destillation erhaltene Bodenfraktion wird mittels Destillation in Aromaten aus dem leichten Kohlenwasserstoffstrom und selektives Lösungsmittel aufgetrennt und

g) das in Stufe f) erhaltene selektive Lösungsmittel wird mindestens teilweise im Kreislauf in die erste Extraktionsvorrichtung zurückgeführt.

2. Ein Verfahren gemäß Anspruch 1, dadurch gekennzeichnet, daß das selektive Lösungsmittel, welches einen höheren Siedepunkt als der leichte Kohlenwasserstoffstrom aufweist, vollständig oder im wesentlichen aus Sulfolan besteht.

3. Ein Verfahren gemäß Anspruch 1 oder 2, dadurch gekennzeichnet, daß der leichte Kohlenwasserstoffstrom im Bereich von 50 bis 170°C siedet.

4. Ein Verfahren gemäß irgendeinem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß der schwere Kohlenwasserstoffstrom im Bereich von 150 bis 350°C siedet.

5. Ein Verfahren gemäß irgendeinem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß die Phase des selektiven Lösungsmittels aus den von der ersten und/oder zweiten Extraktionsvorrichtung erhaltenen Raffinaten durch eine Wasserwäsche entfernt wird.

6. Ein Verfahren gemäß irgendeinem der vorhergehenden Ansprüche, dadurch gekennzeichnet,



zeichnet, daß die in Stufe d) erhaltenen Aromaten aus dem schweren Kohlenwasserstoffstrom und die Nicht-Aromaten aus dem leichten Kohlenwasserstoffstrom mittels Destillation voneinander getrennt werden.

7. Ein Verfahren gemäß irgendeinem der vorhergehenden Ansprüche, in welchem das Kopfprodukt aus der Stufe der extraktiven Destillation mindestens teilweise im Kreislauf an der

zweiten Extraktionsvorrichtung zurückgeführt wird.

8. Ein Verfahren gemäß irgendeinem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß ein Teil des in Stufe f) gewonnenen selektiven Lösungsmittels im Kreislauf in die zweite Extraktionsvorrichtung zurückgeführt wird.

5

10

15

20

25

30

35

40

45

50

55

60

65

6



\* C L N S \*