



- (51) International Patent Classification: Not classified
- (21) International Application Number: PCT/US2014/055713
- (22) International Filing Date: 15 September 2014 (15.09.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 14/028,468 16 September 2013 (16.09.2013) US
- (71) Applicant: MKU PVT LTD [IN/IN]; 103, Chandralok Complex 26/72-D, Birhana Road, Kanpur-UP 2008 001 (IN).
- (72) Inventor; and
- (71) Applicant (for LS only): KLOKE, Daniel C. [US/US]; Sheppard, Mullin, Richter & Hampton LLP, 379 Lytton Avenue, Palo Alto, California 94301 (US).
- (72) Inventor: KHANDELWAL, Manish; 76, Gandhigram, UP Kanpur 208 007 (IN).
- (74) Agents: KLOKE, Daniel C. et al.; Sheppard, Mullin, Richter & Hampton LLP, 379 Lytton Avenue, Palo Alto, California 94301 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,

[Continued on next page]

(54) Title: QUICKLY RELEASABLE VEST




FIG. 1

(57) Abstract: A quickly releasable vest capable of protecting a torso portion of a user is disclosed. The quickly releasable vest includes a self locking buckle assembly, a ferrule, an elongated strip, and a socket member. The self locking buckle assembly comprises a wedge fork with a base portion and a body portion, the base portion comprising a security means for webbing and the body portion comprising a pair of legs and a ferrule guide member. The ferrule is adapted to be slidably disposed on the ferrule guide member. A proximal end portion of the strip is connected to a tape guide member of the ferrule. An opening on the socket member facilitates removably retaining and locking of a prong on each of the pair of legs. The wedge fork, ferrule, and elongated strip is disposed on a torso panel and the socket member is disposed on the other torso panel.



TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*