

PICTURE ANNOTATION METHOD, APPARATUS, PROCESSING DEVICE, AND SYSTEM

Technical Field

The present specification belongs to the field of image processing technologies, and in particular, to a picture annotation method, apparatus, processing device, and system.

Background

With the continuous development of image processing technologies, there are increasingly more scenarios that can use an image processing means to facilitate people's work and life. For example, in traffic monitoring, captured images may be used to determine whether vehicles or drivers violate traffic rules. Alternatively, in identification of traffic accidents or vehicle insurance, it is necessary to process images of damaged parts of vehicles to determine the degree of vehicle damages.

In these scenarios, it may be necessary to annotate photographed images, for example, annotate vehicle violation locations, vehicle damage locations, and the like. Generally, an image annotation is performed manually. However, when there are a large number of images, for example, some businesses need multiple pictures photographed continuously, and the continuous images need to be annotated, content of pictures will be slightly different as a photographer moves or content is delayed with the photographing time although the pictures have the same photographing subject. It takes a long time to annotate subjects to be annotated in this series of similar pictures one by one, and the annotation efficiency may be relatively low.

Summary of the Invention

An objective of embodiments of the present specification is to provide a picture annotation method, apparatus, processing device, and system, for improving the accuracy and efficiency of picture annotation.

In one aspect, a picture annotation method is provided in an embodiment of the present specification, including:

converting multiple pictures in a received set of pictures to be annotated into a video image;

performing video annotation on the video image to obtain an annotation result; and

5 using the annotation result as an annotation result of each picture in the set of pictures to be annotated according to a correspondence between a video frame in the video image and a picture in the set of pictures to be annotated.

In another aspect, a picture annotation apparatus is provided in the present specification, including:

10 a video conversion module configured to convert multiple pictures in a received set of pictures to be annotated into a video image;

a video annotation module configured to perform video annotation on the video image to obtain an annotation result; and

15 an annotation association module configured to use the annotation result as an annotation result of each picture in the set of pictures to be annotated according to a correspondence between a video frame in the video image and a picture in the set of pictures to be annotated.

In still another aspect, a picture annotation data processing device is provided in an embodiment of the present specification, including: at least one processor and a memory for storing processor-executable instructions which, when executed by the processor, implement the above
20 picture annotation method.

In yet another aspect, a picture annotation system is provided in an embodiment of the present specification, including: at least one processor and a memory for storing processor-executable instructions which, when executed by the processor, implement the above picture annotation method.

In the picture annotation method, apparatus, processing device, and system provided in the present specification, annotation to multiple continuous pictures is converted into video annotation. After multiple pictures to be annotated are converted into a video, video annotation may be performed on the video by using a video annotation algorithm, and an annotation result can be quickly obtained based on a video frame. Finally, a video result is mapped to original pictures to obtain annotation results of the original group of pictures. The picture annotation is converted to video annotation, and the efficiency and accuracy of picture annotation can be improved by using the continuity of the video.

Brief Description of the Drawings

To describe the technical solutions in the embodiments of the present application or the prior art more clearly, the accompanying drawings required for describing the embodiments or the prior art are briefly introduced below. It is apparent that the accompanying drawings described in the following are merely some embodiments of the present application, and those of ordinary skill in the art may still derive other drawings from these accompanying drawings without creative efforts.

FIG. 1 is a schematic flowchart of an embodiment of a picture annotation method according to an embodiment of the present specification;

FIG. 2 is a schematic flowchart of picture annotation according to another embodiment of the present specification;

FIG. 3 is a schematic flowchart of picture annotation according to another embodiment of the present specification;

FIG. 4 is a schematic flowchart of frame-selection annotation of a picture according to an embodiment of the present specification;

FIG. 5 is a schematic diagram of a modular structure of an embodiment of a picture annotation apparatus according to the present specification;

FIG. 6 is a schematic structural diagram of a picture annotation apparatus according to another embodiment of the present specification;

FIG. 7 is a schematic structural diagram of a picture annotation apparatus according to another embodiment of the present specification; and

5 FIG. 8 is a block diagram of a hardware structure of a picture annotation server according to an embodiment of the present specification.

Detailed Description

In order to enable those skilled in the art to better understand the technical solutions in the present specification, the technical solutions in the embodiments of the present specification will
10 be described clearly and completely with reference to the accompanying drawings in the embodiments of the present specification. It is apparent that the described embodiments are merely some of rather than all the embodiments of the present application. Based on the embodiments of the present specification, all other embodiments derived by those of ordinary skill in the art without any creative efforts shall fall within the protection scope of the present specification.

15 Picture annotation may be performing annotation on a specified text, image, and the like in a picture. For example, the specified text, image, or other content in the picture may be annotated in the form of frame selection. The annotated picture may be used for vehicle violation query, vehicle loss assessment, target tracking, and the like. Some scenarios may require annotation of continuously photographed pictures to obtain corresponding information, especially for acquisition
20 of information about objects in motion. For example, for vehicle violation capture, it is necessary to continuously photograph vehicles to determine whether vehicles are in violation. Generally, picture annotation may require manual annotation, especially for the annotation of pictures obtained by continuous photographing, the workload is relatively large.

FIG. 1 is a schematic flowchart of an embodiment of a picture annotation method according to
25 an embodiment of the present specification. Although the present specification provides method

operation steps or apparatus structure as described in the following embodiments or accompanying drawings, more steps or module units or partially fewer operation steps or module units after merging may be included in the method or apparatus based on conventional or non-creative efforts. In steps or structures where there is no necessary causal relationship logically, the performing order of these steps or the modular structure of the apparatus is not limited to the performing order or modular structure shown in the embodiments of the present specification or the accompanying drawings. When the method or modular structure is applied in an actual apparatus, server, or terminal product, it can be performed sequentially or in parallel according to the method or modular structure shown in the embodiments or the accompanying drawings (for example, a parallel processor or multi-thread processing environment, or even an environment including distributed processing and server cluster).

A specific embodiment is shown in FIG. 1. In an embodiment of a picture annotation method provided in the present specification, the method is applicable to a terminal device capable of performing image processing, for example, a terminal such as a computer, a tablet, and a server.

The method may include the following steps.

In step 102, multiple pictures in a received set of pictures to be annotated are converted into a video image.

In a specific implementation process, if a user needs to annotate a series of pictures, pictures that need to be annotated may be uploaded to a picture annotation apparatus through a client such as a smart phone, a computer, a smart wearable device, and a tablet computer. In the embodiment of the present specification, a series of pictures obtained by continuous photographing can be annotated mainly, that is, a set of pictures to be annotated may include a group of pictures obtained by continuous photographing, for example, a group of pictures captured continuously by traffic monitoring, a group of pictures photographed continuously on a damaged part of a vehicle rapidly, and so on. Generally, a group of pictures in the set of pictures to be annotated have the same

photographing subject. As a photographer moves or content delays with the photographing time, content of each picture may vary slightly. After the set of pictures to be annotated is received, multiple pictures in the set of pictures to be annotated may be converted into a video image, that is, a group of continuously photographed multiple pictures in the set of pictures to be annotated
5 may be converted into a video, and a video converter or another video conversion method may be used for conversion, which is not specifically limited in the embodiment of the present specification.

In some embodiments of the present specification, before converting multiple pictures in a received set of pictures to be annotated into a video image, the method further includes:

10 receiving a set of pictures to be processed, wherein the set of pictures to be processed includes at least one group of multiple pictures obtained by continuous photographing; and

receiving a picture annotation request, wherein the picture annotation request includes the set of pictures to be annotated, and the set of pictures to be annotated is a group of continuously photographed multiple pictures in the set of pictures to be processed.

15 In the specific implementation process, a user can upload multiple pictures, that is, a set of pictures to be processed. The set of pictures to be processed may include one or more groups of pictures obtained by continuous photographing, and each group of pictures continuously photographed may be pictures with the same photographing subject and similar picture content. The user can choose to perform picture annotation on multiple pictures specified in the set of
20 pictures to be processed. After receiving the multiple pictures selected by the user, the picture annotation apparatus may perform picture annotation on the pictures selected by the user, for example, convert the multiple long pictures selected by the user into a video image, and then perform picture annotation processing.

For example, the user uploads 20 pictures to the picture annotation apparatus through the client,
25 10 of which are pictures photographed for traffic monitoring of vehicle A, the other 10 are pictures

photographed for traffic monitoring of vehicle B, and a set of 20 pictures can be referred to as the above set of pictures to be processed. The user selects 10 pictures photographed for traffic monitoring of vehicle A to request picture annotation. A set of the 10 pictures photographed for traffic monitoring of vehicle A may be referred to as a set of pictures to be annotated, and the picture annotation apparatus, after receiving the picture annotation request sent by the user, may convert the 10 pictures in the picture annotation request into a video image, and the picture annotation processing may be performed based on the video image.

Of course, a group of continuously photographed multiple pictures in the set of pictures to be annotated may be a complete group of pictures, or some pictures in a group of pictures photographed continuously. For example, in the above example, 6 pictures among 10 pictures photographed for traffic monitoring of vehicle A are selected for annotation, and the specific selection may be set according to actual needs, which is not specifically limited in the embodiment of the present specification. Based on the selection of the user, after the specified continuously photographed pictures are converted into a video image, the picture annotation is performed, which improves the efficiency of picture annotation, and at the same time has relatively high flexibility. For example, the user may use clearer pictures in a group of continuously photographed pictures as a set of pictures to be annotated.

Moreover, in some embodiments of the present specification, before converting multiple pictures in a received set of pictures to be annotated into a video image, the method further includes:

determining whether the multiple pictures in the set of pictures to be annotated are a group of continuously photographed pictures, and if so, converting the multiple pictures in the set of pictures to be annotated into a video image.

In the specific implementation process, after the set of pictures to be annotated is received, it can be determined whether the pictures in the set of pictures to be annotated are a group of

continuously photographed pictures. The photographing content of a group of continuously photographed pictures is relatively close, and may have slight differences. Similarities between various pictures may be calculated, if the similarity is greater than a preset value, they are considered as a group of similar pictures. Alternatively, it can be determined, by viewing photographing content of each picture in the set of pictures to be annotated, and the like, whether the pictures in the set of pictures to be annotated are a group of continuously photographed pictures. Of course, other methods can be used for determination according to actual needs, which is not specifically limited in the embodiment of the present specification. If it is determined that the pictures in the set of pictures to be annotated are a group of continuously photographed pictures, the pictures in the set of pictures to be annotated are converted into a video image, and the pictures are annotated by using the method provided in the embodiment of the present specification. If it is determined that the pictures in the set of pictures to be annotated are not a group of continuously photographed pictures, the pictures in the set of pictures to be annotated may not be suitable for the picture annotation method provided in the embodiment of the present specification, but may be annotated by adopting another method such as a manual annotation method, which is not specifically limited in the embodiments of the present specification.

The embodiment of the present specification mainly focuses on the annotation of multiple pictures photographed continuously. After pictures that need to be annotated are received, it may be first determined whether the pictures belong to a group of pictures photographed continuously, and if so, the pictures can be converted into a video image, and automatic annotation is performed by using the video to improve the annotation efficiency of continuously photographed pictures.

In step 104, video annotation is performed on the video image to obtain an annotation result.

In a specific implementation process, after multiple pictures in the set of pictures to be annotated are converted into a video image, video annotation may be performed on the video image. For example, the video image may be annotated by using a video tracking model, a video

tracking algorithm, or the like. For example, a license plate number or a specified graph, text, and the like may be defined as a tracking object, and tracking annotation is performed on the video image to obtain an annotation result of the video image. For example, historical data such as multiple groups of annotated pictures may be used in advance to train the video tracking model, after the video tracking model is constructed, the established video tracking model is used to perform video tracking annotation on the pictures in the set of pictures to be annotated uploaded by the user. The video tracking model may track motion information of objects in adjacent video frames, for example, track a specified target in the video in various video frames.

The annotation may be understood as a method of marking the specified content in the picture or video, and the annotation result may be understood as annotation information text such as a table. The annotation result may include information such as location coordinates of the annotation, content of the annotation, and form of the annotation (such as frame selection and bubble), for example, a video frame at which second has an annotation, the location coordinates of the annotation, the content of the annotation, the form of the annotation (such as frame-selection annotation), and the like. Annotation information corresponding to all video frames is saved as an annotation result.

In some embodiments of the present specification, the following method may be used to perform video annotation on the video image:

acquiring an annotation sample video frame in the video image, using the annotation sample video frame as a video annotation sample, and performing video annotation on another video frame in the video image to obtain the annotation result.

In a specific implementation process, the embodiment of the present specification may obtain a marked video frame from a video image and regard it as an annotation sample video, that is, the annotation sample video frame can be understood as a video frame with annotation information in the video image, and may be used as a basis and reference for annotation of another frame of video

in the video image. A video frame can be understood as a frame of video. Of course, the annotation sample video frame may be a frame of video or multiple frames of video, which may be specifically set according to actual needs, which is not specifically limited in the embodiment of the present specification. For example, one or more frames of video with annotation information may be acquired from the video image and regarded as an annotation sample video frame. If the annotation sample video frame has multiple frames of video, a common point of annotations of the multiple frames of video may be used as a reference basis to annotate another frame of video. After the annotation sample video frame is acquired, the annotation sample video frame may be used as a video annotation sample, and annotation is performed on another video frame in the video image to obtain the annotation result. For example, a video tracking model, a video tracking algorithm, or the like may be used to annotate another video frame in the video image with reference to the annotation sample video frame.

By acquiring an annotation sample video frame with annotation information in the video as an annotation sample, another video frame in the video is annotated. An annotation result can be quickly obtained based on the video frame, and the video result is finally mapped to the original pictures to obtain annotation results of the original group of pictures. The annotation to multiple pictures is converted to annotation to a picture, and annotation is performed on another video frame, thus improving the efficiency and accuracy of picture annotation.

In step 106, the annotation result is used as an annotation result of each picture in the set of pictures to be annotated according to a correspondence between a video frame in the video image and a picture in the set of pictures to be annotated.

In the specific implementation process, the video image is obtained by converting the pictures in the set of pictures to be annotated. Each frame of video in the video image has a correspondence with each picture in the set of pictures to be annotated, and the annotation result of the video image may be used as the annotation result of the picture. For example, in some embodiments, according

to correspondences between the video image and the pictures in the set of pictures to be annotated, the annotation results corresponding to various video frames in the video image are associated with the pictures in the set of pictures to be annotated. For example, there are 10 frames of video in the video image for annotation, and each frame of video in the 10 frames of video corresponds to an annotation result. According to the correspondences between various frames of video in the video image and various pictures in the set of pictures to be annotated, pictures respectively corresponding to the 10 frames of video are obtained, and annotation results corresponding to the 10 frames of video are associated with the corresponding pictures to complete annotation of the various pictures in the set of pictures to be annotated. For example, if the first frame of video corresponds to picture 1, an annotation result of the first frame of video is associated with picture 1, and so on. At the same time, an association between the picture and the annotation result, as well as content of the annotation result may be stored.

As can be seen, the annotation result in the set of pictures to be annotated may be similar to the annotation result of the video image, and both can be saved in the form of text, occupy less memory, facilitate management, and can be updated and adjusted at any time. When the annotation of the picture is adjusted, there is no need to regenerate a picture, and only the text of the annotation result needs to be modified. Of course, if the storage space is relatively large, the annotation result may also be directly marked at a corresponding location of the picture, and the picture with the annotation result is stored or returned to the user.

On the basis of the above embodiment, in some embodiments of the present specification, after the associating the annotation result with the corresponding picture, the method further includes:

saving each annotation result and an association between the annotation result and a picture;
and

when an annotated picture display request is received, acquiring a standard result corresponding to a picture in the annotated picture display request according to the association

between the picture and the annotation result, and displaying the annotation result at a corresponding location of the corresponding picture.

In the specific implementation process, after acquiring the association between the annotation result and the picture, the annotation result corresponding to the picture, such as the annotation coordinates location, the annotation content, the annotation form, and the association between the annotation and the picture, may be saved. When a picture display request is received, the annotation result may be displayed at a corresponding location of the corresponding picture according to the annotation result associated with the picture, which is convenient for users to view. For example, when picture 1 is displayed, the annotation result associated with picture 1 may be acquired.

According to the annotation result, the annotation is displayed at the annotation coordinates location of the picture according to the annotation form and annotation content recorded in the annotation result, for example, the corresponding text is frame-selected at the corresponding location of the picture. The annotation result and the picture are saved separately, which can reduce the space occupied by the picture. At the same time, when the picture needs to be displayed, the annotation result is displayed in the picture based on the saved correspondence between the annotation result and the picture, which is convenient for users to view.

After video annotation is performed on the video image, the user can also adjust the annotation result according to actual needs, and associate the adjusted annotation result with the corresponding picture. By converting a group of pictures into a video image, another video frame in the video image is automatically annotated based on the annotation sample video frames with an annotation. After the video image annotation is completed, the user only needs to perform slight adjustment on an annotation result that is not accurate enough. There is no need to manually annotate the pictures one by one, thus improving the efficiency and accuracy of picture annotation.

In the picture annotation method provided in the embodiments of the present specification, annotation to multiple continuous pictures is converted into video annotation. After multiple

pictures to be annotated are converted into a video, annotation may be performed on the video image by using a video annotation algorithm, and an annotation result can be quickly obtained based on a video frame. Finally, a video result is mapped to original pictures to obtain annotation results of the original group of pictures. The picture annotation is converted to video annotation,
5 and the efficiency and accuracy of picture annotation can be improved by using the continuity of the video.

On the basis of the above embodiment, in some embodiments of the present specification, the acquiring an annotation sample video frame in the video image may include:

acquiring an annotation sample picture in the set of pictures to be annotated; and

10 acquiring a video frame corresponding to the annotation sample picture in the video image and regarding it as the annotation sample video frame.

In the specific implementation process, FIG. 2 is a schematic flowchart of picture annotation according to another embodiment of the present specification. As shown in FIG. 2, when a user uploads a set of pictures to be annotated, one of the pictures (such as the first picture) may be
15 manually annotated, of course, multiple pictures may also be manually annotated, and the annotated picture may be used as an annotation sample picture. After multiple pictures in the set of pictures to be annotated are converted into a video image, a video frame corresponding to the annotated picture also carries annotation information, and a frame of video corresponding to the annotation sample picture in the video image may be obtained and regarded as an annotation
20 sample video frame. The annotation sample video frame is used as an annotation sample to automatically annotate another frame of video in the video image. The user may freely select one picture in a group of pictures for annotation, and annotation content may also be set according to actual needs. Based on the picture annotated by the user, various video frames in the video image after conversion are automatically annotated to ensure the flexibility of picture annotation.

Moreover, the user only needs to manually annotate one picture to realize automatic annotation of a group of pictures, thus improving the efficiency and accuracy of video annotation.

On the basis of the above embodiment, in some embodiments of the present specification, the acquiring an annotation sample video frame in the video image includes:

5 after converting the pictures in the set of pictures to be annotated into the video image, receiving a video annotation request, and annotating a specified video frame in the video image; and

acquiring the annotated specified video frame and regarding it as the annotation sample video frame.

10 In the specific implementation process, FIG. 3 is a schematic diagram of picture annotation according to another embodiment of the present specification. As shown in FIG. 3, after a set of pictures to be annotated uploaded by the user is converted into the video image, the user may annotate a certain frame of video in the video image. For example, the user selects a specified video frame in the video image (such as the frame of video at the very beginning of the video or a video
15 frame at the 2nd second) for annotation, and the content, form, location, and the like of the annotation may be defined. The specified video frame annotated by the user is used as an annotation sample video frame, and the annotation sample video frame is used as an annotation sample to perform automatic annotation on another video frame in the video image. The user may freely select any frame of video in a video image after the conversion for annotation, and annotation
20 content may also be set according to actual needs. Based on the video frame annotated by the user, various video frames in the video image after the conversion are automatically annotated to ensure the flexibility of picture annotation, thus improving the efficiency and accuracy of video annotation.

On the basis of the above embodiment, in some embodiments of the present specification, the using the annotation sample video frame as a video annotation sample, and performing video annotation on another video frame in the video image includes:

5 acquiring an annotation object in the annotation sample video frame, and using the annotation object as a tracking target; and

according to the tracking target, acquiring the tracking target from another video frame in the video image, and establishing an annotation at a location of the tracking target.

10 In the specific implementation process, when another video frame in the video image is annotated based on the annotation sample video frame, an annotation object in the annotation sample video frame may be obtained. The annotation object may include the annotation location, the annotation target (such as a text and an object), and the like, such as annotated text content, annotated image content, or annotated location. The annotation object in the annotation sample video frame is used as a tracking target, a video frame with the tracking target is acquired from other video frames in the video image, and an annotation is established at a location of the tracking
15 target in the video frame with the tracking target. For example, with reference to specific information of the annotation in the annotation sample video frame, the corresponding annotation content, annotation form, and the like are established. For example, if an annotation object in the annotation sample video frame is a cat, annotation is performed by frame selection, and an annotation object with a cat is frame-selected in another video frame.

20 In the embodiments of the present specification, tracking annotation may be performed automatically on other video frames in the video image using the video tracking method based on the annotation sample video frame that has been marked, thereby improving the efficiency and accuracy of picture annotation.

On the basis of the above embodiment, in some embodiments of the present specification, the using the annotation sample video frame as a video annotation sample, and performing video annotation on another video frame in the video image includes:

annotating an adjacent video frame of the annotation sample video frame by using an optical flow method, using the annotated video frame as a new annotation sample video frame, and annotating an adjacent video frame of the new annotation sample video frame until annotation to the video image is completed.

In the specific implementation process, when other video frames in the video image are annotated by using the annotation sample video frame, an adjacent video frame of the annotation sample video frame in the video image may be annotated by using the optical flow method. After annotation of the adjacent video frame is completed, the annotated adjacent video frame is used as a sample to annotate a video frame adjacent to the adjacent video frame, and so on, until all video frames of the video image are annotated. The optical flow method may be understood as a method that uses changes of pixels in a time domain in an image sequence and correlation between adjacent frames to find a correspondence between the previous frame and the current frame, thereby calculating motion information of an object between adjacent frames. Based on the annotation sample video frame, the optical flow method can be used to quickly and automatically complete the annotation of adjacent videos, thus realizing the automatic annotation of the video, and improving the efficiency and accuracy of the picture annotation.

On the basis of the above embodiment, in some embodiments of the present specification, the associating the annotation result with the corresponding picture according to the correspondence between the video frame in the video image and the picture in the set of pictures to be annotated includes:

splitting the annotated video image;

acquiring an annotation result of a video frame corresponding to each picture from the annotation result of the video image according to a correspondence between a video frame in the split video image and each picture in the set of pictures to be annotated; and

5 associating the annotation result of the video frame corresponding to each picture with the corresponding picture.

In the specific implementation process, after the video image is annotated, the annotated video image may be split. For example, each frame of video with the annotation result is split out according to the annotation result. Because the video image is obtained by conversion based on the pictures in the set of pictures to be annotated, each picture has a correspondence with the video
10 frame in the video image, for example, each picture corresponds to a video frame at which second of the video image. According to a correspondence between a video frame in the video image and each picture in the set of pictures annotated, an annotation result of a video frame corresponding to each picture is acquired from the annotation result of the video image. For example, the video image is split into a frame-by-frame video, picture 1 corresponds to a video frame at the 0.1st
15 second in the video image, then an annotation result corresponding to the video frame at the 0.1st second is acquired, and the annotation result is associated with picture 1. Picture 2 corresponds to a video frame at the 0.2nd second in the video image, then an annotation result corresponding to the video frame at the 0.2nd second is acquired, and the annotation result is associated with picture 2, and so on.

20 In the embodiments of the present specification, after pictures are converted into a video, annotation is performed based on the video. After the video annotation is completed, the annotation result is associated with the corresponding picture based on the correspondence between the picture and the video, thus obtaining the annotation result of each picture. It is realized that the workload of annotating multiple pictures is converted into annotating one picture and then performing

automatic annotation by using a video, which reduces the workload of picture annotation and improves the efficiency and accuracy of picture annotation.

FIG. 4 is a schematic flowchart of frame-selection annotation of a picture according to an embodiment of the present specification. The frame-selection annotation may be understood as a form of picture annotation for performing frame-selection on part of the content of a picture, for example, performing frame-selection on multiple text parts in a certificate picture. The process of frame-selection annotation of a picture according to an embodiment of the present specification is introduced specifically below with reference to FIG. 4.

1. Frame-selection annotation need to be performed on pictures of a business user, and the procedure proceeds to a picture frame-selection annotation process in the embodiment of the present specification.

2. It is determined whether the pictures that need to be annotated are continuous pictures. For example, determination can be made by picture similarity calculation and other methods. If the pictures that need to be annotated are not a series of continuous pictures, an ordinary picture frame-selection annotation method (such as manual annotation) is used to perform annotation to obtain an annotation result.

3. If the pictures that need to be annotated are a series of continuous pictures, the business user may choose to use a platform (i.e., a picture annotation apparatus) capability to convert the series of pictures into a video for annotation. An annotation object viewed by the user during annotation is the video.

4. After frame-selection annotation has been performed by the user on one frame in the video, content of an adjacent frame of the video has a certain continuity, so the platform may use an integrated video tracking model (e.g., tracking using an optical flow method) to automatically annotate other frames in the video. The user only needs to slightly adjust results of the automatic

annotation to complete the annotation of the entire video, which greatly improves the efficiency and accuracy of the annotation.

5 5. After the video annotation is completed, the platform will automatically split the annotation result of the video. According to correspondences between video frames and the original pictures, the annotation result of each frame of the video is mapped to the original picture, so as to obtain the annotation results of the original pictures and return them to the business user.

An example of a conversion process of the above picture-video-video result-picture result is described as follows:

10 1. After the PIC(x) group of continuous pictures in the original annotation pictures are correspondingly converted into the VIDEO(x) video, continuous pictures m to n in the PIC(x) group and frames 1 to (n-m+1) in the VIDEO(x) video are in one-to-one correspondence.

2. After the completion of video annotation of the VIDEO(x), a result list VIDEO(x).videoResultList is obtained, which includes frame-selection annotation results of various frames: VIDEO(x).framResult[1] to VIDEO(x).framResult [n-m+1].

15 3. According to the one-to-one correspondence between the PIC(x) picture and the VIDEO(x) video frame, the annotation result of the video may be slightly different from the annotation result of the picture. The annotation results VIDEO(x).framResult[1] to VIDEO (x).framResult[n-m+1] may be converted to the picture annotation results of the pictures PIC(x).m->PIC(x).n according to a picture annotation result format, which are the picture annotation results required by the
20 business party.

The embodiment of the present specification provides a picture annotation capability, which converts a group of continuous pictures into a video, uses the continuity between various frames of the video, and uses a related model for analysis (such as optical flow tracking of the video), as long as an annotator annotates one of the frames of the video, the frame-selection annotation of its
25 adjacent frame may be performed automatically, and the procedure continues based on the

annotation result of the adjacent frame until the frame selection of the entire video is completed. For the automatically annotated frames of the model analysis, the annotator only needs to slightly adjust the annotation results to complete the video annotation. After the video annotation is completed, the platform will analyze the video annotation results and map the result of each frame to each original picture, so that the business party can obtain the annotation results of the original group of pictures. By using this method, the annotation efficiency and annotation accuracy of the annotator can be greatly improved, and the business party can also quickly obtain the desired annotation results. After precise frame selection and annotation is implemented on one of the continuous pictures, the effect of using the model to perform automatic annotation on the remaining frames is equivalent to converting the workload of annotating multiple pictures to the workload of annotating one picture and inspecting the remaining pictures. Turning the workload of the picture annotation into the inspection of the picture annotation results is beneficial to improve the efficiency and accuracy of annotation.

The embodiments of the above methods in the present specification are all described in a progressive manner, and for the same or similar parts between the embodiments, reference can be made to each other. Each embodiment focuses on the differences from other embodiments. For the relevant parts, reference can be made to the description of part of the method embodiments.

Based on the above picture annotation method, a system for picture annotation is further provided in one or more embodiments of the present specification. The system may include a system (including a distributed system), software (an application), modules, components, servers, client terminals, etc. using the method described in the embodiments of the present specification in combination with necessary hardware implementation apparatuses. Based on the same innovative concept, the apparatuses in one or more embodiments provided by the embodiments of the present specification are as described in the following embodiments. Since the implementation solution of the apparatus to solve problems are similar to the method, for the implementation of

the specific apparatus in the embodiments of the present specification, reference can be made to the implementation of the foregoing method, and repeated parts will not be repeated here. As used below, the term "unit" or "module" may implement a combination of software and/or hardware having a predetermined function. Although the apparatuses described in the following
5 embodiments are preferably implemented in software, the implementation of hardware or a combination of software and hardware is also possible and conceived.

Specifically, FIG. 5 is a schematic diagram of a modular structure of an embodiment of a picture annotation apparatus according to the present specification. The apparatus may be a device management platform in the above embodiment. As shown in FIG. 5, the picture annotation
10 apparatus provided in the present specification may include:

video conversion module 51 configured to convert multiple pictures in a received set of pictures to be annotated into a video image;

video annotation module 52 configured to perform video annotation on the video image to obtain an annotation result; and

15 annotation association module 53 configured to associate the annotation result with the corresponding picture according to a correspondence between a video frame in the video image and a picture in the set of pictures to be annotated.

In the picture annotation apparatus provided in the embodiments of the present specification, annotation to multiple continuous pictures is converted into video annotation. After multiple
20 pictures to be annotated are converted into a video, annotation may be performed on the video by using a video annotation algorithm, and an annotation result can be quickly obtained based on a video frame. Finally, a video result is mapped to original pictures to obtain annotation results of the original group of pictures. The picture annotation is converted to video annotation, and the efficiency and accuracy of picture annotation can be improved by using the continuity of the video.

In some embodiments of the present specification, the video annotation module is specifically configured to acquire an annotation sample video frame in the video image, use the annotation sample video frame as a video annotation sample, and perform video annotation on another video frame in the video image to obtain the annotation result.

5 In the embodiments of the present specification, by acquiring an annotation sample video frame with annotation information in the video as an annotation sample, another video frame in the video is annotated. An annotation result can be quickly obtained based on the video frame, and the video result is finally mapped to the original pictures to obtain annotation results of the original group of pictures. The annotation to multiple pictures is converted to annotation to a picture, and annotation
10 is performed on another video frame, thus improving the efficiency and accuracy of picture annotation.

In some embodiments of the present specification, the video annotation module is specifically configured to:

acquire an annotation sample picture in the set of pictures to be annotated; and
15 acquire a video frame corresponding to the annotation sample picture in the video image and regard it as the annotation sample video frame.

In the picture annotation apparatus provided in the embodiments of the present specification, the user may freely select one picture in a group of pictures for annotation, and annotation content may also be set according to actual needs. Based on the picture annotated by the user, various video
20 frames in the video image after conversion are automatically annotated to ensure the flexibility of picture annotation, thus improving the efficiency and accuracy of video annotation.

In some embodiments of the present specification, the video annotation module is specifically configured to:

after the video conversion module converts the pictures in the set of pictures to be annotated into the video image, receive a video annotation request, and annotate a specified video frame in the video image; and

acquire the annotated specified video frame and regard it as the annotation sample video frame.

5 In the picture annotation apparatus provided in the embodiment of the present specification, the user may freely select any frame of video in a video image after the conversion for annotation, and annotation content may also be set according to actual needs. Based on the video frame annotated by the user, various video frames in the video image after the conversion are automatically annotated to ensure the flexibility of picture annotation, thus improving the
10 efficiency and accuracy of video annotation.

In some embodiments of the present specification, the video annotation module is specifically configured to:

acquire an annotation object in the annotation sample video frame, and use the annotation object as a tracking target; and

15 according to the tracking target, acquire the tracking target from another video frame in the video image, and establish an annotation at a location of the tracking target.

In the picture annotation apparatus provided in the embodiments of the present specification, tracking annotation may be performed automatically on other video frames in the video image using the video tracking method based on the annotation sample video frame that has been marked,
20 thereby improving the efficiency and accuracy of picture annotation.

In some embodiments of the present specification, the video annotation module is specifically configured to:

annotate an adjacent video frame of the annotation sample video frame by using an optical flow method, use the annotated video frame as a new annotation sample video frame, and annotate an

adjacent video frame of the new annotation sample video frame until annotation to the video image is completed.

In the picture annotation apparatus provided in the embodiments of the present specification, based on the annotation sample video frame, the optical flow method can be used to quickly and automatically complete the annotation of adjacent videos, thus realizing the automatic annotation of the video, and improving the efficiency and accuracy of the picture annotation.

In some embodiments of the present specification, the annotation association module is specifically configured to:

- split the annotated video image;
- acquire an annotation result of a video frame corresponding to each picture from the annotation result of the video image according to a correspondence between a video frame in the split video image and each picture in the set of pictures to be annotated; and
- associate the annotation result of the video frame corresponding to the picture with the picture.

In the picture annotation apparatus provided in the embodiments of the present specification, after pictures are converted into a video, annotation is performed based on the video. After the video annotation is completed, the annotation result is associated with the corresponding picture based on the correspondence between the picture and the video, thus obtaining the annotation result of each picture. It is realized that the workload of annotating multiple pictures is converted into annotating one picture and then performing automatic annotation by using a video, which reduces the workload of picture annotation and improves the efficiency and accuracy of picture annotation.

FIG. 6 is a schematic structural diagram of a picture annotation apparatus according to another embodiment of the present specification. As shown in FIG. 6, in some embodiments of the present specification, the apparatus further includes annotation display module 61 configured to:

- save each annotation result and an association between the annotation result and a picture; and

when an annotated picture display request is received, acquire a standard result corresponding to a picture in the annotated picture display request according to the association between the picture and the annotation result, and display the annotation result at a corresponding location of the corresponding picture.

5 In the picture annotation apparatus provided in the embodiments of the present specification, the annotation result and the picture are saved separately, which can reduce the space occupied by the picture. At the same time, when the picture needs to be displayed, the annotation result is displayed in the picture based on the saved correspondence between the annotation result and the picture, which is convenient for users to view.

10 FIG. 7 is a schematic structural diagram of a picture annotation apparatus according to another embodiment of the present specification. As shown in FIG. 7, in some embodiments of the present specification, the apparatus further includes picture receiving module 71 configured to:

receive a set of pictures to be processed, wherein the set of pictures to be processed includes at least one group of multiple pictures obtained by continuous photographing; and

15 receive a picture annotation request, wherein the picture annotation request includes the set of pictures to be annotated, and the set of pictures to be annotated is a group of continuously photographed multiple pictures in the set of pictures to be processed.

In the picture annotation apparatus provided in the embodiments of the present specification, based on the selection of the user, after the specified continuously photographed pictures are
20 converted into a video image, the picture annotation is performed, which improves the efficiency of picture annotation, and at the same time has relatively high flexibility. For example, the user may use clearer pictures in a group of continuously photographed pictures as a set of pictures to be annotated.

In some embodiments of the present specification, the video conversion module is further
25 configured to:

determine whether the multiple pictures in the set of pictures to be annotated are a group of continuously photographed pictures, and if so, convert the multiple pictures in the set of pictures to be annotated into a video image.

In the picture annotation apparatus provided in the embodiments of the present specification, a group of pictures photographed continuously is annotated. After pictures that need to be annotated are received, it may be first determined whether the pictures belong to a group of pictures photographed continuously, and if so, the pictures can be converted into a video image, and automatic annotation is performed by using the video to improve the annotation efficiency of continuously photographed pictures.

It should be noted that the description of the above apparatus according to the corresponding method embodiments may further include other implementations. For a specific implementation, reference may be made to the description of the above corresponding method embodiments, and details are not repeated herein.

A picture annotation data processing device is further provided in the embodiments of the present specification, including: at least one processor and a memory for storing processor-executable instructions which, when executed by the processor, implement the picture annotation method of the above embodiment, for example:

converting multiple pictures in a received set of pictures to be annotated into a video image;

performing video annotation on the video image to obtain an annotation result; and

associating the annotation result with the corresponding picture according to a correspondence between a video frame in the video image and a picture in the set of pictures to be annotated.

A picture annotation system is further provided in the embodiments of the present specification, including: at least one processor and a memory for storing processor-executable instructions which, when executed by the processor, implement the picture annotation method of the above embodiment, for example:

converting multiple pictures in a received set of pictures to be annotated into a video image;
performing video annotation on the video image to obtain an annotation result; and
associating the annotation result with the corresponding picture according to a correspondence
between a video frame in the video image and a picture in the set of pictures to be annotated.

5 It should be noted that the description of the above device and system according to the method
embodiments may further include other implementations. For specific implementations, reference
may be made to the description of relevant method embodiments, and details are not repeated
herein.

10 The picture annotation apparatus provided in the present specification may also be used in a
variety of data analysis and processing systems. The system or server or terminal or device may be
a separate server, or may include a server cluster, a system (including a distributed system),
software (an application), an actual operating device, a logic gate circuit device, a quantum
computer, etc. using one or more of the methods or one or more embodiment systems or servers or
terminals or devices of the present specification in combination with necessary hardware
15 implementation terminal apparatus. The system may include at least one processor and a memory
storing computer-executable instructions which, when executed by the processor, implement the
steps of the method as described in any one or more of the above embodiments.

20 The method embodiments provided in the embodiments of the present specification can be
executed in a mobile terminal, a computer terminal, a server, or a similar arithmetic apparatus.
Taking running on a server as an example, FIG. 8 is a block diagram of a hardware structure of a
picture annotation server according to an embodiment of the present specification. The computer
terminal may be the picture annotation server or the picture annotation apparatus in the above
embodiment. As shown in FIG. 8, server 10 may include one or more (only one is shown in the
drawing) processors 100 (processor 100 may include, but is not limited to, a processing device
25 such as a microprocessor (MCU) or a programmable logic device (FPGA)), non-volatile memory

200 for storing data, and transmission module 300 for communication functions. Those of ordinary skill in the art may understand that the structure shown in FIG. 8 is merely illustrative, which does not limit the structure of the above electronic apparatuses. For example, server 10 may also include more or fewer components than those shown in FIG. 8. For example, it may also include other processing hardware, such as a database or a multi-level cache, a GPU, or may have a configuration different from that shown in FIG. 8.

Non-volatile memory 200 can be used to store software programs and modules of application software, such as program instructions/modules corresponding to the picture annotation method in the embodiments of the present specification, and processor 100 performs various functional applications and resource data updating by running the software programs and modules stored in non-volatile memory 200. Non-volatile memory 200 may include a high-speed random access memory, and may also include a non-volatile memory, such as one or more magnetic storage apparatuses, a flash memory, or another non-volatile solid-state memory. In some examples, non-volatile memory 200 may further include memories remotely arranged with respect to processor 100, and these remote memories may be connected to a computer terminal through a network. Examples of the above network include, but are not limited to, the Internet, an intranet, a local area network, a mobile communication network, and a combination thereof.

Transmission module 300 is configured to receive or send data via a network. Specific examples of the above network may include a wireless network provided by a communication provider of the computer terminal. In one example, transmission module 300 includes a Network Interface Controller (NIC), which can be connected to other network devices through a base station so as to communicate with the Internet. In one example, transmission module 300 may be a Radio Frequency (RF) module, which is configured to communicate with the Internet in a wireless manner.

The foregoing describes specific embodiments of the present specification. Other embodiments are within the scope of the appended claims. In some cases, the actions or steps recorded in the claims can be performed in an order different from the orders in the embodiments and can still achieve desired results. In addition, the processes depicted in the drawings do not necessarily
5 require the particular order shown or a sequential order to achieve the desired results. In some embodiments, multitasking and parallel processing may also be feasible or may be advantageous.

The methods or apparatuses described in the above embodiments provided in the present specification can implement business logic through a computer program and record the same on a storage medium. The storage medium can be read and executed by a computer to achieve the
10 effects of the solutions described in the embodiments of the present specification, for example:

including: at least one processor and a memory for storing processor-executable instructions which, when executed by the processor, implement the picture annotation method of the above embodiment, for example:

converting multiple pictures in a received set of pictures to be annotated into a video image;
15 acquiring an annotation sample video frame from the video image;
annotating another video frame in the video image by using the annotation sample video frame as an annotation sample to obtain an annotation result; and
associating the annotation result with the corresponding picture according to a correspondence between the video image and a picture in the set of pictures to be annotated.

20 The storage medium may include a physical apparatus for storing information, which usually digitizes the information and then stores the same in a medium in an electrical, magnetic, or optical manner. The storage medium may include: an apparatus that stores information by means of electrical energy, such as various types of memories, for example, a RAM and a ROM; an apparatus that stores information by means of magnetic energy, such as a hard disk, a floppy disk,
25 a magnetic tape, a magnetic core memory, a bubble memory, and a USB disk; and an apparatus

that stores information by optical means, such as a CD or a DVD. Of course, there are other forms of readable storage media, such as a quantum memory and a graphene memory.

The above picture annotation method or apparatus provided in the embodiments of the present specification can be implemented by a processor executing corresponding program instructions in
5 a computer, such as being implemented at a PC terminal by using the c++ language of the windows operating system, being implemented in a linux system, or in other manners, for example, being implemented at a smart terminal by using the programming languages of the android and iOS systems, being implemented based on the processing logic of a quantum computer, etc.

It should be noted that the description of the above apparatuses, computer storage media, and
10 systems according to the relevant method embodiments in the present specification may also include other implementations. For specific implementations, reference may be made to the description of the corresponding method embodiments, which will not be repeated here.

The embodiments in the present specification are all described in a progressive manner, and for the same or similar parts between the embodiments, reference can be made to each other. Each
15 embodiment focuses on the differences from other embodiments. In particular, for hardware + program embodiments, since they are basically similar to method embodiments, the description is relatively simple. For the relevant parts, reference can be made to part of the description of the method embodiments.

The embodiments of the present specification are not limited to the situations that must comply
20 with industry communication standards, standard computer data processing and data storage rules, or the situations described in one or more embodiments of the present specification. Some industry standards, or implementation solutions obtained through slight modifications in a customized manner or based on implementations described in the embodiments can also achieve the same, equivalent, or similar implementation effects of the above embodiments, or predictable
25 implementation effects after variations. Embodiments acquired by applying these modified or

deformed data acquisition, storage, determination, processing manners, etc. can still fall within the scope of optional implementation solutions of the embodiments in the present specification.

In the 1990s, it can be obviously distinguished whether an improvement to a technology is an improvement in hardware (e.g., an improvement to a circuit structure, such as a diode, a transistor, or a switch) or an improvement in software (an improvement to a process). However, with the development of technologies, nowadays, the improvement to many method flows can be regarded as a direct improvement to a hardware circuit structure. Almost all designers program improved method flows into hardware circuits to obtain corresponding hardware circuit structures. Therefore, it cannot be said that an improvement to a method flow cannot be implemented by hardware physical modules. For example, a Programmable Logic Device (PLD) (e.g., a Field Programmable Gate Array (FPGA)) is such an integrated circuit, of which the logic function is determined by a user through programming the device. Designers "integrate" a digital system onto a piece of PLD by independent programming without asking a chip manufacturer to design and manufacture a dedicated integrated circuit chip. Moreover, at present, instead of manually making an integrated circuit chip, this programming is also implemented mostly using "logic compiler" software, which is similar to a software compiler used for program development and compilation. However, the original code before compilation also has to be compiled using a specific programming language, which is known as a Hardware Description Language (HDL). There is not only one, but many kinds of HDLs, such as ABEL (Advanced Boolean Expression language), AHDL (Altera Hardware Description Language), Confluence, CUPL (Cornell University Programming Language), HDCal, JHDL (Java Hardware Description Language), Lava, Lola, MyHDL, PALASM, and RHDL (Ruby Hardware Description Language). At present, VHDL (Very-High-Speed Integrated Circuit Hardware Description Language) and Verilog are the most commonly used. Those skilled in the art should also know that a hardware circuit for implementing a logic

method flow can be easily obtained by slightly logically programming the method flow using the above several hardware description languages and programming it into an integrated circuit.

A controller may be implemented in any suitable manner. For example, a controller may be in the form of a microprocessor or processor and a computer-readable medium storing computer-readable program code (such as software or firmware) executable by this (micro)processor, a logic gate, a switch, an Application Specific Integrated Circuit (ASIC), a programmable logic controller, and an embedded microcontroller. Examples of the controller include, but are not limited to, the following microcontrollers: ARC 625D, Atmel AT91SAM, Microchip PIC18F26K20, and Silicone Labs C8051F320. A controller of a memory may also be implemented as part of the control logic of the memory. Those skilled in the art also know that, in addition to implementing a controller in the form of pure computer-readable program code, the method steps can absolutely be logically programmed to enable the controller to realize the same function in the form of logic gates, switches, special integrated circuits, programmable logic controllers, embedded microcontrollers, or the like. Therefore, such a controller can be regarded as a hardware component, and the devices included therein for realizing various functions can also be regarded as the structure within the hardware component. Alternatively, the devices for realizing various functions can even be regarded as both a software module for implementing a method and a structure within a hardware component.

The systems, devices, modules, or units explained in the above embodiments may be specifically implemented by a computer chip or entity, or by a product with a certain function. A typical implementation apparatus is a computer. Specifically, the computer may be, for example, a personal computer, a laptop computer, an on-board human-machine interaction device, a cellular phone, a camera phone, a smart phone, a personal digital assistant, a media player, a navigation device, an email device, a game console, a tablet computer, a wearable device, or a combination of any of these devices.

Although one or more embodiments of the present specification provide method operation steps as described in the embodiments or flowcharts, more or fewer operation steps may be included based on conventional or non-creative means. The sequence of steps listed in the embodiments is only one of many sequences of execution of the steps, which does not represent a
5 unique sequence of execution. When an actual apparatus or terminal product is executed, it can be executed sequentially or in parallel according to the method shown in the embodiments or the drawings (for example, a parallel processor or multi-thread processing environment, or even a distributed resource data updating environment). The terms "comprise," "include," or any other variations thereof are intended to cover non-exclusive inclusion, so that a process, method, product,
10 or device including a series of elements not only includes the elements, but also includes other elements not clearly listed, or further includes elements inherent to the process, method, product, or device. Without more restrictions, it is not excluded that there are other identical or equivalent elements in the process, method, product, or device including the elements. Words such as first and second are used to indicate names, and do not indicate any particular order.

15 For ease of description, when describing the apparatus above, it is divided into various units based on functions for separate description. Of course, when implementing one or more of the present specification, the functions of the various modules can be implemented in the same one or more pieces of software and/or hardware, or the modules that realize the same function can be implemented by a combination of multiple submodules or subunits. The apparatus embodiments
20 described above are only schematic. For example, the division of the units is only a logical function division. In actual implementations, there may be another division manner. For example, multiple units or components may be combined or integrated into another system, or some features can be ignored or not implemented. In addition, the displayed or discussed mutual coupling or direct coupling or communication connection may be indirect coupling or communication connection
25 through some interfaces, devices, or units, and may be in electrical, mechanical, or other forms.

The present invention is described with reference to flowcharts and/or block diagrams of methods, apparatuses (systems), and computer program products according to embodiments of the present invention. It should be understood that each flow and/or block in the flowcharts and/or block diagrams and a combination of flows and/or blocks in the flowcharts and/or block diagrams
5 may be implemented by computer program instructions. These computer program instructions can be provided to a processor of a general-purpose computer, a special-purpose computer, an embedded processor, or a further programmable resource data updating device to produce a machine, so that the instructions executed by the processor of the computer or further programmable resource data updating device produce an apparatus for realizing the functions
10 specified in one or more flows of the flowcharts and/or one or more blocks of the block diagrams.

These computer program instructions may also be stored in a computer-readable memory that can direct a computer or a further programmable resource data updating device to work in a specific manner, so that the instructions stored in this computer-readable memory produce an article of manufacture including an instruction apparatus which implements the functions specified in one
15 or more flows of the flowcharts and/or one or more blocks of the block diagrams.

These computer program instructions can also be loaded onto a computer or a further programmable resource data updating device, so that a series of operation steps are performed on the computer or another programmable device to produce computer-implemented processing, so that the instructions executed on the computer or another programmable device provide steps for
20 implementing the functions specified in one or more flows of the flowcharts and/or one or more blocks of the block diagrams.

In a typical configuration, the computing device includes one or more central processing units (CPUs), an input/output interface, a network interface, and a memory.

The memory can include a volatile memory, a Random Access Memory (RAM), and/or non-volatile memory in computer-readable media, e.g., a Read-Only Memory (ROM) or a flash RAM. The memory is an example of the computer-readable medium.

5 The computer-readable medium includes permanent and non-permanent, removable and non-removable media, and can store information by any method or technology. The information may be computer-readable instructions, data structures, program modules, or other data. Examples of a storage medium of a computer include, but are not limited to, phase change memory (PRAM), static random access memory (SRAM), dynamic random access memory (DRAM), other types of random access memory (RAM), read-only memory (ROM), electrically erasable programmable
10 read-only memory (EEPROM), flash memory or other memory technologies, read-only compact disc read-only memory (CD-ROM), digital versatile disc (DVD) or other optical storage, magnetic tape cassettes, magnetic tape magnetic disk storage, graphene storage, or other magnetic storage devices, or any other non-transmission medium, and can be used to store information that can be accessed by computing devices. As defined herein, the computer-readable medium does not
15 include temporary computer-readable media (transitory media), such as a modulated data signal and a carrier.

Those skilled in the art should understand that one or more embodiments of the present specification may be provided as a method, system, or computer program product. Therefore, one or more embodiments of the present specification may be in the form of an entirely hardware
20 embodiment, an entirely software embodiment, or an embodiment combining software and hardware aspects. Moreover, one or more embodiments of the present specification may be in the form of a computer program product which is implemented on one or more computer-usable storage media (including, but not limited to, disk storage, CD-ROM, optical storage, etc.) containing computer-usable program code.

One or more embodiments of the present specification may be described in the general context of computer-executable instructions executed by a computer, such as a program module. Generally, the program module includes a routine, a program, an object, an assembly, a data structure, and the like used for executing a specific task or implementing a specific abstract data type. One or
5 more embodiments of the present specification may also be practiced in distributed computing environments in which tasks are performed by remote devices connected through a communication network. In the distributed computing environments, the program module may be located in local and remote computer storage media including a storage device.

The embodiments in the present specification are all described in a progressive manner, and
10 for the same or similar parts between the embodiments, reference can be made to each other. Each embodiment focuses on the differences from other embodiments. In particular, for the system embodiment, since it is basically similar to the method embodiment, the description is relatively simple. For the relevant parts, reference can be made to part of the description of the method embodiment. In the description of the present specification, the description with reference to terms
15 "one embodiment," "some embodiments," "example," "specific example," or "some examples" means specific features, structures, materials, or characteristics described in conjunction with the embodiment or example are included in at least one embodiment or example of the present specification. In the present specification, the schematic expression of the above terms does not necessarily refer to the same embodiment or example. Moreover, the specific features, structures,
20 materials, or characteristics described may be combined in any suitable manner in any one or more embodiments or examples. In addition, without contradicting each other, those skilled in the art may combine and assemble different embodiments or examples and features of different embodiments or examples described in the present specification.

The above description is only an embodiment of one or more embodiments of the present
25 specification and is not intended to limit one or more embodiments of the present specification.

For those skilled in the art, various modifications and changes can be made to one or more embodiments of the present specification. Any modifications, equivalent replacements, improvements, etc. made within the spirit and principle of the present specification shall be included in the scope of the claims.

CLAIMS

1. A picture annotation method, comprising:

converting multiple pictures in a received set of pictures to be annotated into a video image;

performing video annotation on the video image to obtain an annotation result; and

5 using the annotation result as an annotation result of each picture in the set of pictures to be annotated according to a correspondence between a video frame in the video image and a picture in the set of pictures to be annotated.

2. The method of claim 1, wherein the performing video annotation on the video image comprises:

10 acquiring an annotation sample video frame in the video image, using the annotation sample video frame as a video annotation sample, and performing video annotation on another video frame in the video image to obtain the annotation result.

3. The method of claim 2, wherein the acquiring an annotation sample video frame in the video image comprises:

15 acquiring an annotation sample picture in the set of pictures to be annotated; and
acquiring a video frame corresponding to the annotation sample picture in the video image and regarding it as the annotation sample video frame.

4. The method of claim 2, wherein the acquiring an annotation sample video frame in the video image comprises:

20 after converting the pictures in the set of pictures to be annotated into the video image, receiving a video annotation request, and annotating a specified video frame in the video image;
and

acquiring the annotated specified video frame and regarding it as the annotation sample video frame.

5. The method of claim 2, wherein the using the annotation sample video frame as a video annotation sample, and performing video annotation on another video frame in the video image comprises:

acquiring an annotation object in the annotation sample video frame, and using the annotation
5 object as a tracking target; and

according to the tracking target, acquiring the tracking target from another video frame in the video image, and establishing an annotation at a location of the tracking target.

6. The method of claim 2, wherein the using the annotation sample video frame as a video annotation sample, and performing video annotation on another video frame in the video image
10 comprises:

annotating an adjacent video frame of the annotation sample video frame by using an optical flow method, using the annotated video frame as a new annotation sample video frame, and annotating an adjacent video frame of the new annotation sample video frame until annotation to the video image is completed.

15 7. The method of claim 1, wherein the using the annotation result as an annotation result of each picture in the set of pictures to be annotated according to a correspondence between a video frame in the video image and a picture in the set of pictures to be annotated comprises:

splitting the annotated video image;

acquiring an annotation result of a video frame corresponding to each picture from the
20 annotation result of the video image according to a correspondence between a video frame in the split video image and each picture in the set of pictures to be annotated; and

associating the annotation result of the video frame corresponding to each picture with the corresponding picture.

8. The method of claim 1, wherein before converting multiple pictures in a received set of
25 pictures to be annotated into a video image, the method further comprises:

receiving a set of pictures to be processed, wherein the set of pictures to be processed comprises at least one group of multiple pictures obtained by continuous photographing; and

receiving a picture annotation request, wherein the picture annotation request comprises the set of pictures to be annotated, and the set of pictures to be annotated is a group of continuously
5 photographed multiple pictures in the set of pictures to be processed.

9. The method of claim 7, wherein before converting multiple pictures in a received set of pictures to be annotated into a video image, the method further comprises:

determining whether the multiple pictures in the set of pictures to be annotated are a group of continuously photographed pictures, and if so, converting the multiple pictures in the set of pictures
10 to be annotated into a video image.

10. The method of claim 1, wherein after the associating the annotation result with the corresponding picture, the method further comprises:

saving each annotation result and an association between the annotation result and a picture;
and

15 when an annotated picture display request is received, acquiring a standard result corresponding to a picture in the annotated picture display request according to the association between the picture and the annotation result, and displaying the annotation result at a corresponding location of the corresponding picture.

11. A picture annotation apparatus, comprising:

20 a video conversion module configured to convert multiple pictures in a received set of pictures to be annotated into a video image;

a video annotation module configured to perform video annotation on the video image to obtain an annotation result; and

an annotation association module configured to use the annotation result as an annotation result of each picture in the set of pictures to be annotated according to a correspondence between a video frame in the video image and a picture in the set of pictures to be annotated.

5 12. The apparatus of claim 11, wherein the video annotation module is specifically configured to:

acquire an annotation sample video frame in the video image, use the annotation sample video frame as a video annotation sample, and perform video annotation on another video frame in the video image to obtain the annotation result.

10 13. The apparatus of claim 12, wherein the video annotation module is specifically configured to:

acquire an annotation sample picture in the set of pictures to be annotated; and

acquire a video frame corresponding to the annotation sample picture in the video image and regard it as the annotation sample video frame.

15 14. The apparatus of claim 12, wherein the video annotation module is specifically configured to:

after the video conversion module converts the pictures in the set of pictures to be annotated into the video image, receive a video annotation request, and annotate a specified video frame in the video image; and

20 acquire the annotated specified video frame and regard it as the annotation sample video frame.

15. The apparatus of claim 12, wherein the video annotation module is specifically configured to:

acquire an annotation object in the annotation sample video frame, and use the annotation object as a tracking target; and

according to the tracking target, acquire the tracking target from another video frame in the video image, and establish an annotation at a location of the tracking target.

16. The apparatus of claim 12, wherein the video annotation module is specifically configured to:

5 annotate an adjacent video frame of the annotation sample video frame by using an optical flow method, use the annotated video frame as a new annotation sample video frame, and annotate an adjacent video frame of the new annotation sample video frame until annotation to the video image is completed.

17. The apparatus of claim 11, wherein the apparatus further comprises a picture receiving
10 module configured to:

 receive a set of pictures to be processed, wherein the set of pictures to be processed comprises at least one group of multiple pictures obtained by continuous photographing; and

 receive a picture annotation request, wherein the picture annotation request comprises the set of pictures to be annotated, and the set of pictures to be annotated is a group of continuously
15 photographed multiple pictures in the set of pictures to be processed.

18. The apparatus of claim 17, wherein the video conversion module is further configured to:
 determine whether the multiple pictures in the set of pictures to be annotated are a group of continuously photographed pictures, and if so, convert the multiple pictures in the set of pictures to be annotated into a video image.

20 19. A picture annotation data processing device, comprising at least one processor and a memory for storing processor-executable instructions which, when executed by the processor, implement the method of any one of claims 1 to 10.

 20. A picture annotation system, comprising at least one processor and a memory for storing processor-executable instructions which, when executed by the processor, implement the method
25 of any one of claims 1 to 10, and return an annotation result to a user terminal.