CLAIMS

1. A computer-implemented method for communicating shared blockchain data, the method comprising:

sending, by a consensus node of a blockchain network, current state information associated with a current block of a blockchain to a trusted node with proof of authority outside of the blockchain network, wherein the consensus node stores the current state information as a current state tree and the trusted node stores historic state information associated with every block of the blockchain as a historic state tree, and wherein the historic state tree includes key-value pairs (KVPs) with values being account states of accounts associated with the blockchain network and keys being hash values of the corresponding account states;

sending, by the consensus node, a hash value to the trusted node for retrieving an account state stored in the historic state tree;

receiving, by the consensus node, the account state in response to sending the hash value; and

verifying, by the consensus node, that the account state is part of the blockchain based on the hash value.

2. The computer-implemented method of claim 1, wherein the current state tree includes KVPs with values being account sates associated with the current block and keys being node IDs corresponding to nodes of the current state tree.

3. The computer-implemented method of any preceding claim, wherein each of the keys included in the current state tree further includes a block ID corresponding to the current block.

4. The computer-implemented method of any preceding claim, wherein the current state information sent by the consensus node includes a digital signature generated based on a private key associated with the consensus node.

5. The computer-implemented method of any preceding claim, wherein sending the current state information further comprises sending the current state information and a hash value of the current state information as KVP to the trusted node.

6. The computer-implemented method of any preceding claim, wherein verifying that the account state is part of the blockchain is performed based on hashing the account state to generate a hashed account state and comparing the hashed account state to the hash value.

7. The computer-implemented method of any preceding claim, wherein the trusted node stores historic state information locally or on a cloud storage.

8. The computer-implemented method of any preceding claim, wherein the current state tree and the historic state tree are stored as a fixed depth Merkle tree.

9. A system communicating shared blockchain data, comprising:

one or more processors; and

one or more computer-readable memories coupled to the one or more processors and having instructions stored thereon that are executable by the one or more processors to perform the method of any of claims 1 to 8.

10. An apparatus for communicating shared blockchain data, the apparatus comprising a plurality of modules for performing the method of any of claims 1 to 8.