

FIG. 1




COMPUTER 100

FIG. 2



PROCESSOR BUS
115

FIG. 3



* NOTE: The shaded vertical bar indicates one or more clock cycles are allowed between different phases.

FIG. 4



FULL CLOCK ALLOWED
FOR SIGNAL PROPAGATION
FULL CLOCK ALLOWED
FOR LOGIC DELAYS
1
2
3
4
BCLK
A#
B#
ASSERT
A#
LATCH
A#
ASSERT
B#
LATCH
B#

FIG. 5



FULL CLOCK ALLOWED
FOR SIGNAL PROPAGATION
1
2
0.125
0.25
0.375
0.50
0.625
0.75
0.875
BCLK[0]
DRDY#
D#(@driver)
DSTBp#(@driver)
DSTBn#(@driver)
D#(@receiver)
DSTBp#(@receiver)
DSTBn#(@receiver)
D1
D2
D3
D4
Drive D1#
Drive D2#
Capture D1#
Capture D2#
Latch D1, D2, D3, D4
(Latest)

FIG. 6




FULL CLOCK ALLOWED
FOR SIGNAL PROPAGATION
1
2
3
4
0.50
0.25
0.75
BCLK[0]
ADS#
A#(@driver)
Aa
Ab
1
ADSTB#(@driver)
2
A#(@receiver)
Aa
Ab
ADSTB#(@receiver)
1
2
Drive Aa#
Drive Ab#
Capture Aa#
Capture Ab2#
Latest Aa#, Ab#
(Latest)

FIG. 7


TRANSACTION 1
TRANSACTION 2
ARB
2
REQ
3(2)
4(3)
SNOOP
2 SNOOP STALL
3(2)
2
RESP
3(2)
TRDY
1
3(2)
ARB
4 THROTTLE
2 STALL
BNR
3(2)
REQ
2
SNOOP STALL
SNOOP
RESP



832
D. STROBE GENERATOR1/RCVR1
D. STROBE GENERATOR2/RCVR2
RECEIVE CIRCUIT
TRANSMIT CIRCUIT
BUS XCVR 836
SECOND BUS AGENT
820
DSTBp#
DSTBn#
822
DATA[63:0]
826
810
COMMON BUS CLOCK GENERATOR
D. STROBE GENERATOR1/RCVR1
D. STROBE GENERATOR2/RCVR2
RECEIVE CIRCUIT
TRANSMIT CIRCUIT
BUS XCVR 806
FIRST BUS AGENT
802

FIG. 8



942
832
AD. STROBE GENERATOR/RCVR
RECEIVE CIRCUIT
TRANSMIT CIRCUIT
BUS XCVR 936
SECOND BUS AGENT
920
ADSTB
ADDRESS[35:0]
926
940
810
COMMON BUS CLOCK GENERATOR
AD. STROBE GENERATOR/RCVR
RECEIVE CIRCUIT
TRANSMIT CIRCUIT
BUS XCVR 906
FIRST BUS AGENT
802

FIG. 9