

DISPOSABLE UNDERGARMENT

BACKGROUND OF THE INVENTION

This invention relates to disposable undergarments
5 adapted for absorption and containment of excretion and
more particularly to disposable undergarments such as a
diaper, training pants, incontinence pants or the like.

Japanese Patent Application Publication No. 1996-
24291A describes a disposable pants-type diaper
10 comprising a liquid-pervious topsheet, a liquid-
impervious backsheet and a liquid-absorbent core disposed
between these two sheets so as to configure, in a
longitudinal direction, a front waist region, a rear
waist region and a crotch region extending between these
15 two waist regions. The front and rear waist regions are
connected to each other along transversely opposite side
edge portion of these front and rear waist regions to
define a waist-opening and a pair of leg-openings.

In the known diaper, the crotch region has a pair
20 of transversely opposite side edge portions curving
inward transversely to define peripheral edge portions of
the respective leg-openings. The diaper is provided with
a first elastic member attached under tension to the

diaper so as to extend between front ends of the respective opposite side edge portions and to describe a circular arc which is convex rearward in the longitudinal direction and a second elastic member attached under
5 tension to the diaper so as to extend between rear ends of the respective opposite side edge portions and to describe a circular arc which is convex forwardly in the longitudinal direction. The first and second elastic members respectively comprise side portions extending in
10 the vicinity of the front and rear ends of the transversely opposite side edge portions and middle portions spaced in the longitudinal direction from each other and extending across the crotch region. Between the first and second elastic members, there are provided
15 with a pair of third elastic members extending in the longitudinal direction along the transversely opposite side edge portions and bonded under tension to the diaper. The third elastic members intersect the middle portions of the first and second elastic members.

20 With this diaper put on the wearer's body, the elastic members continuously extend along the peripheral edge portions of the respective leg-openings, so the wearer's thighs are fully and tightly surrounded by the

first - third elastic members although the first and second elastic members are spaced in the longitudinal direction from each other in the crotch region. Therefore, there is no anxiety that leakage of excretion
5 might occur in the crotch region.

In the case of the diaper disclosed in the above-identified Publication, the third elastic members spaced in the transverse direction from each other in the crotch region rectilinearly extend along the transversely
10 opposite side edge portions in the longitudinal direction. With a consequence, the third elastic members are not able to extend in a thigh-surrounding direction as the diaper is worn thereby to surround the wearer's thighs. Thus, tensile stress of the third elastic members is not
15 effective in the thigh-surrounding direction and efficiently used to fit the diaper around the wearer's thighs.

In addition, zones of the transversely opposite side edge portions extending from the vicinity of
20 respective branching points between the side portions and the middle portions to the vicinity of the front and rear ends are inevitably apt to be spaced apart from the wearer's skin. These zones should be kept in close

contact with the thighs using any effective means. However, none of such means is disclosed in the above-identified Publication.

5 SUMMARY OF THE INVENTION

It is an object of this invention to provide a disposable undergarment improved so that the tensile stress of the third elastic members may be adequately utilized to keep the above described zones of the
10 transversely opposite side edge portions in close contact with the wearer's thighs and to make the undergarment fit around the wearer's thighs.

According to this invention, there is provided a disposable undergarment comprising a front waist region,
15 a rear waist region and a crotch region extending between these waist regions, a pair of leg-openings defined at transversely opposite side edge portions of the crotch region, stretchable elastic members associated with the leg-openings which comprise a first elastic member
20 extending substantially in a circular arc from a vicinity of respective front ends of the transversely opposite side edge portions rearward longitudinally, a second elastic member extending substantially in a circular arc

from a vicinity of respective rear ends of the transversely opposite side edge portions forward longitudinally and third elastic members extending in the longitudinal direction along the transversely opposite side edge portions between the first and second elastic members.

The first elastic member has first both side portions extending in the vicinity of the respective front ends of the transversely opposite side edge portions and a first middle portion extending across the crotch region. The second elastic member has second both side portions extending in the vicinity of the rear ends of the transversely opposite side edge portions and a second middle portion spaced rearward in the longitudinal direction from the first middle portion by a given dimension and extending across the crotch region. The third elastic members respectively extend along the transversely opposite side edge portions so as to describe circular arcs which are convex inward transversely and have first connecting portions extending from a vicinity of respective branching points between the first both side portions and the first middle portion and merged into generally entire lengths of the first

both side portions and second connecting portions which extend from a vicinity of respective branching points between the second both side portions and the second middle portion and merged into generally entire lengths of the second both side portions..

According to one preferred embodiment of this invention, tensile stress of zones in which the first and second both side portions overlap the first and second connecting portions is higher than that of the remaining zone in which the first - third elastic members extend.

According to another preferred embodiment of this invention, the undergarment is a disposable diaper comprising a liquid-pervious topsheet, a liquid-impervious backsheet and a liquid-absorbent core disposed between these sheets.

According to still another preferred embodiment of this invention, the undergarment is a disposable diaper comprising a liquid-absorbent panel including a liquid-absorbent core disposed between a liquid-pervious topsheet and a leak-barrier sheet, and a liquid-impervious backsheet defining the front and rear waist regions and the crotch region, the panel extending across the crotch region in the longitudinal direction and being

joined to inner surface of the backsheet with the leak-barrier sheet lying therebetween, the first and second elastic members being attached to the backsheet, and the third elastic members are attached to transversely opposite side edge portions of the panel extending along the transversely opposite side edge portions of the crotch region.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a partially cutaway plan view showing a diaper as before it is shaped in pants-type;

Fig. 2 is a partially cutaway perspective view showing the diaper shaped from the state of Fig. 1 into pants-type;

Fig. 3 is a sectional view taken along a line A - A in Fig. 1;

Fig. 4 is a sectional view taken along a line B - B in Fig. 1 with a middle zone of a panel eliminated;

Fig. 5 is a partially cutaway plan view showing an open-type diaper;

Fig. 6 is a partially cutaway perspective view showing the diaper with its front and rear waist regions connected together to wear the diaper;

Fig. 7 is a sectional view taken along a line C - C in Fig. 5; and

Fig. 8 is a sectional view taken along a line D - D in Fig. 5 with a middle zone of an absorbent eliminated.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Details of a disposable diaper according to this invention will be more fully understood from the description given hereunder with reference to the accompanying drawings.

Fig. 1 is a partially cutaway plan view showing a diaper 1A before it is shaped in pants-type, Fig. 2 is a partially cutaway perspective view showing the diaper 1A having been shaped in pants-type from the state of Fig. 1, Fig. 3 is a sectional view taken along a line A - A in Fig. 1 and Fig. 4 is a sectional view taken along a line B - B in Fig. 1 with a middle zone P2 of a panel P eliminated. In Fig. 1, a transverse direction is indicated by an arrow X and a longitudinal direction is indicated by an arrow Y. In Fig. 2, a waist-surrounding direction is indicated by an arrow X and a thigh-surrounding direction is indicated by an arrow Y. Surfaces of top- and backsheets 2, 3 as well as a leak-

15

20

barrier sheet 5 facing an absorbent core 4 will be referred to herein as inner surfaces thereof and surfaces of these sheets 2, 3, 5 not facing the core 4 will be referred to herein as outer surfaces thereof.

5 A diaper 1A basically comprises the liquid-absorbent panel P and a liquid-impervious backsheet 3 formed of a composite sheet composed of a plastic film 3b joined to a hydrophobic fibrous nonwoven fabric 3a.

10 The diaper 1A is composed, in the longitudinal direction, of a front waist region 30, a rear waist region 32 and a crotch region 31 extending between the waist regions 30, 32. The diaper 1A has longitudinally opposite end portions 6 transversely extending in the front and rear trunk regions 30, 32 and transversely
15 opposite side edge portions 7, 8 longitudinally extending in the front and rear waist regions 30, 32. Specifically the diaper 1A is formed by the backsheet 3 of hourglass-shape 3 defining the front and rear waist regions 30, 32 and the crotch region 31 and the panel P attached to the
20 inner surface of the backsheet 3 in the crotch region 31 and extending in the longitudinal direction.

 The panel P comprises the liquid-permeable topsheet 2, the liquid-impervious backsheet 3 and a liquid-

absorbent core 4 disposed between the topsheet 2 and the leak-barrier sheet 5 and joined to these sheets 2, 5.

The panel P presents an hourglass-shape smaller than that presented by the backsheet 3 and has a front zone P1, a rear zone P3 and a middle zone P2 extending
5 between the front and rear zones P1, P3. Transversely opposite side edge portions 9 of the panel P curve to describe circular arcs which are convex inward as viewed in the transverse direction of the diaper 1A. The panel
10 P is joined to the nonwoven fabric 3a with the leak-barrier sheet 5 lying therebetween.

The topsheet 2 and the leak-barrier sheet 5 have peripheral portions thereof extending outward slightly beyond a peripheral edge of the core 4 and put flat and
15 joined together along the peripheral portions thereof.

Transversely opposite side edge portions of the crotch region 31 partially define transversely opposite side edge portions 10 curving inward transversely so that the portions 10 define the peripheral edge portions of
20 respective leg-openings. The crotch region 31 is provided with elastically stretchable first, second and third elastic members 11, 12, 13 each comprising a plurality of elastic elements secured under tension to

the crotch region 31. The front and rear waist regions 30, 32 are respectively provided with elastically stretchable elastic members 14 associated with the waist-opening and auxiliary elastic members 15 each comprising a plurality of elastic elements bonded under tension to the waist regions 30, 32.

The first elastic member 11 extends substantially in a circular arc from respective front ends 10a of the transversely opposite side edge portions 10 lying in the front waist region 30 rearward longitudinally. The first elastic member 11 comprises side portions 11a extending along the transversely opposite side edges 10 in the vicinity of the front ends 10a thereof and a middle portion 11b extending across the front end zone P1 of the panel P.

The second elastic member 12 extends substantially in a circular arc from respective rear ends 10b of the transversely opposite side edge portions 10 lying in the rear waist region 32 forward longitudinally. The second elastic member 12 comprises side portions 12a extending along the transversely opposite side edges 10 in the vicinity of the rear ends 10b thereof and a middle portion 12b spaced rearward from the middle portion 11b

of the first elastic member 11 by a given dimension in the longitudinal direction and extending across the rear end zone P3 of the panel P.

The elastic members 14 associated with the waist-opening extend along the longitudinally opposite end portions 6 in the transverse direction. The auxiliary elastic member 15 extends in the transverse direction between the first and second elastic members 11, 12, on one hand, and the elastic members 14 associated with the waist-opening, on the other hand. The elastic members 11, 12, 13, 14, 15 are disposed between the nonwoven fabric 3a and the plastic film 3b forming together the backsheet 3 and secured to them.

The third elastic members 13 are attached to the transversely opposite side edge portions 10 of the panel P and extend in the longitudinal direction so as to describe circular arcs which are convex inward as viewed in the transverse direction of the diaper 1A. The third elastic members 13 respectively have connecting portions 13a extending in the front zone P1 of the panel P and connecting portions 13b extending in the rear zone P3 of the panel P. The third elastic members 13 are disposed between the topsheet 2 and the leak-barrier sheet 5 and

secured to inner surfaces of these sheets 2, 5.

The connecting portions 13a respectively extend from the associated branching points 16 between the side portions 11a and the middle portions 11b of the
5 respective first elastic members 11 to overlap the respective side portions 11a and extend together with the side portions 11a toward the front ends 10a of the opposite side edge portions 10. The connecting portions 13b respectively extend from the associated branching
10 points 17 between the side portions 12a and the middle portions 12b of the respective first elastic members 12 to overlap the respective side portions 12a and extend together with the side portions 12a toward the rear ends 10b of the opposite side edge portions 10.

15 In the diaper 1A, the connecting portions 13a, 13b overlap the transversely opposite side edge portions 11a, 12a in this manner and thereby the first and second elastic members 11, 12 are substantially merged into the third elastic members 13 on the transversely opposite
20 side edge portions 10. Consequently, the diaper 1A is formed on the transversely opposite side edge portions 1A with zones 18, 19 in which the elastic members 11, 12, 13 extend together.

As shown in Fig. 2, the front and rear waist regions 30, 32 are joined to each other along transversely opposite side edge portions 7, 8 of the waist regions 30, 32 by means of joining zones 20
5 arranged intermittently in the longitudinal direction to shape the diaper 1A in pants-type. A waist-opening 21 and a pair of leg-openings 22 are defined as the diaper 1A is shaped in pants-type in this manner. Of the diaper 1A, the longitudinally opposite end portions 6 define a
10 peripheral edge portion of the waist-opening 21 and the transversely opposite side edge portions 10 define peripheral edge portions of the respective leg-openings 22.

The side portions 11a, 12a of the first and second
15 elastic members 11, 12 and the third elastic members 13 extend in the thigh-surrounding direction along the peripheral edge portions of the leg-openings 21. The elastic member 14 associated with the waist-opening extends in a waist-surrounding direction along the
20 peripheral edge portion of the waist-opening 21. The auxiliary elastic members 15 extend in the waist-surrounding direction across the front and rear waist regions 30, 32. In the diaper 1A, a plurality of gathers

are formed along the peripheral edge portions of the waist- and leg-openings 21, 22 as well as in the front and rear waist regions 30, 32 as the elastic members 11, 12, 13, 14 contract.

5 In the zones 18, 19 of the diaper 1A, the side portions 11a, 12a and the connecting portions 13a, 13b extend together, so that the tensile stress in the zones 17, 18 is higher than that in the remaining zone in which the first - third elastic members 11, 12, 13 extend. In
10 this way, the diaper 1A allows the zones 17, 18 of the transversely opposite side edge portions to be placed against the wearer's thighs thereby to be kept in close contact with the wearer's thighs during use of the diaper 1A.

15 Fig. 5 is a partially cutaway plan view showing an open-type diaper 1B, Fig. 6 is a partially cutaway perspective view showing the diaper 1B with the front and rear waist regions 30, 32 connected to each other to be ready for wearing, Figs. 7 is a sectional view taken
20 along a line C - C in Fig. 5 and Fig. 8 is a sectional view taken along a line D - D in Fig. 5 with the middle zone 4b of the core eliminated. In Fig. 5, a transverse direction is indicated by an arrow X and a longitudinal

direction is indicated by an arrow Y. In Fig. 6, a waist-surrounding direction is indicated by an arrow X and a leg-surrounding direction is indicated by an arrow Y.

5 The diaper 1B basically comprises a liquid-pervious topsheet 2, a liquid-impervious backsheet 3 composed of a plastic film 3b joined to a hydrophobic fibrous nonwoven fabric 3a and a liquid-absorbent core 4 disposed between these sheets 2, 3 and entirely covered with
10 tissue paper (not shown) and joined thereto.

 The liquid-absorbent core 4 extends in the longitudinal direction in the crotch region 31 and comprises front and rear end zones 4a, 4c and a middle zone 4b extending between these two end zones 4a, 4c.
15 The core 4 is disposed between the top- and backsheets 2, 3 and joined to inner surfaces of these sheets 2, 3 with the tissue paper lying therebetween.

 Transversely opposite side edge portions of the crotch region 31 partially define transversely opposite
20 side edge portions 10 curving inward transversely of the diaper 1B so that the portions 10 are destined to define the peripheral edge portions of respective leg-openings. The crotch region 31 is provided with a first elastic

member 11 extending substantially in a circular arc from front ends 10a of the transversely opposite side edge portions 10 rearward as viewed in the longitudinal direction and a second elastic member 12 extending
5 substantially in a circular arc from rear ends 10b of the transversely opposite side edge portions 10 forward as viewed in the longitudinal direction, both of these elastic members 11, 12 being attached under tension to the crotch region 31. The crotch region 31 further
10 includes third elastic members 13 extending in the longitudinal direction between the first and second elastic members 11, 12 and secured under tension to the crotch region 31.

The first and second elastic members 11, 12
15 respectively comprise side portions 11a, 12a extending along the transversely opposite side edge portions 10 in the vicinity of the front and rear ends 10a, 10b thereof and middle portions 11b, 12b spaced apart from each other by a given dimension in the longitudinal direction and
20 extending across the front and rear end zones 4a, 4c of the core 4.

The third elastic members 13 extend in the longitudinal direction so as to describe circular arcs

which are convex inward as viewed in the transverse direction of the diaper 18. The third elastic members 13 respectively have connecting portions 13a extending from respective branching points 16 between the side portions 11a and the middle portion 11b of the first elastic member 11 so as to be merged into the side portions 11a and connecting portions 13b extending from respective branching points 17 between the side portions 12a and the middle portion 12b of the second elastic member 12 so as to be merged into the side portions 12a. The connecting portions 13a extend together with the side portions 11a to the respective front ends 10a of the transversely opposite side edge portions 10. The connecting portions 13b extend together with the side portions 12a to the respective rear ends 10b of the transversely opposite side edge portions 10.

A ribbon-like elastic member 14 associated with the waist-opening is attached under tension to the rear waist region 32 along its longitudinal end portion 6. The elastic members 11, 12, 13, 14 are disposed between the nonwoven fabric 3a and the plastic film 3b and joined to them.

The transversely opposite side edge portions 8 of

the rear waist region 32 are provided with tape fasteners 23 extending inward transversely. The tape fasteners 23 respectively have proximal end portions disposed between the nonwoven fabric 3a and the plastic film 3b and bonded to them. Free end portions of the respective tape fasteners 23 are coated with pressure-sensitive adhesive (not shown).

The front waist region 30 is provided on the outer surface of the backsheet 3 with a rectangular target tape strip 24 made of a plastic film. This target tape strip 24 serves as a landing zone for the tape fasteners 23.

To wear this diaper 1B, the transversely opposite side edge portions 8 of the rear waist region 32 are placed upon outer sides of the transversely opposite side edge portions 7 of the front waist region 30 and the free end portions of the tape fasteners 23 are anchored to the target tape strip 24 by means of pressure-sensitive adhesive to connect the front waist region 30 with the rear waist region 32. With the front and rear waist regions 30, 32 connected to each other, the diaper 1B defines, as seen in Fig. 5, a waist-opening 21 and a pair of leg-openings 22.

The transversely opposite side edge portions 10 of

the diaper 1B are formed with zones 18, 19 in which the side portions 11a, 12a extend together with the connecting portions 13a, 13b, respectively. In the diaper 1B, the stretch stress in the zones 18, 19 is
5 higher than that in the remaining zone in which the first - third elastic members 11, 12, 13 extend. In this way, the diaper 1B allows the zones 18, 19 of the transversely opposite side edge portions 10 to be placed against the wearer's thighs and thereby to be kept in close contact
10 with the wearer's thighs during use of the diaper 1B.

In the diaper 1A as well as in the diaper 1B have been illustrated and described above, the third elastic members 13 extend along the transversely opposite side edge portions 10 so as to describe circular arcs which
15 are convex inward as viewed in the transverse direction of the diaper 1A, 1B. The third elastic members 13 thus extend in the thigh-surrounding direction around the wearer's thighs as the diaper 1A, 1B is worn. The tensile stress of the third elastic members 13 is
20 effectively exerted on the wearer's thighs and adequately utilized to ensure desired fitness of the diaper 1A, 1B around the wearer's thighs.

In both embodiments of diaper 1A, 1B, the first and

second elastic members 11, 12 extend continuously with the third elastic members 13 to surround the wearer's thighs thereby to seal full circumferences of the respective thighs of the wearer. In this way, leakage of excretion possibly occurring in the crotch region 31 is reliably avoided although the first and second elastic members 11, 12 are spaced from each other in the crotch region 31.

In both embodiments of diaper 1A, 1B, the front and rear zones P1, P3 of the panel P or the front and rear zones 4a, 4c of the core 4 are placed against the wearer's skin as the middle portions 11b, 12b of the first and second elastic members 11, 12 contract. In this way, the front and rear zones P1, P3, 4a, 4c are reliably kept in close contact with the wearer's skin.

The topsheet 2 may be formed of a hydrophilic fibrous nonwoven fabric or porous plastic film. The leak-barrier sheet 17 may be formed of a liquid-impervius plastic film. Stock material for the backsheet 3 is not limited to the composite sheet composed of the hydrophobic fibrous nonwoven fabric 3a and the plastic film 3b joined to the hydrophobic fibrous nonwoven fabric 3a. In addition to such composite sheet, the stock

material may be selected from a group including a hydrophobic fibrous nonwoven fabric, a liquid-impervious plastic film and laminated two layers of a hydrophobic fibrous nonwoven fabric. The leak-barrier sheet 5 may be formed of a hydrophobic fibrous nonwoven fabric or a liquid-impervious plastic film.

It is also possible to form the backsheet 3 with a composite nonwoven fabric composed of a melt blown fibrous nonwoven fabric having high water-resistance and two layers of a spun bond fibrous nonwoven fabric having high strength and flexibility.

The nonwoven fabric may be selected from a group including spun lace-, needle punch-, melt blown-, thermal bond-, spun bond-, chemical bond- and air through-nonwoven fabrics. The component fibers of the nonwoven fabric may be selected from a group including polyolefine, polyester and polyamide fibers, and polyethylene/polypropylene or polyethylene/polyester core-sheath-type or side-by-side type conjugated fibers.

The liquid-absorbent core 4 is formed of a mixture of fluff pulp fibers and superabsorbent polymer particles or a mixture of fluff pulp fibers, superabsorbent polymer particles and thermoplastic synthetic resin fibers

compressed to a desired thickness. The polymer contained in the core 4 may be selected from a group including a starch- and cellulose-based polymer and a synthetic polymer. The first, second elastic members 11, 12, the
5 third elastic members 13, the elastic member 14 associated with the waist-opening and the auxiliary elastic member 15 may be made of elastomer such as synthetic or natural rubber.

Joining of the sheets 2, 3, 5 to one other, fixing
10 of the core 4, attachment of the elastic members 11, 12, 13, 14, 15 may be carried out using hot melt adhesive or heat welding technique such as heat-sealing or sonic sealing.

Application of this invention is not limited to
15 disposable diapers such as the embodiments 1A, 1B. This invention is applicable also to training pants for baby adapted to promote freedom from a diaper or to a diaper cover adapted to be combined with a liquid-absorbent pad detachably attached to its inner surface.

20 With the disposable wearing article according to this invention, the third elastic members extend along the transversely opposite side edge portions so as to describe circular arcs which are convex inward as viewed

in the transverse direction of the article. This feature enables the third elastic members to extend in the thigh-surrounding direction as the article is worn. With this article, the stretch stress of the third elastic members
5 is exerted around the wearer's thighs and adequately utilized to keep the transversely opposite side edge portions in close contact with the wearer's thighs.

With the article according to this invention, the connecting portions of the third elastic members are
10 merged into the side portions of the first and second elastic members and the stretch stress in the zones in which these elastic members extend together is higher than that in the remaining zone in which these elastic members extend. This feature enables these zones to be
15 tightly placed against the wearer's thighs. With the article according to this invention, it is possible to keep the transversely opposite side edge portions in close contact with the wearer's thighs in these zones extending from the vicinity of the respective branching
20 points between the side portions of the first and second elastic members, on one hand, and the middle portions thereof, on the other hand, to the vicinity of the front and rear ends of the transversely opposite side edge

20 MAY 2005

- 25 -

portions.

WHAT IS CLAIMED IS:

1. A disposable undergarment (1A, 13) comprising a front waist region (30), a rear waist region (32) and a
5 crotch region (31) extending between these waist regions (30, 32); a pair of leg-openings (22) defined at transversely opposite side edge portions (10) of said crotch (31); stretchable elastic members associated with said leg-openings (22) comprising a first elastic member
10 (11) extending substantially in a circular arc from a vicinity of respective front ends (10a) of said transversely opposite side edge portions (10) rearward longitudinally; a second elastic member (12) extending substantially in a circular arc from a vicinity of
15 respective rear ends (10b) of said transversely opposite side edge portions (10) forward longitudinally; and third elastic members (13) extending in the longitudinal direction along said transversely opposite side edge portions (10) between said first and second elastic
20 members (11, 12); characterizing in that:

said first elastic member (11) has first both side portions (11a) extending in the vicinity of the respective front ends (10a) of said transversely opposite

side edge portions (10) and a first middle portion (11b) extending across said crotch region (31);

said second elastic member (12) having second both side portions (12a) extending in the vicinity of said rear ends (10b) of said transversely opposite side edge portions (10) and a second middle portion (12b) spaced rearward in the longitudinal direction from said first middle portion (11b) by a given dimension and extending across said crotch region (31); and

said third elastic member (13) respectively extend along said transversely opposite side edge portions (10) so as to describe circular arcs which are convex inward transversely and having first connecting portions (13a) extend which from a vicinity of respective branching points (16) between said first both side portions (11a) and said first middle portion (11b) and merged into generally entire lengths of said first both side portions (11a) and second connecting portions (13b) which extend from a vicinity of respective branching points (17) between said second both side portions (12a) and said second middle portion (12b) and merged into generally entire lengths of said second both side portions (12a).

2. The disposable undergarment (1A, 1B) according to Claim 1, wherein tensile stress of zones in which said first and second both side portions (11a, 12a) overlap said first and second connecting portions (13a, 13b) is
5 higher than that of the remaining zone in which said first - third elastic members (11, 12, 13) extend.

3. The disposable weaving undergarment (1A, 1B) according to Claim 1, wherein said undergarment (1A, 1B)
10 is a disposable diaper comprising a liquid-pervious topsheet (12), a liquid-impervious backsheet (13) and a liquid-absorbent core (14) disposed between these sheets (12, 13).

15 4. The disposable weaving undergarment (1A, 1B) according to Claim 1, wherein said undergarment (1A, 1B) is a disposable diaper comprising a liquid-absorbent panel (P) including a liquid-absorbent core (4) disposed between a liquid-pervious topsheet (2) and a leak-barrier
20 sheet (5), and a liquid-impervious backsheet (3) defining said front and rear waist regions (30, 32) and said crotch region (31), said panel (P) extending across said crotch region (31) in the longitudinal direction and

being joined to inner surface of said backsheet (3) with said leak-barrier sheet (5) lying therebetween, said first and second elastic members (11, 12) being attached to said backsheet (3), and said third elastic members
5 (13) are attached to transversely opposite side edge portions (10) of said panel (P) extending along said transversely opposite side edge portions (10) of said crotch region (31).