



(51) International Patent Classification:

C09D 167/00 (2006.01) **C04B 41/63** (2006.01)
C09D 1/00 (2006.01) **C08L 63/00** (2006.01)
C09D 7/12 (2006.01) **C08L 67/00** (2006.01)

(21) International Application Number:

PCT/AU2013/000473

(22) International Filing Date:

9 May 2013 (09.05.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2012901896 10 May 2012 (10.05.2012) AU

(71) Applicant: **VERO INDUSTRIES IP PTY LTD**
[AU/AU]; c/o Michael Buck IP, PO Box 4361, St Lucia,
QLD 4067 (AU).

(72) Inventors: **HINE, Rohan James**; c/o Michael Buck IP,
PO Box 4361, St Lucia, QLD 4067 (AU). **SPINAZE, Mi-**
chael Peter; c/o Michael Buck IP, PO Box 4361, St Lucia,
QLD 4067 (AU).

(74) Agent: **MICHAEL BUCK IP**; PO Box 4361, St Lucia,
QLD 4067 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: A SURFACE COMPOSITION AND METHOD OF APPLICATION THEREOF

(57) Abstract: A composition for forming a protective layer on a substrate comprises a plurality of silicas having different particle size ranges, and a curable resin. The substrate may be a building substrate such as a floor or wall concrete, blocks or bricks. The silica is typically white or colorless crystalline compound, SiO₂, occurring abundantly as quartz, sand, flint, agate, and many other minerals used to manufacture a wide variety of materials, especially glass and concrete.

