

REPLACED SHEETS		SG
☒	Description : paged 471.13 to paged	
☒	Claim(s) : paged 471.13 to paged 471.13	
☐	Drawing(s) : paged to paged	
☒	Abstract : paged 471.13 to paged 471.13	
DATE OF RECEIPT		

TAPE LOADING MECHANISM

The present invention relates to a tape loading mechanism, and more particularly to a pinch roller drive mechanism to guide a magnetic tape.

FIG.1 is an oblique view of the constitution of a pinch roller unit of the prior art. In FIG.1, numeral 1 denotes a pinch roller member which has a pinch roller 10 with which a magnetic tape is brought into contact, an L-shaped base 11 to hold the pinch roller 10, a hollow shaft 11a located at the center of the base 11, a rotary shaft 11b of the pinch roller 10 located at one end of the base 11, a U-shaped hook 11c located at the other end and a contact face 11d located at the opposite side of the hook 11c.

Numerical 2 denotes a rotary member to rotate the pinch roller member 1. The rotary member 2 has a hole 20a through which the hollow shaft 11a of the pinch roller member 1 is inserted, a projection 20b with which the contact face 11d comes in contact so as to prevent the pinch roller member 1 from rotating beyond a specified amount, hooks 20c and 20d,

a projection 20e and a contact face 20f. A spring 4 is provided to link the hook 20c to the hook 11c of the pinch roller member 1, so that the force to press the pinch roller 10 against a capstan shaft is imparted to the pinch roller member 1. The capstan shaft is made to rotate by a capstan motor which supplies the force to drive the magnetic tape to run.

Numeral 3 denotes a sliding member which causes the pinch roller member 1 and the rotary member 2 to slide in the direction along the shaft, and has a hole 30a through which the hollow shaft 11a of the pinch roller member 1 is inserted, a hook 30b, a projection 30c to slide along a cam groove of a cam to be described later, and a contact face 30d. A spring 5 is provided to link the hook 30b to the hook 20d of the rotary member 2, so that the force to pull the pinch roller 10 away from the capstan shaft is imparted to the pinch roller member 1. The pinch roller member 1, the rotary member 2 and the sliding member 3 constitute the pinch roller unit.

FIG.2 is a plan view and a side view of the cam of the prior art. In FIG.2, numeral 6 denotes a cam having a hole 60f which penetrates through the cam in the direction of the axis thereof, and helical cam grooves 60a, 60b and 60c are cut thereon and a rim 60d and a gear 60e are provided below the cam grooves 60a, 60b and 60c. A cam follower 30c of the

sliding member 3 slides along the cam grooves 60a, 60b and 60c.

Now the operation of the pinch roller unit having such a constitution as described above in a magnetic recording/reproducing apparatus will be described. FIG.3 and FIG.4 are schematic plan views of a tape drive system of an ordinary magnetic recording/reproducing apparatus. FIG.3 shows the state before loading and FIG.4 shows the state after loading. As shown in FIG.3, a magnetic tape 9 is set in the magnetic recording/reproducing apparatus, and a guide pole 7 is moved in the direction of arrow 18c by a loading motor not shown in the drawing, thereby drawing the magnetic tape 9 toward a rotary drum 16 (as shown with a broken line 9a). Then guide rollers 15 comprising rollers 15a and guide poles 15b draw the magnetic tape 9 in the directions of arrows 18a and 18b and wind it around the rotary drum 16 as shown in FIG.4.

The operation of the pinch roller during the loading of the magnetic tape 9 will be described below. As shown in FIG.3, a rotary shaft 12a and a rotary shaft 12b are provided near the capstan shaft 8 and the hollow shaft 11a of the pinch roller unit is set movably in the rotary shaft 12a, while a rim member 6 is set movably in the rotary shaft 12b. As the cam 6 is driven by the loading motor to rotate counterclockwise and the cam follower 30c of the sliding

member 3 slides along the cam grooves 60a and 60b, the pinch roller unit moves sliding downward. FIG.5 is a partially sectional view of the state of the pinch roller unit during the sliding motion. When the cam follower 30c reaches the cam groove 60c, the downward movement stops. Then as the projection 20e of the rotary member 2 rotates clockwise along the rim 60d of the cam 6, the spring 4 pulls the pinch roller member 1, thereby rotating the rotary member 2 and the pinch roller member 1 clockwise. At this time, the spring 5 is stretched.

As the pinch roller member 1 rotates clockwise as described above, the pinch roller 10 moves toward and comes in contact with the capstan shaft 8. Then the pinch roller member 1 is locked and only the rotary member 2 rotates clockwise so as to stretch the spring 4. The resilient force of the spring 4 imparts pressing force to the pinch roller 10, and thus the loading operation is completed.

When unloading, the cam 6 is driven by the loading motor to rotate clockwise, so that the sliding member 3 rotates counterclockwise to contract the spring 5. The contracting force of the spring 5 causes the pinch roller member 1 to rotate counterclockwise, thereby contracting the spring 4 and rotating the rotary member 2 counterclockwise. Thus, the pinch roller 10 is moved away from the capstan shaft 8.

The reason for the pinch roller 10 to move away from the capstan shaft 8 is because contracting force of the stretched spring 4 drives the pinch roller member 1 to rotate counterclockwise. The pinch roller 10, however, occasionally does not move away from the capstan shaft 8 smoothly due to the loading force of the spring 4. The magnetic tape 9 is damaged in such a case.

Also, the cam follower 30c occasionally does not slide smoothly along the cam groove 60b when the pinch roller unit moves sliding as shown in FIG.5. This is because the weight of the pinch roller unit on the cam follower 30c side and that on the pinch roller 10 side is not well balanced, and because the cam and the pinch roller unit are linked via the cam follower 30c alone. In case the cam follower 30c does not slide smoothly along the cam groove 60b, there is a possibility of the cam follower 30c coming off the cam groove 60b.

The present invention has been devised in order to solve the above problems. One object of the invention is to provide a tape loading mechanism wherein a pinch roller unit slides along a cam groove smoothly during the loading/unloading operation, and another object of the invention is to provide a magnetic reproducing apparatus wherein a pinch roller is completely moved away from a

capstan shaft.

The tape loading mechanism of the invention has a capstan shaft, a pinch roller to press a magnetic tape against the peripheral surface of the capstan shaft, a pinch roller unit which rotates around its axis in such a direction as the pinch roller moves toward/away from the capstan shaft, and a cam capable of rotating around its axis and having a groove to make the pinch roller unit rotate and move in the axial direction. The pinch roller unit has a cam follower which slides in the groove and a guide member provided along the cam.

Also in the tape loading mechanism of the invention, the guide member is in a cylindrical shape so as to surround the cam.

Consequently, because the guide member is provided along the cam and the cam follower of the pinch roller unit slides in the groove under a constant load, the pinch roller unit moves smoothly without coming off the groove.

Also the tape loading mechanism of the invention has a capstan shaft, a pinch roller to press the magnetic tape against the peripheral surface of the capstan shaft and a cam provided with a groove and first and second rims to make the pinch roller unit rotate around its axis in such a direction as the pinch roller moves toward/away from the capstan shaft. The pinch roller unit has a cam follower



which slides in the groove, a first sliding face which slides along the first rim in the direction as the pinch roller moves toward the capstan shaft and a second sliding face which slides along the second rim in the direction as the pinch roller away from the capstan shaft.

Consequently, because the second sliding face slides along the rim of the cam in such a direction as the pinch roller moves away from the capstan shaft, rotating force is imparted to the pinch roller unit to make the pinch roller move completely away from the capstan shaft.

The above and further objects and features of the invention will more fully be apparent from the following detailed description of an exemplary embodiment and the accompanying drawings, in which:

FIG.1 is an oblique view of the constitution of a pinch roller unit of the prior art.

FIG.2 is a plan view and a side view of a cam structure of the prior art.

FIG.3 is a schematic plan view of a tape drive system of an ordinary magnetic recording/reproducing apparatus before loading.

FIG.4 is a schematic plan view of the tape drive system of the ordinary magnetic recording/reproducing apparatus after loading.



FIG.5 is a partially sectional view of the pinch roller unit of the prior art during its sliding motion.

FIG.6 is an oblique view of a pinch roller unit of the invention.

FIG.7 is a plan view and a side view of a cam structure of the invention.

FIG.8 is a partially sectional view of the pinch roller unit of the invention during its sliding motion.

The invention will be described in detail below with reference to the drawings illustrative of the preferred embodiments.

FIG.6 is an oblique view of the constitution of a pinch roller unit of the invention. In FIG.6, numeral 1 denotes a pinch roller member provided with a pinch roller 10 with which a magnetic tape is brought into contact, an L-shaped base 11 to hold the pinch roller 10, a hollow shaft 11a located at the center of the base 11, a rotary shaft 11b of the pinch roller 10 located at one end of the base 11, a U-shaped hook 11c located at the other end and a contact face 11d located at the opposite side of the hook 11c.

Numeral 2 denotes a rotary member to rotate to the pinch roller member 1. The rotary member 2 has a hole 20a through which the hollow shaft 11a of the pinch roller

member 1 is inserted, a projection 20b with which the contact face 11d comes in contact so as to prevent the pinch roller member 1 from rotating beyond a specified amount, hooks 20c and 20d, a first projection 20e, a second projection 20f and a contact face 20f. When the rotary member 2 rotates around the hole 20a, a first sliding face 20ef which becomes the inner peripheral surface of the first projection 20e and a second sliding face 20gf which becomes the inner peripheral surface of the second projection 20g are formed at positions where they slide along first and second rims of the cam, respectively, as described below.

A spring 4 is provided to link the hook 20c to the hook 11c of the pinch roller member 1, so that the force for pressing the pinch roller 10 against a capstan shaft described later is imparted to the pinch roller member 1.

Numeral 3 denotes a sliding member which causes the pinch roller member 1 and the rotary member 2 to slide in the direction along the shaft. The sliding member 3 has a hole 30a through which the hollow shaft 11a of the pinch roller member 1 is inserted, a hook 30b, and a contact face 30d with which the contact face 20f of the rotary member 2 comes in contact. A cylindrically shaped guide 30e is fixed at one end to movably accommodate a cam described later, and a cam follower 30c is formed so as to project inward on the inner peripheral surface of the guide 30e and slide in the

cam groove of the cam described later. A spring 5 is provided to link the hook 30b to the hook 20d of the rotary member 2, so that the spring 5 and the projection 20g of the rotary member 2 impart the force to the pinch roller member 1 for pulling the pinch roller 10 away from the capstan shaft. The pinch roller member 1, the rotary member 2 and the sliding member 3 constitute the pinch roller unit.

FIG.7 is a plan view and a side view of the cam structure of the invention. In FIG.7, numeral 6 denotes the cam having a hole 60f penetrating therethrough in the direction along a rotation axis 12b (refer to FIG.3), and helical cam grooves 60a, 60b and 60c are cut therein and a first rim 60d, a second rim 60g and a gear 60e are provided below the cam grooves 60a, 60b and 60c. A guide 30e of the sliding member 3 is movably fitted on the periphery of the cam 6, and a cam follower 30c slides in the cam grooves 60a, 60b and 60c.

FIG.8 is a partially sectional view of of the pinch roller unit during its sliding movement. When the cam follower 30c slides in the cam groove 60b, because the guide 30e moves along the cam 6 as shown in the drawing, the cam follower 30c can move smoothly sliding along the cam groove 60b without coming thereof.

As the cam follower 30c slides in the cam groove 60b and reaches the cam groove 60c, the downward movement of the

pinch roller unit stops. Then as the first sliding face 20ef of the rotary member 2 rotates clockwise along the rim 60d of the cam 6, the spring 4 pulls the pinch roller member 1, thereby rotating the rotary member 2 and the pinch roller member 1 clockwise. At this time, the spring 5 is stretched.

As the pinch roller member 1 rotates clockwise as described above, the pinch roller 10 moves toward and comes in contact with the capstan shaft 8. Then the pinch roller member 1 stops the movement, while only the rotary member 2 rotates clockwise to stretch the spring 4. The resilient force of the spring 4 imparts pressing force to the pinch roller 10, and thus the loading operation is completed.

When unloading, the cam 6 is driven by the loading motor to rotate clockwise, so that the sliding member 3 rotates counterclockwise to contract the spring 5. The contracting force of the spring 5 rotates the pinch roller member 1 counterclockwise, thereby contracting the spring 4 and rotating the rotary member 2 counterclockwise, so that the pinch roller 10 moves away from the capstan shaft 8. At the same time, as the cam 6 rotates clockwise, the second sliding face 20ef moves sliding along the outer peripheral surface of the second rim 60g of the cam 6. This movement imparts counterclockwise rotating force to the rotary member 2, thereby moving the pinch roller 10 completely away from the capstan shaft 8.

When the cam follower 30c of the sliding member 3 moves sliding in the cam groove 60b of the cam 6 and the pinch roller unit moves upward thereby moving the sliding face 20ge away from the rim 60g, the pinch roller member 1 is driven by the contracting force of the spring 5 to rotate counterclockwise so that the pinch roller 10 rotates in such a direction as to move away from the capstan shaft 8.

According to the invention, because the pinch roller unit is provided with the guide member to slide in the groove as described above, the cam follower moves smoothly without coming off the groove during the loading/unloading operation. Also because the pinch roller unit is provided with the sliding face to slide along the rim of the cam in such a direction as the pinch roller moves away from the capstan shaft, it is possible to impart rotating force other than the resilient force of the spring to the pinch roller, and the pinch roller can be moved completely away from the capstan shaft during the unloading.

As this invention may be embodied in several forms without departing from the spirit of essential characteristics thereof, the present embodiment is therefore illustrative and not restrictive, since the scope of the invention is defined by the appended claims rather than by the description preceding them, and all changes that fall within metes and bounds of the claims, or equivalence of



such metes and bounds thereof are therefore intended to be embraced by the claims.





C L A I M S

1. A tape loading mechanism, comprising:

a capstan shaft to load a magnetic tape which is pressed against said capstan shaft onto a rotary head by
5 the rotation thereof;

a pinch roller to guide said magnetic tape to the peripheral surface of said capstan shaft and press said magnetic tape thereto;

a pinch roller unit for supporting and moving
10 said pinch roller in the direction along its axis and rotating around its axis in such a direction as said pinch roller moves toward/away from said capstan shaft, said pinch roller unit having a cam follower; and

a cam being rotatable around its axis and having
15 a helical groove, which said cam follower moved sliding in, formed on the peripheral surface thereof in order to make said pinch roller unit rotate and move in the axial direction, said cam including a guide member near said cam follower for guiding said cam follower along said cam.

20 2. A tape loading mechanism according to claim 1, wherein said guide member is of a cylindrical shape so as to surround said cam.

3. A tape loading mechanism, comprising:

a capstan shaft to load a magnetic tape which is
25 pressed against said capstan shaft onto a rotary head by the rotation thereof;





- 15 -

a pinch roller to guide said magnetic tape to the peripheral surface of said capstan shaft and press said magnetic tape thereto;

5 a pinch roller unit for supporting said pinch roller and rotating around its axis in such a direction as said pinch roller moves toward/away from said capstan shaft, said pinch roller unit including a cam follower and a first sliding face; and

10 a cam rotatable around its axis and having a helical groove, which said cam follower moved sliding in, and first rim, which said first sliding face adapted to slide along rim in the direction as said pinch roller moves toward said capstan shaft, formed on the peripheral surface thereof in order to make said pinch roller unit
15 rotate,

said cam including:

a second rim formed on the peripheral surface thereof in order to make said pinch roller unit rotate; and

20 a second sliding face adapted to slide along said second rim in the direction as said pinch roller moves away from said capstan shaft.

4. A tape loading apparatus constructed and arranged to operate substantially as hereinbefore
25 described with reference to and as illustrated in Figures 6 to 8 of the accompanying drawings.

This Sheet Has Been Replaced



16

16-14 to company abstract

A B S T R A C T

TAPE LOADING MECHANISM


The present invention relates to a tape loading mechanism having a guide member provided on a pinch roller unit to prevent a cam follower provided on the pinch roller unit from coming off a cam groove, and capable of smoothly moving the pinch roller unit, wherein a sliding face provided on the pinch roller unit moves sliding along the rim of a cam to impart rotating force to the pinch roller unit, so that the pinch roller moves away from a capstan shaft, and therefore the pinch roller can be moved completely away from the capstan shaft.

This Sheet Has Been Replaced




1/8

FIG. 1
PRIOR ART




218

FIG. 2
PRIOR ART




3/8

FIG. 3



418

FIG. 4



5/8

FIG. 5
PRIOR ART






FIG. 6

618




718

FIG. 7



818

FIG. 8




- 16 -

A B S T R A C T

TAPE LOADING MECHANISM

The present invention relates to a tape loading mechanism having a guide member provided on a pinch roller unit to prevent a cam follower provided on the pinch roller unit from coming off a cam groove, and capable of smoothly moving the pinch roller unit, wherein a sliding face provided on the pinch roller unit moves sliding along the rim of a cam to impart rotating force to the pinch roller unit, so that the pinch roller moves away from a capstan shaft, and therefore the pinch roller can be moved completely away from the capstan shaft.

THIS SHEET HAS BEEN
REPLACED



This Sheet Has Been Replaced




- 16 -

A B S T R A C T
TAPE LOADING MECHANISM

The present invention relates to a tape loading mechanism having a guide member provided on a pinch roller unit to prevent a cam follower provided on the pinch roller unit from coming off a cam groove, and capable of smoothly moving the pinch roller unit, wherein a sliding face provided on the pinch roller unit moves sliding along the rim of a cam to impart rotating force to the pinch roller unit, so that the pinch roller moves away from a capstan shaft, and therefore the pinch roller can be moved completely away from the capstan shaft.

- FIGURE 1 -



This Sheet Has Been Replaced



REPLACEMENT SHEETS		SG
☒ Description :	paged 671 ¹² to paged 700	
☒ Claim(s) :	paged 13 to paged 14	
☐ Drawing(s) :	paged to paged	
☒ Abstract :	paged 5 to paged 7	
DATE OF RECEIPT		4/2/98

- 6 -

The tape loading mechanism of the invention comprises:

a capstan shaft against which a magnetic tape is pressed when said tape is in a loaded state;

a pinch roller to guide said magnetic tape to the peripheral surface of said capstan shaft and press said magnetic tape thereto;

a pinch roller unit for supporting said pinch roller, said pinch roller unit being rotatable around an axis in such a direction that said pinch roller moves toward/away from said capstan shaft, said pinch roller unit including a cam follower, a first sliding face and a second sliding face; and

a cam rotatable around its axis and having a helical groove in which said cam follower slides, and a first rim, formed on the peripheral surface of said cam in order to make said pinch roller unit rotate, said first sliding face being adapted to slide along said first rim in such a direction that said pinch roller moves toward said capstan shaft,

said cam further comprising:

a second rim formed on the peripheral surface thereof in order to make said pinch roller unit rotate, said second sliding face being adapted to slide along said second rim in such a direction that said pinch roller moves away from said capstan shaft.

Consequently, because the second sliding face slides along the second rim of the cam in such a direction as the pinch roller moves away from the capstan shaft, rotating force is imparted to the pinch roller unit to make the pinch roller move completely away from the capstan shaft.

Preferably, said helical groove is formed on the peripheral surface of said cam, and said cam is rotatable in order to make said pinch roller unit rotate and move in the axial direction, and wherein said pinch roller unit

9609163-2

04 FEB 1998

This is the replacement sheet

Date: - 4 FEB 1998

includes a guide member for guiding said cam follower along said helical groove.

Preferably said guide member is of a cylindrical shape so as to surround said cam.

The above and further objects and features of the invention will more fully be apparent from the following detailed description of an exemplary embodiment and the accompanying drawings, in which:

Fig. 1 is an oblique view of the constitution of a pinch roller unit of the prior art.

Fig. 2 is a plan view and a side view of a cam structure of the prior art.

Fig. 3 is a schematic plan view of a tape drive system of an ordinary magnetic recording/reproducing apparatus before loading.

Fig. 4 is a schematic plan view of the tape drive system of the ordinary magnetic recording/reproducing apparatus after loading.

When the cam follower 30c of the sliding member 3 moves sliding in the cam groove 60b of the cam 6 and the pinch roller unit moves upward thereby moving the sliding face 20gf away from the rim 60g, the pinch roller member 1 is driven by the contracting force of the spring 5 to rotate counterclockwise so that the pinch roller 10 rotates in such a direction as to move away from the capstan shaft 8.

With the arrangement described above because the pinch roller unit is provided with the sliding face to slide along the rim of the cam in such a direction as the pinch roller moves away from the capstan shaft, it is possible to impart rotating force other than the resilient force of the spring to the pinch roller, and the pinch roller can be moved completely away from the capstan shaft during the unloading. Also, because the pinch roller unit is provided with the guide member to slide in the groove as described above, the cam follower moves smoothly without coming off the groove during the loading/unloading operation.

This is the replacement sheet

Date: 4 FEB 1998



C L A I M S

THIS SHEET HAS BEEN
REPLACED

1. A tape loading mechanism, comprising:

a capstan shaft against which a magnetic tape is pressed when said tape is in a loaded state;

a pinch roller to guide said magnetic tape to the peripheral surface of said capstan shaft and press said magnetic tape thereto;

a pinch roller unit for supporting said pinch roller, said pinch roller unit being rotatable around an axis in such a direction that said pinch roller moves toward/away from said capstan shaft, said pinch roller unit including a cam follower, a first sliding face and a second sliding face; and

a cam rotatable around its axis and having a helical groove in which said cam follower slides, and a first rim formed on the peripheral surface of said cam in order to make said pinch roller unit rotate, said first sliding face being adapted to slide along said first rim in such a direction that said pinch roller moves toward said capstan shaft,

said cam further comprising:

a second rim formed on the peripheral surface thereof in order to make said pinch roller unit rotate, said second sliding face being adapted to slide along said second rim in such a direction that said pinch roller moves away from said capstan shaft.

2. A tape loading mechanism, according to claim



This is the replacement sheet

Date: - 4 FEB 1998

THIS SHEET HAS BEEN
REPLACED

- 14 -

1, wherein said helical groove is formed on the peripheral surface of said cam, and said cam is rotatable in order to make said pinch roller unit rotate and move in the axial direction, and wherein said pinch roller unit includes a
5 guide member for guiding said cam follower along said helical groove.

3. A tape loading mechanism according to claim 2, wherein said guide member is of a cylindrical shape so as to surround said cam.

4. A tape loading apparatus constructed and
10 arranged to operate substantially as hereinbefore described with reference to and as illustrated in Figures 6 to 8 of the accompanying drawings.

This Sheet Has Been Replaced



* C L M S *

This is the replacement sheet

4 FEB 1998

Date:

A B S T R A C T
TAPE LOADING MECHANISM

The present invention relates to a tape loading mechanism having a guide member provided on a pinch roller unit to prevent a cam follower provided on the pinch roller unit from coming off a cam groove, and capable of smoothly moving the pinch roller unit, wherein a sliding face provided on the pinch roller unit moves sliding along the rim of a cam to impart rotating force to the pinch roller unit, so that the pinch roller moves away from a capstan shaft, and therefore the pinch roller can be moved completely away from the capstan shaft.

- FIGURE 1 -

This is the replacement sheet

Date: - 4 FEB 1998

9609163-2

- 1 -

CLAIMS

REPLACEMENT SHEETS		SC
☐ Description	: paged to paged	
☒ Claim(s)	: paged <u>1/2</u> to paged <u>7/2</u>	
☐ Drawing(s)	: paged to paged	
☐ Abstract	: paged to paged	
DATE OF RECEIPT <u>14/9/99</u>		

1. A tape loading mechanism, comprising:

a capstan shaft against which a magnetic tape is pressed when said tape is in a loaded state;

a pinch roller to guide said magnetic tape to the peripheral surface of said capstan shaft and press said magnetic tape thereto;

a pinch roller unit for supporting said pinch roller, said pinch roller unit being rotatable around an axis in such a direction that said pinch roller moves toward/away from said capstan shaft, said pinch roller unit including a cam follower, a first sliding face and a second sliding face; and

a cam rotatable around its axis and having a helical groove in which said cam follower slides, and a first rim formed on the peripheral surface of said cam in order to make said pinch roller unit rotate, said first sliding face being adapted to slide along said first rim in the direction as said pinch roller moves toward said capstan shaft,

said cam further comprising:

a second rim formed on the peripheral surface thereof in order to make said pinch roller unit rotate, said second sliding face being adapted to slide along said second rim in the direction as said pinch roller moves away from said capstan shaft.

2. A tape loading mechanism, according to claim



1, wherein said helical groove is formed on the peripheral surface of said cam, and said cam is rotatable in order to make said pinch roller unit rotate and move in the axial direction, and wherein said pinch roller unit includes a guide member for guiding said cam follower along said cam.

3. A tape loading mechanism according to claim 2, wherein said guide member is of a cylindrical shape so as to surround said cam.

4. A tape loading apparatus constructed and arranged to operate substantially as hereinbefore described with reference to and as illustrated in Figures 6 to 8 of the accompanying drawings.

